Table of Contents

Introduction		1.1
	Features	1.1.1
	Architecture	1.1.2
	Installing	1.1.3
	Themeing	1.1.4
(Getting Started	1.1.5
API		1.2
•	Table	1.2.1
	Inputs	1.2.1.1
	Outputs	1.2.1.2
	Methods	1.2.1.3
	Internals	1.2.1.4
	Column	1.2.2
	Inputs	1.2.2.1
	Modes	1.2.2.2
	Internals	1.2.2.3
ļ	Row Detail	1.2.3
	Inputs	1.2.3.1
	Outputs	1.2.3.2
Demos		1.3
	Online	1.3.1
	Source Code	1.3.2
Contributing		1.4
	Building	1.4.1
(Guidelines	1.4.2
	Community	1.4.3
	Credits	1.4.4
Changelog		1.5

ngx-datatable

ngx-datatable is a Angular component for presenting large and complex data. It has all the features you would expect from any other table but in a light package with *no external dependencies*. The table was designed to be extremely flexible and light; it doesn't make any assumptions about your data or how you: filter, sort or page it.

It was built for modern browsers using *TypeScript, CSS3 and HTML5* and Angular >=4.0.0. This is the sister project of the angular-data-table that is designed for Angular 1.x.

In The News

AngularAir Esp 76



Video link

The project was featured on AngularAir where @amcdnl spoke about the project, challenges and whats to come.

Features

The table was designed to be *extremely flexible and light*; it doesn't make any assumptions about your data or how you: filter, sort or page it. That said, we wanted to keep the features strictly related to dealing with the data rather than implementing complex filtering/etc that is often very use-case specific. The current features include:

- Handle large data sets (Virtual DOM)
- Expressive Header and Cell Templates
- Horizontal & Vertical Scrolling
- · Column Reordering & Resizing
- Client/Serve side Pagination & Sorting
- Intelligent Column Width Algorithms (Force-fill & Flex-grow)
- Integrated Pager
- Cell & Row Selection (Single, Multi, Keyboard, Checkbox)
- Fixed AND Fluid height
- Left and Right Column Pinning
- Row Detail View
- Decoupled theme'ing with included Google Material theme
- Light codebase / No external dependencies

Roadmap

We are really excited about the table and wanted to get it out into the open as quickly as possible so we had to delay some of the features but we plan to add the following:

- Touch selection
- Tree Grids
- Row Grouping

Alternatives

This might not be the best fit for you given the above, there are some other great solutions and some this project borrows from; heres a short list:

- ng2-super-table
- ng2-table
- vaadin-grid
- iron-data-table
- paper-datatable

Architecture

Manifesto

There is some things that it doesn't do nor do we plan to do. Lets say you have a requirement to have the ability to edit cell values in the row. Thats a awesome feature but somewhat catered to your use case. How do you invoke the edit? What type of control do you show in the cell? If its a date, do you have controls for that? Its a slippery slope...if you do want to do that you can use the expressive column templates to put whatever components inside your table you want.

What we wanted to do is design a table component that isn't bloated with features that won't fit every use case but instead make a component that does what it does the best possible and is flexible enough to allow you to do what you need to do to solve your requirement.

Some examples of the things we don't plan to build in this project are:

- Export such as CSV
- Context Menus
- Column Filters
- Column Toggling
- Inline Editing

If you are interested in building something like that for this project, I'm happy to help point you in the right direction and would be happy to list a link as a extension.

Installing

You can grab the latest release from the Releases Page in Github or via NPM.

• npm install @swimlane/ngx-datatable

Also, the release code is checked in and resides here.

Module Version

The module is packaged using UMD. The file is release/index.js.

CSS

If you want to use material theme, include ./release/material.css . For more information, visit the 'Themes' section.

Developing

If you are wanting to run the demos locally, just do:

- npm i
- npm start
- Browse to http://localhost:9999

Themes

Out of the box, the data-table is not styled. This gives you maximum flexibility.

There is a separate material theme distributed with data-table. In order to use it, you need to include that in your application release/material.css and add the CSS class material to your data-table.

This is a simple way to apply the style of the demo.

```
@import '~@swimlane/ngx-datatable/release/index.css';
@import '~@swimlane/ngx-datatable/release/themes/material.css';
@import '~@swimlane/ngx-datatable/release/assets/icons.css';
```

You can just add above to your scss file and then specify the class of your ngx-datatable to <ngx-datatable class="material">

CSS Classes

- ngx-datatable : Master Table class
 - fixed-header: The header is fixed on the table
- datatable-header: Header row class
 - o datatable-header-cell: Header cell class
 - resizeable : Cell resizeable class
 - sortable : Cell drag/drop sortable class
 - longpress : Cell long-press activated
 - dragging : Cell dragging activated
 - sort-active : Sort active on column
 - sort-asc: Sort active on column with ascending applied
 - sort-desc: Sort active on column with descending applied
 - o datatable-header-cell-label: Header cell text label
 - draggable : Header cell draggable class
- datatable-body-row : Body row class
 - o datatable-row-even : Odd row class
 - datatable-row-odd : Even row class
 - datatable-body-cell : Body cell class

- sort-active : Sort active on column
- sort-asc : Sort active on column with ascending applied
- sort-desc: Sort active on column with descending applied

Getting Started

After Installing, include NgxDatatableModule in your application module like:

```
import { NgModule } from '@angular/core';
import { BrowserModule } from '@angular/platform-browser';
import { NgxDatatableModule } from '@swimlane/ngx-datatable';

import { AppComponent } from './app.component';

@NgModule({
   declarations: [AppComponent],
   imports: [NgxDatatableModule, BrowserModule],
   bootstrap: [AppComponent]
})
export class AppModule { }
```

then in your app.component.ts you define a table like:

```
import { Component } from '@angular/core';
@Component({
  selector: 'app',
  template: `
    <div>
     <ngx-datatable
       [rows]="rows"
        [columns]="columns">
     </ngx-datatable>
   </div>
})
export class AppComponent {
  rows = [
    { name: 'Austin', gender: 'Male', company: 'Swimlane' },
    { name: 'Dany', gender: 'Male', company: 'KFC' },
    { name: 'Molly', gender: 'Female', company: 'Burger King' },
 1;
  columns = [
    { prop: 'name' },
    { name: 'Gender' },
    { name: 'Company' }
 ];
}
```

and your off to the races!

For more examples, visit the demos directory in the source code!

Table Inputs

columnMode

The mode which the columns are distributed across the table. For example: flex will use flex-grow api, force will distribute proportionally and standard will just distribute based on widths. Default value: standard

columns

Array of columns to display.

count

The total count of all rows. Default value: 0

cssClasses

Custom CSS classes that can be defined to override the icons classes for up/down in sorts and previous/next in the pager. Defaults:

```
sortAscending: 'datatable-icon-down',
sortDescending: 'datatable-icon-up',
pagerLeftArrow: 'datatable-icon-left',
pagerRightArrow: 'datatable-icon-right',
pagerPrevious: 'datatable-icon-prev',
pagerNext: 'datatable-icon-skip'
```

externalPaging

Should the table use external paging vs client-side. Default value: false

externalSorting

Should the table use external sorting vs client-side. Default value: false

footerHeight

The height of the footer in pixels. Pass a falsey for no footer. Default value: 0

headerHeight

The height of the header in pixels. Pass a falsey for no header. Default value: 30

messages

Static messages in the table you can override for localization.

```
{
  // Message to show when array is presented
  // but contains no values
  emptyMessage: 'No data to display',

  // Footer total message
  totalMessage: 'total'
}
```

limit

The page size to be shown. Default value: undefined .

loadingIndicator

Show the linear loading bar. Default value: false

offset

The current offset (page - 1) shown. Default value: 0

reorderable

Column re-ordering enabled/disabled. Default value: true

rowHeight: Function|number|undefined

The height of the row.

Pass undefined for fluid heights, this is not possible in virtual scrolling.

If using virtual scrolling, you must pass a function or a number to caculate the heights.

Using a function, you can bind individual row heights such as:

```
getRowHeight(row) {
  // set default
  if(!row) return 50;

  // return my height
  return row.height;
}
```

rowIdentity

This will be used when displaying or selecting rows. When tracking/comparing them, we'll use the value of this fn (fn(x) === fn(y)) instead of (x === y).

rows

Array of rows to display.

scrollbarH

Enabled horizontal scrollbars. Default value: false

scrollbarV

Enable vertical scrollbar for fixed height vs fluid. This is necessary for virtual scrolling. Default value: false

selectCheck

A boolean/function you can use to check whether you want to select a particular row based on a criteria. Example:

```
(row, column, value) => { return value !== 'Ethel Price'; }
```

selected

List of row objects that should be represented as selected in the grid. It does object equality, for prop checking use the selectcheck function.

Default value: []

selectionType

Type of row selection. Options are single, multi, multiclick and chkbox. For no selection pass a falsey. Default value: undefined

sorts

Array of sorted columns by property and type. Default value: []

sortType

Single vs Multi sorting. When in single mode, any click after the initial click will replace the current selection with the next selection. In multi selection mode, any incremental click will add to the current selection array.

Default value: single

trackByProp

A property on the row object that uniquely identifies the row. Example: name

rowClass

A function that will invoked with each row's properties. The result of the function can be a string or object with key/boolean like:

```
getRowClass(row) {
  return {
    'is-age-10': row.age === 10
  }
}
```

Table Outputs

All outputs are Angular2 EventEmitter ers.

activate

A cell or row was focused via keyboard or mouse click.

```
{
  type: 'keydown'|'click'|'dblclick'
  event
  row
  column
  value
  cellElement
  rowElement
}
```

detailToggle

Row detail row was toggled.

```
{
  rows
  currentIndex
}
```

page

The table was paged either triggered by the pager or the body scroll.

```
{
  count
  pageSize
  limit
  offset
}
```

reorder

Columns were re-ordered.

```
{
  column
  newValue
  prevValue
}
```

resize

Column was resized.

```
{
  column
  newValue
}
```

tableContextmenu

The context menu was invoked on the table.

```
{
  event,
  type,
  content
}
```

scroll

Body was scrolled typically in a scrollbarv:true scenario.

```
{
   offsetX
   offsetY
}
```

select

A cell or row was selected.

```
{
   selected
}
```

sort

Column sort was invoked.

```
{
  sorts
  column
  prevValue
  newValue
}
```

Table Methods

recalculate()

Recalculate the grid sizes.

Table Internals

Row Indexes

Each row is decorated with a \$\$index attribute. This allows us to track the actual index of the row. This is needed because if you are lazy loading data into the grid the index upon which the data is loaded might not always be the 'actual' index its inserted.

This is also leveraged by the virtual scroll so it knows how to offset the row in the page's view port.

Table Column Options

name: string

Column label. If none specified, it will use the prop value and decamelize it.

prop : string

The property to bind the row values to. If undefined, it will camelcase the name value.

flexGrow : number

The grow factor relative to other columns. Same as the flex-grow API. It will any available extra width and distribute it proportionally according to all columns' flexGrow values. Default value: 0

minWidth: number

Minimum width of the column in pixels. Default value: 100

maxWidth: number

Maximum width of the column in pixels. Default value: undefined

width: number

The width of the column by default in pixels. Default value: 150

resizeable: boolean

The column can be resized manually by the user. Default value: true

comparator

Custom sort comparator, used to apply custom sorting via client-side. See MDN for more info.

sortable: boolean

Sorting of the row values by this column. Default value: true

draggable : boolean

The column can be dragged to re-order. Default value: true

canAutoResize: boolean

Whether the column can automatically resize to fill extra space. Default value: true

cellTemplate: TemplateRef

Angular TemplateRef allowing you to author custom body cell templates

headerTemplate: TemplateRef

Angular TemplateRef allowing you to author custom header cell templates

checkboxable: boolean

Indicates whether the column should show a checkbox component for selection. Only applicable when the selection mode is checkbox.

headerCheckboxable: boolean

Indicates whether the column should show a checkbox component in the header cell. Only applicable when the selection mode is checkbox.

headerClass: string|Function

Header CSS classes to apply to the header cell

cellClass: string|Function

Cell classes to apply to the body cell

Column Modes

Column modes allow you to have a variety of different ways to apply column width distribution to the columns. The table comes with 3 modes; standard, flex, force.

Standard

Columns are distributed given the width's defined in the column options.

Flex

Flex mode distributes the width's grow factor relative to other columns. It works the same as the flex-grow API in CSS. Basically it takes any available extra width and distribute it proportionally according to each column's flexgrow value.

Flex is **not** suggested for when using scrollH.

Force

Force mode forces the widths of the columns to distribute equally but overflowing when the min-width of each column is reached. The rules are:

- If combined withs are less than the total width of the grid, proportion the widths given the min / max / normal widths to fill the width.
- If the combined widths, exceed the total width of the grid, use the standard widths.
- If a column is resized, it should always use that width.
- The proportional widths should never fall below min size if specified.
- If the grid starts off small but then becomes greater than the size (+ /) the width should use the original width; not the newly proportioned widths.

Force is usually the ideal column distribution method when columns do not need to be a fixed sized.

Column Internals

lds

Each row is decorated with a ssid attribute. This allows us to track the column for faster change detection/etc.

Row Detail Options

template: TemplateRef

Template to use in the detail row. Example:

rowHeight: Number|Function

Height of the detail row.

Template

Typescript

```
getHeight(row: any, index: number): number {
  return row.someHeight;
}
```

Row Detail Outputs

All outputs are Angular2 EventEmitter ers.

toggle

Row detail row was toggled.

```
{
  type: 'all' || 'row'
  value: boolean || row object
}
```

Building

This project uses npm tasks for builds.

Pre-reqs

- Node >= 6.0.0
- Angular CLI
- TypeScript >= 2.0.0

Commands

- npm start: Starts Webpack dev server
- npm run release : Builds code to dist folder
- npm run test : Runs E2E Tests
- npm run package: Runs builds, packages and copies results to ./release

Depedencies

- webpack (npm install --global webpack)
- webpack-dev-server (npm install --global webpack-dev-server)
- karma (npm install --global karma-cli)
- protractor (npm install --global protractor)
- typescript (npm install --global typescript)

Guidelines

We would love for you to contribute to our project and help make it ever better! As a contributor, here are the guidelines we would like you to follow.

Found an Issue?

If you find a bug in the source code or a mistake in the documentation, you can help us by submitting an issue to our GitHub Repository. Including an issue reproduction (via CodePen, JsBin, Plunkr, etc.) is the absolute best way to help the team quickly diagnose the problem. Screenshots are also helpful.

You can help the team even more and submit a Pull Request with a fix.

Want a Feature?

You can request a new feature by submitting an issue to our GitHub Repository. If you would like to implement a new feature, please submit an issue with a proposal for your work first, to be sure that we can use it. Please consider what kind of change it is:

- For a Major Feature, first open an issue and outline your proposal so that it can be
 discussed. This will also allow us to better coordinate our efforts, prevent duplication of
 work, and help you to craft the change so that it is successfully accepted into the
 project.
- Small Features can be crafted and directly submitted as a Pull Request.

Issue Etiquette

Before you submit an issue, search the archive, maybe your question was already answered.

If your issue appears to be a bug, and hasn't been reported, open a new issue. Help us to maximize the effort we can spend fixing issues and adding new features by not reporting duplicate issues. Providing the following information will increase the chances of your issue being dealt with quickly:

- Overview of the Issue if an error is being thrown a non-minified stack trace helps
- Angular and angular2-data-table Versions which versions of Angular and angular2data-table are affected
- Motivation for or Use Case explain what are you trying to do and why the current

behavior is a bug for you

- Browsers and Operating System is this a problem with all browsers?
- Reproduce the Error provide a live example (using CodePen, JsBin, Plunker, etc.) or a unambiguous set of steps
- Screenshots Due to the visual nature of angular2-data-table, screenshots can help the team triage issues far more quickly than a text description.
- Related Issues has a similar issue been reported before?
- Suggest a Fix if you can't fix the bug yourself, perhaps you can point to what might be causing the problem (line of code or commit)

Community

Below is a list of community contributions and projects that use the table.

• ng2-inline-editor - inline edit cell values with ng2-inline-editor and angular2-data-table projects.

If you have a project using the table and would love to share with the community, please reach out on gh issues and we would love to add it to the growing list!

Credits

angular2-data-table is a Swimlane open-source project; we believe in giving back to the open-source community by sharing some of the projects we build for our application. Swimlane is an automated cyber security operations and incident response platform that enables cyber security teams to leverage threat intelligence, speed up incident response and automate security operations.

Contributors

Changelog

9.3.0

• Feature: Unviseral Rendering (#764)

9.2.0

- Enhancement: Add header context menu event
- Bug: Fix sort blowing up when undefined and adding new sort
- Bug: Fix multi-selection key with Mac

9.1.0

- Enhancement: Add more context to cells #720
- Enhancement: Export Pager component #735
- Bug: Header checkbox when row selection is changed #659
- Bug: When rowClass() returns a string, the class is not properly added #710
- Bug: Rename icons so don't conflict with other libs #729

9.0.0

- BREAKING: Fixes for external pagination fixes. Index calculation change being last page = 0 + pageSize (#714, #138, #391)
- Feature: Server-side virtual scrolling pagination
- Demos: Deep linking of demo pages

8.2.1

• Bug: Fix footer styles

8.2.0

• Feature: Footer Templates

8.1.0

· Feature: Dark Theme

8.0.1

- Bug: Fix memory leak (#702)
- Bug: Don't add column header title attribute when custom template provided (#643)
- Bug: Only apply pointer to header text (#682)
- Bug: Fix prop field name with dots (#596)
- Bug: Virtual scroll + dynamic height in cell detail not working right (#703)
- Bug: Fix dynamic row height not working right if using server-side pagination
- Chore: Implement noImplicitAny (#671)

8.0.0

- Breaking: Removed cssclass from columns in favor of explicit
- Feature: Added explicit headerclass and cellclass
- Feature: Add ability to have callback for those class getters
- · Bug: Fix checkbox select all not updating ui correctly

7.3.1

- Bug: Fix resize handle drag triggering long press
- Bug: Fix dragging trigging column sorting
- Bug: Fix column re-ordering not working on FF

7.3.0

- Feature: Dynamic row heights for virtual scrolling
- Bug: Do not use document for universal support (#668)

7.2.1

Bug: Fix missing type

7.2.0

- Feature: Allow for dynamic Detail Row heights (#653)
- Feature: Numeric prop support via support array rows (#494)
- Perf: Optimize sort code by caching valueGetter and compareFn outside loop.
- Perf: Set ValueGetter on TableColumn.\$\$valueGetter
- Bug: Alter setColumnDefaults to work with numeric prop values.

7.1.1

- Perf: Fix memory leaks with templates (#464)
- · Bug: Fix row detail expanded and then collapsed not showing anything until scroll

7.1.0

- Bug: Fix title not set on cell template (#629)
- Chore: Update to official Angular4
- · Chore: Misc build dep updates

7.0.0

- BREAKING: Update to Angular4!
- Feature: Row classes (#571), (#348)
- Bug: Show first page after sorting (#553)
- Bug: When reordering and skipping a column, the column gets duplicated (#497), (#562), (#563)
- Chore: Upgrade misc deps and lint fixes

NOTE: If you need support for ~Angular2, use version 6.x.

6.3.0

- Bug: Perform sort when sort icon is clicked (#536)
- Bug: Fix resize handle overlaped by label (#521)
- Chore: Fix relative imports for rollup (#542)
- Chore: Linting

6.2.1

• Bug: Revert #516 causing server-side paging issue (#543)

6.2.0

- Bug: Fix AoT builds with SCSS (#534)
- Bug: Fix offset incorrect when filtering (#516)
- Bug: Fix mouse press subscription cleanups (#522)
- Bug: Fix header cell wrapper empty span (#504)
- Bug: Fix selected count undefined in footer template (#537)
- Bug: Fix orderable unsubscribe listeners (#538)
- Chore: Update Angular and ZoneJS

6.1.2

• Bug: Fix default sort (#475)

6.1.1

• Bug: Fix tree-shaking issue (#511)

6.1.0

- Feature: Add selected count in footer (#508)
- Bug: Fix drag/drop/long-press (#506)
- Bug: Fix row widths not set correctly (#510)
- Perf: Better mouseup handling (#507)
- Chore: Bump Depedencies

6.0.2

• Bug: Move scss to release dir (#459)

6.0.1

- Bug: Fix CSS not working with AoT (#459)
- Chore: Fix ExtractText plugin causing build issue
- Chore: Upgrade Angular 2.4.5

6.0.0 (2017-01-25)

- BREAKING: Renamed datatable css class to ngx-datatable
- BREAKING: Embedded core css file with Angular styleurls
- Enhancement: Allow sorting from inline templates (#431)
- Enhancement: Fix re-ordering columns throwing errors (#438)
- Enhancement: Add nice drag indicator to material theme
- Chore: Update Depedencies

5.0.0

- BREAKING: Re-worked all inputs, methods and outputs of row detail to its own container
- Enhancement: Implement Finder/Explorer shift selection behavior
- Bug: Fix reverse selection de-selecting first index in reverse
- · Bug: Fix row detail not rendering

4.2.0

- Enhancement: Ability to add CSS Classes on Header/Column
- Bug: Fix CPU Perf on Resort (#409)
- Chore: Upgrade to Angular ^2.4.3
- Chore: Correct RxJS Imports

4.1.0

- Feature: Adding multi-click selection
- Bug: Use tracking fn vs inline (#388)
- Bug: Fix AoT header issue (#389)
- Bug: Fix reorderable not being honored (#387)
- Bug: Fix multi-select CTRL not working (#381)
- Chore: Upgrade Angular to ^2.4.1
- Docs: Multi-select

4.0.0

 BREAKING!!!! - Renamed project from angular2-datatable to ngx-datatable and updated components from <swui-datatable> to <ngx-datatable>

3.0.0

- BREAKING: Removed shiftMulti option, its not useful and creates odd scenarios
- Bug: Permanently high CPU utilization after sorting (#359)
- Bug: Fix checkbox showing in header if defined but not using checkbox select
- Bug: Fix AoT errors (#370)
- Bug: Fix build not outputing AoT files in correct directory
- Bug: Fix checkbox selection not working w/ shift key
- Chore: Upgrade Angular/Webpack

2.2.3

• Bug: Fix header checkbox mutating selection array

2.2.2

Bug: Fix default selections and don't mutate selection arrow now

2.2.1

• Bug: Fix AoT by reverting TypeScript upgrade until CLI is updated

2.2.0

- Bug: Fix AoT private props (#352)
- Bug: Added null chk to selection getter (#340)
- Bug: multiShift not working after first page (#294)
- Chore: Update Angular to 2.3.0
- Chore: Update TypeScript to 2.1.x
- Chore: Update RxJS to 5.0.0-rc.4
- Chore: Update ZoneJS to 0.7.2

• Demo: Add templates for Webpack plugin for Google Analytics

2.1.3

- Bug: Fix footer not updating when all removes removed
- Bug: Fix Add/Remove items in array not updating (#255)

2.1.2

• Bug: Fix sizing method being debounced on view inits rather than just window resize.

2.1.1

• Bug: Fix memory leak with visibility observer

2.1.0

- Feature: Checkbox selection mode
- Enhancement: Selection mode auto added to host class for easier styling
- Style: Remove row active/select state when in cell mode of material theme
- Bug: Force fill column mode w/ scrollbarH false allowing bleed when resized
- Perf: Faster render time by adding css class via host
- Perf: Debounce window resize calcs

2.0.0

- BREAKING: Rename from datatable to swui-datatable (#320)
- BREAKING: Redo how row-detail/cell/header templates are described in markup (#304)
- BREAKING: Change Detection switched back to normal
- Enhancement: Row Context Menu Event rowContextmenu (#331)
- Bug: Set default value for selected (#314)
- Bug: Fix widths being int vs float (#309)
- Bug: Fix column resize not setting widths to the right (#308)
- Bug: Fix row object mutations (#255)
- Bug: Async Problem when using @Input (#253)
- Bug: Sort doesn't work on the first click (#254)
- Bug: Pagination "skip to last page" is not selected after click (#324)

- Bug: ngFor Not working in the datatable-row-detail-template (#274)
- Chore: Resolve all implicit any s (#330)
- Chore: Bump Angular to latest 2.2.4

1.7.0

- Enhancement: Add RxJS Support
- · Chore: Fix builds on windows

1.6.0

- Bug: Column headers not re-ordering (#238)
- Bug: Datatable doesn't sort data correctly when data changed (#284)
- BREAKING: comparator now is a normal sort function arguments of propA, propB.

1.5.1

- Bug: Custom comparator should return new array (#286)
- Bug: Init selection to empty array (#285)

1.5.0

- Enhancement: externalsorting input for simpler server-sorting usage (#281)
- Enhancement: Add trackByProp for change detection with mutation of row data
- Bug: Row height variable access protection (#280)
- Chore: Upgrade to Angular 2.2.0
- · Demo: Inline editing updates
- · Demo: Live data refresh demo
- Breaking: Remove refresh method per recommendation by @robwormald

1.4.1

- Bug: Ignore next page when already at last (#223)
- · Chore: Redid Webpack Config to be clean
- Chore: TESTS! TRAVIS BUILDS! COVERAGE REPORTING!

1.4.0

- Enhancement: Added refresh API for updating table (#255)
- Bug: Fix intersection observer type errors (#268)

1.3.1

• Bug: Fix force column width distribution overriding new resize (#245)

1.3.0

- Enhancement: selectCheck fn to prevent selection
- Bug: Fix columns leaking event handlers
- Bug: Fix column toggling errors (#245)
- Bug: Fix AoT Metadata not creating

1.2.0

- Bug: Fix columns loosing templates on resize (#252)
- Bug: Fix pager not having right pages when hidden by default
- Bug: Fix expressive column width as attribute with standard column distribution
- Bug: Fix body columns not readjusting after window resize (#251)
- Enhancement: Refactor emptyMessage and totalMessage to messages object
- Enhancement: Huge perf improvement for tables hidden by default

1.1.0

- Feature: NGC Complation
- Bug: Null value in deepValueGetter (#243)
- Chore: Update Depedencies

1.0.0

- Feature: Cell Selection and Keyboard Navigation
- Feature: activation events
- Enhancement: onPush all the things!

- Enhancement: Add totalMessage option for localization
- Enhancement: Demo Page
- Enhancement: Page Count Formatted
- Enhancement: Automatically format column prop when no name passed
- Enhancement: Add ability to pass false to comparator for sort handling via event
- Bug: Window resize not updating rows in virtual scrolling
- Chore: Switch to SemVer
- BREAKING: TableOptions has been removed and options are Input on component now
- BREAKING: TableColumn class has been removed, just pass normal objects
- BREAKING: Event names has been renamed using Angular2 standards
- BREAKING: Components have been renamed to Angular2 standards
- BREAKING: Removed StateService

0.12.0

- Bug: Return empty string on undefined deep values (#232)
- Bug: Fix force fill alog (#218)
- Enhancement: Support for other icon types (#235)
- Enhancement: Add ability to identify rows for proper selection (#154)

0.11.2

- Enhancement: Add ability to define css icon classes for pager / header
- Chore: Uprade to Angular 2.1.1

0.11.1

· Chore: Polish on new build

0.11.0

- Chore: New build process
- Bug: Fix detail row bug (#212)

0.10.1

Bug: Fix \$\$expanded undefined with server paging (#210)

0.10.0

- Chore: Upgrade to Angular 2.1.0 (#202)
- Chore: Removed engine restrictions (#195)
- Bug: windows builds with node-sass (#207)
- Bug: resizing not closing correctly (#196)
- Bug: Fix height paging (#208)
- Enhancement: Improve Active CSS (#204)
- Enhancement: Add Empty Message (#194)
- Enhancement: Add deep value getter to sortRows function (#181)
- Enhancement: Sort Classes are applied to body cells (#166)
- Enhancement: AoT Compatibility (#199)
- Feature: Row Detail (#201)

0.9.3

- Column resize sometimes gives weird behaviour on mouse resize/click (#155)
- Fix order of setters in DataTable ngOnChanges (#179)
- Remove document event listener subscription leak in draggable & resizeable
- Fix setScrollTop undefined error (#182)

0.9.2

• Fix name being undefined introduced in 0.9.0 release

0.9.1

• Export component references for external consumption (#176)

0.9.0

- Fix accidental breaking change of renaming HeaderCell column property to model. See commit.
- Ensure minWidth and maxWidth values are specified saved as numbers (#167)
- Add row double click option (#168)

0.8.0

Added the ability to define header templates expressively Breaking Change! Renamed
 template to cellTemplate in column options

0.7.4

- Removed #142 in favor of style height
- Fixed issue with height + scrollbarV not sizing right
- Fix limit not applied (#133)
- Fix sort not resetting to top of page (#136)
- · Added option validation

0.7.3

• Huge perf bumps (#149)

0.7.2

Build fixes

0.7.1

• Removed template wrapper in favor of native template outlet

0.7.0

- Upgrade Angular 2.0.1 & ZoneJS
- Angular Code Style Compliance (#147)
- Fix initial load of rows jumbled (#156)
- Update row/options setting to ngOnChanges (#151)
- Fix column height not set correctly (#144)

0.6.1

Virtual Scrolling Emits Paging (#130)

0.6.0

- Update to Angular 2.0.0!
- Fix horizontal header issue (#129)

0.5.1

- Fixed Multiple Tables on Same Page (#103)
- Fix TS Helpers not being included in release (#107)
- Update onPage API to reflect docs (#116)

0.5.0

• Upgrade to Angular2 RC7