Lab2.1

1. Struct Person with Associated Methods

1. Define a Go struct named Person with fields: Name (string), Age (int), Job (string), and Salary (float64).

2. Add two methods with appropriate receivers: one to read data into the struct from user input, and one to print all fields in a formatted manner.

3. Create at least two Person objects in main() and call both methods on each. 4. Push the source file to your GitHub repository

```go
package main

import "fmt"

// Define Person structure
type Person struct {
    Name   string
    Age    int
    Job    string
    Salary float64
}

// Method to read person details
func (p *Person) ReadData() {
    fmt.Print("Enter Name: ")
    fmt.Scan(&p.Name)

    fmt.Print("Enter Age: ")
    fmt.Scan(&p.Age)

    fmt.Print("Enter Job: ")
    fmt.Scan(&p.Job)

    fmt.Print("Enter Salary: ")
    fmt.Scan(&p.Salary)
}

// Method to display person details
func (p Person) DisplayData() {
    fmt.Println("\n----- Person Details -----")
    fmt.Println("Name:", p.Name)
    fmt.Println("Age:", p.Age)
    fmt.Println("Job:", p.Job)
    fmt.Printf("Salary: %.2f\n", p.Salary)
}
```

```go
func main() {

    // Create first Person object
    var p1 Person

    fmt.Println("Enter First Person Details:")
    p1.ReadData()
    p1.DisplayData()

    // Create second Person object
    var p2 Person

    fmt.Println("\nEnter Second Person Details:")
    p2.ReadData()
    p2.DisplayData()
}
```

```
Enter details of Person 1
Enter Name:
Anjali
Enter Age:
21
Enter Job:
Analyst
Enter Salary:
90000

Person Details
Name: Anjali
Age: 21
Job: Analyst
Salary: 90000

Enter details of Person 2
Enter Name:
Jigyasa
Enter Age:
21
Enter Job:
Developer
Enter Salary:
95000

Person Details
Name: Jigyasa
Age: 21
Job: Developer
Salary: 95000
```