

Note – Ensure date and time are visible.

1. Use centos 9 server and create a user with name “svradmin” with a password (of your choice). Use this user to create another user (without making it sudo user) and try adding another user (cliadmin) and see if that works. Validate the e-mail received from the linux machine.
2. Install a windows 10 machine and configure it as per CIS benchmark standards for the following:
 - a. Password policy
 - i. Min length: 14+
 - ii. Complexity: Enabled
 - iii. History: 24
 - iv. Max age: 60 days
 - b. Account lockout policy
 - i. Threshold: 5 attempts
 - ii. Lockout: 15 minutes
 - c. Login Title → “Welcome to Week 4 – Practical session”.
 - d. Login text → “This PC belongs to RPS Consulting Pvt. Ltd. Please use it wisely.”
3. Use appropriate VMs to fetch the username and password of a user/email ID by perform DNS spoofing. Make user that the user’s credentials are visible on terminal.
4. Use Windows server DC machine and create a user named “tryme” and add a password (of your choice) and perform brute force attack on this user.
5. Configure Squid proxy on a fresh machine and block the below websites. Verify if its working and logs are getting generated.
 - a. Facebook.com
 - b. YouTube.com
 - c. Gmail.com
 - d. Instagram.com
6. Use DC machine to fetch the login and logged out user list for last 2 hours.
7. Use appropriate VMs to create a malware and block this by enabling the antivirus.
8. Use Cisco Packet Tracer and configure DHCP server and verify if client machine is able to receive dynamic IP address from this DHCP server.
9. Write the powershell code to achieve the output as given below.

```
Logged user is: Jeetu
Your IP address is: 192.168.1.2
Your hostname is: WORKSTATION
Today's date & time is: 16-Feb-26 9:23:11 AM
```

10. From DC ping to centos 9 (and vice-versa) and check for connectivity. Block the pinging of the two servers and verify.