

4. Calling Functions in R

CT1100 - J. Duggan

Functions

- A function is a group of instructions (with a name) that:
 - takes input(s)
 - uses the input(s) to compute other value, and
 - returns a result (Matloff 2009)
 - result usually stored in a variable
- Functions are a fundamental building block of R
- Users of R should adopt the habit of creating simple functions which will make their work more effective and also more trustworthy (Chambers 2008).
- Two approaches:
 - Use R functions (Base R and other packages)
 - Write your own functions

R - A function “ecosystem”

John Chambers: “To understand computations in R, two slogans are helpful:

- Everything that exists is an object.
- Everything that happens is a **function call**.”

```
x <- 1:6  
sqrt(x)
```

```
## [1] 1.000000 1.414214 1.732051 2.000000 2.236068 2.449490
```

```
min(x)
```


```
## [1] 1
```

```
mean(x)
```

```
## [1] 3.5
```

Coding with functions

- “Stand on the shoulders of giants”
- Use Tools -> Install Packages from RStudio



Calling functions: input - process - output


```
x <- c(1,4,9,16,25)  
sqrt(x)
```

```
## [1] 1 2 3 4 5
```

Input Vector



Output Vector



Challenge 4.1

- Use the sample function to generate 30 random numbers between 50 and 100 and call the function set.seed(100) before you call sample
- Use R functions to calculate the mean, max and min
- Show all the numbers greater than the mean
- Use length() to count the number greater than the mean

```
set.seed(100)
x <- sample(30:100,30,replace=T)
x[1:12]
```

```
## [1] 52 99 33 84 99 36 36 84 72 90 41 80
```

Function Arguments

- It is useful to distinguish between formal arguments and the actual arguments
 - Formal arguments are the property of the function
 - Actual arguments can vary each time the function is called.
- When calling functions, arguments can be specified by
 - Position
 - Complete name
- Guidelines (Wickham 2015)
 - Use positional mapping for the first one or two arguments (most commonly used)
 - Avoid using positional mapping for less commonly used attributes
 - Named arguments should always come after unnamed arguments

Fuel Economy Data Set (ggplot2::mpg)

This dataset contains a subset of the fuel economy data that the EPA makes available on <http://fuelconomy.gov>. It contains only models which had a new release every year between 1999 and 2008 - this was used as a proxy for the popularity of the car.


manufacturer	car manufacturer	drv	drive type
model	model name	cty	city miles per gallon
displ	engine disp (l)	hwy	highway miles per gallon
year	year of make	fl	fuel type
cyl	number of cylinders	class	"type" of car
trans	type of transm.		

Data Set Elements

manufacturer	model	displ	year	cyl	trans	drv	cty
audi	a4	1.8	1999	4	auto(l5)	f	18
audi	a4	1.8	1999	4	manual(m5)	f	21
audi	a4	2.0	2008	4	manual(m6)	f	20
audi	a4	2.0	2008	4	auto(av)	f	21
audi	a4	2.8	1999	6	auto(l5)	f	16
audi	a4	2.8	1999	6	manual(m5)	f	18
audi	a4	3.1	2008	6	auto(av)	f	18
audi	a4 quattro	1.8	1999	4	manual(m5)	4	18
audi	a4 quattro	1.8	1999	4	auto(l5)	4	16
audi	a4 quattro	2.0	2008	4	manual(m6)	4	20

Calling a function to create a plot (from package ggplot2)

```
library(ggplot2)
ggplot(data=mpg)+
  geom_point(mapping=aes(x=displ,y=cty))
```



Calling functions to filter data

```
library(ggplot2)
library(dplyr)
f <- mpg %>% select(manufacturer,model,year,displ,cty) %>%
  filter(model=="a4") %>% arrange(desc(year))
f
```

```
## # A tibble: 7 x 5
##   manufacturer model  year displ  cty
##   <chr>         <chr> <int> <dbl> <int>
## 1 audi         a4     2008  2     20
## 2 audi         a4     2008  2     21
## 3 audi         a4     2008  3.1   18
## 4 audi         a4     1999  1.8   18
## 5 audi         a4     1999  1.8   21
## 6 audi         a4     1999  2.8   16
## 7 audi         a4     1999  2.8   18
```

Writing Functions

- **function** (*arguments*) *expression*
- arguments gives the arguments, separated by commas.
- Expression (body of the function) is any legal R expression, usually enclosed in { }
- Last evaluation is returned
- return() can also be used, but usually for exceptions.

```
f <- function(x)x^2 # this function squares a vector  
f(1:3)
```

```
## [1] 1 4 9
```

Summary

- Functions are a fundamental building block of R
- Functions:
 - are declared using the function reserved word
 - are objects
- Functions can access variables within the environment where they are created
- Functionals are functions that takes a function as an input and returns a vector as output (can be used as a looping structure)
- The apply family in R are functionals (**apply**, **sapply**, **lapply**)