

Programming for Data Analytics

4. ggplot2

Dr. Jim Duggan,
School of Engineering & Informatics
National University of Ireland Galway.

https://twitter.com/_jimduggan



Course Overview

Lectures 1-3	R Fundamentals <i>Atomic Vectors – Functions – Lists – Matrices – Data Frames</i>
Lectures 4-9	Data Science with R <i>ggplot2 – dplyr – tidyr – stringr – lubridate – purrr</i>
Lectures 10-11	Advanced Programming with R <i>Environments – Closures – S3 Object System</i>
Lectures 12	Machine Learning with R – Case Studies <i>Electricity Generation, Health</i>



Lecture Overview

- Data Exploration
- Aesthetic Mappings
- Common Problems
- Facets
- Geometric Objects
- Statistical Transformations
- Coordinate Systems
- Layered Grammar of Graphics

Lectures
1-3

R Fundamentals

Atomic Vectors – Functions – Lists – Matrices – Data Frames

Lectures
4-8

Data Science with R

ggplot2 – dplyr – tidyr – stringr – lubridate – forcats – purrr

Lectures
9-10

Advanced Programming with R

Environments – Closures – S3 Object System

Lectures
11-12


Machine Learning with R – Case Studies

Electricity Generation, Marketing, Epidemiology



(1) Data Exploration

“Data exploration is the art of looking at your data, rapidly generating hypotheses, quickly testing them, then repeating again and again and again.” (Wickham and Grolemund 2017).



Data Visualisation with **ggplot2**

“The simple graph has brought more information to the data analyst’s mind than any other device.” – John Tukey

```
> dt <- ggplot2::mpg
>
> dt
# A tibble: 234 × 11
  manufacturer    model displ  year  cyl    trans  drv  cty   hwy fl   class
    <chr>         <chr> <dbl> <int> <int>    <chr> <chr> <int> <int> <chr> <chr>
1      audi      a4    1.8  1999     4 auto(l5)  f    18    29 p compact
2      audi      a4    1.8  1999     4 manual(m5) f    21    29 p compact
3      audi      a4    2.0  2008     4 manual(m6) f    20    31 p compact
4      audi      a4    2.0  2008     4 auto(av)   f    21    30 p compact
5      audi      a4    2.8  1999     6 auto(l5)  f    16    26 p compact
6      audi      a4    2.8  1999     6 manual(m5) f    18    26 p compact
7      audi      a4    3.1  2008     6 auto(av)   f    18    27 p compact
8      audi a4 quattro  1.8  1999     4 manual(m5) 4    18    26 p compact
9      audi a4 quattro  1.8  1999     4 auto(l5)   4    16    25 p compact
10     audi a4 quattro  2.0  2008     4 manual(m6) 4    20    28 p compact
# ... with 224 more rows
```

Fuel Economy Data Set (ggplot2::mpg)

This dataset contains a subset of the fuel economy data that the EPA makes available on <http://fuelconomy.gov>. It contains only models which had a new release every year between 1999 and 2008 - this was used as a proxy for the popularity of the car.

manufacturer	manufacturer	drv	f = front-wheel drive, r = rear wheel drive, 4 = 4wd
model	model name	cty	city miles per gallon
displ	engine displacement, in litres	hwy	highway miles per gallon
year	year of manufacture	fl	fuel type
cyl	number of cylinders	class	“type” of car
trans	type of transmission		

First Steps

- Generate a first graph to help answer the following question:
 - *Do cars with big engines use more fuel than cars with small engines*
- What might the relationship between **engine size** and **fuel efficiency** look like?
 - Positive or negative?
 - Linear or non-linear?




Selecting data

```
> dt
# A tibble: 234 × 11
  manufacturer model displ year cyl trans drv cty hwy fl class
  <chr>         <chr> <dbl> <int> <int> <chr> <chr> <int> <int> <chr> <chr>
1 audi         a4     1.8  1999   4 auto(l5) f    18    29 p compact
2 audi         a4     1.8  1999   4 manual(m5) f    21    29 p compact
3 audi         a4     2.0  2008   4 manual(m6) f    20    31 p compact
4 audi         a4     2.0  2008   4 auto(av) f    21    30 p compact
5 audi         a4     2.8  1999   6 auto(l5) f    16    26 p compact
```


- Among the variables are:
 - **displ**, a car's engine size in litres
 - **hwy**, a car's fuel efficiency on the highway in miles per gallon

Creating a ggplot



Interpreting the plot

- The plot shows a negative relationship between engine size (displ) and fuel efficiency (hwy)
- Cars with big engines use more fuel
- Does this confirm or refute your hypothesis about fuel efficiency and engine size?



Challenge 4.1

- Explore the hypothesis that city driving is less fuel efficient than highway driving
- Use ggplot to present the points on the same graph, and colour each data set differently
- Does the data confirm or refute your initial hypothesis?




(2) Aesthetic Mappings

“The greatest value of a picture is when it forces us to notice what we never expected to see” – John Tukey

```
> unique(dt$class)
[1] "compact"      "midsize"      "suv"          "2seater"      "minivan"
[6] "pickup"       "subcompact"
```

- A third variable can be added to a 2-D plot by mapping it to an aesthetic.
- An aesthetic is a visual property of the plot's objects.
- An aesthetic's *level* could be colour, size or shape.

```
ggplot(data = dt) +  
  geom_point(mapping = aes(x=displ,y=hwy,colour=class))
```



(3) Common Problems


- R can be “extremely picky, and a misplaced character can make all the difference”
- Make sure every (is matched with a)
- For ggplot calls, the + must come at the end of the line, not at the start (see below)
- You can get help about any function by running ?function_name

```
> ggplot(data=d)
>   +geom_point(aes(x=displ,y=hwy),colour="blue")
Error in +geom_point(aes(x = displ, y = hwy), colour = "blue") :
  invalid argument to unary operator
```


(4) Facets

- Another way to add categorical variables is to split a plot into facets, subplots that display one subset of the data.
- To facet your plot by a single variable, use `facet_wrap()`, with `~` followed by the variable name
- To facet on the combination of two variables, used `facet_grid()`


```
ggplot(data = dt) +  
  geom_point(mapping = aes(x=displ,y=hwy)) + facet_wrap(~class)
```





```
ggplot(data = dt) +
  geom_point(mapping = aes(x=displ,y=hwy,colour=class)) +
  facet_wrap(~manufacturer)
```




```
ggplot(data=mpg) +  
  geom_point(mapping = aes(x=displ, y = hwy)) +  
  facet_grid(drv ~ cyl)
```



```
ggplot(data=mpg) +  
  geom_point(mapping = aes(x=displ, y = hwy)) +  
  facet_grid(. ~ cyl)
```



```
ggplot(data=mpg) +  
  geom_point(mapping = aes(x=displ, y = hwy)) +  
  facet_grid(cyl ~ .)
```





Challenge 4.2

- When using `facet_grid()` you should usually put the variable with more unique levels in the columns. Why?



(5) Geometric Objects

- Both of these plots contain the same x and y variable, and describe the same data
- The plots are not identical, they use a different visual object to represent the data
- In ggplot2 syntax, we say the use different *geoms*





geom

- A geom is a geometrical object that a plot uses to represent data
- Bar charts use **bar geoms**, line charts use **line geoms**, and scatter plots use the **point geom**.
- To change the geom in your plot, simply change the geom function that is added to the ggplot call.

Examples of using different geoms


```
ggplot(data=mpg)+  
  geom_smooth(mapping=aes(x=displ,y=hwy))
```



```
ggplot(data=mpg)+  
  geom_point(mapping=aes(x=displ,y=hwy))
```



Displaying Multiple geoms

- Multiple geoms can be displayed on the same plot
- Data can be specified in first `ggplot()` call, and shared by all geoms
- Also, different geoms can have their own data




```
ggplot(data=mpg, mapping = aes(x=displ, y= hwy)) +  
  geom_point(aes(colour=class)) + geom_smooth()
```

- Data and x,y can be defined in the first call, and then used by the different geoms
- Additional attributes can then be added for geoms (i.e. for specific layers)
- *This makes it possible to display different aesthetics in different layers*



```
ggplot(data=mpg,mapping=aes(x=displ,y=hwy))+
  geom_point(mapping=aes(colour=class))+
  geom_smooth(data=filter(mpg,class=="subcompact"),
              se=F)+
  geom_smooth(data=filter(mpg,class=="suv"),
              se=F,colour="red")
```

- Different data can be specified for each layer
- A local data argument can override a global data argument for a specific layer
- `filter()` will be explained in a subsequent lecture, it is part of `dplyr()`



Sample plot geoms

Geom	Purpose
<code>geom_smooth()</code>	Fits a smoother to data and displays the smooth and its standard error
<code>geom_boxplot()</code>	Produces a box-and-whisker plot to summarise the distribution of a set of points
<code>geom_histogram()</code> <code>geom_freqpoly()</code>	Shows the distribution of continuous variables
<code>geom_bar()</code>	Shows the distribution of categorical variables
<code>geom_path()</code> <code>geom_line()</code>	Draws lines between data points
<code>geom_area()</code>	Draws an area plot, which is a line plot filled to the y-axis. Multiple groups will be stacked upon each other
<code>geom_rect()</code> <code>geom_tile()</code> <code>geom_raster()</code>	Draw rectangles
<code>geom_polygon()</code>	Draws polygons, which are filled paths.

Challenge 4.2.2

- Will these two graphs look different. Why/why not?

```
ggplot(data=mpg,mapping=aes(x=displ,y=hwy))+  
  geom_point()+  
  geom_smooth()
```

```
ggplot()+  
  geom_point(data=mpg,mapping=aes(x=displ,y=hwy))+  
  geom_smooth(data=mpg,mapping=aes(x=displ,y=hwy))
```

diamonds data set (ggplot2)

A dataset containing the prices and other attributes of almost 54,000 diamonds.

carat	cut	color	clarity	depth	table	price	x	y	z
0.23	Ideal	E	SI2	61.5	55.0	326	3.95	3.98	2.43
0.21	Premium	E	SI1	59.8	61.0	326	3.89	3.84	2.31
0.23	Good	E	VS1	56.9	65.0	327	4.05	4.07	2.31
0.29	Premium	I	VS2	62.4	58.0	334	4.20	4.23	2.63
0.31	Good	J	SI2	63.3	58.0	335	4.34	4.35	2.75
0.24	Very Good	J	VVS2	62.8	57.0	336	3.94	3.96	2.48
0.24	Very Good	I	VVS1	62.3	57.0	336	3.95	3.98	2.47
0.26	Very Good	H	SI1	61.9	55.0	337	4.07	4.11	2.53
0.22	Fair	E	VS2	65.1	61.0	337	3.87	3.78	2.49
0.23	Very Good	H	VS1	59.4	61.0	338	4.00	4.05	2.39

Explanation of variables

Feature	Explanation
price	price in US dollars \$326–\$18,823
carat	weight of the diamond (0.2–5.01)
cut	quality of the cut (Fair, Good, Very Good, Premium, Ideal)
color	diamond colour, from J (worst) to D (best)
clarity	a measurement of how clear the diamond is (I1 (worst), SI1, SI2, VS1, VS2, VVS1, VVS2, IF (best))
x	length in mm (0–10.74)
y	width in mm (0–58.9)
z	depth in mm (0–31.8)
depth	total depth percentage = $z / \text{mean}(x, y) = 2 * z / (x + y)$ (43–79)
table	width of top of diamond relative to widest point (43–95)

Summary of dataset


```
> summary(diamonds)
```

carat		cut	color	clarity	depth		
Min.	:0.2000	Fair	: 1610	D: 6775	SI1 :13065	Min.	:43.00
1st Qu.	:0.4000	Good	: 4906	E: 9797	VS2 :12258	1st Qu.	:61.00
Median	:0.7000	Very Good	:12082	F: 9542	SI2 : 9194	Median	:61.80
Mean	:0.7979	Premium	:13791	G:11292	VS1 : 8171	Mean	:61.75
3rd Qu.	:1.0400	Ideal	:21551	H: 8304	VVS2 : 5066	3rd Qu.	:62.50
Max.	:5.0100			I: 5422	VVS1 : 3655	Max.	:79.00
				J: 2808	(Other): 2531		

table	price	x	y	z					
Min.	:43.00	Min.	: 326	Min.	: 0.000	Min.	: 0.000	Min.	: 0.000
1st Qu.	:56.00	1st Qu.	: 950	1st Qu.	: 4.710	1st Qu.	: 4.720	1st Qu.	: 2.910
Median	:57.00	Median	: 2401	Median	: 5.700	Median	: 5.710	Median	: 3.530
Mean	:57.46	Mean	: 3933	Mean	: 5.731	Mean	: 5.735	Mean	: 3.539
3rd Qu.	:59.00	3rd Qu.	: 5324	3rd Qu.	: 6.540	3rd Qu.	: 6.540	3rd Qu.	: 4.040
Max.	:95.00	Max.	:18823	Max.	:10.740	Max.	:58.900	Max.	:31.800

(6) Statistical Transformations

- Lets explore the *bar chart*: appears simple, yet reveals a subtle feature of plots
- The bar chart `geom_bar()` shows the total number of diamonds, grouped by cut
- **But where does the count come from?**



```
ggplot(data=diamonds) +  
  geom_bar(mapping = aes(x = cut))
```

Explanation

- Many graphs, like scatterplots, plot the raw values of the dataset
- However, other graphs (e.g. bar charts) calculate new values to plot
 - **Bar charts, histograms and frequency polygons** bin your data and plot bin counts, the number of points that fall in each bin
 - **Smoothers** fit a model to your data and the plot predictions from the model
 - **Boxplots** compute a robust summary of the distribution and display a specially formatted box




Overriding the default stat

- Every geom has a default stat, and every stat has a default geom.
- What is the aggregated data was already contained in 5 rows?
- **Use stat="identity"**


	cut	Count
	<ord>	<int>
1	Fair	1610
2	Good	4906
3	Very Good	12082
4	Premium	13791
5	Ideal	21551

```
ggplot(data=agr) +  
  geom_bar(mapping = aes(x = cut, y=Count),  
            stat="identity")
```




fill aesthetic for bar charts

- Bar charts can be coloured using the fill aesthetic
- When a different variable is used, the graph has further detail



```
ggplot(data=diamonds) +  
  geom_bar(mapping=aes(x=cut, fill=clarity))
```




```
ggplot(data=diamonds) +  
  geom_bar(mapping=aes(x=cut, fill=cut))
```

Stacking options


- Stacking is performed automatically by the position adjustment specified by the **position** argument
- Examples include “identity”, “fill” and “dodge”
- “fill”
 - Works like stacking, but each stacked bar is the same height
 - Makes it easier to compare proportions
- “dodge”
 - Places objects directly beside one another
 - Makes it easier to compare individual values



```
ggplot(data=diamonds) +  
  geom_bar(mapping=aes(x=cut,fill=clarity),  
            position="fill")
```




```
ggplot(data=diamonds) +  
  geom_bar(mapping=aes(x=cut,fill=clarity),  
            position="dodge")
```





Additional adjustment

- Recall our first scatterplot
- 126 points displayed, yet there are 234 observations
- Many points can overlap, so it makes it hard to see where the mass of data is
- Are all points spread equally, or is there one special combination that contains 129 values?
- “jitter” adds random noise to each point.





```
ggplot(data=mpg)+  
  geom_point(mapping=aes(x=displ,y=hwy),  
               position="jitter",colour="blue")
```




Histogram

```
ggplot(data=diamonds,mapping=aes(x=price)) +  
  geom_histogram(binwidth = 500)
```




Boxplot

- Display the distribution of a continuous variable broken down by a categorical variable
- Box that stretches from the 25th to 75th percentile a distance known as the interquartile range (IRQ)
- Median in the middle of box
- Points outside more that 1.5 times the IQR from either edge of the box are displayed (outliers)
- Whisker extends to the farthest non-outlier point in the distribution



```
ggplot(data=mpg,mapping=aes(x=class,y=hwy)) +  
  geom_boxplot()
```




(7) Coordinate Systems



- Probably the most complicated part of ggplot2
- Default is the Cartesian coordinate system where the x and y position act independently to find the location of each point
- A number of other coordinate systems can be helpful:
 - `coord_flip()`, switches the x and y axes
 - `coord_quickmap()` sets the aspect ratio correctly for maps, important for plotting spatial data



```
ggplot(data=diamonds) +  
  geom_bar(mapping = aes(x = cut)) + coord_flip()
```



```
ggplot(nz, aes(long,lat, group=group)) +  
  geom_polygon(fill="white", colour="black") +  
  coord_quickmap()
```



(8) The Layered Grammar of Graphics

- The ggplot2 approach can be summarised by a template
- It can take seven parameters, but usually not all need to be applied (defaults used)
- These seven parameters compose the grammar of graphics

```
ggplot(data=<DATA>) +  
  <GEOM_FUNCTION>(  
    mapping=aes(<MAPPINGS>),  
    stat=<STAT>,  
    position=<POSITION>  
  ) +  
  <COORDINATE_FUNCTION>+  
  <FACET_FUNCTION>
```