

# My Orders

## ORDER HISTORY: BCR

### ORDER INFORMATION

**Order Date** 03 December, 2011  
**Order Source** Internet  
**Order Confirmation Number** **13756016**  
**Account Number** 799995  
**Customer ID Number (CID)** 208289  
**PO Number** BCR

### INVOICING ADDRESS

Webb Inc.  
 46 Arabella st  
 Longueville  
 Sydney  
 NSW  
 2066  
 AU

### DELIVERY ADDRESS

UNSW  
 School of Elec Eng  
 UNSW  
 Sydney  
 NSW  
 2052  
 AU

### DELIVERY DETAILS

**Delivery Method** Same Day Despatch before 6pm (AEST) \*\*

### PAYMENT INFORMATION

**Payment Method** Credit Card

[Back To Order Summary List](#)

[Add All To Basket](#)

Order Code	Mftr. & Part No.	Qty Ordered	Qty Delivered	Ship Date	Tracking	Status	Price	Line Price
<a href="#">1648008</a>	LINEAR TECHNOLOGY LT1513-2CR#PBF	10	0			<a href="#">Back Order</a>	\$10.76	\$107.60
<b>Description:</b> BATT CHARGER, SEPIC CONST, 7D2PAK; Battery Type:Lead Acid / Li-Ion / NiCd / NiMH; Input Voltage:25V; Battery Charge Voltage:20V; Battery IC Case Style:TO-252; No. of Pins:7; Operating Temperature Range:0°C to +125°C; SVH								
<a href="#">1194362</a>	COILTRONICS DRQ125-100-R	10	0			<a href="#">Received</a>	\$3.14	\$31.40
<b>Description:</b> POWER INDUCTOR, 10UH, 5.35A, 20%; Inductance:10µH; Inductance Tolerance:± 20%; DC Resistance Max:0.0189ohm; DC Current Rating:5.35Arms; Core Material:Ferrite; Inductor Case Style:SMD; No. of Pins:4; C 27K7201								
<a href="#">9229329</a>	KEMET T495X226K035ATE275	25	0			<a href="#">Received</a>	\$2.12	\$53.00
<b>Description:</b> CAPACITOR, 22UF, 35V; Capacitance:22µF; Capacitance Tolerance:± 10%; Voltage Rating:35V; ESR:0.275ohm; Capacitor Case Style:2917; Operating Temperature Range:-55°C to +125°C; SVHC:No SVHC (20-Jun-2011); Capacitor Mountin								
<a href="#">1658891</a>	AVX 12105C475KAT2A	10	0			<a href="#">Received</a>	\$1.03	\$10.30
<b>Description:</b> CAPACITOR, 4.7 UF, 50V, 1210, X7R; Dielectric Characteristic:X7R; Capacitance:4.7µF; Capacitance Tolerance:± 10%; Voltage Rating:50V; Capacitor Case Style:1210; Capacitor Mounting:SMD; Operating Temperature Range:-55°C t								
<a href="#">1431096</a>	ON SEMICONDUCTOR MBRD340G	10	0			<a href="#">Received</a>	\$1.04	\$10.40
<b>Description:</b> DIODE, SCHOTTKY, 3A, 40V, D-PAK; Diode Type:Schottky; Repetitive Reverse Voltage Vrrm Max:40V; Forward Current If(AV):3A; Forward Voltage VF Max:600mV; Forward Surge Current Ifsm Max:75A; Diode Case Style:TO-252; No. of								
<a href="#">1671445</a>	KEMET C1206C104M5RACTU	50	0			<a href="#">Received</a>	\$0.032	\$1.60

**Description:** CAPACITOR CERAMIC, 0.1UF, 50V, X7R, 1206; Dielectric Characteristic:X7R; Capacitance:0.1µF; Capacitance Tolerance:± 20%; Voltage Rating:50V; Capacitor Case Style:1206; Capacitor Mounting:SMD 14N2184

[1362557](#) YAGEO (PHYCOMP) 10 0 [Received](#) \$0.075 \$0.75  
CC1206KKX7R9BB224

**Description:** CAPACITOR, 1206, 220NF, 50V, X7R; Dielectric Characteristic:X7R; Capacitance:0.22µF; Capacitance Tolerance:± 10%; Voltage Rating:50V; Capacitor Case Style:1206; Capacitor Mounting:SMD; Operating Temperature Range:-55°C t

[1107357](#) VISHAY DALE 5 0 [Back Order](#) \$1.16 \$5.80  
WSL1206R0800FEB

**Description:** RESISTOR, METAL STRIP, 0.08 OHM 1%; Resistance:0.08ohm; Resistance Tolerance:± 1%; Power Rating:250mW; Voltage Rating:140mV; Temperature Coefficient:± 70ppm/°C; Resistor Element Material:Solid Metal Nickel-Chrome or Mang

[9336257](#) MULTICOMP 50 0 [Received](#) \$0.008 \$0.40  
MC 0.125W 1206 1%  
270R

**Description:** RESISTOR, 1206 270R; Resistance:270ohm; Resistance Tolerance:± 1%; Power Rating:125mW; Voltage Rating:200V; Temperature Coefficient:± 100ppm/°C; Resistor Element Material:Thick Film; Resistor Case Style:1206; Resistor Mo

[9336508](#) MULTICOMP 50 0 [Back Order](#) \$0.008 \$0.40  
MC 0.125W 1206 1%  
39R

**Description:** RESISTOR, 1206 39R; Resistance:39ohm; Resistance Tolerance:± 1%; Power Rating:125mW; Voltage Rating:200V; Temperature Coefficient:± 200ppm/°C; Resistor Element Material:Thick Film; Resistor Case Style:1206; Resistor Moun

[1501718](#) TE CONNECTIVITY / 10 0 [Back Order](#) \$3.34 \$33.40  
HOLSWORTHY  
RP73D2B12K4BTG

**Description:** RESISTOR, 1206, 12K4 0.1% 15PPM; Resistance:12.4kohm; Resistance Tolerance:± 0.1%; Power Rating:250mW; Voltage Rating:200V; Temperature Coefficient:± 15ppm/°C; Resistor Element Material:Thin Film; Resistor Case Style:120

[4663329](#) HAKKO 2 [Received](#) \$18.63 \$37.26  
599B-02

**Description:** CLEANER, SOLDERING IRON TIP; Accessory Type:Cleaning wire; For Use With:FX-838

[1356132](#) LINDSTROM 1 [Back Order](#) \$139.05 \$139.05  
8152

**Description:** CUTTER, OVAL HEAD, ULTRA; Overall Length:112.5mm; Cutter Type:Diagonal; Cut Type:Ultra Flush; Cutting Capacity Max:1.25mm; Cutting Edge Hardness:65°; SVHC:No SVHC (20-Jun-2011)

[1219335](#) PRO POWER 1 [Received](#) \$33.08 \$33.08  
MC6A-1/0.6T2-BK-100

**Description:** WIRE, BLACK, 1/0.6MM, 100M; Reel Length (Imperial):328ft; Reel Length (Metric):100m; Conductor Area CSA:0.28mm²; Jacket Colour:Black; Jacket Material:PVC (Polyvinyl Chloride); Conductor Material:Copper; External Diameter

[Back To Order Summary List](#)

[Add All To Basket](#)

**Goods Subtotal:** \$464.44

**GST:** \$46.44

**Total:** \$510.88

#### LINE STATUS DEFINITIONS

Status	Definition
--------	------------

<b>Pending</b>	Your order has been received.
<b>Received</b>	Your order has been assigned an order number and is currently being processed.
<b>Complete</b>	Your order has been processed and shipped.
<b>Processing</b>	Your order is being processed.
<b>Shipped</b>	This item has been processed and shipped.
<b>Partially shipped</b>	Part of this item has been shipped.
<b>Back Order</b>	This item is on back order and will be despatched when stock is available.
<b>Scheduled</b>	This item is scheduled for delivery at a future date.
<b>Cancelled</b>	This item has been cancelled.

**Hotline: 1300 361 005 | Contact Us**

[Shop](#) | [Community](#) | [Live Technical Support](#) | [About Us](#) | [Help](#) | [Sitemap](#) | [Privacy Statement](#) | [Terms & Conditions](#) | [Terms Of Use](#) | [REACH/RoHS](#)

Copyright © 2007 Premier Farnell plc ALL RIGHTS RESERVED Copyright in the whole and every part of this website belongs to Premier Farnell plc ("the Owner") and may not be used, sold, licensed, transferred, copied or reproduced in the whole or in part of any manner or form or in or on any media to any person other than in accordance with the terms of the Owner's agreement, without prior written consent of the owner.

element14 is a trading name of element14 Pty Ltd, ACN 003 211 345 , PMB 6, Chester Hill NSW 2162, Australia