Project B

Δημήτριος Τσιομπίκας ΑΜ: 3180223

Ζήτημα Πρώτο

Άσκηση 1

Κώδικας βάσης:

```
∃CREATE TABLE campdata(
     custID int,
     fname varchar(30),
     lname varchar(30),
     cID int,
     country varchar(30),
     bookID int,
     bookDate date,
     campCode char(3),
     campName varchar(50),
     empno int,
     catCode char(1),
     category varchar(20),
     unitCost numeric(4,2),
     startDate date,
     overnights int,
     persons int
BULK INSERT campdata
 WITH (FIRSTROW =2, FIELDTERMINATOR='\', ROWTERMINATOR = '\n');
```

Επέλεξα για λογικό πλάνο τους εξής πίνακες :

Dimension tables: customer, Camp, Emplacement, timeinfo


Fact table : Booking

Εντολές :

```
CREATE TABLE customer
     custID int,
    fname varchar(30),
     lname varchar(30),
     cID int,
     country varchar(30),
    PRIMARY KEY(custID, cID)
CREATE TABLE Camp(
    campCode char(3) primary key,
     campName varchar(50)
CREATE TABLE Emplacement(
    empno int,
    catCode char(1),
    category varchar(20),
    PRIMARY KEY(empno, catCode)
CREATE TABLE timeinfo(
    time key datetime primary key,
    t_year int,
    t_month int,
    t_dayofmonth int,
    t_hour int,
    t_quarter int,
    t_week int,
    t_dayofyear int,
    t_dayofweek int
```

```
OCREATE TABLE Booking( /* Fact table */
    custID int,
    cID int,
    campCode char(3),
    empno int,
    time key datetime,
    catCode char(1),
    bookID int,
    bookDate datetime,
    unitCost numeric(4,2),
    overnights int,
    persons int,
    PRIMARY KEY(custID,cID,campCode,empno,time_key,catCode,bookID),
    FOREIGN KEY(custID,cID) REFERENCES customer(custID,cID),
    FOREIGN KEY(campCode) REFERENCES Camp(campCode),
    FOREIGN KEY(empno,catCode) REFERENCES Emplacement(empno,catCode),
    FOREIGN KEY(time_key) REFERENCES timeinfo(time_key)
```

```
/* Gemisma pinakwn */
INSERT INTO customer
 SELECT DISTINCT custID, fname, lname, cID, country
 FROM campdata;
□INSERT INTO Camp
 SELECT DISTINCT campCode, campName
 FROM campdata;
INSERT INTO Emplacement
 SELECT DISTINCT empno, catCode, category
 FROM campdata;
 SET datefirst 1;
insert INTO timeinfo
 SELECT DISTINCT startDate,DATEPART(year,startDate),DATEPART(month,startDate),
 DATEPART(day,startDate),DATEPART(hour,startDate),DATEPART(quarter,startDate),
 DATEPART(week, startDate), DATEPART(dayofyear, startDate), DATEPART(dw, startDate)
 FROM campdata;
SELECT DISTINCT custID, cID, campCode, empno, startDate, catCode, bookID, bookDate,
 unitCost, overnights, persons
 FROM campdata;
```



Ζήτημα Δεύτερο

Άσκηση 1

```
/* Query 1 */

SELECT TOP 100 country, fname, lname, SUM(unitCost * overnights * persons) AS BookingCost

FROM customer, Booking

WHERE customer.cID = Booking.cID AND customer.custID = Booking.custID

GROUP BY country, fname, lname

ORDER BY BookingCost DESC;
```

```
/* Query 2 */
□SELECT campName,category,SUM(unitCost * overnights * persons) AS BookingCost
FROM Emplacement,Camp,Booking,timeinfo
WHERE Emplacement.empno = Booking.empno AND Emplacement.catCode = Booking.catCode AND Camp.campCode = Booking.campCode
AND timeinfo.time_key = Booking.time_key AND t_year = 2000
GROUP BY category,campName;
```

```
/* Query 3 */
3SELECT campName,t_month,SUM(unitCost * overnights * persons) AS BookingCost
FROM Camp,timeinfo,Booking
WHERE Camp.campCode = Booking.campCode AND timeinfo.time_key = Booking.time_key AND t_year = 2018
GROUP BY campName,t_month
ORDER BY campName,t_month;
```

```
/* Query 4 */
ESELECT t_year,campName,category,COUNT(persons) AS totalPersonCount
FROM Booking,timeinfo,Camp,Emplacement
WHERE timeinfo.time_key = Booking.time key AND Camp.campCode = Booking.campCode AND
Emplacement.empno = Booking.empno AND Emplacement.catCode = Booking.catCode
GROUP BY ROLLUP (t_year,campName,category);
```

- (t_year,campName,category) (group by t_year,campName,category)
- (t_year,campName,null) (group by t_year,campName)
- (t_year,null,null) (group by t_year)
- (null,null,null) (group by none)

```
CREATE VIEW v1 AS
 SELECT t_year,campName,COUNT(persons) AS totalPersonCount
 FROM timeinfo , Booking, Camp
 WHERE timeinfo.time_key = Booking.time_key AND Camp.campCode = Booking.campCode
 AND t_year = 2017
 GROUP BY t_year,campName;
CREATE VIEW v2 AS
 SELECT t_year,campName,COUNT(persons) AS totalPersonCount
 FROM timeinfo , Booking, Camp
 WHERE timeinfo.time_key = Booking.time_key AND Camp.campCode = Booking.campCode
 AND t_year = 2018
 GROUP BY t_year,campName;
FROM v1, v2
 WHERE v1.campName = v2.campName AND v2.totalPersonCount > v1.totalPersonCount
 GROUP BY v2.campName;
```

Ζήτημα Τρίτο

Επερώτηση: εμφάνισε το συνολικό ποσό πληρωμών κρατήσεων για έναν συνδυασμό στηλών (t_year, campName,category), περισσότερα παρακάτω:

```
/* Ζήτημα Τρίτο */

SELECT t_year,campName,category,SUM(unitCost * overnights * persons) AS totalBookingCosts
FROM timeinfo,Camp,Booking,Emplacement
WHERE timeinfo.time_key = Booking.time_key AND Camp.campCode = Booking.campCode
AND Emplacement.catCode = Booking.catCode
GROUP BY CUBE(t_year,campName,category);
```

Το αποτέλεσμα της επερώτησης είναι η δημιουργία ενός κύβου, κάθε κελί του οποίου περιέχει τα συνολικά ποσά πληρωμών κρατήσεων για έναν συνδυασμό τιμών (έτους, Κατασκήνωσης, κατηγορίας θέσης), πιο συγκεκριμένα:

- t_year,campName,category (group by t_year,campName,category)
- t_year,campName,null (group by t_year,campName)
- t year,null,category (group by t year,category)
- null, campName, category (group by campName, category)
- t_year,null,null (group by t_year)
- null,campName,null (group by campName)
- null,null,category (group by category)
- null,null,null (group by none)

Ζήτημα Τέταρτο

Ο πίνακας θα έχει την εξής μορφή (το ευρετήριο είναι στη στήλη country):

	Austria	Denmark	Germany	Spain	Finland	Sweden	Italy	France	Netherlands	Belgium
Row#										
69	0	0	0	1	0	0	0	0	0	0
70	0	0	0	1	0	0	0	0	0	0
71	0	1	0	0	0	0	0	0	0	0
72	1	0	0	0	0	0	0	0	0	0
73	1	0	0	0	0	0	0	0	0	0
74	0	0	1	0	0	0	0	0	0	0
75	0	0	1	0	0	0	0	0	0	0
76	0	0	1	0	0	0	0	0	0	0