

Uploading the MIRS Laravel App to a Redkite S

Generated 2026-05-31

Prepared for deploying the Material Inspection Recording System to a z.com/cPanel subdomain such as mirs.redkite.com.ph.

NOTE: Important difference from WordPress: WordPress is usually uploaded directly into public_html. Laravel should not be deployed that way. Only Laravel's public folder should be visible to browsers.

1. Recommended Folder Layout

Use two server folders: one private folder for the Laravel application, and one public folder for the subdomain document root.

```
/home/YOUR_CPANEL_USER/mirs_app/  
  app/  
  bootstrap/  
  config/  
  database/  
  public/  
  resources/  
  routes/  
  storage/  
  vendor/  
  .env  
  artisan  
  composer.json  
  composer.lock  
  
/home/YOUR_CPANEL_USER/public_html/mirs/  
  index.php  
  .htaccess  
  build/  
  favicon.ico  
  robots.txt
```

2. Files to Upload

Upload: app, bootstrap, config, database, public, resources, routes, storage, vendor, artisan, composer.json, composer.lock, and .env.

Do not upload: .git, node_modules, tests, temp_backup, local-only notes, or temporary helper files.

3. Create the Subdomain in z.com/cPanel

- Log in to z.com and open cPanel.
- Go to Domains and create the subdomain, for example mirs.redkite.com.ph.
- Set the document root to public_html/mirs.
- If cPanel offers Share document root, leave it unchecked.

4. Build the Frontend Before Uploading

Run this locally from the project folder before uploading:

```
npm run build
```

This creates production frontend files inside public/build. The public/build folder must be uploaded with the other public files.

5. Upload the App

- Upload the Laravel project files to /home/YOUR_CPANEL_USER/mirs_app.
- Upload the contents of the local public folder to /home/YOUR_CPANEL_USER/public_html/mirs.
- Make sure hidden files are included, especially .htaccess.
- Do not put .env, app, config, database, storage, or vendor inside the public_html/mirs folder.

6. Edit public_html/mirs/index.php

On the server, open /home/YOUR_CPANEL_USER/public_html/mirs/index.php and update the Laravel paths.

Change this:

```
require __DIR__.'/../vendor/autoload.php';  
$app = require_once __DIR__.'/../bootstrap/app.php';
```

To this typical cPanel layout:

```
require __DIR__.'/../../mirs_app/vendor/autoload.php';  
$app = require_once __DIR__.'/../../mirs_app/bootstrap/app.php';
```

The exact number of ../ segments depends on the real cPanel path. The goal is for index.php in the public folder to load vendor/autoload.php and bootstrap/app.php from the private Laravel folder.

7. Create and Import the Database

- In cPanel, open MySQL Databases or MySQL Database Wizard.
- Create a database, database user, and password.
- Assign the user to the database with full privileges.
- Export the current local database from XAMPP phpMyAdmin.
- Import the SQL file into the z.com database using phpMyAdmin.

8. Configure .env on the Server

```
APP_NAME="Material Inspection Recording System"
APP_ENV=production
APP_DEBUG=false
APP_URL=https://mirs.redkite.com.ph
```

```
DB_CONNECTION=mysql
DB_HOST=localhost
DB_PORT=3306
DB_DATABASE=your_cpanel_database
DB_USERNAME=your_cpanel_database_user
DB_PASSWORD=your_database_password

SESSION_SECURE_COOKIE=true
```

9. Run Laravel Commands If SSH Is Available

```
php artisan key:generate
php artisan config:cache
php artisan route:cache
php artisan view:cache
php artisan storage:link
```

If z.com does not provide SSH or Terminal access, deployment is still possible, but Composer and artisan tasks must be handled locally or through available cPanel tools.

10. No-Index Safeguards Included

The project includes these search engine no-index safeguards:

- public/robots.txt blocks crawling with Disallow: /.
- The main Blade layout includes a robots meta tag: noindex, nofollow, noarchive, nosnippet.
- Laravel responses include X-Robots-Tag: noindex, nofollow, noarchive, nosnippet.
- public/.htaccess adds the same X-Robots-Tag header for Apache-hosted public/static files when mod_headers is enabled.

NOTE: Security reminder: no-index is not the same as private access. It tells search engines not to index the app. For this phase, use Laravel login plus no-index. For stricter employee-only access later, add cPanel password protection, office-IP restrictions, Cloudflare Access, or VPN access.

11. Launch Checklist

- Subdomain created, e.g. mirs.redkite.com.ph.
- Subdomain document root points to the copied Laravel public files.
- index.php paths point to the private Laravel folder.
- .env uses production settings and z.com database credentials.
- Database imported successfully.
- public/build exists after npm run build.
- HTTPS is enabled.
- No-index safeguards are uploaded.
- The app login page loads correctly.