



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the *Copyright Act 1968* (the Act).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.



FIT3080 – Intelligent Systems

Intelligent Agents Chapter 2

Outline


- **Agents and environments**
- **Rationality**
- **PEAS (Performance measure, Environment, Actuators, Sensors)**
- **Environment types**
- **Agent types**

Agents

- **An agent is anything that can be viewed as perceiving its environment through sensors and acting upon that environment through actuators**
- **Human agent:**
 - eyes, ears and other organs for sensors
 - hands, legs, mouth and other body parts for actuators
- **Robotic agent:**
 - cameras and infrared range finders for sensors
 - various motors for actuators




Agents and Environments



- The **agent function** maps from percept histories to actions: $f: \mathcal{P}^* \rightarrow \mathcal{A}$
- The **agent program** runs on the physical **architecture** to produce f
- **agent = architecture + program**

Example: Vacuum-cleaner World and Agent



- **Percepts:** location and contents, e.g., [A,Dirty]
- **Actions:** *Left, Right, Suck*
- **Program:**
 - If** *status=Dirty* **return** Suck
 - Elseif** *Location=A* **return** Right
 - Elseif** *Location=B* **return** Left



Rationality and Rational Agents

- **Rationality depends on**

- Performance measure
- The agent's prior knowledge of the environment
- The actions that the agent can perform
- The percept sequence to date

- **Definition:**

*For each possible **percept sequence**, a rational agent should select an **action** that is expected to maximize its **performance measure**, given the evidence provided by the **percept sequence** and the agent's **built-in knowledge***



Rational Agents

- Rationality is NOT omniscience
- Agents can perform actions to modify future percepts in order to obtain useful information
→ **exploration, learning**
- An agent is **autonomous** if its behavior is determined by its own experience

Task Environment – PEAS

To design a rational agent, we must specify the Task Environment

- **PEAS**
 - Performance measure
 - Environment
 - Actuators
 - Sensors



PEAS – Example (I)

Automated taxi driver:

- **Performance measure**
 - Safe, fast, legal, comfortable trip, minimize fuel consumption, maximize profits
- **Environment**
 - Road types, road contents, customers, operating conditions
- **Actuators**
 - Control over the car, communication with other vehicles and passengers
- **Sensors**
 - Cameras, sonar, speedometer, GPS, odometer, engine sensors, speech recognizer

PEAS – Example (II)

Internet shopping agent:

- **Performance measure**
 - cheap, good quality, appropriate product
- **Environment**
 - current WWW sites, vendors
- **Actuators**
 - display to user, follow URL, fill in form
- **Sensors**
 - HTML pages (text, graphics, scripts)

Environment Types (I)

The environment type largely determines the agent design

- **Fully (partially) observable** – An agent's sensors give it access to the complete state of the environment at all times
- **Known (unknown)** – An agent knows the “laws” of the environment
- **Single (multi) agent** – An agent operating by itself in an environment
- **Deterministic (stochastic)** – The next state is completely determined by the current state and the action executed by the agent

Environment Types (II)

- **Episodic (sequential)** – The agent's experience is divided into atomic *episodes*. The next episode does NOT depend on previous actions
 - In each episode an agent perceives a percept and performs a single action
- **Static (dynamic)** – The environment is unchanged while an agent is deliberating
- **Discrete (continuous)** – Pertains to number of states, the way time is handled, and number of percepts and actions
 - E.g., state may be continuous, but actions may be discrete

Environment Types – Examples

| | Sorting laundry | 8-puzzle | Back-gammon | Medical diagnosis | Taxi |
|----------------|-----------------|----------|-------------|-------------------|------|
| Observable? | | | | | |
| Known? | | | | | |
| Single agent? | | | | | |
| Deterministic? | | | | | |
| Episodic? | | | | | |
| Static? | | | | | |
| Discrete? | | | | | |

The real world is partially observable, unknown, multi-agent, stochastic, sequential, dynamic, continuous

Environments and Methodologies

| | Search | Logical inference | Bayesian networks | Markov decision processes | Reinforcement learning |
|-----------------------|--------|-------------------|-------------------|---------------------------|------------------------|
| Observable? | ✓ | ✓ | | ✓ | ✓ |
| Known? | ✓ | ✓ | ✓ | ✓ | x |
| Single agent? | | | | | |
| Deterministic? | ✓ | ✓ | x | x | x |
| Episodic? | | | | | |
| Static? | ✓ | ✓ | ✓ | ✓ | ✓ |
| Discrete? | ✓ | ✓ | ✓ | ✓ | ✓ |

Agent Functions and Programs

- An agent is completely specified by the agent function that maps percept sequences to actions
- Aim: design a program that implements the rational agent function concisely



Agent Types

Based on the function = how actions are selected

| Agent Type | Action selected based on |
|-----------------|--------------------------|
| Simple reflex | current percept |
| Model based | + internal state |
| Goal based | + goal |
| Utility based | + utility function |
| Learning | |

How Components of Agent Programs Work?

Depends on the representations of states:

- **Atomic** – each state is indivisible (Search, Game playing, Markov Decision Processes)
- **Factored** – splits each state into attributes, each of which has a value (Propositional logic, Planning, Bayesian Networks, Machine learning)
- **Structured** – represents how things are related to each other (First order logic, Bayesian networks, Semantic networks)

Summary (I)

- **Agents interact with environments through actuators and sensors**
- **Agent function – describes what the agent does in all circumstances**
- **Agent program – implements the agent function in an architecture**
- **Performance measure – evaluates the behaviour of an agent in an environment**
- **A perfectly rational agent maximizes expected value of the performance measure**

Summary (II)

- **PEAS define task environments:**
 - performance, environment, actuators, sensors
- **Environments are categorized along several dimensions:**
 - observable? known? single-agent? deterministic?
episodic? static? discrete?
- **Basic agent architectures:**
 - reflex, reflex with state, goal-based, utility-based
 - learning
- **Types of states:**
 - atomic, factored, structured



Reading

- Russell, S. and Norvig, P. (2010), *Artificial Intelligence* – Chapter 2

Next Lecture Topic

- **Lecture Topic 2**
 - Problem Solving as Search