



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the *Copyright Act 1968* (the Act).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.



FIT3080 – Intelligent Systems

Knowledge Representation Chapters 7-9

Knowledge Representation: Learning Objectives

- **Knowledge-based agents**
- **Logic in general – models and entailment**
- **Propositional (Boolean) logic**
- **Equivalence, validity, satisfiability**
- **First-order logic**
- **Inference rules and theorem proving**
 - forward chaining
 - backward chaining
 - resolution refutation systems
 - > substitution
 - > unification
 - > resolution

Assumptions about the Environment


- **Observable**
- **Known**
- **Single/multi agent**
- **Deterministic**
- **Sequential/episodic**
- **Static**
- **Discrete**



Knowledge Representation

- **How do we represent facts about the world?**
- **How do we reason about these facts?**
- **Some widely accepted formal calculi**
 - Propositional logic
 - First-order logic
 - Probability calculus

Knowledge Bases



- **Knowledge base = set of sentences in a formal language**
- **Declarative approach to building an agent:**
 - **Tell** it what it needs to know
 - **Ask** it a question – answers follow by inference from the KB
- **Agents may be viewed**
 - at the **knowledge level** – what they know
 - at the **implementation level** – data structures in the KB and algorithms that manipulate them

A Simple Knowledge-based Agent

```
function KB-AGENT(percept) returns an action
  static: KB, a knowledge base
         t, a counter, initially 0, indicating time

  TELL(KB, MAKE-PERCEPT-SENTENCE(percept, t))
  action ← ASK(KB, MAKE-ACTION-QUERY(t))
  TELL(KB, MAKE-ACTION-SENTENCE(action, t))
  t ← t + 1
  return action
```

- **The agent must be able to:**
 - Represent states, actions, etc
 - Incorporate new percepts
 - Update internal representations of the world
 - Deduce hidden properties of the world
 - Deduce appropriate actions



Logic in General


- **Logics are formal languages for representing information such that conclusions can be drawn**
- **Syntax defines the sentences in the language**
- **Semantics define the meaning of sentences,**
 - i.e., the **truth** of a sentence in each **possible world**
- **E.g., the language of arithmetic**
 - $x+2 \geq y$ is a sentence; $x^2+y > \{ \}$ is not a sentence
 - $x+2 \geq y$ is true in all the worlds where the number $x+2$ is no less than the number y
 - $x+2 \geq y$ is true in a world where $x = 7, y = 1$
 - $x+2 \geq y$ is false in a world where $x = 0, y = 6$

Entailment

- Entailment means that one thing **follows logically** from another:
 $KB \models \alpha$
knowledge base KB entails sentence α iff
 α is true in all worlds where KB is true
- E.g.,
 - the KB containing “the Giants won” and “the Reds won” entails “the Giants won or the Reds won”
 - $x+y = 4$ entails $4 = x+y$
- Entailment is a relationship between sentences (i.e., **syntax**) that is based on **semantics**

Models

- **Models are formally structured worlds with respect to which truth can be evaluated**
- **If a sentence α is true in a model m , we say that**
 - m **is a model of** α , or
 - m **satisfies** α
- **$M(\alpha)$ = the set of all models of α**
 - $KB \models \alpha$ iff $M(KB) \subseteq M(\alpha)$
 - > E.g., KB = Giants won & Reds won
 - α = Giants won



Inference

- $KB \vdash_i \alpha$ means that sentence α can be derived from KB by procedure i
- **Soundness:** procedure i is sound if whenever $KB \vdash_i \alpha$, it is also true that $KB \models \alpha$
- **Completeness:** procedure i is complete if whenever $KB \models \alpha$, it is also true that $KB \vdash_i \alpha$
- **First-order logic (FOL)** is expressive enough to say almost anything of interest, and there exists a sound and complete inference procedure for it

Grounding

The connection between logical reasoning processes and real environments

- **How do we know that KB is true in the real world?**
 - The agent's sensors create a connection, i.e., the meaning and truth of percept sentences are defined by the processes of sensing and sentence construction
- **Where do we get the rest of an agent's knowledge?**
 - By learning (generalizing) from experience



FIT3080 – Intelligent Systems

Propositional Logic

Propositional Logic: Some Definitions

- **Literal:** a proposition or its negation
 - E.g., P , $\neg P$
- **Clause:** a disjunction of literals
 - E.g., $\neg P \vee Q \vee A$

Propositional Logic: Syntax

- **Propositional logic is the simplest logic**
- **The proposition symbols P_1, P_2, \dots are sentences**
 - **Negation:** If S is a sentence, $\neg S$ is a sentence
 - **Conjunction:**
If S_1 and S_2 are sentences, $S_1 \wedge S_2$ is a sentence
 - **Disjunction:**
If S_1 and S_2 are sentences, $S_1 \vee S_2$ is a sentence
 - **Implication:**
If S_1 and S_2 are sentences, $S_1 \Rightarrow S_2$ is a sentence
 - **Biconditional:**
If S_1 and S_2 are sentences, $S_1 \Leftrightarrow S_2$ is a sentence



Propositional Logic: Semantics

- **Each model specifies true/false for each proposition**

– E.g.,

S_1	S_2	S_3
false	true	false

- **Rules for evaluating truth with respect to a model m :**

$\neg S$ is true iff S is false

$S_1 \wedge S_2$ is true iff S_1 is true and S_2 is true

$S_1 \vee S_2$ is true iff S_1 is true or S_2 is true

$S_1 \Rightarrow S_2 \equiv \neg S_1 \vee S_2$ is true iff S_1 is false or S_2 is true

$S_1 \Leftrightarrow S_2$ is true iff $S_1 \Rightarrow S_2$ is true and $S_2 \Rightarrow S_1$ is true

- **Simple recursive process evaluates an arbitrary sentence**

– E.g.,

$\neg S_1 \wedge (S_2 \vee S_3) = \text{true} \wedge (\text{true} \vee \text{false}) = \text{true} \wedge \text{true} = \text{true}$



Truth Tables for Connectives

P	Q	$\neg P$	$P \wedge Q$	$P \vee Q$	$P \Rightarrow Q$	$P \Leftrightarrow Q$
false	false	true	false	false	true	true
false	true	true	false	true	true	false
true	false	false	false	true	false	false
true	true	false	true	true	true	true



Logical Equivalence

- Two sentences are **logically equivalent** iff they are both true in the same models: $\alpha \equiv \beta$ iff $\alpha \models \beta$ and $\beta \models \alpha$

$(\alpha \wedge \beta) \equiv (\beta \wedge \alpha)$	commutativity of \wedge
$(\alpha \vee \beta) \equiv (\beta \vee \alpha)$	commutativity of \vee
$((\alpha \wedge \beta) \wedge \gamma) \equiv (\alpha \wedge (\beta \wedge \gamma))$	associativity of \wedge
$((\alpha \vee \beta) \vee \gamma) \equiv (\alpha \vee (\beta \vee \gamma))$	associativity of \vee
$\neg(\neg\alpha) \equiv \alpha$	double-negation elimination
$(\alpha \Rightarrow \beta) \equiv (\neg\beta \Rightarrow \neg\alpha)$	contraposition
$(\alpha \Rightarrow \beta) \equiv (\neg\alpha \vee \beta)$	implication elimination
$(\alpha \Leftrightarrow \beta) \equiv ((\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha))$	biconditional elimination
$\neg(\alpha \wedge \beta) \equiv (\neg\alpha \vee \neg\beta)$	de Morgan
$\neg(\alpha \vee \beta) \equiv (\neg\alpha \wedge \neg\beta)$	de Morgan
$(\alpha \wedge (\beta \vee \gamma)) \equiv ((\alpha \wedge \beta) \vee (\alpha \wedge \gamma))$	distributivity of \wedge over \vee
$(\alpha \vee (\beta \wedge \gamma)) \equiv ((\alpha \vee \beta) \wedge (\alpha \vee \gamma))$	distributivity of \vee over \wedge



Validity and Satisfiability

- **A sentence is valid if it is true in all models**
 - E.g., *True*, $A \vee \neg A$, $A \Rightarrow A$
- **Validity is connected to inference via the Deduction Theorem**
 - $\alpha \models \beta$ iff $\alpha \Rightarrow \beta$ is valid
- **A sentence is satisfiable if it is true in some model**
 - E.g., $A \vee B$, C
- **A sentence is unsatisfiable if it is true in no models**
 - E.g., $A \wedge \neg A$
- **Satisfiability and validity are connected**
 - α is valid iff $\neg \alpha$ is unsatisfiable
 - α is satisfiable iff $\neg \alpha$ is not valid
 - $\alpha \models \beta$ iff $\alpha \wedge \neg \beta$ is unsatisfiable



Proof Methods

- **Model checking**

Enumerates all possible models to check that a sentence α is true in all models where KB is true

- **Truth table enumeration** (2^n , where n is the number of symbols)
- **Backtracking** (recursive enumeration of all models) with logic-related heuristics

- **Application of inference rules**

Sound generation of new sentences from old

- **Proof** = a sequence of inference rule applications
 - > use inference rules as operators in a standard search algorithm
 - > typically require transformation of sentences into a ***normal form***

Common Rules of Inference

Parent clauses	Resolvent	Name
P and $\neg P \vee Q$	Q	Modus Ponens
$\neg Q$ and $\neg P \vee Q$	$\neg P$	Modus Tollens
P and Q	P or Q	And Elimination
$P \vee Q$ and $\neg P \vee Q$	Q	
$P \vee Q$ and $\neg P \vee \neg Q$	$Q \vee \neg Q$ or $P \vee \neg P$	Tautology
P and $\neg P$	NIL	
$\neg P \vee Q$ and $\neg Q \vee R$	$\neg P \vee R$	Chaining
$P \vee Q$ and $\neg P \vee R$	$Q \vee R$	

Proof as Search

- **Initial state:** initial KB
- **Actions:** the inference rules applied to all the sentences that match the lhs of the rule
- **Result:** add the sentence on the rhs of a rule to the KB
- **Goal:** a state where the KB contains the sentence we are trying to prove

Monotonicity: the set of entailed sentences can only increase as information is added to the KB

Resolution

- **Resolution** – an inference rule applied to clauses that yields a complete inference algorithm when coupled with any complete search algorithm

$$\frac{l_1 \vee \dots \vee \textcircled{l_i} \vee \dots \vee l_k \qquad m_1 \vee \dots \vee \textcircled{m_j} \vee \dots \vee m_n}{l_1 \vee \dots \vee l_{i-1} \vee l_{i+1} \vee \dots \vee l_k \vee m_1 \vee \dots \vee m_{j-1} \vee m_{j+1} \vee \dots \vee m_n}$$

- where l_i and m_j are **complementary literals** ($l_i = \neg m_j$)
 - the resultant clause should contain only one copy of each literal
- **Resolution is sound for propositional logic**

Conversion to Conjunctive Normal Form

- **Every sentence in propositional logic is logically equivalent to a conjunction of clauses**
- **Converting a sentence to Conjunctive Normal Form (CNF)**
 1. Eliminate \Leftrightarrow , replacing $\alpha \Leftrightarrow \beta$ with $(\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)$
 2. Eliminate \Rightarrow , replacing $\alpha \Rightarrow \beta$ with $\neg \alpha \vee \beta$
 3. Move \neg inwards by repeated application of the following equivalences:
 - > double-negation: $\neg (\neg \alpha) \equiv \alpha$
 - > de Morgan $\neg(\alpha \wedge \beta) \equiv \neg \alpha \vee \neg \beta$
 - > de Morgan $\neg(\alpha \vee \beta) \equiv \neg \alpha \wedge \neg \beta$
 4. Apply distributivity law (\wedge over \vee) and flatten

Resolution-refutation Systems

- **Proof by refutation**

1. Negate the goal and add the negation to the set of clauses
2. Apply resolution to the clauses in the set of clauses until a contradiction is reached

- **Answer extraction**

1. Build a tautology by appending the goal itself to the negation of the goal
2. When the negated goal is contradicted, the answer resides in the goal


Resolution-refutation Algorithm

- **Proof by contradiction, i.e., given a goal α , show that $KB \wedge \neg\alpha$ is unsatisfiable**

```
function PL-RESOLUTION( $KB, \alpha$ ) returns true or false  
   $clauses \leftarrow$  the set of clauses in the CNF representation of  $KB \wedge \neg\alpha$   
   $new \leftarrow \{ \}$   
  loop do  
    for each  $C_i, C_j$  in  $clauses$  do  
       $resolvents \leftarrow$  PL-RESOLVE( $C_i, C_j$ )  
      if  $resolvents$  contains the empty clause then return true  
       $new \leftarrow new \cup resolvents$   
    if  $new \subseteq clauses$  then return false  
     $clauses \leftarrow clauses \cup new$ 
```

Resolution-refutation – Example

- $KB = (A \Leftrightarrow (B \vee C)) \wedge \neg A$
 $(\neg A \vee B \vee C) \wedge (\neg B \vee A) \wedge (\neg C \vee A) \wedge \neg A$
- Prove: $\alpha = \neg B$



Soundness and Completeness

Resolution refutation is sound and complete

- **Resolution Closure** $RC(S)$ of a set of clauses S is the set of all clauses derivable by repeated application of the resolution rule to the clauses in S or their derivatives
 - $RC(S)$ is finite \rightarrow Resolution always terminates
- **Ground resolution theorem:** if a set of clauses is unsatisfiable, then the resolution closure of those clauses contains the empty clause
 \rightarrow Resolution-refutation is complete for propositional logic

Horn Clauses and Definite Clauses

- **Definite clause** – a disjunction of literals of which exactly one is positive
 - E.g., $\neg A \vee \neg B \vee C$
 - Definite clauses can be written as implications $(A \wedge B) \Rightarrow C$
- **Horn clause** – a disjunction of literals of which at most one is positive
 - All definite clauses are Horn clauses
 - Clauses with no positive literals are **goal clauses**
 - Inference with Horn clauses can be done with **forward** or **backward** chaining
 - Deciding entailment with Horn clauses can be done in time that is linear on the size of the KB

Forward Chaining Algorithm

- **IDEA: Work forwards from the facts in KB**

```
function PL-FC-ENTAILS?(KB, q) returns true or false
  local variables: count, a table, indexed by clause, initially the number of premises
                  inferred, a table, indexed by symbol, each entry initially false
                  agenda, a list of symbols, initially the symbols known to be true

  while agenda is not empty do
    p ← POP(agenda)
    unless inferred[p] do
      inferred[p] ← true
      for each Horn clause c in whose premise p appears do
        decrement count[c]
        if count[c] = 0 then do
          if HEAD[c] = q then return true
          PUSH(HEAD[c], agenda)

  return false
```


Forward chaining is sound and complete for Horn KBs

Forward Chaining – Example

- KB:**

- R1: $P \Rightarrow Q$
- R2: $L \wedge M \Rightarrow P$
- R3: $B \wedge L \Rightarrow M$
- R4: $A \wedge P \Rightarrow L$
- R5: $A \wedge B \Rightarrow L$
- A
- B

- Prove Q**



Agenda	Count	Inferred
	R R R R R 1 2 3 4 5	
A B	1 2 2 2 2	
B	1 2 2 1 1	A

L

M

Backward Chaining


- **IDEA: Work backwards from the query q :**
 - to prove q by Backward Chaining, check if q is known already, or prove by Backward Chaining all premises of some rule concluding q
- **Avoid loops: check if new subgoal is already on the goal stack**
- **Avoid repeated work: check if a new subgoal**
 1. has already been proved true, or
 2. has already failed

Backward chaining is sound and complete for Horn KBs

Backward Chaining – Example

- **KB:**

- R1: $P \Rightarrow Q$
- R2: $L \wedge M \Rightarrow P$
- R3: $B \wedge L \Rightarrow M$
- R4: $A \wedge P \Rightarrow L$
- R5: $A \wedge B \Rightarrow L$
- A
- B



- **Prove Q**

Forward versus Backward Chaining

- **Forward Chaining**

- **data-driven**, automatic, unconscious processing
 - > e.g., object recognition, routine decisions
- may do lots of work that is irrelevant to the goal

- **Backward Chaining**

- **goal-driven**, appropriate for problem-solving
 - > e.g., How do I get into a PhD program?
- complexity can be **much less** than linear in size of KB

- **Both are sound and complete for Horn KBs**

Pros and Cons of Propositional Logic

😊 **declarative**

😊 **allows partial/disjunctive/negated information**

😊 **compositional:**

– meaning of $A \wedge B$ is derived from meaning of A and of B

😊 **Meaning is context-independent**

😞 **Propositional logic has very limited expressive power**

– E.g., cannot say “all men are mortal”



FIT3080 – Intelligent Systems

First Order Logic

First-order Logic (FOL)

- **First-order logic assumes the world contains**
 - **Objects**: people, houses, numbers, colors, baseball games, wars, ...
 - **Relations**: red, round, prime, brother of, bigger than, part of, comes between, ...
 - **Functions**: father of, best friend, one more than, plus, ...
- **FOL has increased expressive power**

First Order Logic – Syntax (I)

- **term – constant, variable or function**
- **atomic formula – predicate symbol and terms**
 - Example: $\text{MARRIED}(\text{John}, \text{Mother}(x))$
 - > Predicate symbol – MARRIED
 - > Constant – John
 - > Function – Mother
 - > Variable – x
- **literal – atomic formula or negation of an atomic formula**

E.g., $\neg \text{MARRIED}(\text{John}, \text{Mother}(x))$
- **ground literal – literal without variables**

First Order Logic – Syntax (II)

- **connectives**

- disjunction – $P(x) \vee Q(y) \vee W(x,y)$
- conjunction – $P(x) \wedge Q(y)$
- implication – $P(x) \Rightarrow W(x,y) \equiv \neg P(x) \vee W(x,y)$

- **clause – disjunction of literals**

E.g., $\text{MARRIED}(\text{John}, \text{Mother}(x)) \vee \text{MARRIED}(\text{John}, y)$

- **conjunctive normal form – a conjunction of a finite set of clauses**

E.g., $(P1(x) \vee P2(y)) \wedge P3(x)$

Well Formed Formulas (wffs)

Legitimate expressions in predicate calculus

1. Any conjunction of wffs is a wff
2. Any disjunction of wffs is a wff
3. If both the antecedent and the consequent are wffs, so is the implication
4. The negation of a wff is also a wff

First Order Logic – Quantification

Quantification

- Universal (\forall) –
 $\forall x [\text{ELEPHANT}(x) \Rightarrow \text{COLOUR}(x, \text{GRAY})]$
- Existential (\exists) –
 $\exists x \text{ WRITE}(x, \text{COMPUTER-CHESS})$

1. Any conjunction of wffs is a wff
2. Any disjunction of wffs is a wff
3. If both the antecedent and the consequent are wffs, so is the implication
4. The negation of a wff is a wff
5. **Any expression obtained by quantifying a wff is a wff**



FOL – Nesting of Quantifiers

- **Existential inside the scope of universal**
E.g., $\forall s \exists c \text{ Eats}(s,c)$
- **Universal inside the scope of existential**
E.g., $\exists c \forall s \text{ Eats}(s,c)$

FOL – Some Equivalences

- $\neg(\exists x)P(x) \equiv (\forall x) [\neg P(x)]$

There does not exist an x such that $P(x)$ is true \equiv
For all x , $P(x)$ is false

- $\neg(\forall x)P(x) \equiv (\exists x) [\neg P(x)]$

It is not true that for all x $P(x)$ is true \equiv
There exists an x , such that $\neg P(x)$

- $(\forall x)[P(x) \wedge Q(x)] \equiv (\forall x)P(x) \wedge (\forall y)Q(y)$

For all x , $P(x)$ and $Q(x)$ are true \equiv
For all x , $P(x)$ is true, and for all y $Q(y)$ is true

- $(\exists x)[P(x) \vee Q(x)] \equiv (\exists x)P(x) \vee (\exists y)Q(y)$

There is an x , such that $P(x)$ is true or $Q(x)$ is true \equiv
There is an x , such that $P(x)$ is true, or
there is a y , such that $Q(y)$ is true

Rules of Inference – Example

- **Modus Ponens:**
 $[P \text{ and } P \Rightarrow Q] \rightarrow Q$
- **Modus Tollens:**
 $[\neg Q \text{ and } P \Rightarrow Q] \rightarrow \neg P$
- **Universal Specialization**
 $\forall x W(x) \rightarrow W(A)$, where A is a constant
- **Example: Universal Specialization + Modus Ponens**
 1. $\forall x [\text{DOG}(x) \Rightarrow \text{BARKS}(x)]$
 2. $\text{DOG}(\text{FIDO})$From 1 and 2: $\text{BARKS}(\text{FIDO})$

General Inference – Resolution Refutation

- **Resolution**
 - Unification
 - > Substitution
 - Converting wffs into clauses

Substitution

- **Substitution is a set of ordered pairs**
 $s = \{t_1/v_1, t_2/v_2, \dots, t_n/v_n\}$
where t_i/v_i means that t_i is substituted for v_i throughout
- Example:
 $\{A/x, B/y\} P(x,y) \rightarrow P(A,B)$
- **Semantics: all elements are applied *simultaneously***
- Example:
 $\{g(y)/x, h(z)/y, x/z\} P(w, y, g(z), x) \rightarrow P(w, h(z), g(x), g(y))$

Composition of Substitutions

- **s_1s_2 – composition of two substitutions**

- Apply s_2 to the terms of s_1
- Add any pairs of s_2 having variables not in s_1

Example:

$s_1 = \{g(x,y)/z\}$

$s_2 = \{A/x, B/y, C/w, D/z\}$

$s_1s_2 = \{g(A,B)/z, A/x, B/y, C/w\}$

$s_2s_1 = \{A/x, B/y, C/w, D/z\}$

- **Properties of compositions of substitutions**

- $L(s_1s_2) = (Ls_1)s_2$
- Associative: $(s_1s_2)s_3 = s_1(s_2s_3)$
- NOT commutative: $s_1s_2 \neq s_2s_1$



Unification

- A process that finds substitutions of terms for variables, such that two expressions are identical
- A set $\{E_i\}$ of expressions is unifiable, if there exists a substitution s such that $E_1s = E_2s = \dots$
In this case, s is a unifier of $\{E_i\}$
- **mgu (most general unifier)** – the mgu g of $\{E_i\}$ has the property that if s is any unifier of $\{E_i\}$, yielding $\{E_i\}s$, then there exists a substitution s' such that $\{E_i\}s = \{E_i\}gs'$
- Example:
 $s = \{A/x, B/y\}$ unifies $P(x, f(y))$ with $P(x, f(B))$
but the mgu is $\{B/y\}$

Algorithm Unify

Algorithm Unify(E1,E2)

1. If either E1 or E2 is a symbol (predicate, function, constant, negation or variable), then interchange E1 and E2, so that E1 is a symbol
 - a. If E1 and E2 are identical then return { } // no substitution
 - b. If E1 is a variable do
 - i. If E1 occurs in E2 then return **FAIL**
 - ii. return {E2/E1}
 - c. If E2 is a variable then return {E1/E2}
 - d. return **FAIL**
2. $F1 \leftarrow$ the first element of E1, $T1 \leftarrow$ rest of E1
3. $F2 \leftarrow$ the first element of E2, $T2 \leftarrow$ rest of E2
4. $Z1 \leftarrow \text{Unify}(F1, F2)$
5. If $Z1 = \text{FAIL}$, then return **FAIL**
6. $G1 \leftarrow$ result of applying Z1 to T1; $G2 \leftarrow$ result of applying Z1 to T2
7. $Z2 \leftarrow \text{Unify}(G1, G2)$
8. If $Z2 = \text{FAIL}$, then return **FAIL**
9. return the composition of Z1 and Z2



Unification Example: $\text{Unify}(P(y,g(y)),P(z,g(x)))$

4. $Z1 \leftarrow \text{Unify}(P,P)$

1.a P and P are identical \rightarrow return NIL

7. $Z2 \leftarrow \text{Unify}((y,g(y)), (z,g(x)))$

4. $Z1 \leftarrow \text{Unify}(y,z)$: 1.b.ii return $\{z/y\}$

6. $G1 \leftarrow (g(y))\{z/y\} \rightarrow (g(z))$, $G2 \leftarrow (g(x))\{z/y\} \rightarrow (g(x))$

7. $Z2 \leftarrow \text{Unify}((g(z)), (g(x)))$:

4. $Z1 \leftarrow \text{Unify}(g(z), g(x))$

4. $Z1 \leftarrow \text{Unify}(g, g)$

1.a g and g are identical \rightarrow return NIL

7. $Z2 \leftarrow \text{Unify}((z), (x))$

4. $Z1 \leftarrow \text{Unify}(z, x)$: 1.b.ii return $\{x/z\}$

9. return composition of $\{z/y\}\{x/z\} = \{x/y, x/z\}$



Converting wffs into Clauses

1. Eliminate implication symbols
2. Reduce scopes of negation symbols
3. Standardize variables
4. Eliminate existential quantifiers (*skolemize*)
5. Move all universal quantifiers to the front
6. Put result in conjunctive normal form (CNF)
7. Eliminate universal quantifiers
8. Eliminate \wedge symbols
9. Rename variables (standardize variables apart)

Converting wffs into Clauses – Example 1

$\forall x [\text{CanRead}(x) \Rightarrow \text{Intelligent}(x)]$

1. Eliminate \Rightarrow : $\forall x [\neg \text{CanRead}(x) \vee \text{Intelligent}(x)]$

7. Eliminate \forall : $\neg \text{CanRead}(x) \vee \text{Intelligent}(x)$



Converting wffs into Clauses – Example 2

$$\forall x [\neg (\forall y) [P(x,y) \Rightarrow Q(x,y)]]$$

1. Eliminate \Rightarrow : $\forall x [\neg (\forall y) [\neg P(x,y) \vee Q(x,y)]]$

2. Reduce scope of \neg : $\forall x [\exists y \neg [\neg P(x,y) \vee Q(x,y)]]$
 $\forall x \exists y [P(x,y) \wedge \neg Q(x,y)]$

4. Eliminate \exists : $\forall x [P(x,g(x)) \wedge \neg Q(x,g(x))]$

7. Eliminate \forall : $P(x,g(x)) \wedge \neg Q(x,g(x))$

8. Eliminate \wedge symbols: $\{ P(x,g(x)), \neg Q(x,g(x)) \}$

9. Standardize variables apart: $\{ P(x_1,g(x_1)), \neg Q(x_2,g(x_2)) \}$

General Resolution

- Let the prospective parent clauses be $\{L_j\}$ and $\{M_i\}$ (with variables standardized apart)
- Suppose that $\{l_j\}$ is a subset of $\{L_j\}$ and that $\{m_i\}$ is a subset of $\{M_i\}$ such that a most general unifier s exists for the union of the sets $\{l_j\}$ and $\{\neg m_i\}$
- The clauses $\{L_j\}$ and $\{M_i\}$ resolve and the new clause $\{\{L_j\} - \{l_j\}\}s \cup \{\{M_i\} - \{m_i\}\}s$ is a **resolvent** of the two clauses

General Resolution – Example

1. Everyone who can read is literate

$$\forall x [\text{CanRead}(x) \Rightarrow \text{Literate}(x)]$$

2. Whoever goes to school can read

$$\forall x [\text{GoSchool}(x) \Rightarrow \text{CanRead}(x)]$$

$$\begin{array}{ccc} \neg \text{GoSchool}(x_1) \vee \underline{\text{CanRead}(x_1)} & & \neg \underline{\text{CanRead}(x_2)} \vee \text{Literate}(x_2) \\ & \searrow \quad \swarrow & \\ & \text{mgu } s = \{x_1/x_2\} & \\ & \neg \text{GoSchool}(x_1) \vee \text{Literate}(x_1) & \end{array}$$

Resolution-refutation – Example (I)

- 1. If a unit is easy, there are some students who are enrolled in it who are happy**

$$\forall u [\text{Easy}(u) \Rightarrow \exists s [\text{Enrolled}(s,u) \wedge \text{Happy}(s)]]$$

- 2. If a unit has a final exam, no students that are enrolled in it are happy**

$$\forall u [\text{HasFinal}(u) \Rightarrow \neg \exists s [\text{Enrolled}(s,u) \wedge \text{Happy}(s)]]$$

- 3. Prove that if a unit has a final exam, the unit is not easy**

$$\forall u [\text{HasFinal}(u) \Rightarrow \neg \text{Easy}(u)]$$

Resolution-refutation – Example (II)

Converting to clauses

1. $\forall u [\text{Easy}(u) \Rightarrow \exists s [\text{Enrolled}(s,u) \wedge \text{Happy}(s)]]$

Eliminate \Rightarrow : $\forall u [\neg \text{Easy}(u) \vee \exists s [\text{Enrolled}(s,u) \wedge \text{Happy}(s)]]$

Eliminate \exists : $\forall u [\neg \text{Easy}(u) \vee [\text{Enrolled}(g(u),u) \wedge \text{Happy}(g(u))]]$

Turn into CNF: $\forall u [[\neg \text{Easy}(u) \vee \text{Enrolled}(g(u),u)] \wedge [\neg \text{Easy}(u) \vee \text{Happy}(g(u))]]$

Eliminate \forall : $[\neg \text{Easy}(u) \vee \text{Enrolled}(g(u),u)] \wedge [\neg \text{Easy}(u) \vee \text{Happy}(g(u))]$

Eliminate \wedge and rename variables:

1.1 $\neg \text{Easy}(u_1) \vee \text{Enrolled}(g(u_1),u_1)$

1.2 $\neg \text{Easy}(u_2) \vee \text{Happy}(g(u_2))$

Resolution-refutation – Example (III)

2. $\forall u [\text{HasFinal}(u) \Rightarrow \neg \exists s [\text{Enrolled}(s,u) \wedge \text{Happy}(s)]]$

Eliminate \Rightarrow : $\forall u [\neg \text{HasFinal}(u) \vee$
 $\neg \exists s [\text{Enrolled}(s,u) \wedge \text{Happy}(s)]]$

Reduce scope of \neg :

$\forall u [\neg \text{HasFinal}(u) \vee \forall s \neg [\text{Enrolled}(s,u) \wedge \text{Happy}(s)]]$

$\forall u [\neg \text{HasFinal}(u) \vee \forall s [\neg \text{Enrolled}(s,u) \vee \neg \text{Happy}(s)]]$

Move \forall to the front: $\forall u \forall s [\neg \text{HasFinal}(u) \vee$
 $\neg \text{Enrolled}(s,u) \vee \neg \text{Happy}(s)]$

Eliminate \forall and rename variables:

$\neg \text{HasFinal}(u_3) \vee \neg \text{Enrolled}(s_3, u_3) \vee \neg \text{Happy}(s_3)$

Resolution-refutation – Example (IV)

Using resolution to prove statement 3

Negate the goal:

3'. $\neg \forall u [\text{HasFinal}(u) \Rightarrow \neg \text{Easy}(u)]$

Eliminate \Rightarrow : $\neg \forall u [\neg \text{HasFinal}(u) \vee \neg \text{Easy}(u)]$


Reduce scope of \neg : $\exists u [\text{HasFinal}(u) \wedge \text{Easy}(u)]$

Eliminate \exists : $\text{HasFinal}(A) \wedge \text{Easy}(A)$

Eliminate \wedge : 3'.1 $\text{HasFinal}(A)$

3'.2 $\text{Easy}(A)$

Resolution-refutation – Example (V)



Resolution Strategies

- **Unit preference:** prefer resolutions where one of the sentences is a **unit clause** (single literal)
 - **Unit resolution:** every resolution must involve a unit clause
- **Set of support:** every resolution step should involve at least one element of a special set of clauses, the **set of support**. The resolvent is added to the set of support
 - E.g., set of support = $\{\neg Q\}$
- **Input resolution:** every resolution combines one of the original input sentences (from the KB or the query) with another sentence
- **Subsumption:** eliminates all sentences that are subsumed by (more specific than) an existing sentence in the KB

Uses of FOL in AI

- **Theorem proving**

1. $ON(C,A)$
2. $ONTable(A), ONTable(B)$
3. $CLEAR(C), CLEAR(B)$
4. $\forall x [CLEAR(x) \Rightarrow \neg \exists y ON(y,x)]$

Goal: Prove $\neg \exists y ON(y,C)$

- **Question answering**

1. $MANAGER(Purchasing-dept., John-Jones)$
2. $WorksIn(Purchasing-dept., Joe-Smith)$
3. $\forall x \forall y \forall z [WorksIn(x,y) \wedge MANAGER(x,z)] \Rightarrow BossOf(y,z)$

Goal: Who is the boss of Joe Smith?

$\exists x BossOf (Joe-Smith,x)$

- **Planning**



Reading

- **Russell, S. and Norvig, P. (2010), *Artificial Intelligence – A Modern Approach* (3rd edition), Prentice Hall**
 - Chapter 7, Sections 7.1-7.5
 - Chapter 8
 - Chapter 9, Sections 9.1, 9.2 and 9.5