



GE Energy

## Functional Testing Specification

*Parts & Repair Services  
Louisville, KY*

**LOU-GED-IS200RCSAG1A**

### Test Procedure for a IS200RCSAG1A Snubber Card

**DOCUMENT REVISION STATUS:** Determined by the last entry in the "REV" and "DATE" column

REV.	DESCRIPTION	SIGNATURE	REV. DATE
A	Initial release	M. Starling	8/29/16
B			
C			

© COPYRIGHT GENERAL ELECTRIC COMPANY

Hard copies are uncontrolled and are for reference only.

PROPRIETARY INFORMATION – THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL ELECTRIC COMPANY AND MAY NOT BE USED OR DISCLOSED TO OTHERS, EXCEPT WITH THE WRITTEN PERMISSION OF GENERAL ELECTRIC COMPANY.

<b>PREPARED BY</b> M. Starling	<b>REVIEWED BY</b>	<b>REVIEWED BY</b>	<b>QUALITY APPROVAL</b>
<b>DATE</b> 8/29/16	<b>DATE</b>	<b>DATE</b>	<b>DATE</b>

<b>LOU-GED-IS200RCSAG1A REV. A</b>	<div data-bbox="548 205 581 254" data-label="Text"> <b>g</b> </div> <div data-bbox="737 258 980 333" data-label="Text"> <b>GE Energy</b>  <i>Parts &amp; Repair Services</i>  <i>Louisville, KY</i> </div>	<b>Page 2 of 3</b>
--	--	--------------------

## 1. SCOPE

1.1 This is a functional testing procedure for an IS200RCSAG1A Snubber Card.

## 2. STANDARDS OF QUALITY

2.1 Refer to the current revision of the IPC-A-610 standard for workmanship standards.

## 3. APPLICABLE DOCUMENTS

3.1 The following document(s) shall form part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue shall apply.

3.1.1 Check board's electronic folder for more information

## 4. ENGINEERING REQUIREMENTS

### 4.1 Equipment Cleaning

4.1.1 Equipment should be clean and free of debris prior to applying power unless performing an initial check. Refer to site specific SRA's for cleaning guidelines.

### 4.2 Equipment Inspection

4.2.1 Equipment should be visually inspected for any defects prior to applying power. This inspection should include the following as a minimum:

4.2.1.1 Wires - broken, cracked, or loosely connected

4.2.1.2 Terminal strips / connectors - broken or cracked

4.2.1.3 Components - visually damaged

4.2.1.4 Capacitors - bloated or leaking

4.2.1.5 Solder joints - damaged or cold

4.2.1.6 Circuit board - burned or de-laminated

4.2.1.7 Printed wire runs / Traces - burned or damaged

## 5. EQUIPMENT REQUIRED

5.1 The following equipment is required to perform the process requirements. Equipment may be substituted provided that all accuracy's and test ratios are equivalent or better.

Qty	Reference #	Description
1		Fluke 87 DMM (or Equivalent)

<p><b>LOU-GED-IS200RCSAG1A REV. A</b></p>	<p><b>g</b></p> <p><b>GE Energy</b> Parts &amp; Repair Services Louisville, KY</p>	<p><b>Page 3 of 3</b></p>
---	--	---------------------------

**6. Modifications/Upgrades**

6.1 Fill out if applicable.

**7. Testing Process**

**7.1 Setup**

7.1.1 Fill out.



**Note:**

**7.2 Testing Procedure**

7.2.1 Fill out.

**7.3 Post Testing Burn-in**                      **Required**    ☐ **Yes**    ☐ **No**



**Note:** All MARK I, II, & III Turbine related cards require a post testing burn-in of 100 hours.

7.3.1 Apply BUS or Operational power to the card for a period of 100 hours.

7.3.2 Re-test card while warm using the above procedure.

**7.4 \*\*\*TEST COMPLETE\*\*\***

**8. Notes**

8.1 None at this time?

**9. Attachments**

9.1 None at this time?