

<div>g</div> <div>GE Energy</div>		Functional Testing Specification	
Parts & Repair Services Louisville, KY.		LOU-GED-SIEI	
Test Procedure for a AV, DV, and AVi Drives			
DOCUMENT REVISION STATUS: Determined by the last entry in the "REV" and "DATE" column			
REV.	DESCRIPTION	SIGNATURE	REV. DATE
A	Initial release	D. Bush	7/23/2002
B	Added switch box, asset number, changed header	Barry S Cash C. Wade	9/22/2008
C			
<p>© COPYRIGHT GENERAL ELECTRIC COMPANY Hard copies are uncontrolled and are for reference only. PROPRIETARY INFORMATION – THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL ELECTRIC COMPANY AND MAY NOT BE USED OR DISCLOSED TO OTHERS, EXCEPT WITH THE WRITTEN PERMISSION OF GENERAL ELECTRIC COMPANY.</p>			
PREPARED BY David Bush	REVIEWED BY	REVIEWED BY	QUALITY APPROVAL Robert D. Dwyer
DATE 23-July-02	DATE	DATE	DATE 08/09/02

## Functional test procedure for all GE SIEI America Drives

### 1. SCOPE

1.1 This is a functional testing procedure for aa AV-DV-Avi drives

### 2. STANDARDS OF QUALITY

2.1 Refer to the current revision of the IPC-A-610 standard for workmanship standards.

### 3. APPLICABLE DOCUMENTS

3.1 The following document(s) shall form part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue shall apply.

3.1.1 **GEI-100211**

### 4. ENGINEERING REQUIREMENTS

#### 4.1 Equipment Cleaning

4.1.1 Equipment should be clean and free of debris prior to applying power unless performing an initial check. Refer to the local documented procedures for cleaning guidelines.

#### 4.2 Equipment Inspection

4.2.1 Equipment should be visually inspected for any defects prior to applying power. This inspection should include the following as a minimum:

4.2.1.1 Wires broken or cracked

4.2.1.2 Terminal strips / connectors broken or cracked

4.2.1.3 Loose wires

4.2.1.4 Components visually damaged

4.2.1.5 Capacitors leaking

4.2.1.6 Solder joints damaged or cold

4.2.1.7 Circuit board burned or de-laminated

4.2.1.8 Printed wire runs burned or damaged

### 5. EQUIPMENT REQUIRED

5.1 The following equipment is required to perform the process requirements. Equipment may be substituted provided that all accuracy's and test ratios are equivalent or better.

Qty	Reference #	Description
1		Motor control Panel
1		Fluke 85 DMM (or equivalent)
1	H188622	I/O switch box

<p><b>LOU-GED-SIEI REV. B</b></p>	<p><b>g</b></p> <p><b>GE Energy</b> <i>Parts &amp; Repair Services</i> <i>Louisville, KY</i></p>	<p><b>Page 3 of 3</b></p>
---------------------------------------	--	---------------------------

## 6. TESTING PROCESS

### 6.1 Setup

**6.1.1** Reference all shop manuals on the *SIEI America Drives*.

### 6.2 Testing Procedure

**6.2.1** Wire incoming AC power to drive connections L1 L2 and L3.

**6.2.2** Wire in AC motor to connections U V and W on the Drive.

**6.2.3** Wire in DC motor to connections C, D and field.

**6.2.4** Apply proper input voltage.

**6.2.5** Verify the Drive is powered up.

**6.2.6** With a DMM check for proper AC voltage across the three phase incoming power at L1, L2, and L3.

**6.2.7** With a DMM check for voltage at the motor connections U, V, and W.

**6.2.8** Using toolbox load drive with default settings and then run setup wizard to match setting to motor in use.

**6.2.9** It may be necessary to self-tune drive to motor in use.

**6.2.10** Connect appropriate I/O switch box. Use instruction manual to determine I/O and option setup using toolbox again. Test I/O points.

**6.2.11** Verify drive operations using functions using controls on I/O box.

**6.2.12** Reload drive with default setting and be sure to save.

**6.2.13** Disconnect all power.

### 6.3 **\*\*\*TEST COMPLETE\*\*\***

## 7. NOTES

**7.1** None at this time