g		GE Energy	Fund	ctional Testing Sp	ecification
	Parts & Repai Louisville, KY			LOU-GED-IS200J	PDL
	Te	est Procedure for an IS	6200JPDLG1xxx Local	Power Pack.	
DOCUI	MENT REVISION STATUS:	Determined by the last en	try in the "REV" and "DATE	' column	
REV.		DESCRIPTION		SIGNATURE	REV. DATE
Α	Initial release			J. Francis	04/03/2014
В					
С					
	YRIGHT GENERAL ELECTI				
PROPR MAY N	OT BE USED OR DISCLOSI	THIS DOCUMENT CONTAINS ED TO OTHERS, EXCEPT WIT	S PROPRIETARY INFORMATION THE WRITTEN PERMISSION	N OF GENERAL ELECTRIC	COMPANY.
J. Fra	ARED BY Incis	REVIEWED BY R. Johnson	REVIEWED BY	QUALITY AF	
DATE		DATE	DATE	Charlie U	lade

6/11/2014

04/03/2014

5/5/2014

	g	
LOU-GED-IS200JPDL	GE Energy	Page 2 of 3
Rev A	Parts & Repair Services	
	Louisville, KY	

1. SCOPE

1.1 This is a functional testing procedure for an IS200JPDLG1Axx MARK VIe Module.

2. STANDARDS OF QUALITY

2.1 Refer to the current revision of the IPC-A-610 standard for workmanship standards.

3. APPLICABLE DOCUMENTS

- **3.1** The following document(s) shall form part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue shall apply.
 - **3.1.1** Check board's electronic folder for more information.

4. **ENGINEERING REQUIREMENTS**

- 4.1 Equipment Cleaning
 - **4.1.1** Equipment should be clean and free of debris prior to applying power unless performing an initial check. Refer to site specific SRA's for cleaning guidelines.
- **4.2** Equipment Inspection
 - **4.2.1** Equipment should be visually inspected for any defects prior to applying power. This inspection should include the following as a minimum:
 - 4.2.1.1 Wires broken, cracked, or loosely connected
 - 4.2.1.2 Terminal strips / connectors broken or cracked
 - 4.2.1.3 Components visually damaged
 - 4.2.1.4 Capacitors bloated or leaking
 - 4.2.1.5 Solder joints damaged or cold
 - 4.2.1.6 Circuit board burned or de-laminated
 - 4.2.1.7 Printed wire runs / Traces burned or damaged

5. EQUIPMENT REQUIRED

5.1 The following equipment is required to perform the process requirements. Equipment may be substituted provided that all accuracy's and test ratios are equivalent or better.

Qty	Reference #	Description
1		Fluke 87 DMM (or Equivalent)

	g	
LOU-GED-IS200JPDL	GE Energy	Page 3 of 3
Rev A	Parts & Repair Services	
1.22.1.1	Louisville, KY	

6. TESTING PROCESS

6.1 Static Checks

6.1.1 Using Fluke 87 DMM (or Equivalent), set for Resistance function, check for continuity between the following points listed in the table below:

From:	To:	Expected Result:
JL1-5	JL1-4	<1 Ohm
JL1-5	JL2-5	<1 Ohm
JL1-5	JL2-4	<1 Ohm
JL1-5	JT2-2	<1 Ohm
JL1-5	JT1-2	<1 Ohm
JL1-5	JS2-2	<1 Ohm
JL1-5	JS1-2	<1 Ohm
JL1-5	JR2-2	<1 Ohm
JL1-5	JR1-2	<1 Ohm
JL1-3	JL2-3	<1 Ohm
JL1-3	JT2-1	<1 Ohm
JL1-3	JT1-1	<1 Ohm
JL1-2	JL2-2	<1 Ohm
JL1-2	JS2-1	<1 Ohm
JL1-2	JS1-1	<1 Ohm
JL1-1	JL2-1	<1 Ohm
JL1-1	JR2-1	<1 Ohm
JL1-1	JR1-1	<1 Ohm

6.2 ***TEST COMPLETE ***

7. NOTES

7.1 None at this time.

8. ATTACHMENTS

8.1 None at this time.