

# **GE Power Generation Engineering**

PROCESS SPECIFICATION

Materials and Processes Engineering Schenectady, NY 12345

P3K-AL-0436-A01

### TEST INSTRUCTIONS FOR MOTOR DRIVE CIRCUIT BOARD 1L2-GOO2

DOCU	MENT REVISIO	ON STATUS: DETERMINED BY THE LAST ENTRY IN THE "REV"	AND "DATE" COLUMN	
REV.	AN NO.	DESCRIPTION	SIGNATURE	REV. DATE
A	YA00096	SPECIFICATION LISTED IN STEAM TURBINE/GENERATOR INDEX AS "INACTIVE" HAS BEEN FORMALLY REVISED AS "INACTIVE FOR NEW DESIGN". (PR BUDKA)	C.R. Truppe	DEC 0 2 15 .
		INACTIVE FOR NEW DESIGN AS OF 12/02/91		

© COPYRIGHT 1991 GENERAL ELECTRIC COMPANY

PROPRIETARY INFORMATION - THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL ELECTRIC COMPANY AND MAY NOT BE USED OR DISCLOSED TO OTHERS. EXCEPT WITH THE WRITTEN PERMISSION OF GENERAL ELECTRIC COMPANY.

PREPAR	ED E	3Y:
--------	------	-----

P.R. BUDKA

ORIG. ISSUE DATE:

## GENERAL & ELECTRIC

P3K-AL-0436-A01

REV DA

TITLE

CONT ON SHEET

SH NO. -

P3K-AL-0436-A01 CONT ON SHEET 3

TEST INSTRUCTIONS FOR MOTOR DRIVE CIRCUIT BOARD (ASSEMBLY DRAWING 118D1333-G1) EHC MARK II FIRST MADE FOR

REVISIO

#### CIRCUIT DESCRIPTION I.

This board contains the thyrectors and relays that provide 115 VAC to the two phase motors that position the potentiometers for the pressure limiting rotor warming and SPF transfer.

#### II. CIRCUIT SPECIFICATIONS

1. Isolation between circuits. The resistance between any two of the following points should be >1M ohm:

TB1-1 and TB1-3 TB2-18 and TB2-24

Continuity.

The resistance between the following pairs should be  $\boldsymbol{\zeta}$  0.1 ohm:

TB2-24 and TB2-29

TB2-24 and TB2-30

TB2-24 and TB2-31

The resistance from each relay case and TB3-36 should be < 0.1 ohm.

Thyrectors

The resistance between the following pairs should be > 100K ohms. (Use a low voltage instrument for these measurements).

TB2-31 and TB2-23

TB2-31 and TB2-25

TB2-30 and TB2-21

TB2-30 and TB2-22

TB2-29 and TB2-19

TB2-29 and TB2-20

If the board is uncoated these checks can be done across the thyrector themselves.

Logic

Make the following connections:

TB1-1: 24V common TB1-3: +24 VDC

TB2-24: 115 VAC common

TB2-18: 115VAC phase

Connect 115V minature lamps to:

TB2-19, 20, 21, 22, 23, 25, and 115 VAC common.

The logic and path continuity should conform with the following table. acep SEP 21 1977 APPROVALS

SEP 22 1977

Steam Turbine

DIV OR

P3K-AL-0436-A01

CODE IDENT NO

273-5

273-12 273-71

273-138

PRINTS TO

Schenectady,

LOCATION CONT ON SHEET

+

GENERAL BELECTRIC P3K-AL-0436-A01 CONT ON SHEET TITLE TEST INSTRUCTIONS FOR MOTOR DRIVE CIRCUIT BOARD P3K-AL-0436-A01 112-G002 FIRST MADE FOR (ASSEMBLY DRAWING 118D1333-G1) EHC MARK II CONT ON SHEET SH NO. + REVISIONS PINS 25 + CORRECT OUTPUTS AT 21 TB2INPUTS AT PINS VDC) ~ 24 or ø 00 'n 0 0 0 0 0 + PRINTS TO APPROVALS DIV OR Steam Turbine P3K-AL-0436-A01 Schenectady, N.Y. LOCATION CONT ON SHEET FF-803-WA (5-74)

						G	E N	E R	AL	Œ	) E1	LEC	TR	I C		P3K-AL-0436-A01
P3K-AL-		TITLE CONT ON SHEET  TEST INSTRUCTIONS FOR MOTOR DRIVE CIRCUIT BOARD  112-G002														
CONT ON SHEET	CONT ON SHEET 5 SH NO. 5								(A	SSE	MBL	118D13	1333-G1) EHC MARK II			
																re has been is a shortened
r PINS	25	0	0 0	<b>,</b> ,	0	0	0	0	0	0	0	0	0	0	0	or to I
TS AT	23	0	0 0	0	0	0	0	0	0	0	0	0	0	0	0	• 😙
OUTPU	22	0	0 0	. 0	0	0	0	0	0	0	0	0	0	0	0	<i>←</i> 1
CORRECT OUTPUTS	21	0	0 0	, 0	0	0	0	0	0	0	0		0		0	n → 1
COR	20	0	0 0	. 0	0	0	0	0	0	0	0	0	0	0	0	
	19	0	0 0		0	0	0	0	0	0	0	0	0	0	0	stage ; it the ca
(CONTINUED)																, therefore the sequence of transition occurs at a time test set-up; were this not test.
PINS	8	0	0	0 0	0	0	0	0	O	en wymered		<u> </u>		0	endere de la completa	on on equential one input vailable of stage
AT PJ	7 7	0		0 0	0	0	0	0 (	0	0	0 0	0 (	0 0	0 0	0 0	imp off or lamp or lamp s not se it only of the an
TE	(UV OF 5	0		00		0 0	0 0	0 0	0 0	0 0	0	0 0	0	0	0	
	TBI (0	0	0	0 0	0	0	0	0	0	0	0	0	0	0	0	OV 24 115 taken sken sken sken sken sken sken sken s
	2	0	0	0 0	0	0	0	0	0	0	0	0	0	0	0)	NO CO TILL DISCOUNT CO O DE LA COLOR DE LA
1 .	39 WWW SEP 21 1977												T			
more or the	UR	SEP 22 19		1977	^*	PPROVA		5	tea	m I	urb	ine	:		DIV OR	

	REV A	TITLE	•		<del></del>	CONT ON SE	EET	ан ио.	
	P3K-AL-0436-A01	TEST INSTR	UCTIONS FOR	MOTOR DR	CVE CIP	CUIT B	OARD		
+	CONT ON SHEET SH NO. 45		R (ASSEMBLY	DRAWING	118D13	33-G1)	EHC MARK	II	
								REVISIO	NS
	DEED ADD DV 6200 4	moloni				/	20175		
+	PREPARED BY M.J. Sindon:	i.			DATE	2/2	25/75	-	
	EHC DESIGN	ENGINEERING							
							•		
	APPROVED BY	Cell	·		DATE	9	-/2-7	<u>5</u> .	
	P.C. Callan EHC DESIGN				-	•			
7-									
	TEST PROCEDURE		7			_			
	REVIEWED BY Kille	Deletok	,		DATE	<u> </u>	<u>9-77</u>	-	
	R. Deberto EHC TEST EN	GINEER							•
+									
									-
									_
+		•						PRINTS	TĆ
	John SEP 21 1977	APPROVALS	Steam Turb	ine	DIV OR	באגם	AL-0436-A		_
	SEP 22 1977		Schenectad	·	LOCATION	CONT ON SI		SH NO. 4	
	FF-803-WA (5-74) PRINTED IN U.S.A.		<b>†</b>		}			CODE IDENT	. NC