g		GE Energy		Functional Testing Specification						
Parts & Repair Services Louisville, KY				LOU-GED-IS230TSVC2AG01						
Test Procedure for a IS230TSVC2AG01 I/O module assembly										
	MENT REVISION STATUS	: Determined by the last er	ntry in the "REV" a							
REV.	Initial Dalance	DESCRIPTION			GNATURE	REV. DATE				
Α	Initial Release			J	. Francis	05/10/2012				
В										
С										
	YRIGHT GENERAL ELECT									
Hard copies are uncontrolled and are for reference only.  PROPRIETARY INFORMATION – THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL ELECTRIC COMPANY AND MAY NOT BE USED OR DISCLOSED TO OTHERS, EXCEPT WITH THE WRITTEN PERMISSION OF GENERAL ELECTRIC COMPANY.										
J. Fra	ARED BY Incis	REVIEWED BY	REVIEWE	D BY	QUALITY AP					
<b>DATE</b> 05/10	/2012	DATE	DATE		<b>DATE</b> 5/10/2012					

	g	
LOU-GED-IS230TSVC2AG01	GE Energy	Page 2 of 4
Rev A	Parts & Repair Services	
	Louis ville, KY	

#### 1. SCOPE

1.1 This is a functional testing procedure for an IS230TSVC2AG01 I/O module assembly.

## 2. STANDARDS OF QUALITY

**2.1** Refer to the current revision of the IPC-A-610 standard for workmanship standards.

## 3. APPLICABLE DOCUMENTS

- **3.1** The following document(s) shall form part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue shall apply.
  - **3.1.1** Check board's electronic folder for more information

### 4. **ENGINEERING REQUIREMENTS**

- 4.1 Equipment Cleaning
  - **4.1.1** Equipment should be clean and free of debris prior to applying power unless performing an initial check. Refer to site specific SRA's for cleaning guidelines.
- **4.2** Equipment Inspection
  - **4.2.1** Equipment should be visually inspected for any defects prior to applying power. This inspection should include the following as a minimum:
    - 4.2.1.1 Wires broken, cracked, or loosely connected
    - 4.2.1.2 Terminal strips / connectors broken or cracked
    - 4.2.1.3 Components visually damaged
    - **4.2.1.4** Capacitors bloated or leaking
    - 4.2.1.5 Solder joints damaged or cold
    - 4.2.1.6 Circuit board burned or de-laminated
    - 4.2.1.7 Printed wire runs / Traces burned or damaged

#### 5. EQUIPMENT REQUIRED

**5.1** The following equipment is required to perform the process requirements. Equipment may be substituted provided that all accuracy's and test ratios are equivalent or better.

Qty	Reference #	Description	
1	*	Fluke 87 DMM (or equivalent)	
1		Toffee H	
1		Toffee Fixture H188856 for PSVO	
1		Toffee Fixture H190013 for WSVO	

LOU-GED-IS230TSVC2AG01
Rev A

GE Energy
Parts & Repair Services
Louisville, KY

Page 3 of 4

#### 6. TESTING PROCESS

### 6.1 Setup



Note: This procedure will be for an entire *IS230TSVC2AG01* assembly. Since we do NOT have a fully functional assembly test, the assembly will be broken down to individually test each sub-assembly separately using its assigned test. The test procedure will be listed for each sub-assembly.

- **6.1.1** Remove the attached **IS220PSVO** modules and test using test procedure **LOU-TOFFEE-IS220PSVOH1A**, referring to Models Database for latest revision of test procedure.
- **6.1.2** Remove the attached **IS210WSVO** modules and test using test procedure LOU-TOFFEE-IS210WSVO-A, referring to Models Database for latest revision of test procedure.
- **6.1.3** Remove the **IS200TSVC** card and test using test procedure LOU-GED-IS200TSVCH2-A, referring to Models Database for latest revision of test procedure.
- 6.1.4 Test the IS200JGND cards using test procedure LOU-GE-COMPTEST-G, referring to Models Database for latest revision of test procedure. The IS200JGND cards attached to the unit may be tested without removing cards from unit. These are cards with a terminal block attached and all pins are tied together for shielding purposes.
- **6.1.5** Reassemble unit after all sub-assemblies have been repaired and/or tested successfully.

### 6.2 \*\*\*TEST COMPLETE \*\*\*

## 7. NOTES

**7.1** None at this time.

g

LOU-GED-IS230TSVC2AG01 Rev A GE Energy Parts & Repair Services Louisville, KY

Page 4 of 4

# 8. ATTACHMENTS

**8.1** Picture of assembly.

