g	GE Energy		Functional Testing Specification					
	Parts & Repa Louisville, K)			LOU-GE	D-IS230TRPA	H1Axx		
Test Procedure for an IS230TRPAH1AXX Mark VIe Terminal Board Assembly. DOCUMENT REVISION STATUS: Determined by the last entry in the "REV" and "DATE" column								
REV.	MENT REVISION STATUS		IGNATURE	REV. DATE				
A	Initial release	DESCRIPTION			. Francis	01/14/2015		
	miliai icicase				. i iuiioio	01/17/2013		
© COPYRIGHT GENERAL ELECTRIC COMPANY Hard copies are uncontrolled and are for reference only. PROPRIETARY INFORMATION – THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL ELECTRIC COMPANY AND MAY NOT BE USED OR DISCLOSED TO OTHERS, EXCEPT WITH THE WRITTEN PERMISSION OF GENERAL ELECTRIC COMPANY.								
J. Fra	RED BY ncis	REVIEWED BY	REVIEWE	D BY	QUALITY APP L. Groves	ROVAL		
DATE		DATE	DATE		DATE			
01/14	/2015				9-27-2018			

	g	
LOU-GED-IS230TRPAH1Axx	GE Energy	Page 2 of 3
Rev A	Parts & Repair Services	
	Louisville, KY	

1. SCOPE

1.1 This is a functional testing procedure for an **IS230TRPAH1Axx** MARK VIe Terminal board assembly.

2. STANDARDS OF QUALITY

2.1 Refer to the current revision of the IPC-A-610 standard for workmanship standards.

3. APPLICABLE DOCUMENTS

- **3.1** The following document(s) shall form part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue shall apply.
 - **3.1.1** Check board's electronic folder for more information.

4. **ENGINEERING REQUIREMENTS**

- 4.1 Equipment Cleaning
 - **4.1.1** Equipment should be clean and free of debris prior to applying power unless performing an initial check. Refer to site specific SRA's for cleaning guidelines.
- 4.2 Equipment Inspection
 - **4.2.1** Equipment should be visually inspected for any defects prior to applying power. This inspection should include the following as a minimum:
 - 4.2.1.1 Wires broken, cracked, or loosely connected
 - 4.2.1.2 Terminal strips / connectors broken or cracked
 - 4.2.1.3 Components visually damaged
 - 4.2.1.4 Capacitors bloated or leaking
 - 4.2.1.5 Solder joints damaged or cold
 - 4.2.1.6 Circuit board burned or de-laminated
 - 4.2.1.7 Printed wire runs / Traces burned or damaged

5. EQUIPMENT REQUIRED

5.1 The following equipment is required to perform the process requirements. Equipment may be substituted provided that all accuracy's and test ratios are equivalent or better.

Qty	Reference #	Description
3		Fluke 87 DMM (or Equivalent)
1		Tenma Dual Output Power Supply (or Equivalent)

g

LOU-GED-IS230TRPAH1Axx Rev A

GE EnergyParts & Repair Services
Louisville, KY

Page 3 of 3

6. TESTING PROCESS

6.1 Testing Procedure



Note: This procedure will be for an entire *IS230TRPAH1A* assembly. Since we do NOT have a fully functional assembly test, the assembly will be broken down to individually test each sub-assembly separately using its assigned test. The test procedure will be listed for each sub-assembly.

- **6.1.1** Remove the **IS200TRPA** card and test using test procedure <u>LOU-GED-IS200TRPAH1Axx</u>, referring to Models Database for latest revision of test procedure.
- **6.1.2** Remove the **IS220PTUR** units and test using test procedure <u>LOU-TOFFEE-</u>
 <u>IS220PTURH1</u>, referring to Models Database for latest revision of test procedure.
- **6.1.3** Remove the **IS200JPDL** card and test using test procedure <u>LOU-GED-IS200JPDL</u>, referring to Models Database for latest revision of test procedure.
- **6.1.4** Remove the **IS200JGND** card and test using test procedure <u>LOU-GED-IS200JGND</u>, referring to Models Database for latest revision of test procedure.

6.2 ***TEST COMPLETE ***

7. NOTES

7.1 None at this time.

8. ATTACHMENTS

8.1 None at this time.