

[← Back to Rail](#)

# Lines

Route overviews, station lists, operating hours and service patterns.



## Wenhu Line

**BR** 文湖線

Taipei's driverless brown line — no cab, a front window you can stand at, and a rubber-tyred guideway that climbs hills the rest of the network cannot.

## Sanying Line

New Taipei's newest railway — a driverless elevated line to Sanxia and Yingge, open five weeks and still free to ride, written up here while every English source is still a machine translation.



## Tamsui–Xinyi Line

**R** 淡水信義線

The red line — the network's north–south spine, from the riverside at Tamsui through the core to Xiangshan, and the oldest right-of-way on the system.



## Songshan–Xindian Line

**G** 松山新店線

The green line — Songshan to Xindian through the west of the core, with the network's short branch to Xiaobitan.



## Zhonghe–Xinlu Line

**O** 中和新蘆線

The orange line — a Y-shaped route whose two northern arms to Luzhou and Huilong share one southern trunk through Zhonghe.



## Bannan Line

**BL** 板南線

The blue line — the east–west trunk through the main station, built in eight openings over sixteen years, and the one line whose ridership its own operator does not publish separately.



## Circular Line

**Y** 環狀線

New Taipei's orbital, and the line an earthquake took apart — eleven displaced girders, a 92 cm shove, eight months shut, and a Control Yuan report that traced it to a plate milled 36 mm too deep.



## Danhai LRT

**V** 淡海輕軌

New Taipei's first light rail — street-running trams serving the Tamsui new town, with a second phase under construction.



## Ankeng LRT

**K** 安坑輕軌

The second New Taipei light rail line — a valley feeder into the Xindian corridor.



## Taoyuan Airport MRT

**A** 桃園機場捷運線

The purple express-and-commuter line from Taipei Main Station to the airport and on into Taoyuan — a different operator, a different fare system, and the network's only express/local pattern.

## Side by side

|                         | Wenhu Line<br><b>BR</b> | Sanying Line | Tamsui–Xinyi Line<br><b>R</b> | Bannan Line<br><b>BL</b> | Circular Line<br><b>Y</b> |
|-------------------------|-------------------------|--------------|-------------------------------|--------------------------|---------------------------|
| Route length, operating | 25.17 km                | —            | —                             | —                        | —                         |
| Route length, published | 25.7 km                 | —            | —                             | —                        | 15.4 km                   |
| Stations                | 24                      | 12           | —                             | 23                       | 14                        |
| Elevated stations       | 22                      | —            | —                             | —                        | 13                        |
| Underground stations    | 2                       | —            | —                             | —                        | 1                         |

|                                            | Wenhu Line<br>BR | Sanying Line | Tamsui–Xinyi Line<br>R | Bannan Line<br>BL    | Circular Line<br>Y |
|--------------------------------------------|------------------|--------------|------------------------|----------------------|--------------------|
| Underground running                        | 3.9 km           | —            | —                      | —                    | —                  |
| Guideway spacing                           | 1880 mm          | —            | —                      | —                    | —                  |
| Electrification                            | 750 V DC         | —            | —                      | 750 V DC, third rail | —                  |
| Automation grade                           | GoA4             | —            | —                      | —                    | —                  |
| Peak headway                               | 2–4 min          | 6 min        | —                      | —                    | 5–7 min            |
| Off-peak headway                           | 4–10 min         | 8 min        | —                      | —                    | 8–10 min           |
| Late-evening headway                       | 12 min           | —            | —                      | —                    | —                  |
| Design minimum headway                     | 80 s             | —            | —                      | —                    | —                  |
| Maximum operating speed                    | 70 km/h          | —            | —                      | 80 km/h              | —                  |
| Design speed                               | 80 km/h          | —            | —                      | 90 km/h              | —                  |
| End-to-end journey                         | 45 min           | 30 min       | —                      | 48 min               | 34 min             |
| Route length                               | —                | 14.29 km     | —                      | —                    | —                  |
| Base fare                                  | —                | 20 NT\$      | —                      | —                    | —                  |
| Maximum fare                               | —                | 35 NT\$      | —                      | —                    | —                  |
| Cars per train                             | —                | 2            | —                      | —                    | TBC                |
| Fleet size                                 | —                | TBC          | TBC                    | —                    | TBC                |
| Maximum speed                              | —                | TBC          | —                      | —                    | TBC                |
| Tamsui section length                      | —                | —            | 23.8 km                | —                    | —                  |
| Xinyi section length                       | —                | —            | 6.4 km                 | —                    | —                  |
| Xinbeitou branch length                    | —                | —            | 1.2 km                 | —                    | —                  |
| East extension length                      | —                | —            | 1.4 km                 | —                    | —                  |
| Whole-line route length                    | —                | —            | TBC                    | —                    | —                  |
| Tamsui to Xiangshan                        | —                | —            | 54 min                 | —                    | —                  |
| Beitou to Daan                             | —                | —            | 32 min                 | —                    | —                  |
| Beitou to Xinbeitou                        | —                | —            | 3–4 min                | —                    | —                  |
| Peak headway, each pattern                 | —                | —            | 6 min                  | —                    | —                  |
| Peak headway, Beitou–Xiangshan             | —                | —            | 3 min                  | —                    | —                  |
| Initial network budget, 1986               | —                | —            | 444.4 NT\$bn           | —                    | —                  |
| Xinyi section budget                       | —                | —            | 33.862 NT\$bn          | —                    | —                  |
| Line ridership                             | —                | —            | TBC                    | —                    | —                  |
| Route length, BL01 to BL23                 | —                | —            | —                      | 26.65 km             | —                  |
| Route length, as published by zh.wikipedia | —                | —            | —                      | 28.2 km              | —                  |
| Short working, BL05 to BL23                | —                | —            | —                      | 20.48 km             | —                  |
| Short working journey                      | —                | —            | —                      | 38 min               | —                  |
| Peak headway, whole line                   | —                | —            | —                      | 6 min                | —                  |
| Peak headway, overlap section              | —                | —            | —                      | 3 min                | —                  |
| Densest published headway                  | —                | —            | —                      | 2:15 min:s           | —                  |
| Longest gap, BL09 to BL10                  | —                | —            | —                      | 3.08 km              | —                  |
| Shortest gap, BL06 to BL07                 | —                | —            | —                      | 0.65 km              | —                  |
| Cars per train, C341                       | —                | —            | —                      | 6                    | —                  |
| Daily ridership                            | —                | —            | —                      | TBC                  | —                  |
| Route length, chainage Y07—Y20             | —                | —            | —                      | —                    | 15.06 km           |

|                                                     | Wenhu Line<br> | Sanying Line | Tamsui–Xinyi Line<br> | Bannan Line<br> | Circular Line<br> |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------|--------------|--------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| Phase 1 total cost                                  | —                                                                                               | —            | —                                                                                                      | —                                                                                                  | <b>69.973</b> NT\$bn                                                                                 |
| Minimum design seismic force                        | —                                                                                               | —            | —                                                                                                      | —                                                                                                  | <b>0.288</b> g                                                                                       |
| Recorded peak horizontal acceleration, 3 April 2024 | —                                                                                               | —            | —                                                                                                      | —                                                                                                  | <b>0.229</b> g                                                                                       |
| Largest girder displacement                         | —                                                                                               | —            | —                                                                                                      | —                                                                                                  | <b>92</b> cm                                                                                         |
| Pot bearings supplied to the works                  | —                                                                                               | —            | —                                                                                                      | —                                                                                                  | <b>888</b>                                                                                           |
| Line capacity                                       | —                                                                                               | —            | —                                                                                                      | —                                                                                                  | <b>TBC</b>                                                                                           |

An independent, non-commercial reference site. Not affiliated with Taipei Rapid Transit Corporation, Taipei City Government, or any bus operator. Line colours are the official values published by each operator through Taiwan MOTC's open data platform. [About this site](#).

Station names, codes and sequence from TDX Transport Data eXchange, Ministry of Transportation and Communications, operator TRTC. Government open data. Retrieved 2026-08-10; source last updated 2020-01-31. Provenance.