

Rolling Stock

Train fleets — builders, technical specifications, formations and where each type runs.

8 entries

</

	VAL256	C370 (Bombardier Innovia)	
			
Maximum speed	80 km/h	—	-
Passenger doors	4 per car, 2 per side	4 per car, 2 per side	-
Traction motors	2 separately excited DC motors per car	2 AC induction motors per car	-
Train capacity	approximately 420 at 5 standing passengers/m² after interior changes	—	-
Train control	Cityflo 650 moving block	—	-
Inter-car gangway	None	—	-
Empty mass	TBC t	TBC t	-
Maximum operating speed	TBC km/h	70 km/h	;
Current depot allocation	TBC	—	-
Maximum design speed	—	80 km/h	-
Supply	—	750 V DC side-contact conductor rail	-
Carbody	—	Aluminium alloy	-
Motor rating	—	160 hp each at 1,760 rpm	-
Contract value	—	—	;
Cars per train	—	—	;
Formation	—	—	;
Maximum design load	—	—	;
Seats	—	—	;
Power supply	—	—	;
Door width	—	—	;
Original / replacement inverter	—	—	;
Full fleet delivered	—	—	;
Car dimensions	—	—	;
Published train capacity	—	—	-
Track gauge	—	—	-
Original traction control	—	—	-
Service brake	—	—	-
Joint 321/341 propulsion-reset budget	—	—	-
Traction and static inverter control	—	—	-
Train control network	—	—	-
Design speed	—	—	-
Driving-car length	—	—	-
Intermediate-car length	—	—	-

An independent, non-commercial reference site. Not affiliated with any transit operator or government body in Taiwan. Line colours are the official values published by each operator through Taiwan MOTC's open data platform. [About this site.](#)

Station names, codes and sequence from TDX Transport Data eXchange, Ministry of Transportation and Communications, operators TRTC, NTMC, TYMC, and TMRT. Government open data. Retrieved 2026-08-24; source last updated 2016-11-23. The 12 Sanying station records absent from TDX are sourced directly to New Taipei Metro and government publications on their pages. Provenance.