

Technology

The technology layer — signalling, power, guideway and automation — and why Taipei runs several of each.

Taipei operates two incompatible medium-capacity systems, several signalling generations, rubber-tyred and steel-wheel running, and both third-rail and overhead power. Nothing in English explains why, and the answer is mostly history — procurement decisions whose consequences outlived the contracts that made them. The Matra dispute [\[/rail/history/matra-dispute/\]](#) is the opening chapter of that story; the technical threads — automation grades, control centres, depot maintenance tiers, electrification, fire and evacuation design, platform doors, seismic design, signalling generations, track gauge and station-numbering — each have their own page below.

13 entries

Metro systems and operations

Signalling, traction power, depots, service spacing, first and last trains, and platform doors across Taipei-region metro lines.

Three numbering systems on one line

 Wenhu Line

Every Wenhu station has two numbers. On the southern half they run in opposite directions, and the northern half uses a different series again — because the line was built as two projects and a station was added to one of them late.

Metro depot maintenance levels

What Taipei's Level 1 through Level 5 depot labels actually describe, from pre-departure checks to network-wide overhaul.

Neihu Line steel running surface

Why the Neihu half of the Wenhu Line uses a pre-bent, coated steel running surface while the older Muzha half uses reinforced concrete.

Taipei Metro platform screen doors

How Taipei added platform screen doors to the early high-capacity network, and what the primary record does and does not say about completion by line.

Why the Wenhu Line looks the way it does

 Wenhu Line

The official design logic behind the Wenhu Line's steel-and-glass stations, its three Neihu architectural vocabularies, and its river-in-the-sky idea.

Taipei-region metro automation grades

What GoA0 through GoA4 mean on Taipei-region railways, and which current lines have a published automation grade.

Taipei Metro signalling generations

The published boundary between Taipei's fixed-block high-capacity signalling and its later moving-block CBTC systems.

Taipei-region metro electrification

Voltage, collection method and traction-substation boundaries across Taipei Metro, New Taipei Metro and the Airport MRT.

Taipei-region metro control centres

What the three Taipei-region metro operators publish about their control-centre arrangements, and what remains undisclosed.

Taipei-region metro track gauges

The published gauge boundary between Taipei's steel-wheel metro, the rubber-tyred Wenhua system and New Taipei light rail.

Taipei Metro seismic design boundaries

The sourced chronology from Taipei Metro's early seismic basis through structure-specific design methods and the current national-code comparison.

Taipei-region metro fire and evacuation systems

The published boundaries between fire detection, smoke control, life-safety systems, vehicle egress, fixed escape paths and the 2025 Circular Line emergency response.

Side by side

	Metro systems and operations	Metro depot maintenance levels
Taipei Metro service day	06:00–24:00	—
Wenhua peak headway	2–4 min	—
Tamsui-Xinyi peak headway	6 min, with 3 min overlap	—
Songshan-Xindian peak headway	4–6 min, with 3 min overlap	—
Zhonghe-Xinlu peak headway	6 min, with 3 min overlap	—
Bannan peak headway	6 min, with 3 min overlap	—
Level 3 additions	—	Wheel reprofiling and annual route-train maintenance
Level 4 additions	—	Emergency repairs, spares, non-routine inspection
Level 5 additions	—	Network-wide inspection, major overhaul and replacement
Detailed cycles	—	Set by each operator and approved by the company
Neihu section length in the paper	—	—
Reported section steel	—	—
Reported fishplate quantity	—	—
High-capacity platform-door arrangement	—	—
High-capacity platform length	—	—
Xinyi and Songshan design	—	—
Neihu section	—	—
Neihu underground running	—	—
Neihu underground stations	—	—
Neihu elevated bridge described in the design record	—	—
GoA2 operating arrangement	—	—
GoA4 operating arrangement	—	—
GoA4 control family in the Circular and Sanying records	—	—
High-capacity separation method	—	—
Wenhua position/control basis	—	—
Circular location boundary	—	—
High-capacity reset programme value	—	—
High-capacity traction-substation spacing	—	—
Medium-capacity traction-substation spacing	—	—
Wenhua incoming supply	—	—
Airport technical-page equipment count	—	—
TRTC centres in published 2014 arrangement	—	—
TYMC named line control centres	—	—

	Metro systems and operations	Metro depot maintenance levels
High-capacity design gauge	—	—
New Taipei light-rail vehicle gauge	—	—
Wenhu guideway type	—	—
Early metro maximum horizontal ground acceleration	—	—
CEDM tenth-edition maximum horizontal ground acceleration	—	—
Underground-station ODE	—	—
Underground-station MDE	—	—
Cut-and-cover tunnel ODE	—	—
Cut-and-cover tunnel MDE	—	—
Minimum published tunnel emergency airflow	—	—
Maximum published tunnel emergency airflow	—	—
Simulated train fire-resistance time in the Circular design study	—	—
Circular Line vehicle intercar gangway width	—	—

An independent, non-commercial reference site. Not affiliated with any transit operator or government body in Taiwan. Line colours are the official values published by each operator through Taiwan MOTC's open data platform. [About this site.](#)

Station names, codes and sequence from TDX Transport Data eXchange, Ministry of Transportation and Communications, operators TRTC, NTMC, TYMC, and TMRT. Government open data. Retrieved 2026-08-24; source last updated 2016-11-23. The 12 Sanying station records absent from TDX are sourced directly to New Taipei Metro and government publications on their pages. Provenance.