1. Install MySQL Workbench on your computer, connect to the local MySQL server, and take a screenshot of the default databases shown in the Schemas panel.

2.Create a new database called InstaClone in MySQL Workbench, then create a table named Users with columns: user_id (INT, primary key), username (VARCHAR), email (VARCHAR), and followers_count (INT).
Answer:

```
CREATE DATABASE INSTACLONE;
        USE INSTACLONE;

CREATE TABLE Users(
        used_id INT PRIMARY KEY,
        username VARCHAR,
        email VARCHAR,
        followers_count ,INT
        );
```

3.Insert 3 sample users into the Users table you created, using realistic Instagram-style usernames and follower counts.
Answer:

```
INSERT INTO Users(‘‘used_id,’username’,’email’,’followers_count’)VALUES
(1, 'alex_codes', 'alex@example.com', 1420),
(2, 'sarah_bakes', 'sarah@example.com', 28500),
(3, 'fit_liam', 'liam@example.com', 9300);
```

4.Create another table in the InstaClone database called Posts with columns: post_id (INT, primary key), user_id (INT), caption (VARCHAR), and post_date (DATE). Add a foreign key from Posts.user_id to Users.user_id to establish a relationship.
Answer:

```
CREATE TABLE posts(
        post_id INT PRIMARY KEY,
        user_id INT,
        caption VARCHAR,
        post_date DATE,
        FOREIGN KEY (user_id) REFERENCES Users(user_id
        );
```

5.Write a short comparison (3-4 lines each) of MySQL, PostgreSQL, Oracle, and SQLite, focusing on where each one is commonly used (for example: web apps, mobile apps, enterprise systems, etc.)
Answer:
MySQL: Commonly used for web applications, blogs (like WordPress), and e-commerce websites due to its speed and simple web stack integration.
PostgreSQL: Used for complex enterprise software, data analytics, and apps needing advanced feature support and strict data accuracy.
Oracle: Preferred by large corporations, banks, and major enterprise systems requiring high security, scalability, and dedicated support.
SQLite: Used for mobile apps (iOS/Android), embedded devices, and desktop software because it runs serverless inside a single local file