1.Open MySQL Workbench or CLI and write a CREATE TABLE statement to create a table called 'restaurants' with columns: id (INT, primary key, auto-increment), name (VARCHAR(100)), location (VARCHAR(100)), and rating (DECIMAL(2,1)).
Answer:

```
CREATE TABLE restaurants(
        id INT PRIMARY KEY AUTO_INCREMENT,
        Name VARCHAR(100),
        location VARCHAR(100),
        Rating DECIMAL(2,1),
        );
```

2.Use the ALTER TABLE command in MySQL to add a new column 'average_cost' (INT) to your 'restaurants' table.

Hint: Remember to specify the data type when adding a new column.
Answer: ALTER TABLE restaurants ADD COLUMN average_cost INT

3.Write a SQL statement to DROP the 'restaurants' table you created earlier. Double-check your command before running it to avoid accidental data loss.
Answer: DROP TABLE restaurants;

4.Create a new table called 'playlists' for a music app like Spotify, with columns: playlist_id (INT, primary key, auto-increment), title (VARCHAR(50)), created_by (VARCHAR(50)), and created_at (DATE).
Answer:

```
CREATE TABLE playlists(
        Playlist_id INT PRIMARY KEY AUTO_INCREMENT,
        Title VARCHAR(50),
        created_by VARCHAR(50),
        created_at DATE
        );
```