1.Create a SQL table called Restaurants with columns: id (INT, auto-increment), name (VARCHAR), cuisine (VARCHAR), rating (DECIMAL), and city (VARCHAR). Insert 5 sample restaurants into the table, each with a different cuisine and rating.
Answer:

```
CREATE TABLE Restaurants(
        id INT PRIMARY KEY AUTO_INCREMENT,
        name VARCGAR(),
        Rating DECIMAL(),
        city VARCHAR()
        );

INSERT INTO Restaurants (name, cuisine, rating, city) VALUES
('Spice Villa', 'North Indian', 4.3, 'Ahmedabad'),
('Cafe Mocha', 'Cafe', 4.6, 'Ahmedabad'),
('Dragon House', 'Chinese', 3.2, 'Mumbai'),
('Taco Fiesta', 'Mexican', 4.1, 'Ahmedabad'),
('Pasta Corner', 'Italian', 3.0, 'Delhi');
```

2.Write a SQL UPDATE statement to change the rating of the restaurant named 'Spice Villa' to 4.7 in the Restaurants table.
Answer:

```
UPDATE Restaurants SET rating = 4.7 where name = “Spice Villa”;
```

3.Delete all restaurants from the Restaurants table where the rating is less than 3.5 using a SQL DELETE statement.
Answer:

```
DELETE Restaurant where rating <3.5 ;
```

4.Use a SELECT query with WHERE and LIMIT to fetch the top 2 restaurants in the city 'Ahmedabad' with a rating above 4.0 from the Restaurants table.

Hint: Combine WHERE for city and rating, and LIMIT to restrict the number of results.
Answer:

```
SELECT * FROM Restaurants where city = “Ahmedabad” and rating > 4.0
LIMIT 2;
```