



## ITFL SPACE

The journal of our pilgrimage

July 15, 2018

# INSTALLING APACHE JENA FUSEKI ON DEBIAN 9

In this post, we are going to install Apache Jena Fuseki as a SPARQL Endpoint web application on a remote Linux machine running Debian 9 so it can be accessed using our web browser. Let's dive in.

## Keep in mind

This tutorial assumes we have a fresh installation of **Debian 9** and **Apache 2.4** HTTP Server configured. Then we are going to need a couple of things:

- **Apache Tomcat**, since Fuseki is a Java application which needs to be served by a Servlet Container, and it requires Tomcat 7 ([see here](#)). This also means we have to install **Java VM**.
- **Apache Jena Fuseki** binary distribution, which includes a **WAR** file ([get it here](#)). This packaging file contains the whole Fuseki application and we will give it to Tomcat for deployment.

Tomcat will be running at **http://localhost:8080** and Fuseki will be running at **http://localhost:8080/fuseki/** as a web application. In order for it to be accessible from the outside world, we are going to configure reverse proxy using Apache 2.4.

To get started, connect to your remote server and do the following steps with root privileges.

## Step 1: Install Java

```
apt-get install openjdk-8-jdk
java -version
openjdk version "1.8.0_171"
Runtime Environment (build 1.8.0_171-8u171-b11-1~deb9u1-b11)
64-Bit Server VM (build 25.171-b11, mixed mode)
```

## Step 2: Install Tomcat 7

The following commands will create a user for Tomcat, download and install Tomcat 7 and configure the system daemon to handle its process.

```
groupadd tomcat
mkdir /opt/tomcat
useradd -g tomcat -d /opt/tomcat -s /bin/nologin tomcat

mkdir ~/tmp
cd tmp
wget [link to the Tomcat 7.0.90 tar.gz file]
tar -zxvf apache-tomcat-7.0.90.tar.gz
mv apache-tomcat-7.0.90/* /opt/tomcat
chown -R tomcat:tomcat /opt/tomcat/
```

Create file `/etc/systemd/system/tomcat.service` with the following content.

```
nano /etc/systemd/system/tomcat.service
```

```
[Unit]
Description=Apache Tomcat 7
Wants=network.target
After=network.target

[Service]
Type=forking
Environment=JAVA_HOME=/usr/lib/jvm/java-1.8.0-openjdk-amd64/jre
Environment=CATALINA_PID=/opt/tomcat/temp/tomcat.pid
Environment=CATALINA_HOME=/opt/tomcat
Environment='CATALINA_OPTS=-Xms512M -Xmx1G -Djava.net.preferIPv4Stack=true'
Environment='JAVA_OPTS=-Djava.awt.headless=true'
ExecStart=/opt/tomcat/bin/startup.sh
ExecStop=/opt/tomcat/bin/shutdown.sh
SuccessExitStatus=143
User=tomcat
Group=tomcat
UMask=0007
RestartSec=10
Restart=always

[Install]
WantedBy=multi-user.target
```

Reload the system daemon, start Tomcat and check its status.

```
systemctl daemon-reload
systemctl start tomcat
systemctl status tomcat
systemctl enable tomcat
netstat -antup | grep 8080
```

Now Tomcat should be running at **http://localhost:8080**. If we run

```
curl http://localhost:8080
```

we'll get a bunch of HTML containing the Tomcat homepage.

### Step 3: Deploy Apache Jena Fuseki in Tomcat

This step is quite simple. We can just download the Fuseki binary distribution package and extract the **fuseki.war** file to **/opt/tomcat/webapps/** and Tomcat will automatically deploy it as a web application in a couple of seconds.

```
cd ~/tmp
wget [link to the Apache Jena Fuseki 3.8.0 tar.gz file]
tar -zxvf apache-jena-fuseki-3.8.0.tar.gz
mv ./apache-jena-fuseki-3.8.0/fuseki.war /opt/tomcat/webapps/fuseki.war
```

Once that is done, the Fuseki application will be running at **http://localhost:8080/fuseki/**, so if we run

```
curl http://localhost:8080/fuseki/
```

we'll get a bunch of HTML containing the Fuseki homepage.

### Step 4: Make Fuseki public using Reverse proxy

Reverse proxy is an amazing feature of Apache. It allows us to make local web applications public in no time. The main idea is to redirect all requests from the outside web to a local web server. For example, we can redirect **https://our.domain.com/fuseki/** to **http://localhost:8080/fuseki/** and that's exactly what we are going to do.

```
nano /etc/apache2/sites-available/our.domain.com.conf
```

At the end of the **<VirtualHost \_default\_:443>**, put in the following configurations:


```
...
ProxyRequests Off
```

```

ProxyPreserveHost On
<Proxy *>
    Require all granted
</Proxy>
RewriteEngine on
RewriteRule ^/fuseki$ /fuseki/ [R]
ProxyPass /fuseki/ http://localhost:8080/fuseki/
ProxyPassReverse /fuseki/ http://localhost:8080/fuseki/
</VirtualHost>

```

And voila! We can start using Fuseki in our web browser.



Apache Jena Fuseki

Version 3.8.0. Uptime: 2h 4m 05s

### Datasets on this server

dataset name	actions
/yugioh	<a href="#">query</a> <a href="#">add data</a> <a href="#">info</a>

**Use the following pages to perform actions or tasks on this server:**

<b>Dataset</b>	Run queries and modify datasets hosted by this server.
<b>Manage datasets</b>	Administer the datasets on this server, including adding datasets, uploading data and performing backups.
<b>Help</b>	Summary of commands and links to online documentation.

## Gotchas!

Just a couple of troubles to shoot:

- In the virtual host configuration, we used RewriteEngine. For this to work we need to enable the Apache2 Rewrite module with

```
a2enmod rewrite  
systemctl restart apache2
```

- If, for some reason, the Fuseki application couldn't be deployed, take a look at the log file to see what the issue is.

```
cat /opt/tomcat/logs/catalina.out
```

If it says

```
... FUSEKI_BASE is not writeable: /etc/fuseki
```

then we can just run the following command to fix that

```
chown -R tomcat:tomcat /etc/fuseki
```

## References

1. <https://jena.apache.org/documentation/fuseki2/>
2. <https://www.itzgeek.com/how-to/linux/debian/how-to-install-tomcat-8-5-on-debian-9-ubuntu-16-04-linux-mint-18.html>
3. <https://www.rosehosting.com/blog/how-to-install-tomcat-9-on-debian-9/>
4. <https://stackoverflow.com/questions/869092/how-to-enable-mod-rewrite-for-apache-2-2>
5. <https://serverfault.com/questions/134183/how-to-reverse-proxy-with-or-without-trailing-slash>
6. <https://stackoverflow.com/questions/5109112/how-to-deploy-a-war-file-in-tomcat-7>

Share

Labels: apache jena fuseki, graph database, linked data, linux, RDF, semantic web, SPARQL, triple store

Location: Prague, Czechia


COMMENTS



Enter your comment...

#### POPULAR POSTS





September 08, 2018

## WATSON'S DEPICTION OF HOLMES #1

[Share](#) [Post a Comment](#)



Powered by Blogger



### Nguyen Viet Bach

*My interests dwell along the  
mysteries of the universe. I  
like to craft, to listen, to  
understand, to read, to  
observe, to think, to look, to  
uncover, to find out, to feel,  
so to protect the mattered.  
To me, nothing is fascinating  
enough to be meaningful*



*but the most enchanting  
and benevolent perception  
of men which is at times  
called emotion and logically  
systemized resolutions of  
deepest sorts of queries  
around and beyond life  
which, by the way, happens  
to be caught in an infinite  
loop. Have faith in me, I'm  
afraid of nothing but time  
and complexity.*

VISIT PROFILE

---

Archive



---

Labels

