# Project Executable Files

Phase 7 | Run and deployment artifact guide

## Runtime and source entry points

| Artifact | Use |
|---|---|
| backend/app/main.py | FastAPI application entry point: uvicorn app.main:app. |
| backend/requirements.txt | Backend Python dependencies. |
| frontend/package.json | Frontend scripts and npm dependencies. |
| frontend/src/main.jsx | React browser entry point. |
| docker-compose.yml | Local multi-container deployment configuration. |
| backend/Dockerfile | Backend container build definition. |
| frontend/Dockerfile and nginx.conf | Frontend container build and static serving configuration. |
| render.yaml | Render backend service declaration. |
| frontend/vercel.json | Vercel rewrite for direct client-side routes. |

## Local run

- Backend: create a Python virtual environment in backend, install requirements, configure backend/.env, then run uvicorn app.main:app --reload from backend/.
- Frontend: install packages in frontend/ and run npm run dev.
- For persistent trips, configure Supabase and apply backend/schema.sql.
- For remote generation, configure the selected provider; otherwise use the local development provider.

## Hosted setup

For Render, provide production secrets and frontend origin in service environment. For Vercel, set the frontend root directory and VITE_API_BASE_URL to the backend origin. For Docker Compose, configure root/backend environment values per README and place a TLS-enabled reverse proxy in front of public traffic as described by the project setup guide.

## Secrets

*Never publish .env files, JWT signing secrets, AI API keys, or Supabase service-role credentials. Frontend VITE_ variables are bundled into browser code and must not contain privileged secrets.*

Prepared from the current project source and configuration. Product assumptions and proposed work are labeled; no user research, test result, or deployment result is implied unless explicitly stated.