Sample Project Documentation

Phase 7 | Concise system and API overview

Project summary

The Personalized Travel Itinerary Planner is a React web application with a FastAPI backend. It collects trip preferences, generates a day-by-day itinerary, and supports account-based saved-trip management. Supabase provides persistent storage when configured; local development can use in-memory fallback behavior.

Core API

Method and path	Description	Access
POST /auth/register	Register and issue an access token.	Public
POST /auth/login	Authenticate and issue an access token.	Public
GET /auth/me	Get authenticated profile.	Bearer token
POST /trips/plan	Generate itinerary.	Bearer token
POST /trips/create	Save supplied or generated trip.	Bearer token
GET /trips and /trips/{id}	List trips or get one with itinerary.	Bearer token
PATCH /trips/{id}	Update trip fields and optional itinerary.	Bearer token
DELETE /trips/{id}	Delete trip.	Bearer token
POST /trips/regenerate-day	Generate replacement day.	Bearer token

Core data

- User: normalized email, name, password hash, and timestamps.
- Trip: owner, destination, dates, preferences JSON, and timestamps.
- Itinerary day: trip reference, day number, title, activity JSON, notes.
- History: user, optional trip, action, details JSON, and timestamp.

Limitations

Generated activities and costs are suggestions. The app does not book travel or connect to live travel data. Share links do not bypass authentication. In-memory data is temporary and resets when the server stops.

Prepared from the current project source and configuration. Product assumptions and proposed work are labeled; no user research, test result, or deployment result is implied unless explicitly stated.