

# EECS 6893 HW4

---

Jing Qian (jq2282)

## Problem 1

1. Answer these questions in simple words.

### 1.1

SVG Coordinate Space and Mathematical/Graph Coordinate are both 2-dimensional flat space. They work in the same way except following:

- The (0, 0) coordinates of Mathematical Coordinate Space fall on the bottom left while those of SVG Coordinate Space on the top left.
- The Mathematical Coordinate Space has Y coordinate growing from bottom to top while SVG Coordinate Space has Y coordinate growing from top to bottom.

### 1.2

In d3.js, `enter()` and `exit()` are operations that used in joining an array of data to a D3 selection. If the array is longer than the selection, we use `enter()` to represent the missing elements. If the array is shorter than the selection, we use `exit()` to represent elements that need to be removed.

### 1.3

In SVG, transform functions are used for geometric manipulations on the SVG elements, including translation (movement), rotation, scale, and skew (shear).

A translation moves all the points of an element in the same direction and by the same amount. Translation preserves parallelism, angles and distances.

### 1.4


The anonymous function `a.map(function(d,i){return i+5})` here equals to the following command in Python: `[i+5 for i in range(len(a))]`. So the return value of the anonymous function is: `[5, 6, 7, 8, 9]`. 需要描述anonymous function或者map吗？对于定义还是有点迷茫。

2. Modify the sample code to get desired figure.

The screenshots of codes and the output bar-chart are as following:

```
big_data_hw4_part1.html *
1  <!DOCTYPE html>
2  <html lang="en">
3  <head>
4      <script type="text/javascript" src='HW4_Q1.js'> </script>
5      <meta charset="UTF-8">
6      <title>Homework 4 Question 1</title>
7  </head>
8
9  <style>body{}.bar-chart{background-color: #006666;}</style>
10 <svg class="bar-chart"></svg>
11
12 <script src="https://d3js.org/d3.v5.min.js"></script>
13 <body>
14 <script>
15     HW4_Q1();
16 </script>
17
18 </body>
19 </html>
```

```
1 function HW4_Q1(){
2   var data = [80, 100, 56, 120, 180, 30, 40, 120, 160];
3   var svgWidth = 500, svgHeight = 300;
4   // The required padding between bars is 5px.
5   // The label must locate 2px above the middle of each bar.
6
7   var svg = d3.select('svg')
8     .attr("width", svgWidth)
9     .attr("height", svgHeight);
10
11   var barChart = svg.selectAll("rect")
12     .data(data)
13     .enter()
14     .append("rect")
15     .attr("class", "bar")
16     .attr("transform", function(d, i) { return "translate(" + i
17       * 55 + ", " + (svgHeight - d) + ")"; })
18     .attr('width', 50)
19     .attr('height', svgHeight)
20     .attr("fill", "#C0C0C0");
21
22   var text = svg.selectAll(".textlabel")
23     .data(data)
24     .enter()
25     .append("text")
26     .attr("class", "textlabel")
27     .attr("transform", function(d, i) { return "translate(" + (
28       i * 55 + 15) + ", " + (svgHeight - d - 2) + ")"; })
29     .style("font-family", "Arial")
30     .style("color", "#333333")
31     .text(function(d){return d;});
32 }
```



## Problem 2

Step 1: Data processing

```
import numpy as np
import pandas as pd
```

```
data = pd.read_csv('hw3-wordcount.csv')
```

```
time = list(set(data.time))
df = pd.DataFrame(time, columns=['time'])
```

```
words = ['ai', 'data', 'good', 'movie', 'spark']
for i in words:
    df[i] = 0
```

```
for i in range(len(df)):
    for j in words:
        tmp = data[(data.time==df.time[i])&(data.word==j)]
        if not tmp.empty:
            df[j][i] = int(tmp['count'])
df.head()
```

	time	ai	data	good	movie	spark
0	2019-10-31 13:28:50 UTC	10	2	10	244	11
1	2019-10-31 13:29:50 UTC	15	1	4	209	14
2	2019-10-31 13:26:50 UTC	19	4	8	226	14
3	2019-10-31 13:27:50 UTC	13	0	4	178	18
4	2019-10-31 13:25:50 UTC	9	4	3	176	17




Schema   Details   Preview

Row	time	ai	data	good	movie	spark
1	2019-10-31 13:27:50 UTC	13	0	4	178	18
2	2019-10-31 13:29:50 UTC	15	1	4	209	14
3	2019-10-31 13:28:50 UTC	10	2	10	244	11
4	2019-10-31 13:26:50 UTC	19	4	8	226	14
5	2019-10-31 13:25:50 UTC	9	4	3	176	17
6	2019-10-31 13:30:50 UTC	37	5	9	207	8

Step 2: Create Django project

Name	Date Modified
▼ hw4_tutorial	Today at 1:36 AM
▼ hw4_tutorial	Today at 1:34 AM
▶ __pycache__	Today at 1:43 AM
__init__.py	Today at 1:22 AM
settings.py	Today at 1:32 AM
urls.py	Today at 1:43 AM
view.py	Today at 1:40 AM
wsgi.py	Today at 1:22 AM
▼ static	Today at 1:40 AM
▶ css	Today at 1:40 AM
▶ js	Today at 1:40 AM
▼ template	Today at 1:33 AM
helloworld.html	Today at 1:34 AM
db.sqlite3	Today at 1:36 AM
manage.py	Today at 1:22 AM



# Hello World!

### Step 3. Finish the code

Modify the view.py:

```

SQL = "select * from datasetHW3.wordcount2 limit 8"
df = pandas_gbq.read_gbq(SQL)
#print(df)
data = {}

res = []
words = ['ai', 'data', 'good', 'movie', 'spark']
time = sorted(list(df.time))
for i in time:
    tmp = {}
    tmp['Time'] = str(i)[11:16]
    tmp['count'] = {}
    for j in words:
        tmp['count'][j] = int(df[df.time==i][j])
    res.append(tmp)
data['data'] = res
#print(data['data'])
return render(request, 'dashboard.html', data)

```

Modify the dashboard.js

```

function segColor(c) {
    cmap = {ai: "#4753CC", data: "#828499", good: "#73C9FF", movie: "#CC6E47",
    , spark: '#FFD4B3'};
    return cmap[c];/* TO FINISH */
}

// compute total for each state.
fData.forEach(function (d) {
    d.total = d['count']['ai']+d['count']['data']+d['count']['good']+d['count']
    ['movie']+d['count']['spark']; /* TO FINISH */
})

```




```
//create the rectangles.
bars.append("rect")
  .attr("x", function (d,i) {return i*x.rangeBand()*1.1+10;})/* TO
  FINISH */
  .attr("y", hGDim.b/* TO FINISH */)
  .attr("width", x.rangeBand())
  .attr("height", function (d) {
    return hGDim.h - y(d[1]);
  })
  .attr('fill', barColor)
  .on("mouseover", mouseover)
  .on("mouseout", mouseout);

//Create the frequency labels ABOVE the rectangles.
bars.append("text").text(function (d) {
  return d3.format(",")(d[1])
})
  .attr("x", function (d) {
    return x(d[0])/* TO FINISH */ + x.rangeBand() / 2;
  })
  .attr("y", hGDim.b+5/* TO FINISH */)
  .attr("text-anchor", "middle");
```

```
// transition the height and color of rectangles.
bars.select("rect").transition().duration(500)
  .attr("y", function (d) {
    return y(d[1]);
  })/* TO FINISH */
  .attr("height", function (d) {
    return hGDim.h - y(d[1]);
  })
  .attr("fill", color);
```

```
// calculate total count by segment for all state.
var tF = ['ai', 'data', 'good', 'movie', 'spark'].map(function (d) {
  return {
    type: d, count: d3.sum(fData.map(function (t) {
      return d.total/* TO FINISH */;
    }))
  };
});
```

Result:



## Problem 3

Based on the edge.csv and node.csv provided by TA, the view.py is modified as following:

```

SQL1 = 'select * from datasetHW3.node'
df1 = pandas_gbq.read_gbq(SQL1)
#print("node preview: ", df1[:5])
node = []
for i in range(len(df1)):
    tmp = {}
    tmp['node'] = int(df1['node'][i])
    node.append(tmp)
#print("node,", node[:5])

SQL2 = 'select * from datasetHW3.edge'
df2 = pandas_gbq.read_gbq(SQL2)
#print("edge preview: ", df2[:5])
edge = []
visited = set()
for i in range(len(df2)):
    tmp = {}
    pair = (int(df2['source'][i]), int(df2['target'][i]))
    if pair not in visited:
        visited.add(pair)
        tmp['source'] = pair[0]
        tmp['target'] = pair[1]
        edge.append(tmp)
print("len of edge: ", len(edge))
data = {}
data['n'] = node
data['e'] = edge

```

Modified connection.js:

```

SQL = "select * from datasetHW3.wordcount2 limit 8"
df = pandas_gbq.read_gbq(SQL)
print(df)
data = {}

res = []
words = ['ai', 'data', 'good', 'movie', 'spark']
time = sorted(list(df.time))
for i in time:
    tmp = {}
    tmp['Time'] = str(i)[11:16]
    tmp['count'] = {}
    for j in words:
        tmp['count'][j] = int(df[df.time==i][j])
    res.append(tmp)
data['data'] = res
print(data['data'])
return render(request, 'dashboard.html', data)

```

```

var svg = d3.select("body")
    .append("svg")
    .attr("width", width/* TO FINISH */)
    .attr("height", height/* TO FINISH */);

```

```

var svg_edges = svg.selectAll("line")
    .data(edges/* TO FINISH */)
    .enter()
    .append("line"/* TO FINISH */)
    .style("stroke", "#ccc")
    .style("stroke-width", 1);

```

```

var svg_nodes = svg.selectAll("circle")
    .data(nodes/* TO FINISH */)
    .enter()
    .append("circle"/* TO FINISH */)
    .attr("r", 20)
    .style("fill", function(d,i){return color(i);})/* TO FINISH */
    .call(force.drag);

```

```

var svg_texts = svg.selectAll("text")
    .data(nodes)
    .enter()
    .append("text")
    .style("fill", "black")
    .attr("dx", 20)
    .attr("dy", 8)
    .text(function(d){return d.node;}/ * TO FINISH */ );

force.on("tick", function(){
    svg_edges.attr("x1", function(d){return d.source.x;}/ * TO FINISH */)
        .attr("y1", function(d){return d.source.y;}/ * TO FINISH */)
        .attr("x2", function(d){return d.target.x;}/ * TO FINISH */)
        .attr("y2", function(d){return d.target.y;}/ * TO FINISH */);

```

Result:

