Object	1	4 1.6 0.4] = 4 1.5 0.2] = 4 1.6 0.2] = 1 1.6 0.2] = 1 1.5 0.2] = 1 1.5 0.2] = 1 1.5 0.2] = 1 1.5 0.2] = 1 1.5 0.2] = 1 1.5 0.2] = 1 1.5 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.3 0.2] = 1 1.4 0.2] = 1 1.4 0.2] = 1 1.4 0.2] = 1 1.4 0.2] = 1 1.4 0.2] = 1 1.5 0.2] = 1 1.4 0.2] = 1 1.5 0.2] = 1 1.4 0.2] = 1 1.5	===> Class	setosa se	r r r r r r r r r r r r r r r						
Object	1 1	8 4.7 1.2] = 4.3 1.3] = 4.4 1.4] = 8 4.8 1.4] = 9 4.5 1.5] = 6 3.5 1.] = 6 3.5 1.] = 6 3.5 1.] = 6 3.7 1.] = 6 4.5 1.6] = 6 4.5 1.6] = 6 4.5 1.6] = 6 4.4 1.3] = 6 4.4 1.3] = 6 4.4 1.2] = 6 4.4 1.2] = 6 4.5 1.6] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.2 1.3] = 7 4.3 1.3] = 7 4.3 1.3] = 7 5.5 2.1] = 7 5.6 6.6 2.1] = 7 5.6 6.6 2.1] = 7 5.8 2.2] = 7 5.3 1.9] = 7 5.5 2.1] = 7 5.7 2.1] = 7	===> Class	versicolo							
Object Ob	t [7.2 3. t [6.2 2. t [6.1 3. t [6.4 2. t [7.2 3. t [7.4 2. t [7.9 3. t [6.4 2. t [6.3 2. t [6.3 2. t [6.3 3. t [6.3 3. t [6.9 3. t [6.9 3. t [6.9 3. t [6.7 3. t [6.7 3. t [6.3 2. t [6.7 3. t [6.3 2. t [6.7 3. t [6.9 3. t [6.7 3. t [6.9 3. t [6.7 3. t [6.9 3. t [6.7 3.	2 6. 1.8] = 8 4.8 1.8] = 4.9 1.8] = 8 5.6 2.1] = 5.8 1.6] = 8 6.1 1.9] = 8 6.4 2.] = 8 5.6 2.2] = 8 5.1 1.5] = 6 5.6 1.4] = 6.1 2.3] = 4 5.6 2.4] = 1 5.5 1.8] = 4.8 1.8] = 1 5.4 2.1] = 1 5.6 2.4] = 1 5.1 2.3] = 5.2 2.3]	===> Class ===> Class ===> Class ===> Class ==> Class	virginica		and 1 inste	ead of 2,	this shou	ld improve	e the resu	lt:
Prir prir # Co # Va NEW matr: [1	ix: [[022474487 .22474487 .4.934324 ance: 1.0 I np.asarra at (f'Mean of vars X are = prepresented dat ('Transfort (f'matrix at (f'matrix at (f'warian though means are not some reason as formed	0. 1.22474487 5538895844e- ay([[1, -1,	22474487 -0.267261 -1.069044 -17 2], 0], -1]]) %s' % X2. 444444444 AnMaxScale fit_tran ansformed_da aransformed to previous lot smalle not asked	1, no real 1.33630621 24] 97]] mean()) r() sform(X2) data) ta.mean()) d_data.var us values r and this	improvement] ()) (and we don means small	't really oler noise,	care about which is	it becau a lot more	se it is a e signific	ant	
matr: [1. [0. mean varia 39]: # D. # ma pd_i for sb.p # ## # # # # # # # # # # # # # # # # #	ix: [[0.5] 0.481481 ance: 0.16 2	. 0 48148148145 94101508916 andas datafra	and object	t np.c_[iris_ dataset[': f_classes[nget') ength x widength and se flowers ength x perger the flowers t is worth t are seto. be justificine') on	feature_nam n])) dth width are r have simil tal length ower is, th mentioning sa, then co ied here si the graph	roportional ar petals e bigger an that even mes versice	arget']) 1, they sh re both of if flower clor and the results	ould be re its part. s' propor hen virgi.	ound then s. tions are nica. ed and in	similar, given case	the
sepal sepal petal petal target 41]: # D. sb.h # Ye # AJ # Bu # No	print(n) l length (cl width (cl length (cl width (cl wi	m) cm) mi) _iris_data.c correlation n't quite no air, this is ided to use 1	drop(['tarns between bice connict quite bank heatmap in the state of t	[sepal ledection betweet of showed nstead of showed nstea	ngth x peta ween petal on pairplo	l length] a width and s t	and [petal sepal leng	th, I als	o suspect	this is d	
inder color color for plt. 8.0 7.5 (mu) the length (mu) the l	plt.fign ax = 1 ors = ['re ors = [cco first_labe for second ax = n ax.sca ax.gr: index subplots_a show() 2	adjust (wspace of the following of the f	for i in dataset. fe indataset. fe indataset	pd_iris_da ature_names et.feature ex, xlabel= rst_label] pace=0.4) 25 3.0 3. sepal length (a petal length (a rop(['targe aFrame(pca] = pd_iris aFrame(pca] = pd_iris	ata.target] s: _names: _first_labe , pd_iris_d 7 8 cm) 5 4.0 4.5 cm) 20 2.5 cm) fit_3.fit_ s_data['target] fit_2.fit_ fit_2.fit_	1, ylabel=sata[second] 7 6 (m) the sata [second] 7 6 (m) the sata [second	second_lab_label], c 6 sepal length (cm) 3 4 5 petal length (cm)	all x_column	2.5 (m) the stand (m) the stan	sepal width (cm)	2.0
lda_lda_lda_lda_lda_prir 0 -2	fit_2 = Lifitted_ir: fitted_ir: f	DA (n_componed is_dataset = 1	ents=2) pd.DataF target'] caset.head rget 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0	rame (lda_f: = pd_iris_c (5)) size=(13, : lda_fittec pd_iris_da list[data_ pace=0.4) ransofrmat. mum variance	data['targe 13)) d_iris_data ata.target] _list][1], ion technique	set] color = colues,	lors)		s], pd_iri	s_data['t	arç
# Your 1.5 - 1.0 -	Jou can clean Jou ca	-7.5 me reduction peline (caler(), codComponent is_data[x_cdorsClassifications_dataset =	-5.0 with oth csAnalysis per(n_neigh knn.fit(nca.transf	-2.5 er reduction (n_component d_iris_data bors=2) nca.transfor orm (pd_iris 'target']	O.O.O.O.O.O.O.O.O.O.O.O.O.O.O.O.O.O.O.	plue dots l l l l l l data[x_co] lumns]))	z 2	7.5	ta['target		
ax = ax .s ax .g plt. plt. # He # ma 30 - 10 - 10 - 47]: # F	-100 e last part of taset. MNIST	the laboratory	ce=0.4, hs ad green of ally exten	have tried MN	divided in atever reas	on 50 asic dataset o		100			
49]: plt. for plt. # I	figure (figure (figure (figure (figure (figure figure))))))))	ot(10, 10, i) w(train_X[i] render more	2.5)) L+1) , cmap=pl images. D 10 20 10 20 10 20 10 20 10 20 10 20 10 20 10 20 20 10 20 20 10 20 20 20 20 20 20 20 20 20 20 20 20 20	t.get_cmap	('gray'))				10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	10 - 20 - 20 - 20 - 20 - 20 - 20 - 20 -	10