

Reference excerpt 01-015

Source: arXiv:1604.05171v1 | License: CC BY 4.0 | Word window: 498-757

blood even in the absence of a direct measurement of such parameter obtained, for example, by using an ultrasound Doppler scanner. A first attempt to this goal was presented in [Sisini et al.(2015b)], where the instantaneous velocity of the blood in the IJV was determined qualitatively, for one cardiac cycle, using the Womersley equation [Womersley(1955a), Womersley(1955b), Womersley(1955c)]. Physical description of the RA-IJV segment The RA-IJV system is represented in Fig. 1 as a tube with a circular section. G indicates a reference point on the right IJV. The $w(z, r, t)$ function represents the velocity of the blood in the z direction. It depends on z coordinate, on r (the distance from the axis z) and on t (the time). The symbol $w(z, t)$ is used to indicate the blood velocity averaged over the CSA. The pressure at the right end of the tube ($z = 0$) is the residual arterial pressure and it is assumed to have a constant value p_r while at the left end of the tube ($z = z_{RA}$) the pressure feels the effects of the RA activity varying periodically with the cardiac cycle. The pressure at $z = z_{RA}$ (see Fig. 1) is supposed to be the sum of a component p_c constant in time and of a periodic component $p_a(t)$ which varies according to the atrial cardiac activity. The blood flow is due to the pressure gradient between the ends of the cylinder. It produces a velocity $w_T(t)$ that results from a constant component w_0