Types of products	:type	Type/Model	: cookware
Type of Material	:material	Brand	: TATA
Coating Material	:pb	Standard no.	:SNI 8752:2020
Form	:1	Job Order No.	:

Test equipment / Equipment no:		Test method No.	:SNI IEC-4005
Measuring Cup, Steel Rule		Serial No.	:123456
		Room Temp. Humidity	:25 45
		Place / Date testing	: Qualis 1,_____21-03-2026 - 21-03-2026_____
Examiner:_____	Checked : _____	Approval: _____	Decision:

Klausul Clause	Parameter Uji Test Parameters	Satuan Unit	Hasil Tes Test Results	Persyaratan Mutu Quality Requirements
6	**TEST METHOD**			
6.1	Physical properties test	54	54	54
6.1.1	Visible properties test	54	54	54
	Done visually and without any aids	54	5	The surface of all types of cooking utensils made of metal must not have defects such as holes, cracks, uneven surfaces, and other surface defects that can reduce their usefulness in use.
6.1.2	Surface Sharpness Test	45	4	Every surface on all types of cooking utensils made of metal must not have sharp parts that could cause

				injury and be unsafe when used
	It is done visually and without any tools (finger feel) by feeling each surface.	45	4	Every surface on all types of cooking utensils made of metal must not have sharp parts that could cause injury and be unsafe when used
6.3	**Base material thickness test**			
	Refer to Requirement	4		45
	Impact bonding or brazing testing is carried out on cookware in an empty condition.	45	45	45
6.4	**Strength Test**			
6.4.1	Bottom sandwich strength test of stainless steel cookware	454		The handle of the cookware must be able to support a load equivalent to 1.5 times the volume of water of the cookware capacity.
	Impact bonding or brazing testing is carried out on cookware in an empty condition.	45		Resistance to high heat stove flames for a certain period of time where no base part can be separated from the body, and no filler can melt out of the body of the cookware, except for the plain type (without coating).
6.4.2	Fatigue resistance test on handle strength	4	54	The handle of the cookware must be able to support a load equivalent to 1.5 times the volume of water of the cookware capacity.

	Testing was carried out using single grip, combination grip, and	45	45	445
	Testing was carried out using single grip, combination grip, and short grip strength testing equipment.	45	45	45

8.2 Table: Product Thickness Measurement

8.2.1 Tableware

Diameter	Test duration (minutes)	Test results	Decision
45			
Additional information:			

6.2 Form test

6.2.1 Measuring round cookware

D1	D2	Roundness value	Roundness value tolerance Max 2%	Decision
45				
Additional information:				

6.3 Base material thickness test

0° angle point	90° angle point	180° angle point	270° angle point	Average	Thickness (t) Min (mm)	Decision
9852985						
Additional information:						

6.4.2 Fatigue resistance test on handle strength

Water volume	5 x 1.5 Water volume (V)	Number of cycles 15,000 times	Test results	Decision
Additional information:				

6.6 Non-stick coating adhesion test

Soaking duration (minutes)	Number of scratches	Stroke distance	Test results	Decision
6544				
Additional information:				

6.7 Thermal shock test for enameled cookware			
Test Temperature 1	Test Temperature 2	Test results	Decision
5			
Additional information:			

6.8 Coating Thickness Test							
Type of material	Coating Material	Results of				Min layer thickness	Decision
		Measurement	Measurement	Measurement	Average		
7465							
Additional information:							

PT Qualis Indonesia	Witnessed by		
	Name	Company	Signature
Tested by:			
Checked by:			