Types of products	:type	Type/Model	: cookware
Type of Material	:material	Brand	: TATA
Coating Material	:pb	Standard no.	:SNI 8752:2020
Form	:1	Job Order No.	:

Test equipment / Equipment no:		Test method No.	:SNI IEC-4005
Measuring Cup, Steel Rule		Serial No.	:123456
		Room Temp. Humidity	:25 45
		Place / Date testing	: Qualis 1,_____21-03-2026 - 21-03-2026_____
Examiner:_____	Checked : _____	Approval: _____	Decision:

Klausul Clause	Parameter Uji Test Parameters	Satuan Unit	Hasil Tes Test Results	Persyaratan Mutu Quality Requirements
6	**TEST METHOD**			
6.1	Physical properties test	54	54	54
6.1.1	Visible properties test	54	54	54
	Done visually and without any aids	54	5	The surface of all types of cooking utensils made of metal must not have defects such as holes, cracks, uneven surfaces, and other surface defects that can reduce their usefulness in use.
6.1.2	Surface Sharpness Test	45	4	Every surface on all types of cooking utensils made of metal must not have sharp parts that could cause

				injury and be unsafe when used
	It is done visually and without any tools (finger feel) by feeling each surface.	45	4	Every surface on all types of cooking utensils made of metal must not have sharp parts that could cause injury and be unsafe when used
6.3	**Base material thickness test**			
	Refer to Requirement	4		45
	Impact bonding or brazing testing is carried out on cookware in an empty condition.	45	45	45
6.4	**Strength Test**			
6.4.1	Bottom sandwich strength test of stainless steel cookware	454		The handle of the cookware must be able to support a load equivalent to 1.5 times the volume of water of the cookware capacity.
	Impact bonding or brazing testing is carried out on cookware in an empty condition.	45		Resistance to high heat stove flames for a certain period of time where no base part can be separated from the body, and no filler can melt out of the body of the cookware, except for the plain type (without coating).
6.4.2	Fatigue resistance test on handle strength	4	54	The handle of the cookware must be able to support a load equivalent to 1.5 times the volume of water of the cookware capacity.

	Testing was carried out using single grip, combination grip, and	45	45	445
	Testing was carried out using single grip, combination grip, and short grip strength testing equipment.	45	45	45
6.2	**Form test**			
6.2.1	For round shape			The roundness value of cookware should not be more than 2%
6.2.1	Determined based on Figure 4 with the following formula: Roundness Value (NK) = (D1 – D2)/ D1 x 100% Figure 4 - Illustration of roundness difference calculation Information:D1: Maximum cooking tool hole diameter. D2: Minimum cooking tool hole diameter			The roundness value of cookware should not be more than 2%
6.5	**Volume capacity test**			
	Pour water into the test sample to the maximum limit.			- The capacity of cooking equipment is determined by the volume of water it can hold. fully on the cookware, with a capacity tolerance of ± 5%, in liters or quarts. For short type cookware, the volume capacity is stated in inches or centimeters of the top surface diameter with a tolerance of ± 2%. For kettle-type cooking utensils, the volume capacity is determined with a tolerance of ± 5% of the kettle's full capacity. Record the measurement results, then compare them with the volume

				specifications listed on the test sample.
6.6	**Non-stick coating adhesion test**			
	Testing was carried out by means of cross cuts for the non-stick coating.			Must withstand cross-scratch adhesion tests and the result must be that there is no peeling of the coating.
6.7				Must be able to withstand thermal shock conditions and must not crack or peel up to temperatures of 220°C.
6.8	**Coating thickness test**			
	Place the cooking utensil to be tested for coating thickness on a flat surface.			Coating of cookware is determined based on the type of material used with requirements according to Table 3.
6.9	**Acid resistance test**			
	Acid resistance is achieved with citric acid monohydrate (C6H8O7-H2O)			After testing, visually observe the test surface from various angles, to ensure that there is no color change on the test surface.
6.10	**Product stability test**			
6.10.1				
	Place the test sample on a flat surface			The test sample should not rotate or sway
6.10.2				
	Then touch any position of the test sample.			The test sample should not rotate or sway

6.10.3				
	The test sample should not rotate or sway			The test sample should not rotate or sway
8	**MARKING**			
8.1	**Product**			
	Every product that meets the quality requirements is labeled by stating at least:			
	Factory name and/or trademark			
	Type of material			
8.2	**Packaging**			
	Every product packaging that meets quality requirements is labeled by stating at least:			
	Factory name and/or trademark			
	Type of Products			
	Type of material			
	Size			

8.2 Table: Product Thickness Measurement			
8.2.1 Tableware			
Diameter	**Test duration (minutes)**	**Test results**	**Decision**
45			
Additional information:			

6.2 Form test				
6.2.1 Measuring round cookware				
D1	**D2**	**Roundness value**	**Roundness value tolerance Max 2%**	**Decision**
45				
Additional information:				

6.3 Base material thickness test						
0° angle point	90° angle point	180° angle point	270° angle point	Average	Thickness (t) Min (mm)	Decision
9852985						
Additional information:						

6.4.2 Fatigue resistance test on handle strength				
Water volume	5 x 1.5 Water volume (V)	Number of cycles 15,000 times	Test results	Decision
Additional information:				

6.6 Non-stick coating adhesion test				
Soaking duration (minutes)	Number of scratches	Stroke distance	Test results	Decision
6544				
Additional information:				

6.7 Thermal shock test for enameled cookware			
Test Temperature 1	Test Temperature 2	Test results	Decision
5			
Additional information:			

6.8 Coating Thickness Test							
Type of material	Coating Material	Results of				Min layer thickness	Decision
		Measurement	Measurement	Measurement	Average		
7465							
Additional information:							

PT Qualis Indonesia	Witnessed by		
	Name	Company	Signature
Tested by:			
Checked by:			