

lebhart, WRITE YOUR ARTICLES IN A COLORFUL WAY

JINWEN

May 2021, Beijing

ABSTRACT

lebhart is a member of the colorist class series. Its name is taken from German word “lebhaft” (“vividly”), combined with the first three letters of “artikel” (“article”). The entire collection includes colorart and lebhart for typesetting articles and colorbook and beaulivre for typesetting books. My original intention in designing this series was to write drafts and notes that look colorful yet not dazzling.

lebhart supports six languages: English, French, German, Chinese, Japanese and Russian. These languages can be switched seamlessly in a single document. Due to the usage of custom fonts, lebhart requires $\text{Xe}_\text{L}^\text{A}\text{T}_\text{E}_\text{X}$ or $\text{Lua}^\text{L}_\text{A}\text{T}_\text{E}_\text{X}$ to compile.

This documentation is typeset using lebhart. You can think of it as a short introduction and demonstration.

CONTENTS

1	Initialization	2
1.1	How to load	2
1.2	Options	2
2	On the fonts	2
3	Some instructions	3
3.1	Language configuration	3
3.2	Theorems and how to reference them	3
3.3	Define a new theorem-like environment	5
3.4	Draft mark	6
3.5	On the title, abstract and keywords	6
4	Known issues	7
5	Document templates	8
5.1	The standard way	8
5.2	The $\mathcal{A}_\mathcal{M}\mathcal{S}$ way	9

Remind

Multi-language support, theorem-like environments, draft marks and some other features are provided by the [ProjLib](#) toolkit. Here we only briefly discuss how to use it with this document class. For more detailed information, you can refer to the documentation of [ProjLib](#).

1 INITIALIZATION

1.1 HOW TO LOAD

One only needs to put

```
\documentclass{lebhart}
```

as the first line to use the lebhart class. Please note that you need to use either $\text{X}_{\text{E}}\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ or $\text{L}^{\text{u}}\text{a}\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ engine to compile.

1.2 OPTIONS

lebhart offers the following options:

- **draft** or **fast**
 - The option **fast** enables a faster but slightly rougher style, main differences are:
 - * Use simpler math font configuration;
 - * Do not use `hyperref`;
 - * Enable the fast mode of ProjLib toolkit.
- **a4paper** or **b5paper**
 - Optional paper size. The default paper size is $7\text{in} \times 10\text{in}$.
- **allowbf**
 - Allow boldface. When this option is enabled, the title, titles of all levels and names of theorem-like environments will be bolded.

Remind

- During the draft stage, it is recommended to use the **fast** option to speed up compilation. At the end, one should remove the “fast” option to get the final version. When in **fast** mode, there will be a watermark “DRAFT” to indicate that you are currently in the draft mode.

2 ON THE FONTS

By default, lebhart uses Palatino Linotype as the English font, FounderType’s YouSong and YouHei GBK as the Chinese fonts, and partially uses Neo Euler as the math font. Among them, Neo Euler can be downloaded at <https://github.com/khaledhosny/euler-otf>. The other fonts are not free, you need to purchase and use them on your own. (For the Chinese fonts, visit FounderType’s website for detail: <https://www.foundertype.com>).

Font demonstration

- English main font. English sans serif font. English typewriter font.
- 中文主要字体，中文无衬线字体
- 数学示例: $\alpha, \beta, \gamma, \delta, 1, 2, 3, 4, a, b, c, d,$

$$\text{li}(x) := \int_2^x \frac{1}{\log t} dt$$

When the corresponding font is not installed, fonts that comes with TeX Live will be used instead. In this case, the experience might be reduced.

3 SOME INSTRUCTIONS

Many of the features described next are provided by the [ProjLib](#) toolkit. Only the basic usage is mentioned here. For more details, please refer to its user documentation.

3.1 LANGUAGE CONFIGURATION

lebhart has multi-language support, including simplified Chinese, traditional Chinese, English, French, German, Japanese, and Russian. The language can be selected by the following macros:

- `\UseLanguage{⟨language name⟩}` is used to specify the language. The corresponding setting of the language will be applied after it. It can be used either in the preamble or in the main body. When no language is specified, “English” is selected by default.
- `\UseOtherLanguage{⟨language name⟩}{⟨content⟩}`, which uses the specified language settings to typeset `⟨content⟩`. Compared with `\UseLanguage`, it will not modify the line spacing, so line spacing would remain stable when CJK and Western texts are mixed.

`⟨language name⟩` can be:

- Simplified Chinese: `Chinese`, `chinese`, `SChinese`, `schinese`, `SimplifiedChinese` or `simplifiedchinese`
- Traditional Chinese: `TChinese`, `tchinese`, `TraditionalChinese` or `traditionalchinese`
- English: `English` or `english`
- French: `French` or `french`
- German: `German`, `german` or `ngerman`
- Japanese: `Japanese` or `japanese`
- Russian: `Russian` or `russian`

In addition, you can also add new settings to selected language:

- `\AddLanguageSetting{⟨settings⟩}`
 - Add `⟨settings⟩` to all supported languages.
- `\AddLanguageSetting(⟨language name⟩){⟨settings⟩}`
 - Add `⟨settings⟩` to the selected language `⟨language name⟩`.

For example, `\AddLanguageSetting(German){\color{orange}}` can make all German text displayed in orange (of course, one then need to add `\AddLanguageSetting{\color{black}}` in order to correct the color of the text in other languages).

3.2 THEOREMS AND HOW TO REFERENCE THEM

Environments such as definitions and theorems have been pre-defined and can be used directly.

More specifically, preset environments include: `assumption`, `axiom`, `conjecture`, `convention`, `corollary`, `definition`, `definition-proposition`, `definition-theorem`, `example`, `exercise`, `fact`, `hypothesis`, `lemma`, `notation`, `problem`, `property`, `proposition`, `question`, `remark`, `theorem`, and the corresponding unnumbered version with an asterisk `*` in the name. The display of these environments will change according to the current language.

When referencing a theorem-like environment, it is recommended to use smart reference `\cref{⟨label⟩}`. In this way, there is no need to explicitly write down the name of the corresponding environment every time.

Example

```
\begin{definition}[Strange things] \label{def: strange} ...
```

will produce

DEFINITION 3.1 (Strange things) This is the definition of some strange objects. There is approximately an one-line space before and after the theorem environment, and there will be a symbol to mark the end of the environment.

`\cref{def: strange}` will be displayed as: **DEFINITION 3.1**.

After using `\UseLanguage{French}`, a theorem will be displayed as:

THÉORÈME 3.2 (Inutile) Un théorème en français.

By default, when referenced, the name of the theorem always matches the language of the context in which the theorem is located. For example, the definition above is still displayed in English in the current French mode : **DEFINITION 3.1** and **THÉORÈME 3.2**. If you want the name of the theorem to match the current context when referencing, you can add `regionalref` to the global options.

The following are the main styles of theorem-like environments:

THEOREM 3.3 Theorem style: theorem, proposition, lemma, corollary, ...

Proof | Proof style



Remark style



CONJECTURE 3.4 Conjecture style

EXAMPLE Example style: example, fact, ...

PROBLEM 3.5 Problem style: problem, question, ...

For aesthetics, adjacent definitions will be connected together automatically:

DEFINITION 3.6 First definition.

DEFINITION 3.7 Second definition.

3.3 DEFINE A NEW THEOREM-LIKE ENVIRONMENT

If you need to define a new theorem-like environment, you must first define the name of the environment in the language used: $\langle \text{name of environment} \rangle \langle \text{language abbr} \rangle$, where $\langle \text{language abbr} \rangle$ is the abbreviation of language, which can be:

CN	Simplified Chinese	DE	German
TC	Traditional Chinese	JP	Japanese
EN	English	RU	Russian
FR	French		

Remind

If you want to define an environment with an asterisk $*$ after the name, you don't need to write an asterisk in the $\langle \text{name of environment} \rangle$ above. See the example below.

And then define this environment in one of following five ways:

- $\backslash \text{CreateTheorem} * \{ \langle \text{name of environment} \rangle \}$
 - Define an unnumbered environment $\langle \text{name of environment} \rangle$
- $\backslash \text{CreateTheorem} \{ \langle \text{name of environment} \rangle \}$
 - Define a numbered environment $\langle \text{name of environment} \rangle$, numbered in order 1,2,3,...
- $\backslash \text{CreateTheorem} \{ \langle \text{name of environment} \rangle \} [\langle \text{numbered like} \rangle]$
 - Define a numbered environment $\langle \text{name of environment} \rangle$, which shares the counter $\langle \text{numbered like} \rangle$
- $\backslash \text{CreateTheorem} \{ \langle \text{name of environment} \rangle \} < \langle \text{numbered within} \rangle >$
 - Define a numbered environment $\langle \text{name of environment} \rangle$, numbered within the counter $\langle \text{numbered within} \rangle$
- $\backslash \text{CreateTheorem} \{ \langle \text{name of environment} \rangle \} (\langle \text{existed environment} \rangle)$
 $\backslash \text{CreateTheorem} * \{ \langle \text{name of environment} \rangle \} (\langle \text{existed environment} \rangle)$
 - Identify $\langle \text{name of environment} \rangle$ with $\langle \text{existed environment} \rangle$ or $\langle \text{existed environment} \rangle *$.
 - This method is usually useful in the following two situations:
 1. To use a more concise name. For example, with $\backslash \text{CreateTheorem} \{ \text{thm} \}$ (theorem), one can then use the name `thm` to write theorem.
 2. To remove the numbering. For example, one can remove the numbering of the `remark` environment with $\backslash \text{CreateTheorem} \{ \text{remark} \} (\text{remark} *)$.

Remind

It uses `amsthm` internally, so the traditional `theoremstyle` is also applicable to it. One only needs declare the style before the relevant definitions.

Here is an example. The following code:

```
\def\proofideanameEN{Idea}
\CreateTheorem*{proofidea*}
\CreateTheorem{proofidea}<subsection>
```

defines an unnumbered environment `proofidea*` and a numbered environment `proofidea` (numbered within subsection) respectively. They can be used in English context. The effect is as follows:

Idea | The `proofidea*` environment.

Idea 3.3.1 | The `proofidea` environment.

3.4 DRAFT MARK

You can use `\dnf` to mark the unfinished part. For example:

- `\dnf` or `\dnf<...>`. The effect is: `To be finished #1` or `To be finished #2: ...`.
The prompt text changes according to the current language. For example, it will be displayed as `Pas encore fini #3` in French mode.

Similarly, there is `\needgraph` :

- `\needgraph` or `\needgraph<...>`. The effect is:

A graph is needed here #1

or

A graph is needed here #2: ...

The prompt text changes according to the current language. For example, in French mode, it will be displayed as

Il manque une image ici #3

3.5 ON THE TITLE, ABSTRACT AND KEYWORDS

lebhart has both the features of standard classes and that of the \mathcal{AMS} classes.

Therefore, the title part can either be written in the usual way, in accordance with the standard class article:

```
\title{<title>}
\author{<author>}
\date{<date>}
\maketitle
\begin{abstract}
  <abstract>
\end{abstract}
\begin{keyword}
  <keywords>
\end{keyword}
```

or written in the way of \mathcal{AMS} classes:

```
\title{<title>}
\author{<author>}
\address{<address>}
\email{<email>}
\date{<date>}
\keywords{<keywords>}
\subjclass{<subclass>}
\begin{abstract}
  <abstract>
\end{abstract}
\maketitle
```

The author information can contain multiple groups, written as:

```
\author{\author 1}  
\address{\address 1}  
\email{\email 1}  
\author{\author 2}  
\address{\address 2}  
\email{\email 2}  
...
```

Among them, the mutual order of `\address`, `\curraddr`, `\email` is not important.

4 KNOWN ISSUES

- The font settings are still not perfect.
- Since many features are based on the [ProjLib](#) toolkit, lebhart inherits all its problems. For details, please refer to the "Known Issues" section of the [ProjLib](#) documentation.
- The error handling mechanism is incomplete: there is no corresponding error prompt when some problems occur.
- There are still many things that can be optimized in the code.

5 DOCUMENT TEMPLATES

5.1 THE STANDARD WAY

If you want to write in the standard way, you can refer to the following example:

```
\documentclass{lebhart}
\usepackage{PJLtoolkit} % Load ProjLib toolkit

\UseLanguage{French} % Use French from here

\begin{document}

\title{Le Titre}
\author{Auteur}
\date{\PJLdate{2022-04-01}}

\maketitle

\begin{abstract}
  Ceci est un résumé. \dnf<Plus de contenu est nécessaire.>
\end{abstract}
\begin{keyword}
  AAA, BBB, CCC, DDD, EEE
\end{keyword}

\section{Un théorème}

%% Theorem-like environments can be used directly
\begin{theorem}\label{thm:abc}
  Ceci est un théorème.
\end{theorem}

Référence du théorème: \cref{thm:abc}
  % It is recommended to use clever reference

\end{document}
```

If you wish to switch to the standard class later, just replace the first two lines with:

```
\documentclass{article}
\usepackage[a4paper,margin=1in]{geometry}
\usepackage[hidelinks]{hyperref}
\usepackage{palatino}{PJLtoolkit} % Load ProjLib toolkit
```

5.2 THE \mathcal{AMS} WAY

If you intend to switch to the journal template in the future and thus want to use the writing style as in the \mathcal{AMS} classes, you can refer to the following example:

```
\documentclass{lebhart}
\usepackage{PJLtoolkit} % Load ProjLib toolkit

\UseLanguage{French} % Use French from here

\begin{document}

\title{Le Titre}
\author{Auteur 1}
\address{Adresse 1}
\email{\href{Courriel 1}{Courriel 1}}
\author{Auteur 1}
\address{Adresse 1}
\email{\href{Courriel 2}{Courriel 2}}
\date{\PJLdate{2022-04-01}}
\subjclass{*****}
\keywords{...}

\begin{abstract}
  Ceci est un résumé. \dnf<Plus de contenu est nécessaire.>
\end{abstract}

\maketitle

\section{Première section}

%% Theorem-like environments can be used directly
\begin{theorem}\label{thm:abc}
  Ceci est un théorème.
\end{theorem}

Référence du théorème: \cref{thm:abc}
  % It is recommended to use clever reference

\end{document}
```

In this way, if you wish to switch to \mathcal{AMS} class later, just replace the first two lines with:

```
\documentclass{amsart}
\usepackage[a4paper,margin=1in]{geometry}
\usepackage[hidelinks]{hyperref}
\usepackage[palatino]{PJLtoolkit} % Load ProjLib toolkit
```
