

CS-005 CNC Machining of Tooling Board (ShopSabre)

Doc ID	CS-005
Title	CNC Machining of Tooling Board — ShopSabre @ RFS
Revision	B
Status	Draft — pending Lead signature
Effective date	2026-07-13
Supersedes	Jacobs Shopbot as primary mold machine (see Appendix); <i>Shopbot Procedure Checklist</i> still applies to the Shopbot when we use it

Approvals

Role	Name	Date
Author	Simon Starbuck (drafted w/ Claude — SN6 Resources)	2026-07-12
Reviewer	simon (reviewer agent)	2026-07-12
Approver (Composites Lead)		

Revision history

Rev	Date	Author	Description of change
A	2026-07-12	Claude	Initial issue
B	2026-07-13	Claude	Corrected machine facts: 5×10 bed (not 4×8), vacuum hold-down, automatic tool changer w/ auto tool measurement; zeroing section rewritten around the ATC

1. Purpose

We spent most of SN5 machining molds on the Jacobs Shopbot's daily slot scramble, right up until Jacobs staff pulled us aside for block-reserving (2026-02-23) — not a conversation we want to have twice (PP-06). We now machine on the **ShopSabre at RFS**: our own reservation system, a 5×10 ft bed, vacuum hold-down, and an automatic tool changer. This doc covers how to book it, who can run it, and the setup rules that cost us parts when we skipped them.

2. Scope

Machining polyurethane tooling-board molds and stock on the RFS ShopSabre. The Jacobs Shopbot is still fine as a fallback for small jobs — use the SN5 *Shopbot Procedure Checklist* there (that machine has none of the features below; everything is manual).

3. References

Ref	Document	Where
R1	RFS/RSO reservation website (booking) + ShopSabre training doc	RFS website
R2	ShopSabre 5×10 specs (IS-A 510 class)	shopsabre.com product pages, accessed 2026-07 — confirm exact model/options on the machine placard
R3	<i>Shopbot Procedure Checklist</i> (fallback machine)	SN5 Drive root
R4	PP-06 RCA; Z-plunge incidents	FEB-COMP-PP-001
R5	CS-003 (mold design/stock), CS-004 (post-machine cleaning)	this series

4. Definitions

- **HOT** — RFS hands-on-training sign-off; required before you run the machine on your own.
- **Certified operator** — did the RFS ShopSabre training doc + HOT. End-of-SN5 list: Ansh, Simon, Kina, Nico, Nick, Justin, Sam, Alvin, Ernesto — re-check who’s still around each fall and train replacements early (October, not February).
- **CAM review** — Larry requires whoever is machining to have made their own CAM, and he reviews it before it runs. Build this into the schedule; it has saved us more than it has cost us.
- **ATC** — automatic tool changer. The machine swaps tools from its rack mid-program and measures each tool’s length automatically, so tool changes don’t need a manual re-zero.

5. Equipment & Materials

Item	Spec	Notes
ShopSabre CNC router (5×10)	Cut area 65.5 × 122 ; max cut depth 6 ; Z travel 14 (R2)	Full 5×10 sheets fit flat — no more sectioning sheet stock. Mold stacks taller than ~6 still need splitting in CAD (CS-003 §7.1.6); confirm usable depth against your tool length before gluing a tall stack
Vacuum hold-down table	Zoned vacuum through the spoilboard (R2)	Sheet stock and boards hold with no tape or nails. See 7.3 for when vacuum alone isn’t enough
Automatic tool changer	Tool rack + automatic tool length measurement (R2)	Tool offsets live in the controller’s tool table — see 7.4
End mills / collets	Per CAM plan	Inspect before use; tell Larry if a tool in the rack looks tired
Dust extraction	Machine system	PU dust rules in §6

6. Safety

- **Machine:** hands away from a live spindle; know where the e-stop is before every run; watch the first minutes with a hand near it. Max 2 people at the machine during setup (kept from the Shopbot rules — still a good rule).

- **Tooling-board dust:** abrasive and irritating. Extraction on, dust mask minimum (respirator for long jobs). Vacuum shared rooms — don't blow dust around with compressed air.
- **Vacuum table:** don't reach under a held part to "check" it while zones are on; release zones first.

7. Procedure

7.1 Plan and book (the PP-06 discipline)

1. When mold CAM **starts** (not when it finishes), put the machining time estimate on the WO and book the slot on the RFS/RSO site (R1). Our SN5 UT molds ran 0:17–6:16 each — CAM simulation gets you a real number.
2. Book under the name of whoever is actually running the machine. RFS rule: you attend your own reservation. No covering slots for each other — that's the exact thing that burned us at Jacobs.
3. Booking-site quirks (as of spring 2026): multi-day and some short blocks fail — book day-by-day chunks and report bugs to Joey.
4. The weekly summary carries the next 2 weeks of machine load so conflicts show up Monday night, not at the machine.

7.2 Prerequisites at the machine

1. Certified operator, running their own CAM, reviewed by Larry (R1).
2. Mold design review initialed on the WO (CS-003 §7.2). **No initials, no cutting.**
3. Stock glued/cured per CS-003 §7.3 and labeled — and check the label is actually the job you booked.

7.3 Workholding (vacuum table)

1. Sheet stock and flat boards: place on the spoilboard, open the zones under the part, keep unused zones closed for suction where it counts. No tape, no nails.
2. **Tall glued mold stacks with small footprints are the case to think about:** holding force scales with footprint area, and a 6" stack on a small base sees real side loads. Do a firm hand-push test before running; if it moves at all, add mechanical fixing (screws through waste margin into the spoilboard, or cleats) and note it in the CAM so nothing cuts there.
3. Porous/already-sealed surfaces hold differently — when in doubt, test-push and ask Larry.

7.4 Zeroing and tooling — where SN5 lost parts

1. **Zero Z once per job, from the top of the stock, at the highest point of the finished stack.** Never the bed. (The Feb 2026 "it plunged into the part" incidents were zeroing mistakes on the old machine — the rule carries over.)
2. **Tool changes are the ATC's job, not yours.** The machine measures each tool's length and applies offsets from the tool table — there's no manual re-zero between tools. What that means for you:
 - Make sure your CAM tool numbers match what's physically in the rack. A mismatched tool table does the same thing a bad zero does, just faster.
 - If anyone has manually swapped a bit in a rack position, the tool must be re-measured before your program trusts it. When in doubt, run the tool-measure cycle — it costs a minute.
3. Verify X/Y zero against the stock corner and the CAM origin before starting.
4. Deep cuts: split toolpaths into depth stages rather than one full-depth pass.
5. Watch the first minutes of every program, hand near the stop.

Machine doing anything unexpected — stop first, figure it out second. A scrapped hour is cheaper than a scrapped mold stack.

[PHOTO: zeroing Z off the top of the glued stack; ATC rack in background]

7.5 During and after

1. Stay with the machine; dust management per RFS rules.

2. Record actual machining time on the WO (this is how next season's estimates get good).
3. Check scribes/surfaces **before** releasing the vacuum — rework is easiest while the part is still located.
4. Clean up, hand the room back better than you found it. The RFS relationship is our machining capacity.
5. Mold goes to cleaning + sealing per CS-004; update the WO mold location.

8. Quality checks / acceptance criteria

Check	Target	Method	Record where
Booking under actual operator	Always	Lead spot-check	—
Z zeroed from stock top (once/job); tool table matches rack	Every run	Operator; buddy check on first solo runs	WO step initials
Hand-push test on tall/small-footprint stacks	Before every such run	Operator	WO step notes
First-cut watch	First 5 min minimum	—	—
Actual vs estimated machine time	Recorded	Machine log	WO
Surface/scribe quality	Scribes crisp, no unexpected steps	Visual before releasing vacuum	WO qualityChecks

9. Records

WO machining step: operator, date, slot, estimate vs actual, tool list, incidents. Actual times feed the capacity model — ~2 molds/week was SN5 reality on a worse machine; find out what this one actually does instead of assuming.

Appendix — the Shopbot era (why this doc exists)

Jacobs Shopbot: per-person daily slots, ShopbotBot morning scramble, 3-reservation caps, trading slots with other teams, a ~3 cut depth that forced tall molds to be sectioned and re-glued, manual tool changes with a re-zero every time, and tape/nail workholding (tape thickness literally showed up as Z error across a sheet). We out-demanded the system, block-booked through multiple members, and on 2026-02-23 Jacobs staff formally objected. The ShopSabre fixes the access problem and most of the setup failure modes — vacuum table kills the tape-Z-error problem, the ATC kills the forgot-to-re-zero problem, 6 of cut depth kills most mold sectioning. It does not fix physics: one machine, bursty demand. The habit that transfers is forward capacity planning — estimates on WOs, booking at CAM start, machine load in the weekly summary.