

## OOP Lab 13 Part 1: Generics

Purpose	Practice type parameter usage
What to Submit	You don't have to submit this problem.

### Problem 1: Generics

1. Write a class named `ku.util.ListUtil` that has a static append method:

```
static <E> void append(List<E> list, List<E> args)
```

the method should append each element of the `args` List to the end of `list` (first parameter).

2. Write some code to verify that the method works if you have two lists of type `Number`:

```
List<Number> list = new ArrayList<Number>( );
// TODO add a BigInteger to list
List<Number> appendee = new ArrayList<Number>( );
// actual values in appendee are doubles
appendee.add( new Double(0.5) );
appendee.add( new Double(2.5) );
ListUtil.append( list, appendee );
//TODO print the list to verify it worked
```

3. It is OK to add doubles to the list in problem 2 because `Double` is a subclass of `Number`. So, we should be able to write:

```
List<Double> appendee = new ArrayList<Double>( );
// actual values in appendee are doubles
appendee.add( new Double(0.5) );
appendee.add( new Double(2.5) );
ListUtil.append( list, appendee );
```

Try this code to verify that it **won't compile**. What is the reason?

4. Modify the method signature on `append()` to mean "*args is a List of elements from any subclass of E*". Hint: use a *wildcard* in the type parameter.

```
public static <E> void append( List<E> list, List<_____> args )
```

and verify that now problem 3 compiles and works as expected.

5. In Write a generic "max" method in `ListUtil` that returns the "maximum" of its arguments, and accepts a variable number of arguments (the `"..."` notation). The arguments can be any type that implements `Comparable<E>`

```
Double max = ListUtil.max( 1.5, 2.98E8, Math.PI );
// max is Double(2.98E8)
String last = ListUtil.max( "ant", "cat", "zebra", "monkey");
// max is "zebra"
```

6. The "max" method in the previous problem works for `String` because `String` implements `Comparable<String>`, and similarly for `Double`. But what about `Coin` from the Purse lab? `Coin` implements `Comparable<Valuable>` not `Comparable<Coin>`.

Try to invoke `max( new Coin(5), new Coin(10) )` to verify this.

## OOP Lab 13 Part 1: Generics

---

To correct the problem, you need to modify the type declaration in the max method:

```
public static <E extends Comparable<_____>> E max( E ... args )
```

Hint: use a wildcard ? with "extends" or "super"