



Threads in Swing

Using threads for long running tasks.

Other ways to use threads:

- 1) TimerTask in java.util and javax.swing
- 2) Executor - manage a thread pool
- 3) Future - return a result later

3 Kinds of Threads

In a Swing app:

- **initial thread** starts the application
- **Event Dispatcher Thread**
 - handles all UI events, updates Swing UI
- **Worker Threads (Background Threads)**
 - perform long running tasks

Why Bother with Threads?

- Prevent UI from *Freezing* while work is being done
 - connecting to database
 - downloading something
- Avoid *Thread Interference* and memory inconsistency
 - Like in Homework 3

"main" method - the wrong way

- your "main" class runs in the initial thread (any thread)
- this code starts Swing UI on the same thread.

```
public class PurseApp {  
    public static void main(String[] args) {  
        Purse purse = new Purse( 10 );  
        // dependency injection  
        PurseUI ui = new PurseUI( purse );  
        ui.setVisible(true);  
    }  
}
```

Use SwingUtilities to launch UI

- Oracle says you should both create and launch the UI on the *Event Dispatcher thread*.

Use `SwingUtilities.invokeLater(runnable);`

```
public class PurseApp {  
    public static void main(String[] args) {  
        SwingUtilities.invokeLater(  
            new Runnable( ) {  
                public void run() {  
                    // create and start Swing UI  
                }  
            }  
        );  
    }  
}
```

SwingUtilities Example

- Create PurseUI inside the Runnable task, because the UI will create Swing components.
- `purse` is `final` so it can be accessed in anonymous class

```
public static void main(String[] args) {  
    final int capacity = 10;  
    final Purse purse = new Purse( capacity );  
    SwingUtilities.invokeLater(  
        new Runnable( ) {  
            public void run() {  
                // Must CREATE PurseUI inside Runnable  
                PurseUI pui = new PurseUI( purse );  
                pui.setVisible(true);  
            }  
        }  
    );  
}
```

SwingUtilities

SwingUtilities

invokeLater(Runnable): void

invokeAndWait(Runnable): void

isEventdispatcherThread() : bool

many more methods

Rules for Event Dispatcher Thread

To prevent UI from freezing and to prevent memory inconsistency:

- 1) operations on UI components should be done only in the Event Dispatcher thread
- 2) time-consuming operations should never be done on the Event Dispatcher thread


Note that all UI events (button press, state change) invoke event handlers on the event dispatcher thread.

Example: Fibonacci

- as an example of a slow operation, let's compute Fibonacci numbers **by recursion**.
- $\text{fib}(0) = 1$, $\text{fib}(1) = 1$, $\text{fib}(n) = \text{fib}(n-1) + \text{fib}(n-2)$

```
public class Ribonacci {  
  
    // this method could be static  
    public long fibonacci(int n) {  
        if (n < 0) return 0;  
        if (n <= 1) return 1;  
        return fibonacci(n-2) + fibonacci(n-1);  
    }  
  
    //TODO: test this code  
}
```

UI for Fibonacci



Status or error message.

TODO:
add ActionListener

Frozen UI


UI freezes (unresponsive) if you use try to compute large fibonacci numbers on the event dispatcher thread.

```
// ActionListener method for fibonacci UI
public void actionPerformed(ActionEvent evt) {
    String value = inputField.getText().trim();
    if (value.isEmpty()) return;
    int n = Integer.parseInt( value );
    setMessage( "working" );
    long result = Fibonacci.fibonacci( n );
    outputField.setText( Long.toString(result) );
    setMessage( "" );
}
```

SwingWorker

SwingWorker runs a task in a background thread.

SwingWorker communicates result to Event Dispatcher Thread.



How to Use SwingWorker

1) Create a subclass of SwingWorker for your task.

2) Override 2 methods:

doInBackground() - do the work (on background thread)

done() - communicate the result to UI (this method runs on event dispatcher thread)

Optional:

publish(V stuff) - publish intermediate results

Fibonacci Worker

R = return type = Long,

use constructor param to pass value of n for Fibonacci

```
class FibonacciWorker
    extends SwingWorker<Long,Void> {
    private int n;
    public FibonacciWorker(int n) { this.n = n; }

    @Override
    protected Long doInBackground() throws ... {
        long result = Fibonnaci.fibonacci(n);
        return result;
    }
}
```

Getting Result of Fibonacci Worker

Use `SwingWorker.done()` to display the result.
`get()` throws exception if the result is not ready yet.

```
@Override
protected void done( ) {
    try {
        result = this.get( );
        // update the UI
        outputfield.setText(result.toString());
        setMessage(""); // clear status msg
    } catch (InterruptedException |
            InterruptedException ex) {
        setMessage("Execution Error");
    }
}
```

More About SwingWorker

- 1) Can invoke only one time. Create a new instance each time you need to do a task.
- 2) Can "cancel" a SwingWorker, but requires cooperation of the task. See *Java Tutorial*.
- 3) Status methods:
`getProgress ()`
`isDone ()`
`isCancelled ()`

References

The Java Tutorial:

<https://docs.oracle.com/javase/tutorial>

Concurrency in Swing

<https://docs.oracle.com/javase/tutorial/uiswing/concurrency/index.html>

Concurrency (general)

<https://docs.oracle.com/javase/tutorial/essential/concurrency/index.html>