

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT * FROM crime_scene_report
2 WHERE date = 20180115
3 AND type = 'murder'
4 AND city = 'SQL City';
5 -- Apparently, and conveniently, only one murder was committed on 2018-01-15 in
6 -- SQL city. From this result we can reference the 'person' table which contains
7 -- names and (more importantly) addresses.
```

RUN ↴

RESET

date	type	description	city
20180115	murder	Security footage shows that there were 2 witnesses. The first witness lives at the last house on "Northwestern Dr". The second witness, named Annabel, lives somewhere on "Franklin Ave".	SQL City

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT * from person
2     WHERE name LIKE '%Annabel%'
3     AND address_street_name LIKE '%Franklin Ave%';
4 -- Witness 1 identified
```

RUN ↴

RESET

id	name	license_id	address_number	address_street_name	ssn
16371	Annabel Miller	490173	103	Franklin Ave	318771143

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT * from person
2     WHERE address_street_name LIKE '%Northwestern Dr%'
3     ORDER BY address_number DESC;
4 -- Witness 2 is Morty Schapiro, assuming by the "last house" on Northwestern
5 -- Drive we mean the highest address_number.
```

RUN ↴

RESET

id	name	license_id	address_number	address_street_name	ssn
14887	Morty Schapiro	118009	4919	Northwestern Dr	111564949
17729	Lasonya Wildey	439686	3824	Northwestern Dr	917817122

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT * FROM interview
2 WHERE person_id = 16371 OR person_id = 14887
3 -- Person_id exists in person table as id, and id was returned when identifying
4 -- witnesses. 14887 is Morty, 16371 is Annabel.
```

RUN ↴

RESET

person_id	transcript
14887	I heard a gunshot and then saw a man run out. He had a "Get Fit Now Gym" bag. The membership number on the bag started with "48Z". Only gold members have those bags. The man got into a car with a plate that included "H42W".
16371	I saw the murder happen, and I recognized the killer from my gym when I was working out last week on January the 9th.

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT *
2 FROM get_fit_now_check_in gym_log
3 JOIN get_fit_now_member gym_mem
4     ON gym_log.membership_id = gym_mem.id
5 WHERE check_in_date = 20180109
6 AND membership_id LIKE '48Z%'
7 AND membership_status LIKE '%gold%'
8 -- Returns two results pictured below. Not pictured is the membership_status,
9 -- both of which are 'gold'.
10 -- Next, see if these dudes were interviewed? Their person_id is listed in the
11 -- get_fit_now_member table.
```

RUN ↴

RESET

membership_id	check_in_date	check_in_time	check_out_time	id	person_id	name	membership_start_date
48Z7A	20180109	1600	1730	48Z7A	28819	Joe Germuska	20160305
48Z55	20180109	1530	1700	48Z55	67318	Jeremy Bowers	20160101

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT *
2 FROM interview
3 WHERE person_id = 28819 OR person_id = 67318;
4 -- Apparently Jeremy Bowers, a rat fink bastard, can't hold his tongue. And
5 -- that's unfortunate, because apparently he is a hitman. Which is a hell of a
6 -- thing to give up under very little pressure. But OK, so now I'm looking for
7 -- a ginger woman 5'5"-5'7" who drives a Tesla Model S and is a frequent
8 -- symphony-goer.
```

RUN ↴

RESET

person_id	transcript
67318	I was hired by a woman with a lot of money. I don't know her name but I know she's around 5'5" (65") or 5'7" (67"). She has red hair and she drives a Tesla Model S. I know that she attended the SQL Symphony Concert 3 times in December 2017.

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT person_id, COUNT(event_id) AS visits FROM facebook_event_checkin
2     WHERE date LIKE '201712%'
3     AND event_name LIKE '%Symphony%'
4 GROUP BY person_id HAVING visits = 3
5 -- This took a minute to work out. First time I've used HAVING.
6 -- So now we run these two person_id values through person.
7
```

RUN ↴

RESET

person_id	visits
24556	3
99716	3

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT * FROM person
2 WHERE id = 24556 OR id = 99716
3 -- This query returns two hits. Can't assume only one of them is a woman.
4 -- That's gender essentialism and potentially transphobia.
5 -- So let's run these two against drivers_license.
```

RUN ↓

RESET

id	name	license_id	address_number	address_street_name	ssn
24556	Bryan Pardo	101191	703	Machine Ln	816663882
99716	Miranda Priestly	202298	1883	Golden Ave	987756388

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT * FROM drivers_license
2 WHERE id = 99716 or id = 24556
3 -- Well that's a pickle. drivers_licence info could give me height and hair_color,
4 -- which I could align to my red-hair 5'5" - 5'7" clue. Hm. OK, well, we have ssn
5 -- from person which we can at least stack against income, since our redhead
6 -- is allegedly wealthy.
```

RUN ↓

RESET

No data returned

Use your knowledge of the database schema and SQL commands to find out who committed the murder.

When you think you know the answer, go to the next section.

```
1 SELECT * FROM drivers_license
2 WHERE id = 202298 OR id = 101191
3 -- Or we can disregard that last guess about SSN, since id in person is a different
4 -- value than id in drivers_license. We have license_id for our two suspects, so
5 -- we search those against drivers_license.id
6 -- Et voila: a 5.5' tall redhaired woman. Whose name is...
7 -- Well we could run another query but we know that this is the license_id of
8 -- Miranda Priestly from our query that gave us our two potential suspects.
```

RUN ↴

RESET

id	age	height	eye_color	hair_color	gender	plate_number	car_make	car_model
202298	68	66	green	red	female	500123	Tesla	Model S

Check your solution

Did you find the killer?

```
1 INSERT INTO solution VALUES (1, 'Miranda Priestly');  
2  
3 SELECT value FROM solution;
```

RUN ↓

RESET

value
Congrats, you found the brains behind the murder! Everyone in SQL City hails you as the greatest SQL detective of all time. Time to break out the champagne!