

# INDEX

## List of Practical

<b>Sr. No.</b>	<b>Experiment Title</b>	<b>Page No.</b>
<b>1</b>	<b>Exploring Git Commands through Collaborative Coding.</b>	<b>2</b>
<b>2</b>	<b>Implement GitHub Operations</b>	<b>7</b>
<b>3</b>	<b>Implement GitLab Operations</b>	<b>11</b>
<b>4</b>	<b>Implement BitBucket Operations</b>	<b>15</b>
<b>5</b>	<b>Applying CI/CD Principles to Web Development Using Jenkins, Git, and Local HTTP Server</b>	<b>19</b>
<b>6</b>	<b>Exploring Containerization and Application Deployment with Docker</b>	<b>23</b>
<b>7</b>	<b>Applying CI/CD Principles to Web Development Using Jenkins, Git, using Docker Containers</b>	<b>27</b>
<b>8</b>	<b>Demonstrate Maven Build Life Cycle</b>	<b>31</b>
<b>9</b>	<b>Demonstrate Container Orchestration using Kubernetes.</b>	<b>36</b>
<b>10</b>	<b>Certificates</b>	<b>40</b>

## Experiment No. 1

### Title : Exploring Git Commands through Collaborative Coding.

#### Objective:

The objective of this experiment is to familiarise participants with essential Git concepts and commands, enabling them to effectively use Git for version control and collaboration.

#### Introduction:

Git is a distributed version control system (VCS) that helps developers track changes in their codebase, collaborate with others, and manage different versions of their projects efficiently. It was created by Linus Torvalds in 2005 to address the shortcomings of existing version control systems.

Unlike traditional centralised VCS, where all changes are stored on a central server, Git follows a distributed model. Each developer has a complete copy of the repository on their local machine, including the entire history of the project. This decentralisation offers numerous advantages, such as offline work, faster operations, and enhanced collaboration.

Git is a widely used version control system that allows developers to collaborate on projects, track changes, and manage codebase history efficiently. This experiment aims to provide a hands-on introduction to Git and explore various fundamental Git commands. Participants will learn how to set up a Git repository, commit changes, manage branches, and collaborate with others using Git.

#### Key Concepts:

- **Repository:** A Git repository is a collection of files, folders, and their historical versions. It contains all the information about the project's history, branches, and commits.
- **Commit:** A commit is a snapshot of the changes made to the files in the repository at a specific point in time. It includes a unique identifier (SHA-1 hash), a message describing the changes, and a reference to its parent commit(s).
- **Branch:** A branch is a separate line of development within a repository. It allows developers to work on new features or bug fixes without affecting the main codebase. Branches can be merged back into the main branch when the changes are ready.
- **Merge:** Merging is the process of combining changes from one branch into another. It integrates the changes made in a feature branch into the main branch or any other target branch.
- **Pull Request:** In Git hosting platforms like GitHub, a pull request is a feature that allows developers to propose changes from one branch to another. It provides a platform for code review and collaboration before merging.

- **Remote Repository:** A remote repository is a copy of the Git repository stored on a server, enabling collaboration among multiple developers. It can be hosted on platforms like GitHub, GitLab, or Bitbucket.

### Basic Git Commands:

- **git init:** Initialises a new Git repository in the current directory.
- **git clone:** Creates a copy of a remote repository on your local machine.
- **git add:** Stages changes for commit, preparing them to be included in the next commit.
- **git commit:** Creates a new commit with the staged changes and a descriptive message.
- **git status:** Shows the current status of the working directory, including tracked and untracked files.
- **git log:** Displays a chronological list of commits in the repository, showing their commit messages, authors, and timestamps.
- **git branch:** Lists, creates, or deletes branches within the repository.
- **git checkout:** Switches between branches, commits, or tags. It's used to navigate through the repository's history.
- **git merge:** Combines changes from different branches, integrating them into the current branch.
- **git pull:** Fetches changes from a remote repository and merges them into the current branch.
- **git push:** Sends local commits to a remote repository, updating it with the latest changes.

### Materials:

- Computer with Git installed (<https://git-scm.com/downloads>)
- Command-line interface (Terminal, Command Prompt, or Git Bash)

### Experiment Steps:

#### Step 1: Setting Up Git Repository

- Open the command-line interface on your computer.
- Navigate to the directory where you want to create your Git repository.
- Run the following commands:

#### *git init*

- This initialises a new Git repository in the current directory.

```
C:\Users\PALLAVI J S>cd C:\Users\PALLAVI J S\Desktop\devassignment
C:\Users\PALLAVI J S\Desktop\devassignment>git init
Initialized empty Git repository in C:/Users/PALLAVI J S/Desktop/devassignment/.git/
```

#### Step 2: Creating and Committing Changes

- Create a new text file named "example.txt" using any text editor.
- Add some content to the "example.txt" file.
- In the command-line interface, run the following commands:

### ***git status***

- This command shows the status of your working directory, highlighting untracked files.

```
C:\Users\PALLAVI J S\Desktop\devassignment>git status
On branch main

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
    example.txt

nothing added to commit but untracked files present (use "git add" to track)
```

### ***git add example.txt***

- This stages the changes of the "example.txt" file for commit.

### ***git commit -m "Add content to example.txt"***

- This commits the staged changes with a descriptive message.

```
C:\Users\PALLAVI J S\Desktop\devassignment>git add example.txt

C:\Users\PALLAVI J S\Desktop\devassignment>git commit -m"welcome to git"
[main (root-commit) 6706606] welcome to git
 1 file changed, 1 insertion(+)
 create mode 100644 example.txt
```

## **Step 3: Exploring History**

Modify the content of "example.txt."

Run the following commands:

### ***git status***

- Notice the modified file is shown as "modified."

```
C:\Users\PALLAVI J S\Desktop\devassignment>git status
On branch main
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
    modified:   example.txt

no changes added to commit (use "git add" and/or "git commit -a")
```

### ***git diff***

- This displays the differences between the working directory and the last commit.

```
C:\Users\PALLAVI J S\Desktop\devassignment>git diff
diff --git a/example.txt b/example.txt
index abd81a7..e247deb 100644
--- a/example.txt
+++ b/example.txt
@@ -1,2 @@
    hello git!!
+i m pallavi
\ No newline at end of file
```

### ***git log***

- This displays a chronological history of commits.

```
C:\Users\PALLAVI J S\Desktop\devassignment>git log
commit 6706606e31fc237c903595a4db2d22aabea93130 (HEAD -> main)
Author: Pallavi-519 <jspallavi9@gmail.com>
Date: Sat Jun 7 10:30:22 2025 +0530

welcome to git
```

## **Step 4: Branching and Merging**

Create a new branch named "feature" and switch to it:

### ***git branch feature***

### ***git checkout feature***

or shorthand:

### ***git checkout -b feature***

- Make changes to the "example.txt" file in the "feature" branch.
- Commit the changes in the "feature" branch.
- Switch back to the "master" branch:

```
C:\Users\PALLAVI J S\Desktop\devassignment>git branch feature

C:\Users\PALLAVI J S\Desktop\devassignment>git checkout feature
M       exmple.txt
Switched to branch 'feature'
```

### ***git checkout master***

- Merge the changes from the "feature" branch into the "master" branch:

```
C:\Users\PALLAVI J S\Desktop\devassignment>git checkout main
M       exmple.txt
Switched to branch 'main'
```

### ***git merge feature***

## **Step 5: Collaborating with Remote Repositories**

- Create an account on a Git hosting service like GitHub (<https://github.com/>).
- Create a new repository on GitHub.

```
C:\Users\PALLAVI J S\Desktop\devassignment>git remote add origin https://github.com/Pallavi-519/devopsassignment.git

C:\Users\PALLAVI J S\Desktop\devassignment>git push origin main
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 228 bytes | 114.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/Pallavi-519/devopsassignment.git
 * [new branch]      main -> main
```

- Link your local repository to the remote repository:

### ***git remote add origin <repository\_url>***

- Push your local commits to the remote repository:

### ***git push origin master***

**Conclusion:**

Through this experiment, participants gained a foundational understanding of Git's essential commands and concepts. They learned how to set up a Git repository, manage changes, explore commit history, create and merge branches, and collaborate with remote repositories. This knowledge equips them with the skills needed to effectively use Git for version control and collaborative software development.

## Experiment No. 2

**Title:** Implement GitHub Operations using Git.

### Objective:

The objective of this experiment is to guide you through the process of using Git commands to interact with GitHub, from cloning a repository to collaborating with others through pull requests.

### Introduction:

GitHub is a web-based platform that offers version control and collaboration services for software development projects. It provides a way for developers to work together, manage code, track changes, and collaborate on projects efficiently. GitHub is built on top of the Git version control system, which allows for distributed and decentralised development.

### Key Features of GitHub:

- **Version Control:** GitHub uses Git, a distributed version control system, to track changes to source code over time. This allows developers to collaborate on projects while maintaining a history of changes and versions.
- **Repositories:** A repository (or repo) is a collection of files, folders, and the entire history of a project. Repositories on GitHub serve as the central place where code and project-related assets are stored.
- **Collaboration:** GitHub provides tools for team collaboration. Developers can work together on the same project, propose changes, review code, and discuss issues within the context of the project.
- **Pull Requests:** Pull requests (PRs) are proposals for changes to a repository. They allow developers to submit their changes for review, discuss the changes, and collaboratively improve the code before merging it into the main codebase.
- **Issues and Projects:** GitHub allows users to track and manage project-related issues, enhancements, and bugs. Projects and boards help organize tasks, track progress, and manage workflows.
- **Forks and Clones:** Developers can create copies (forks) of repositories to work on their own versions of a project. Cloning a repository allows developers to create a local copy of the project on their machine.
- **Branching and Merging:** GitHub supports branching, where developers can create separate lines of development for features or bug fixes. Changes made in branches can be merged back into the main codebase.
- **Actions and Workflows:** GitHub Actions enable developers to automate workflows, such as building, testing, and deploying applications, based on triggers like code pushes or pull requests.
- **GitHub Pages:** This feature allows users to publish web content directly from a GitHub repository, making it easy to create websites and documentation for projects.

### Benefits of Using GitHub:

- **Collaboration:** GitHub facilitates collaborative development by providing tools for code review, commenting, and discussion on changes.
- **Version Control:** Git's version control features help track changes, revert to previous versions, and manage different branches of development.

- **Open Source:** GitHub is widely used for hosting open-source projects, making it easier for developers to contribute and for users to find and use software.
- **Community Engagement:** GitHub fosters a community around projects, enabling interaction between project maintainers and contributors.
- **Code Quality:** The code review process on GitHub helps maintain code quality and encourages best practices.
- **Documentation:** GitHub provides a platform to host project documentation and wikis, making it easier to document codebases and project processes.
- **Continuous Integration/Continuous Deployment (CI/CD):** GitHub Actions allows for automating testing, building, and deploying applications, streamlining the development process.

### Materials:

- Computer with Git installed (<https://git-scm.com/downloads>)
- GitHub account (<https://github.com/>)
- Internet connection

### Experiment Steps:

#### Step 1: Cloning a Repository

- Sign in to your GitHub account.
- Find a repository to clone (you can use a repository of your own or any public repository).
- Click the "Code" button and copy the repository URL.
- Open your terminal or command prompt.
- Navigate to the directory where you want to clone the repository.
- Run the following command:

#### ***git clone <repository\_url>***

- Replace <repository\_url> with the URL you copied from GitHub.
- This will clone the repository to your local machine.

```
C:\Users\PALLAVI J S>cd C:\Users\PALLAVI J S\Desktop\devassignment
C:\Users\PALLAVI J S\Desktop\devassignment>git clone https://github.com/Pallavi-519/devopsassignment.git
Cloning into 'devopsassignment'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 3 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (3/3), done.
```

#### Step 2: Making Changes and Creating a Branch

Navigate into the cloned repository:

#### ***cd <repository\_name>***

- Create a new text file named "example.txt" using a text editor.
- Add some content to the "example.txt" file.
- Save the file and return to the command line.
- Check the status of the repository:

#### ***git status***

- Stage the changes for commit:



## **git add example.txt**

- Commit the changes with a descriptive message:

```
C:\Users\PALLAVI J S\Desktop\devassignment>cd devopsassignment
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git status
On branch main
Your branch is up to date with 'origin/main'.

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        example.txt

nothing added to commit but untracked files present (use "git add" to track)
```

## **git commit -m "Add content to example.txt"**

- Create a new branch named "feature":

```
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git add example.txt
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git commit -m"hello git"
[main 94c0387] hello git
 1 file changed, 1 insertion(+)
 create mode 100644 example.txt
```

## **git branch feature**

- Switch to the "feature" branch:

## **git checkout feature**

```
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git branch feature
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git checkout feature
Switched to branch 'feature'
```

## **Step 3: Pushing Changes to GitHub**

- Add Repository URL in a variable

## **git remote add origin <repository\_url>**

- Replace <repository\_url> with the URL you copied from GitHub.
- Push the "feature" branch to GitHub:

## **git push origin feature**

- Check your GitHub repository to confirm that the new branch "feature" is available

```
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git remote add origin https://github.com/Pallavi-519/devopsassignment.git
error: remote origin already exists.

C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git push origin feature
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 12 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 306 bytes | 153.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: Create a pull request for 'feature' on GitHub by visiting:
remote:   https://github.com/Pallavi-519/devopsassignment/pull/new/feature
remote:
To https://github.com/Pallavi-519/devopsassignment.git
 * [new branch]      feature -> feature
```

#### Step 4: Collaborating through Pull Requests

- Create a pull request on GitHub:
- Go to the repository on GitHub.
- Click on "Pull Requests" and then "New Pull Request."
- Choose the base branch (usually "main" or "master") and the compare branch ("feature").
- Review the changes and click "Create Pull Request."
- Review and merge the pull request:
- Add a title and description for the pull request.
- Assign reviewers if needed.
- Once the pull request is approved, merge it into the base branch.

#### Step 5: Syncing Changes

- After the pull request is merged, update your local repository:

##### *git checkout main*

```
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git checkout main
Switched to branch 'main'
Your branch is ahead of 'origin/main' by 1 commit.
(use "git push" to publish your local commits)
```

##### *git pull origin main*

```
C:\Users\PALLAVI J S\Desktop\devassignment\devopsassignment>git pull origin main
remote: Enumerating objects: 1, done.
remote: Counting objects: 100% (1/1), done.
remote: Total 1 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (1/1), 884 bytes | 176.00 KiB/s, done.
From https://github.com/Pallavi-519/devopsassignment
* branch      main      -> FETCH_HEAD
   6706606..f4295fd  main   -> origin/main
Updating 94c0387..f4295fd
Fast-forward
```

#### Conclusion:

This experiment provided you with practical experience in performing GitHub operations using Git commands. You learned how to clone repositories, make changes, create branches, push changes to GitHub, collaborate through pull requests, and synchronise changes with remote repositories. These skills are essential for effective collaboration and version control in software development projects using Git and GitHub.

## Experiment No. 3

**Title:** Implement GitLab Operations using Git.

### Objective:

The objective of this experiment is to guide you through the process of using Git commands to interact with GitLab, from creating a repository to collaborating with others through merge requests.

### Introduction:

GitLab is a web-based platform that offers a complete DevOps lifecycle toolset, including version control, continuous integration/continuous deployment (CI/CD), project management, code review, and collaboration features. It provides a centralized place for software development teams to work together efficiently and manage the entire development process in a single platform.

### Key Features of GitLab:

- **Version Control:** GitLab provides version control capabilities using Git, allowing developers to track changes to source code over time. This enables collaboration, change tracking, and code history maintenance.
- **Repositories:** Repositories on GitLab are collections of files, code, documentation, and assets related to a project. Each repository can have multiple branches and tags, allowing developers to work on different features simultaneously.
- **Continuous Integration/Continuous Deployment (CI/CD):** GitLab offers robust CI/CD capabilities. It automates the building, testing, and deployment of code changes, ensuring that software is delivered rapidly and reliably.
- **Merge Requests:** Merge requests in GitLab are similar to pull requests in other platforms. They enable developers to propose code changes, collaborate, and get code reviewed before merging it into the main codebase.
- **Issues and Project Management:** GitLab includes tools for managing project tasks, bugs, and enhancements. Issues can be assigned, labeled, and tracked, while project boards help visualize and manage work.
- **Container Registry:** GitLab includes a container registry that allows users to store and manage Docker images for applications.
- **Code Review and Collaboration:** Built-in code review tools facilitate collaboration among team members. Inline comments, code discussions, and code snippets are integral parts of this process.
- **Wiki and Documentation:** GitLab provides a space for creating project wikis and documentation, ensuring that project information is easily accessible and well-documented.
- **Security and Compliance:** GitLab offers security scanning, code analysis, and compliance features to help identify and address security vulnerabilities and ensure code meets compliance standards.
- **GitLab Pages:** Similar to GitHub Pages, GitLab Pages lets users publish static websites directly from a GitLab repository.

## Benefits of Using GitLab:

- **End-to-End DevOps:** GitLab offers an integrated platform for the entire software development and delivery process, from code writing to deployment.
- **Simplicity:** GitLab provides a unified interface for version control, CI/CD, and project management, reducing the need to use multiple tools.
- **Customizability:** GitLab can be self-hosted on-premises or used through GitLab's cloud service. This flexibility allows organizations to choose the hosting option that best suits their needs.
- **Security:** GitLab places a strong emphasis on security, with features like role-based access control (RBAC), security scanning, and compliance checks.
- **Open Source and Enterprise Versions:** GitLab offers both a free, open-source Community Edition and a paid, feature-rich Enterprise Edition, making it suitable for individual developers and large enterprises alike.

## Materials:

- Computer with Git installed (<https://git-scm.com/downloads>)
- GitLab account (<https://gitlab.com/>)
- Internet connection

## Experiment Steps:

### Step 1: Creating a Repository

- Sign in to your GitLab account.
- Click the "New" button to create a new project.
- Choose a project name, visibility level (public, private), and other settings.
- Click "Create project."

### Step 2: Cloning a Repository

- Open your terminal or command prompt.
- Navigate to the directory where you want to clone the repository.
- Copy the repository URL from GitLab.
- Run the following command:

#### ***git clone <repository\_url>***

- Replace <repository\_url> with the URL you copied from GitLab.
- This will clone the repository to your local machine.

```
C:\Users\PALLAVI J S>cd C:\Users\PALLAVI J S\Desktop\devassignment
C:\Users\PALLAVI J S\Desktop\devassignment>git clone git@gitlab.com:pallavi-519-group/devops-project.git
Cloning into 'devops-project'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (3/3), done.
```

### Step 3: Making Changes and Creating a Branch

- Navigate into the cloned repository:

#### ***cd <repository\_name>***

- Create a new text file named "example.txt" using a text editor.
- Add some content to the "example.txt" file.

- Save the file and return to the command line.
- Check the status of the repository:

### ***git status***

```
C:\Users\PALLAVI J S\Desktop\devassignment>cd devops-project

C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git status
On branch main
Your branch is up to date with 'origin/main'.

Untracked files:
  (use "git add <file>..." to include in what will be committed)
       example.txt

nothing added to commit but untracked files present (use "git add" to track)
```

- Stage the changes for commit:

### ***git add example.txt***

- Commit the changes with a descriptive message:

### ***git commit -m "Add content to example.txt"***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git add example.txt

C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git commit -m"hello gitlab"
[main 4777903] hello gitlab
 1 file changed, 1 insertion(+)
 create mode 100644 example.txt
```

- Create a new branch named "feature":

### ***git branch feature***

- Switch to the "feature" branch:

### ***git checkout feature***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git branch feature

C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git checkout feature
Switched to branch 'feature'
```

## **Step 4: Pushing Changes to GitLab**

- Add Repository URL in a variable

### ***git remote add origin <repository\_url>***

- Replace <repository\_url> with the URL you copied from GitLab.

- Push the "feature" branch to GitLab:

### ***git push origin feature***

Check your GitLab repository to confirm that the new branch "feature" is available.

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git remote add origin git@gitlab.com:pallavi-519-group/devops-project.git
error: remote origin already exists.

C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git push origin feature
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 12 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 320 bytes | 160.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: To create a merge request for feature, visit:
remote:   https://gitlab.com/pallavi-519-group/devops-project/-/merge_requests/new?merge_request%5Bsource_branch%5D=feature
remote:
To gitlab.com:pallavi-519-group/devops-project.git
 * [new branch]   feature -> feature
```

## Step 5: Collaborating through Merge Requests

1. Create a merge request on GitLab:
  - Go to the repository on GitLab.
  - Click on "Merge Requests" and then "New Merge Request."
  - Choose the source branch ("feature") and the target branch ("main" or "master").
  - Review the changes and click "Submit merge request."
2. Review and merge the merge request:
  - Add a title and description for the merge request.
  - Assign reviewers if needed.
  - Once the merge request is approved, merge it into the target branch.

## Step 6: Syncing Changes

- After the merge request is merged, update your local repository:

### ***git checkout main***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git checkout main
Switched to branch 'main'
Your branch is ahead of 'origin/main' by 1 commit.
(use "git push" to publish your local commits)
```

### ***git pull origin main***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git pull origin main
remote: Enumerating objects: 1, done.
remote: Counting objects: 100% (1/1), done.
remote: Total 1 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (1/1), 255 bytes | 36.00 KiB/s, done.
From gitlab.com:pallavi-519-group/devops-project
* branch      main      -> FETCH_HEAD
   40e6144..712b96f  main   -> origin/main
Updating 4777903..712b96f
Fast-forward
```

## Conclusion:

This experiment provided you with practical experience in performing GitLab operations using Git commands. You learned how to create repositories, clone them to your local machine, make changes, create branches, push changes to GitLab, collaborate through merge requests, and synchronise changes with remote repositories. These skills are crucial for effective collaboration and version control in software development projects using GitLab and Git.

## **Experiment No. 4**

### **Title: Implement BitBucket Operations using Git.**

#### **Objective:**

The objective of this experiment is to guide you through the process of using Git commands to interact with Bitbucket, from creating a repository to collaborating with others through pull requests.

#### **Introduction:**

Bitbucket is a web-based platform designed to provide version control, source code management, and collaboration tools for software development projects. It is widely used by teams and individuals to track changes in code, collaborate on projects, and streamline the development process. Bitbucket offers Git and Mercurial as version control systems and provides features to support code collaboration, continuous integration/continuous deployment (CI/CD), and project management.

#### **Key Features of Bitbucket:**

- **Version Control:** Bitbucket supports both Git and Mercurial version control systems, allowing developers to track changes, manage code history, and work collaboratively on projects.
- **Repositories:** In Bitbucket, a repository is a container for code, documentation, and other project assets. It houses different branches, tags, and commits that represent different versions of the project.
- **Collaboration:** Bitbucket enables team collaboration through features like pull requests, code reviews, inline commenting, and team permissions. These tools help streamline the process of merging code changes.
- **Pull Requests:** Pull requests in Bitbucket allow developers to propose and review code changes before they are merged into the main codebase. This process helps ensure code quality and encourages collaboration.
- **Code Review:** Bitbucket provides tools for efficient code review, allowing team members to comment on specific lines of code and discuss changes within the context of the code itself.
- **Continuous Integration/Continuous Deployment (CI/CD):** Bitbucket integrates with CI/CD pipelines, automating processes such as building, testing, and deploying code changes to various environments.
- **Project Management:** Bitbucket offers project boards and issue tracking to help manage tasks, track progress, and plan project milestones effectively.
- **Bitbucket Pipelines:** This feature allows teams to define and automate CI/CD pipelines directly within Bitbucket, ensuring code quality and rapid delivery.
- **Access Control and Permissions:** Bitbucket allows administrators to define user roles, permissions, and access control settings to ensure the security of repositories and project assets.

#### **Benefits of Using Bitbucket:**

- **Version Control:** Bitbucket's integration with Git and Mercurial provides efficient version control and code history tracking.

- Collaboration: The platform's collaboration tools, including pull requests and code reviews, improve code quality and facilitate team interaction.
- CI/CD Integration: Bitbucket's integration with CI/CD pipelines automates testing and deployment, resulting in faster and more reliable software delivery.
- Project Management: Bitbucket's project management features help teams organize tasks, track progress, and manage milestones.
- Flexibility: Bitbucket offers both cloud-based and self-hosted options, providing flexibility to choose the deployment method that suits the organization's needs.
- Integration: Bitbucket integrates with various third-party tools, services, and extensions, enhancing its functionality and extending its capabilities.

#### Materials:

- Computer with Git installed (<https://git-scm.com/downloads>)
- Bitbucket account (<https://bitbucket.org/>)
- Internet connection

#### Experiment Steps:

##### Step 1: Creating a Repository

- Sign in to your Bitbucket account.
- Click the "Create" button to create a new repository.
- Choose a repository name, visibility (public or private), and other settings.
- Click "Create repository."

##### Step 2: Cloning a Repository

- Open your terminal or command prompt.
- Navigate to the directory where you want to clone the repository.
- Copy the repository URL from Bitbucket.
- Run the following command:

##### ***git clone <repository\_url>***

- Replace <repository\_url> with the URL you copied from Bitbucket.
- This will clone the repository to your local machine.

```
C:\Users\PALLAVI J S>cd C:\Users\PALLAVI J S\Desktop\devassignment
C:\Users\PALLAVI J S\Desktop\devassignment>git clone git@gitlab.com:pallavi-519-group/devops-project.git
Cloning into 'devops-project'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (3/3), done.
```

##### Step 3: Making Changes and Creating a Branch

- Navigate into the cloned repository:

##### ***cd <repository\_name>***

- Create a new text file named "example.txt" using a text editor.
- Add some content to the "example.txt" file.
- Save the file and return to the command line.
- Check the status of the repository:



## ***git status***

```
C:\Users\PALLAVI J S\Desktop\devassignment>cd devops-project

C:\Users\PALLAVI J S\Desktop\devassignment\devops-project>git status
On branch main
Your branch is up to date with 'origin/main'.

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        example.txt

nothing added to commit but untracked files present (use "git add" to track)
```

- Stage the changes for commit:

## ***git add example.txt***

- Commit the changes with a descriptive message:

## ***git commit -m "Add content to example.txt"***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git add example.txt

C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git commit -m"hello bit-bucket"
[main 4303a9a] hello bit-bucket
 1 file changed, 1 insertion(+)
 create mode 100644 example.txt
```

- Create a new branch named "feature":

## ***git branch feature***

- Switch to the "feature" branch:

## ***git checkout feature***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git branch feature

C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git checkout feature
Switched to branch 'feature'
```

## **Step 4: Pushing Changes to Bitbucket**

- Add Repository URL in a variable

## ***git remote add origin <repository\_url>***

- Replace <repository\_url> with the URL you copied from Bitbucket.
- Push the "feature" branch to Bitbucket:

## ***git push origin feature***

- Check your Bitbucket repository to confirm that the new branch "feature" is available.

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git remote add origin https://jspallavi9@bitbucket.org/jspallavi/devops_assignment
.git
error: remote origin already exists.

C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git push origin feature
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 12 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 306 bytes | 153.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: Create pull request for feature:
remote:   https://bitbucket.org/jspallavi/devops_assignment/pull-requests/new?source=feature&t=1
remote:
To https://bitbucket.org/jspallavi/devops_assignment.git
 * [new branch]      feature -> feature
```

## Step 5: Collaborating through Pull Requests

1. Create a pull request on Bitbucket:
  - Go to the repository on Bitbucket.
  - Click on "Create pull request."
  - Choose the source branch ("feature") and the target branch ("main" or "master").
  - Review the changes and click "Create pull request."
2. Review and merge the pull request:
  - Add a title and description for the pull request.
  - Assign reviewers if needed.
  - Once the pull request is approved, merge it into the target branch.

## Step 6: Syncing Changes

- After the pull request is merged, update your local repository:

### ***git checkout main***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git checkout main
Switched to branch 'main'
Your branch is ahead of 'origin/main' by 1 commit.
(use "git push" to publish your local commits)
```

### ***git pull origin main***

```
C:\Users\PALLAVI J S\Desktop\devassignment\devops_assignment>git pull origin main
remote: Enumerating objects: 1, done.
remote: Counting objects: 100% (1/1), done.
remote: Total 1 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (1/1), 227 bytes | 32.00 KiB/s, done.
From https://bitbucket.org/jspallavi/devops_assignment
 * branch      main      -> FETCH_HEAD
    5bf361c..3b00f11  main    -> origin/main
Updating 4303a9a..3b00f11
Fast-forward
```

## Conclusion:

This experiment provided you with practical experience in performing Bitbucket operations using Git commands. You learned how to create repositories, clone them to your local machine, make changes, create branches, push changes to Bitbucket, collaborate through pull requests, and synchronise changes with remote repositories. These skills are essential for effective collaboration and version control in software development projects using Bitbucket and Git.

## Experiment No. 5

### Title: Applying CI/CD Principles to Web Development Using Jenkins, Git, and Local HTTP Server

#### Objective:

The objective of this experiment is to set up a CI/CD pipeline for a web development project using Jenkins, Git, and webhooks, without the need for a Jenkinsfile. You will learn how to automatically build and deploy a web application to a local HTTP server whenever changes are pushed to the Git repository, using Jenkins' "Execute Shell" build step.

#### Introduction:

Continuous Integration and Continuous Deployment (CI/CD) is a critical practice in modern software development, allowing teams to automate the building, testing, and deployment of applications. This process ensures that software updates are consistently and reliably delivered to end-users, leading to improved development efficiency and product quality.

In this context, this introduction sets the stage for an exploration of how to apply CI/CD principles specifically to web development using Jenkins, Git, and a local HTTP server. We will discuss the key components and concepts involved in this process.

#### Key Components:

- **Jenkins:** Jenkins is a widely used open-source automation server that helps automate various aspects of the software development process. It is known for its flexibility and extensibility and can be employed to create CI/CD pipelines.
- **Git:** Git is a distributed version control system used to manage and track changes in source code. It plays a crucial role in CI/CD by allowing developers to collaborate, track changes, and trigger automation processes when code changes are pushed to a repository.
- **Local HTTP Server:** A local HTTP server is used to host and serve web applications during development. It is where your web application can be tested before being deployed to production servers.

#### CI/CD Principles:

- **Continuous Integration (CI):** CI focuses on automating the process of integrating code changes into a shared repository frequently. It involves building and testing the application each time code is pushed to the repository to identify and address issues early in the development cycle.
- **Continuous Deployment (CD):** CD is the practice of automatically deploying code changes to production or staging environments after successful testing. CD aims to minimize manual intervention and reduce the time between code development and its availability to end-users.

#### The CI/CD Workflow:

- **Code Changes:** Developers make changes to the web application's source code locally.

- **Git Repository:** Developers push their code changes to a Git repository, such as GitHub or Bitbucket.
- **Webhook:** A webhook is configured in the Git repository to notify Jenkins whenever changes are pushed.
- **Jenkins Job:** Jenkins is set up to listen for webhook triggers. When a trigger occurs, Jenkins initiates a CI/CD pipeline.
- **Build and Test:** Jenkins executes a series of predefined steps, which may include building the application, running tests, and generating artifacts.
- **Deployment:** If all previous steps are successful, Jenkins deploys the application to a local HTTP server for testing.
- **Verification:** The deployed application is tested locally to ensure it functions as expected.
- **Optional Staging:** For more complex setups, there might be a staging environment where the application undergoes further testing before reaching production.
- **Production Deployment:** If the application passes all tests, it can be deployed to the production server.

### Benefits of CI/CD in Web Development:

- **Rapid Development:** CI/CD streamlines development processes, reducing manual tasks and allowing developers to focus on writing code.
- **Improved Quality:** Automated testing helps catch bugs early, ensuring higher code quality.
- **Faster Time to Market:** Automated deployments reduce the time it takes to release new features or updates.
- **Consistency:** The process ensures that code is built, tested, and deployed consistently, reducing the risk of errors.

### Materials:

- A computer with administrative privileges
- Jenkins installed and running (<https://www.jenkins.io/download/>)
- Git installed (<https://git-scm.com/downloads>)
- A local HTTP server for hosting web content (e.g., Apache, Nginx)
- A Git repository (e.g., on GitHub or Bitbucket)

### Experiment Steps:

#### Step 1: Set Up the Web Application and Local HTTP Server

- Create a simple web application or use an existing one. Ensure it can be hosted by a local HTTP server.
- Set up a local HTTP server (e.g., Apache or Nginx) to serve the web application. Ensure it's configured correctly and running.

#### Step 2: Set Up a Git Repository

Create a Git repository for your web application. Initialize it with the following commands:

***git init***

***git add .***

***git commit -m "Initial commit"***

- Create a remote Git repository (e.g., on GitHub or Bitbucket) to push your code to later.

### **Step 3: Install and Configure Jenkins**

- Download and install Jenkins following the instructions for your operating system (<https://www.jenkins.io/download/>).
- Open Jenkins in your web browser (usually at <http://localhost:8080>) and complete the initial setup.
- Install the necessary plugins for Git integration, job scheduling, and webhook support.
- Configure Jenkins to work with Git by setting up your Git credentials in the Jenkins Credential Manager.

### **Step 4: Create a Jenkins Job**

- Create a new Jenkins job using the "Freestyle project" type.
- Configure the job to use a webhook trigger. You can do this by selecting the "GitHub hook trigger for GITScm polling" option in the job's settings.

### **Step 5: Set Up the Jenkins Job (Using Execute Shell)**

- In the job configuration, go to the "Build" section.
- Add a build step of type "Execute shell."
- In the "Command" field, define the build and deployment steps using shell commands. For example:

```
# Checkout code from Git
```

```
# Build your web application (e.g., npm install, npm run build)
```

```
# Copy the build artefacts to the local HTTP server directory
```

```
rm -rf /var/www/html/webdirectory/*
```

```
cp -r * /var/www/html/webdirectory/
```

### **Step 6: Set Up a Webhook in Git Repository**

- In your Git repository (e.g., on GitHub), go to "Settings" and then "Webhooks."
- Create a new webhook, and configure it to send a payload to the Jenkins webhook URL (usually <http://jenkins-server/github-webhook/>). Make sure to set the content type to "application/json."
- OR use "GitHub hook trigger for GITScm polling?" Under Build Trigger

### **Step 7: Trigger the CI/CD Pipeline**

- Push changes to your Git repository. The webhook should trigger the Jenkins job automatically, executing the build and deployment steps defined in the "Execute Shell" build step.
- Monitor the Jenkins job's progress in the Jenkins web interface.

## Step 8: Verify the CI/CD Pipeline

Visit the URL of your local HTTP server to verify that the web application has been updated with the latest changes.

### Conclusion:

This experiment demonstrates how to set up a CI/CD pipeline for web development using Jenkins, Git, a local HTTP server, and webhooks, without the need for a Jenkinsfile. By defining and executing the build and deployment steps using the "Execute Shell" build step, you can automate your development workflow and ensure that your web application is continuously updated with the latest changes.

```
Microsoft Windows [Version 10.0.22631.5335]
(c) Microsoft Corporation. All rights reserved.

C:\Users\shett>python --version
Python 3.13.4

C:\Users\shett>cd C:\Users\shett\OneDrive\Desktop\CI025

C:\Users\shett\OneDrive\Desktop\CI025>notepad index.html

C:\Users\shett\OneDrive\Desktop\CI025>python -m http.server 8000
Serving HTTP on :: port 8000 (http://[::]:8000/) ...
::1 - - [09/Jun/2025 14:31:15] "GET / HTTP/1.1" 200 -

Keyboard interrupt received, exiting.

C:\Users\shett\OneDrive\Desktop\CI025>cd C:\Users\shett\OneDrive\Desktop\CI025

C:\Users\shett\OneDrive\Desktop\CI025>git init
Initialized empty Git repository in C:/Users/shett/OneDrive/Desktop/CI025/.git/

C:\Users\shett\OneDrive\Desktop\CI025>git add .

C:\Users\shett\OneDrive\Desktop\CI025>git commit -m "Initial commit"
[master (root-commit) 225130c] Initial commit
 1 file changed, 9 insertions(+)
 create mode 100644 index.html
```

```
C:\Users\shett\OneDrive\Desktop\CI025>git remote add origin https://github.com/08ananya/webapp-ci-cd.git

C:\Users\shett\OneDrive\Desktop\CI025>git push -u origin master
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Delta compression using up to 12 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 313 bytes | 156.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/08ananya/webapp-ci-cd.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

C:\Users\shett\OneDrive\Desktop\CI025>java --version
java 24.0.1 2025-04-15
Java(TM) SE Runtime Environment (build 24.0.1+9-30)
Java HotSpot(TM) 64-Bit Server VM (build 24.0.1+9-30, mixed mode, sharing)

C:\Users\shett\OneDrive\Desktop\CI025>
```

## Experiment No. 6

### Title: Exploring Containerization and Application Deployment with Docker

#### Objective:

The objective of this experiment is to provide hands-on experience with Docker containerization and application deployment by deploying an Apache web server in a Docker container. By the end of this experiment, you will understand the basics of Docker, how to create Docker containers, and how to deploy a simple web server application.

#### Introduction

Containerization is a technology that has revolutionised the way applications are developed, deployed, and managed in the modern IT landscape. It provides a standardised and efficient way to package, distribute, and run software applications and their dependencies in isolated environments called containers.

Containerization technology has gained immense popularity, with Docker being one of the most well-known containerization platforms. This introduction explores the fundamental concepts of containerization, its benefits, and how it differs from traditional approaches to application deployment.

#### Key Concepts of Containerization:

- **Containers:** Containers are lightweight, stand-alone executable packages that include everything needed to run a piece of software, including the code, runtime, system tools, libraries, and settings. Containers ensure that an application runs consistently and reliably across different environments, from a developer's laptop to a production server.
- **Images:** Container images are the templates for creating containers. They are read-only and contain all the necessary files and configurations to run an application. Images are typically built from a set of instructions defined in a Dockerfile.
- **Docker:** Docker is a popular containerization platform that simplifies the creation, distribution, and management of containers. It provides tools and services for building, running, and orchestrating containers at scale.
- **Isolation:** Containers provide process and filesystem isolation, ensuring that applications and their dependencies do not interfere with each other. This isolation enhances security and allows multiple containers to run on the same host without conflicts.

#### Benefits of Containerization:

- **Consistency:** Containers ensure that applications run consistently across different environments, reducing the "it works on my machine" problem.
- **Portability:** Containers are portable and can be easily moved between different host machines and cloud providers.
- **Resource Efficiency:** Containers share the host operating system's kernel, which makes them lightweight and efficient in terms of resource utilization.
- **Scalability:** Containers can be quickly scaled up or down to meet changing application demands, making them ideal for microservices architectures.

- **Version Control:** Container images are versioned, enabling easy rollback to previous application states if issues arise.
- **DevOps and CI/CD:** Containerization is a fundamental technology in DevOps and CI/CD pipelines, allowing for automated testing, integration, and deployment.

### Containerization vs. Virtualization:

- Containerization differs from traditional virtualization, where a hypervisor virtualizes an entire operating system (VM) to run multiple applications. In contrast:
- Containers share the host OS kernel, making them more lightweight and efficient.
- Containers start faster and use fewer resources than VMs.
- VMs encapsulate an entire OS, while containers package only the application and its dependencies.

### Materials:

- A computer with Docker installed (<https://docs.docker.com/get-docker/>)
- A code editor
- Basic knowledge of Apache web server

### Experiment Steps:

#### Step 1: Install Docker

- If you haven't already, install Docker on your computer by following the instructions provided on the Docker website (<https://docs.docker.com/get-docker/>).

#### Step 2: Create a Simple HTML Page

- Create a directory for your web server project.
- Inside this directory, create a file named `index.html` with a simple "Hello, Docker!" message. This will be the content served by your Apache web server.

#### Step 3: Create a Dockerfile

- Create a Dockerfile in the same directory as your web server project. The Dockerfile defines how your Apache web server application will be packaged into a Docker container. Here's an example:

#### Dockerfile

***# Use an official Apache image as the base image FROM  
httpd:2.4***

***# Copy your custom HTML page to the web server's document root COPY  
index.html /usr/local/apache2/htdocs/***

#### Step 4: Build the Docker Image

- Build the Docker image by running the following command in the same directory as your Dockerfile:



## **`docker build -t my-apache-server .`**

- Replace my-apache-server with a suitable name for your image.

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker build -t my-apache-server .
[+] Building 60.7s (8/8) FINISHED
=> [internal] load build definition from Dockerfile
=> => transferring dockerfile: 220B
=> [internal] load metadata for docker.io/library/httpd:2.4
=> [auth] library/httpd:pull token for registry-1.docker.io
=> [internal] load .dockerignore
=> => transferring context: 2B
=> [internal] load build context
=> => transferring context: 171B
=> [1/2] FROM docker.io/library/httpd:2.4@sha256:09cb4b94edaaa796522c545328b62e9a0db60315c7be9f2b4e02204919926405
=> => resolve docker.io/library/httpd:2.4@sha256:09cb4b94edaaa796522c545328b62e9a0db60315c7be9f2b4e02204919926405
=> => sha256:8dbbd44856ed41e4c9b3b82fdbfe7aca26519f741196c793e9c972b4f97f1be4 294B / 294B
=> => sha256:162ef2c73af17d2a253799fe883dcb915eb04c1ca69d1f4910f07430f1800428 26.06MB / 26.06MB
=> => sha256:8f86928406fdf71ab1fca056bbf29e53e35a1a84dca61f510a1f66ed88bd918f 4.20MB / 4.20MB
=> => sha256:4f4fb700ef54461cfa02571ae0db9a0dc1e0cdb5577484a6d75e68dc38e8acc1 32B / 32B
=> => sha256:be60498bea0a2c1ed42b24855b189c4839fe9221e997519e5ded5f9b0b8ce0e1 145B / 145B
=> => extracting sha256:be60498bea0a2c1ed42b24855b189c4839fe9221e997519e5ded5f9b0b8ce0e1
=> => extracting sha256:4f4fb700ef54461cfa02571ae0db9a0dc1e0cdb5577484a6d75e68dc38e8acc1
=> => extracting sha256:8f86928406fdf71ab1fca056bbf29e53e35a1a84dca61f510a1f66ed88bd918f
=> => extracting sha256:162ef2c73af17d2a253799fe883dcb915eb04c1ca69d1f4910f07430f1800428
=> => extracting sha256:8dbbd44856ed41e4c9b3b82fdbfe7aca26519f741196c793e9c972b4f97f1be4
=> [2/2] COPY index.html /usr/local/apache2/htdocs/
=> exporting to image
=> => exporting layers
=> => exporting manifest sha256:4518ec9b67851941fe7e926b218b7cd1de272fa85f77d39176b9d37f89b7a285
=> => exporting config sha256:e39a14a38dd813b5f45fa3457ada381456be550e26259583fbcc1b2e784e854c
=> => exporting attestation manifest sha256:bf81c655b11ad69a427f56f8352bf015b7c04dc37377bc354e44ba8e507fd38d
=> => exporting manifest list sha256:a1e6bfbfbf87a6d5119692affa4d66ca84d61d07d458a2e43559139c2e1cbb90
=> => naming to docker.io/library/my-apache-server:latest
=> => unpacking to docker.io/library/my-apache-server:latest
```

## **Step 5: Run the Docker Container**

Start a Docker container from the image you built:

### **`docker run -p 8080:80 -d my-apache-server`**

- This command maps port 80 in the container to port 8080 on your host machine and runs the container in detached mode.

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker run -p 8080:80 -d my-apache-server
e08f80f1bb1665449b38d4275aac650f65a68da53ca5876758b759c6716b8699
```

## **Step 6: Access Your Apache Web Server**

Access your Apache web server by opening a web browser and navigating to `http://localhost:8080`. You should see the "Hello, Docker!" message served by your Apache web server running within the Docker container.

## **Step 7: Cleanup**

Stop the running Docker container:

### **`docker stop <container_id>`**

- Replace `<container_id>` with the actual ID of your running container.
- Optionally, remove the container and the Docker image:

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker stop e08f80f1bb1665449b38d4275aac650f65a68da53ca5876758b759c6716b8699
e08f80f1bb1665449b38d4275aac650f65a68da53ca5876758b759c6716b8699
```

### **`docker rm <container_id>`**

### **`docker rmi my-apache-server`**

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker rm e08f80f1bb1665449b38d4275aac650f65a68da53ca5876758b759c6716b8699
e08f80f1bb1665449b38d4275aac650f65a68da53ca5876758b759c6716b8699

C:\Users\PALLAVI J S\Desktop\devassignment>docker rmi my-apache-server
Untagged: my-apache-server:latest
Deleted: sha256:a1e6bfbfbf87a6d5119692affa4d66ca84d61d07d458a2e43559139c2e1cbb90
```

**Conclusion:**

In this experiment, you explored containerization and application deployment with Docker by deploying an Apache web server in a Docker container. You learned how to create a Dockerfile, build a Docker image, run a Docker container, and access your web server application from your host machine. Docker's containerization capabilities make it a valuable tool for packaging and deploying applications consistently across different environments.

## **Experiment No. 7**

### **Title: Applying CI/CD Principles to Web Development Using Jenkins, Git, using Docker Containers**

#### **Objective:**

The objective of this experiment is to set up a CI/CD pipeline for a web application using Jenkins, Git, Docker containers, and GitHub webhooks. The pipeline will automatically build, test, and deploy the web application whenever changes are pushed to the Git repository, without the need for a pipeline script.

#### **Introduction:**

Continuous Integration and Continuous Deployment (CI/CD) principles are integral to modern web development practices, allowing for the automation of code integration, testing, and deployment. This experiment demonstrates how to implement CI/CD for web development using Jenkins, Git, Docker containers, and GitHub webhooks without a pipeline script. Instead, we'll utilize Jenkins' "GitHub hook trigger for GITScm polling" feature.

In the fast-paced world of modern web development, the ability to deliver high-quality software efficiently and reliably is paramount. Continuous Integration and Continuous Deployment (CI/CD) are integral principles and practices that have revolutionized the way software is developed, tested, and deployed. These practices bring automation, consistency, and speed to the software development lifecycle, enabling development teams to deliver code changes to production with confidence.

#### **Continuous Integration (CI):**

CI is the practice of frequently and automatically integrating code changes from multiple contributors into a shared repository. The core idea is that developers regularly merge their code into a central repository, triggering automated builds and tests. Key aspects of CI include:

- **Automation:** CI tools, like Jenkins, Travis CI, or CircleCI, automate the building and testing of code whenever changes are pushed to the repository.
- **Frequent Integration:** Developers commit and integrate their code changes multiple times a day, reducing integration conflicts and catching bugs early.
- **Testing:** Automated tests, including unit tests and integration tests, are run to ensure that new code changes do not introduce regressions.
- **Quick Feedback:** CI provides rapid feedback to developers about the quality and correctness of their code changes.

#### **Continuous Deployment (CD):**

CD is the natural extension of CI. It is the practice of automatically and continuously deploying code changes to production or staging environments after successful integration and testing. Key aspects of CD include:

- **Automation:** CD pipelines automate the deployment process, reducing the risk of human error and ensuring consistent deployments.

- Deployment to Staging: Code changes are deployed first to a staging environment where further testing and validation occur.
- Deployment to Production: After passing all tests in the staging environment, code changes are automatically deployed to the production environment, often with zero downtime.
- Rollbacks: In case of issues, CD pipelines provide the ability to rollback to a previous version quickly.

#### **Benefits of CI/CD in Web Development:**

- Rapid Development: CI/CD accelerates development cycles by automating time-consuming tasks, allowing developers to focus on coding.
- Quality Assurance: Automated testing ensures code quality, reducing the number of bugs and regressions.
- Consistency: CI/CD ensures that code is built, tested, and deployed consistently, regardless of the development environment.
- Continuous Feedback: Developers receive immediate feedback on the impact of their changes, improving collaboration and productivity.
- Reduced Risk: Automated deployments reduce the likelihood of deployment errors and downtime, enhancing reliability.
- Scalability: CI/CD can scale to accommodate projects of all sizes, from small startups to large enterprises.

#### **Materials:**

- A computer with Docker installed (<https://docs.docker.com/get-docker/>)
- Jenkins installed and configured (<https://www.jenkins.io/download/>)
- A web application code repository hosted on GitHub

#### **Experiment Steps:**

##### **Step 1: Set Up the Web Application and Git Repository**

- Create a simple web application or use an existing one. Ensure it can be hosted in a Docker container.
- Initialise a Git repository for your web application and push it to GitHub.

##### **Step 2: Install and Configure Jenkins**

- Install Jenkins on your computer or server following the instructions for your operating system (<https://www.jenkins.io/download/>).
- Open Jenkins in your web browser (usually at <http://localhost:8080>) and complete the initial setup, including setting up an admin user and installing necessary plugins.
- Configure Jenkins to work with Git by setting up Git credentials in the Jenkins Credential Manager.

##### **Step 3: Create a Jenkins Job**

- Create a new Jenkins job using the "Freestyle project" type.
- In the job configuration, specify a name for your job and choose "This project is parameterized."
- Add a "String Parameter" named `GIT_REPO_URL` and set its default value to your Git repository URL.

- Set Branches to build -> Branch Specifier to the working Git branch (ex \*/master)
- In the job configuration, go to the "Build Triggers" section and select the "GitHub hook trigger for GITScm polling" option. This enables Jenkins to listen for GitHub webhook triggers.

#### Step 4: Configure Build Steps

- In the job configuration, go to the "Build" section.
- Add build steps to execute Docker commands for building and deploying the containerized web application. Use the following commands:

**# Remove the existing container if it exists docker rm --force container1**

**# Build a new Docker image docker build -t nginx-image1 .**

**# Run the Docker container  
docker run -d -p 8081:80 --name=container1 nginx-image1**

- These commands remove the existing container (if any), build a Docker image named "nginx-image1," and run a Docker container named "container1" on port 8081.

```
C:\Users\PALLAVI J S>echo %JAVA_HOME%
C:\Program Files\Eclipse Adoptium\jdk-17.0.15.6-hotspot

C:\Users\PALLAVI J S>cd C:\Users\PALLAVI J S\Desktop\devassignment

C:\Users\PALLAVI J S\Desktop\devassignment>git init
Reinitialized existing Git repository in C:/Users/PALLAVI J S/Desktop/devassignment/.git/

C:\Users\PALLAVI J S\Desktop\devassignment>git add .

C:\Users\PALLAVI J S\Desktop\devassignment>git commit -m "Initial commit"
[main 94dd5b1] Initial commit
 3 files changed, 11 insertions(+), 11 deletions(-)
 delete mode 100644 MavenDemo/MyWebApp/index.html
 create mode 100644 index2.html

C:\Users\PALLAVI J S\Desktop\devassignment>git remote add origin https://github.com/Pallavi-519/web-app.git
error: remote origin already exists.

C:\Users\PALLAVI J S\Desktop\devassignment>git push origin main
Enumerating objects: 8, done.
Counting objects: 100% (8/8), done.
Delta compression using up to 12 threads
Compressing objects: 100% (5/5), done.
Writing objects: 100% (5/5), 669 bytes | 223.00 KiB/s, done.
Total 5 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To https://github.com/Pallavi-519/devopsassignment.git
 4051d8c..94dd5b1  main -> main

C:\Users\PALLAVI J S\Desktop\devassignment>docker rm --force container1
Error response from daemon: No such container: container1

C:\Users\PALLAVI J S\Desktop\devassignment>docker build -t nginx-image1 .
[+] Building 3.9s (8/8) FINISHED                                docker:desktop-linux
=> [internal] load build definition from Dockerfile             0.1s
=> => transferring dockerfile: 220B                             0.0s
=> [internal] load metadata for docker.io/library/httpd:2.4     2.9s
```

#### Step 5: Set Up a GitHub Webhook

- In your GitHub repository, navigate to "Settings" and then "Webhooks."
- Create a new webhook, and configure it to send a payload to the Jenkins webhook URL (usually http://jenkins-server/github-webhook/). Set the content type to "application/json."

#### Step 6: Trigger the CI/CD Pipeline

- Push changes to your GitHub repository. The webhook will trigger the Jenkins job automatically, executing the build and deployment steps defined in the job configuration.
- Monitor the Jenkins job's progress in the Jenkins web interface.

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker run -d -p 8081:80 --name container1 nginx-image1
876d5bfce65c1dc87be6b0fc9aa0133f1b9e5c44bff880e89abf02d7f56a4c3d

C:\Users\PALLAVI J S\Desktop\devassignment>ngrok http 8080
'ngrok' is not recognized as an internal or external command,
operable program or batch file.

C:\Users\PALLAVI J S\Desktop\devassignment>npm install -g localtunnel

added 22 packages in 7s

8 packages are looking for funding
  run 'npm fund' for details
npm notice
npm notice New major version of npm available! 10.9.0 -> 11.4.1
npm notice Changelog: https://github.com/npm/cli/releases/tag/v11.4.1
npm notice To update run: npm install -g npm@11.4.1
npm notice

C:\Users\PALLAVI J S\Desktop\devassignment>lt --port 8080
your url is: https://ninety-rocks-smile.loca.lt
C:\Users\PALLAVI J S\AppData\Roaming\npm\node_modules\localtunnel\bin\lt.js:81
  throw err;
    ^
```

### Step 7: Verify the Deployment

Access your web application by opening a web browser and navigating to <http://localhost:8081> (or the appropriate URL if hosted elsewhere).

### Conclusion:

This experiment demonstrates how to apply CI/CD principles to web development using Jenkins, Git, Docker containers, and GitHub webhooks. By configuring Jenkins to listen for GitHub webhook triggers and executing Docker commands in response to code changes, you can automate the build and deployment of your web application, ensuring a more efficient and reliable development workflow.

## **Experiment No. 8**

### **Title: Demonstrate Maven Build Life Cycle**

#### **Objective:**

The objective of this experiment is to gain hands-on experience with the Maven build lifecycle by creating a simple Java project and executing various Maven build phases.

#### **Introduction:**

Maven is a widely-used build automation and project management tool in the Java ecosystem. It provides a clear and standardised build lifecycle for Java projects, allowing developers to perform various tasks such as compiling code, running tests, packaging applications, and deploying artefacts. This experiment aims to demonstrate the Maven build lifecycle and its different phases.

#### **Key Maven Concepts:**

- **Project Object Model (POM):** The POM is an XML file named pom.xml that defines a project's configuration, dependencies, plugins, and goals. It serves as the project's blueprint and is at the core of Maven's functionality.
- **Build Lifecycle:** Maven follows a predefined sequence of phases and goals organized into build lifecycles. These lifecycles include clean, validate, compile, test, package, install, and deploy, among others.
- **Plugin:** Plugins are extensions that provide specific functionality to Maven. They enable tasks like compiling code, running tests, packaging artifacts, and deploying applications.
- **Dependency Management:** Maven simplifies dependency management by allowing developers to declare project dependencies in the POM file. Maven downloads these dependencies from repositories like Maven Central.
- **Repository:** A repository is a collection of artifacts (compiled libraries, JARs, etc.) that Maven uses to manage dependencies. Maven Central is a popular public repository, and organisations often maintain private repositories.

#### **Maven Build Life Cycle:**

The Maven build process is organised into a set of build lifecycles, each comprising a sequence of phases. Here are the key build lifecycles and their associated phases:

##### **Clean Lifecycle:**

- **clean:** Deletes the target directory, removing all build artifacts.

##### **Default Lifecycle:**

- **validate:** Validates the project's structure.
- **compile:** Compiles the project's source code.
- **test:** Runs tests using a suitable testing framework.
- **package:** Packages the compiled code into a distributable format (e.g., JAR, WAR).
- **verify:** Runs checks on the package to verify its correctness.
- **install:** Installs the package to the local repository.
- **deploy:** Copies the final package to a remote repository for sharing.

### Site Lifecycle:

- site: Generates project documentation.

Each phase within a lifecycle is executed in sequence, and the build progresses from one phase to the next. Developers can customise build behaviour by configuring plugins and goals in the POM file.

### Materials:

- A computer with Maven installed (<https://maven.apache.org/download.cgi>)
- A code editor (e.g., Visual Studio Code, IntelliJ IDEA)
- Java Development Kit (JDK) installed (<https://www.oracle.com/java/technologies/javase-downloads.html>)

### Experiment Steps:

#### Step 1: Setup Maven and Java

- Ensure that you have Maven and JDK installed on your system. You can verify their installations by running the following commands:

**mvn -v**

**java -version**

```
C:\Users\PALLAVI J S>cd C:\Users\PALLAVI J S\Desktop\devassignment

C:\Users\PALLAVI J S\Desktop\devassignment>mvn -v
Apache Maven 3.9.9 (8e8579a9e76f7d015ee5ec7bfc97d260186937)
Maven home: C:\Maven\apache-maven-3.9.9
Java version: 23, vendor: Oracle Corporation, runtime: C:\Program Files\Java\jdk-2
Default locale: en_IN, platform encoding: UTF-8
OS name: "windows 11", version: "10.0", arch: "amd64", family: "windows"

C:\Users\PALLAVI J S\Desktop\devassignment>java -version
java version "23" 2024-09-17
Java(TM) SE Runtime Environment (build 23+37-2369)
Java HotSpot(TM) 64-Bit Server VM (build 23+37-2369, mixed mode, sharing)
```

#### Step 2: Create a Maven Java Project

- Create a new directory for your project, e.g., MavenDemo.
- Inside the project directory, create a simple Java class, e.g., HelloWorld.java, with a main method that prints "Hello, Maven!".

```
public class HelloWorld {
    public static void main(String[] args) {
        System.out.println("Hello, Maven!");
    }
}
```

```
C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>mkdir src\main\java
C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>cd src\main\java
```



Create a pom.xml file (Maven Project Object Model) in the project directory. This file defines project metadata, dependencies, and build configurations. Here's a minimal example:

```
<project                xmlns="http://maven.apache.org/POM/4.0.0"
                        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
                        xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>com.example</groupId>
  <artifactId>MavenDemo</artifactId>
  <version>1.0-SNAPSHOT</version>
</project>
```

### Step 3: Explore the Maven Build Phases

- Maven has several build phases, and each phase is responsible for specific tasks. In this step, we'll explore some of the most commonly used build phases.
- Clean Phase: To clean the project (remove generated files), run:

**mvn clean**

```
C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\main\java>cd ../../..
C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>mvn clean
[INFO] Scanning for projects...
[INFO]
[INFO] -----< com.example:MavenDemo >-----
[INFO] Building MavenDemo 1.0-SNAPSHOT
[INFO]    from pom.xml
[INFO] -----[ jar ]-----
[INFO]
[INFO] --- clean:3.2.0:clean (default-clean) @ MavenDemo ---
[INFO]
[INFO] BUILD SUCCESS
[INFO]
[INFO] Total time:  0.851 s
[INFO] Finished at: 2025-06-08T12:12:16+05:30
[INFO]
```

- Compile Phase: To compile the Java source code, run:

**mvn compile**

```
C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>mvn compile
[INFO] Scanning for projects...
[INFO]
[INFO] -----< com.example:MavenDemo >-----
[INFO] Building MavenDemo 1.0-SNAPSHOT
[INFO]    from pom.xml
[INFO] -----[ jar ]-----
[INFO]
[INFO] --- resources:3.3.1:resources (default-resources) @ MavenDemo ---
[WARNING] Using platform encoding (UTF-8 actually) to copy filtered resources, i.e. build is platform dependent!
[INFO] skip non existing resourceDirectory C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\main\resources
[INFO]
[INFO] --- compiler:3.13.0:compile (default-compile) @ MavenDemo ---
[INFO] Recompiling the module because of changed source code.
[WARNING] File encoding has not been set, using platform encoding UTF-8, i.e. build is platform dependent!
[INFO] Compiling 1 source file with javac [debug target 1.8] to target\classes
[WARNING] bootstrap class path is not set in conjunction with -source 8
  not setting the bootstrap class path may lead to class files that cannot run on JDK 8
  --release 8 is recommended instead of -source 8 -target 1.8 because it sets the bootstrap class path automatically
[WARNING] source value 8 is obsolete and will be removed in a future release
[WARNING] target value 8 is obsolete and will be removed in a future release
[WARNING] To suppress warnings about obsolete options, use -Xlint:-options.
[INFO]
[INFO] BUILD SUCCESS
[INFO]
[INFO] Total time:  2.530 s
[INFO] Finished at: 2025-06-08T12:12:35+05:30
[INFO]
```

- Test Phase: To execute unit tests, run:

### ***mvn test***

```
C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>mvn test
[INFO] Scanning for projects...
[INFO]
[INFO] -----< com.example:MavenDemo >-----
[INFO] Building MavenDemo 1.0-SNAPSHOT
[INFO] from pom.xml
[INFO] -----[ jar ]-----
[INFO]
[INFO] --- resources:3.3.1:resources (default-resources) @ MavenDemo ---
[WARNING] Using platform encoding (UTF-8 actually) to copy filtered resources, i.e. build is platform dependent!
[INFO] skip non existing resourceDirectory C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\main\resources
[INFO]
[INFO] --- compiler:3.13.0:compile (default-compile) @ MavenDemo ---
[INFO] Nothing to compile - all classes are up to date.
[INFO]
[INFO] --- resources:3.3.1:testResources (default-testResources) @ MavenDemo ---
[WARNING] Using platform encoding (UTF-8 actually) to copy filtered resources, i.e. build is platform dependent!
[INFO] skip non existing resourceDirectory C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\test\resources
[INFO]
[INFO] --- compiler:3.13.0:testCompile (default-testCompile) @ MavenDemo ---
[INFO] No sources to compile
[INFO]
[INFO] --- surefire:3.2.5:test (default-test) @ MavenDemo ---
[INFO] No tests to run.
[INFO]
[INFO] BUILD SUCCESS
[INFO]
[INFO] Total time: 1.820 s
[INFO] Finished at: 2025-06-08T12:12:56+05:30
[INFO]
[INFO] -----
```

- Package Phase: To package the application into a JAR file, run:

### ***mvn package***

```
C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>mvn package
[INFO] Scanning for projects...
[INFO]
[INFO] -----< com.example:MavenDemo >-----
[INFO] Building MavenDemo 1.0-SNAPSHOT
[INFO] from pom.xml
[INFO] -----[ jar ]-----
[INFO]
[INFO] --- resources:3.3.1:resources (default-resources) @ MavenDemo ---
[WARNING] Using platform encoding (UTF-8 actually) to copy filtered resources, i.e. build is platform dependent!
[INFO] skip non existing resourceDirectory C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\main\resources
[INFO]
[INFO] --- compiler:3.13.0:compile (default-compile) @ MavenDemo ---
[INFO] Nothing to compile - all classes are up to date.
[INFO]
[INFO] --- resources:3.3.1:testResources (default-testResources) @ MavenDemo ---
[WARNING] Using platform encoding (UTF-8 actually) to copy filtered resources, i.e. build is platform dependent!
[INFO] skip non existing resourceDirectory C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\test\resources
[INFO]
[INFO] --- compiler:3.13.0:testCompile (default-testCompile) @ MavenDemo ---
[INFO] No sources to compile
[INFO]
[INFO] --- surefire:3.2.5:test (default-test) @ MavenDemo ---
[INFO] No tests to run.
[INFO]
[INFO] --- jar:3.4.1:jar (default-jar) @ MavenDemo ---
[INFO] Building jar: C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\target\MavenDemo-1.0-SNAPSHOT.jar
[INFO]
[INFO] BUILD SUCCESS
[INFO]
[INFO] Total time: 3.056 s
[INFO] Finished at: 2025-06-08T12:13:11+05:30
[INFO]
[INFO] -----
```

### ***mvn install***

- Deploy Phase: To deploy artifacts to a remote Maven repository, configure your pom.xml and run:

### ***mvn deploy***

```

C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>mvn deploy
[INFO] Scanning for projects...
[INFO]
[INFO] -----< com.example:MavenDemo >-----
[INFO] Building MavenDemo 1.0-SNAPSHOT
[INFO] from pom.xml
[INFO] -----[ jar ]-----
[INFO]
[INFO] --- resources:3.3.1:resources (default-resources) @ MavenDemo ---
[WARNING] Using platform encoding (UTF-8 actually) to copy filtered resources, i.e. build is platform dependent!
[INFO] skip non existing resourceDirectory C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\main\resources
[INFO]
[INFO] --- compiler:3.13.0:compile (default-compile) @ MavenDemo ---
[INFO] Nothing to compile - all classes are up to date.
[INFO]
[INFO] --- resources:3.3.1:testResources (default-testResources) @ MavenDemo ---
[WARNING] Using platform encoding (UTF-8 actually) to copy filtered resources, i.e. build is platform dependent!
[INFO] skip non existing resourceDirectory C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\src\test\resources
[INFO]
[INFO] --- compiler:3.13.0:testCompile (default-testCompile) @ MavenDemo ---
[INFO] No sources to compile
[INFO]
[INFO] --- surefire:3.2.5:test (default-test) @ MavenDemo ---
[INFO] No tests to run.
[INFO]
[INFO] --- jar:3.4.1:jar (default-jar) @ MavenDemo ---
[INFO]
[INFO] --- install:3.1.2:install (default-install) @ MavenDemo ---
[INFO] Installing C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\pom.xml to C:\Users\PALLAVI J S\.m2\repository\com\example\MavenDemo\1.0-SNAPSHOT\Mav
enDemo-1.0-SNAPSHOT.pom
[INFO] Installing C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo\target\MavenDemo-1.0-SNAPSHOT.jar to C:\Users\PALLAVI J S\.m2\repository\com\example\
MavenDemo\1.0-SNAPSHOT\MavenDemo-1.0-SNAPSHOT.jar
[INFO]
[INFO] --- deploy:3.1.2:deploy (default-deploy) @ MavenDemo ---

```

#### Step 4: Run the Application

- After running the mvn package command, you can find the generated JAR file (e.g., MavenDemo-1.0-SNAPSHOT.jar) in the target directory. Run the application using:

***java -cp target/MavenDemo-1.0-SNAPSHOT.jar HelloWorld***

```

C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>java -cp target/MavenDemo-1.0-SNAPSHOT.jar HelloWorld
Hello, Maven!

C:\Users\PALLAVI J S\Desktop\devassignment\MavenDemo>

```

#### Conclusion:

This experiment demonstrates the Maven build lifecycle by creating a simple Java project and executing various Maven build phases. Maven simplifies the build process by providing a standardized way to manage dependencies, compile code, run tests, and package applications. Understanding these build phases is essential for Java developers using Maven in their projects.

## **Experiment No. 9**

### **Title: Demonstrating Container Orchestration using Kubernetes**

#### **Objective:**

The objective of this experiment is to introduce students to container orchestration using Kubernetes and demonstrate how to deploy a containerized web application. By the end of this experiment, students will have a basic understanding of Kubernetes concepts and how to use Kubernetes to manage containers.

#### **Introduction:**

Container orchestration is a critical component in modern application deployment, allowing you to manage, scale, and maintain containerized applications efficiently. Kubernetes is a popular container orchestration platform that automates many tasks associated with deploying, scaling, and managing containerized applications. This experiment will demonstrate basic container orchestration using Kubernetes by deploying a simple web application.

Kubernetes, often abbreviated as K8s, is an open-source container orchestration platform designed to automate the deployment, scaling, and management of containerized applications. Developed by Google and later donated to the Cloud Native Computing Foundation (CNCF), Kubernetes has become the de facto standard for container orchestration in modern cloud-native application development.

#### **Key Concepts in Kubernetes:**

- **Containerization:** Kubernetes relies on containers as the fundamental unit for packaging and running applications. Containers encapsulate an application and its dependencies, ensuring consistency across various environments.
- **Cluster:** A Kubernetes cluster is a set of machines, known as nodes, that collectively run containerized applications. A cluster typically consists of a master node (for control and management) and multiple worker nodes (for running containers).
- **Nodes:** Nodes are individual machines (virtual or physical) that form part of a Kubernetes cluster. Nodes run containerized workloads and communicate with the master node to manage and orchestrate containers.
- **Pod:** A pod is the smallest deployable unit in Kubernetes. It can contain one or more tightly coupled containers that share the same network and storage namespace. Containers within a pod are typically used to run closely related processes.
- **Deployment:** A Deployment is a Kubernetes resource that defines how to create, update, and scale instances of an application. It ensures that a specified number of replicas are running at all times.
- **Service:** A Service is an abstraction that exposes a set of pods as a network service. It provides a stable IP address and DNS name for accessing the pods, enabling load balancing and discovery.
- **Namespace:** Kubernetes supports multiple virtual clusters within the same physical cluster, called namespaces.

## Key Features of Kubernetes:

- **Automated Scaling:** Kubernetes can automatically scale the number of replicas of an application based on resource usage or defined metrics. This ensures applications can handle varying workloads efficiently.
- **Load Balancing:** Services in Kubernetes can distribute traffic among pods, providing high availability and distributing workloads evenly.
- **Self-healing:** Kubernetes monitors the health of pods and can automatically restart or replace failed instances to maintain desired application availability.
- **Rolling Updates and Rollbacks:** Kubernetes allows for controlled, rolling updates of applications, ensuring zero-downtime deployments. If issues arise, rollbacks can be performed with ease.
- **Storage Orchestration:** Kubernetes provides mechanisms for attaching storage volumes to containers, enabling data persistence and sharing.
- **Configuration Management:** Kubernetes supports configuration management through ConfigMaps and Secrets, making it easy to manage application configurations.
- **Extensibility:** Kubernetes is highly extensible, with a vast ecosystem of plugins and extensions, including Helm charts for packaging applications and custom resources for defining custom objects.

Kubernetes has become a cornerstone of cloud-native application development, enabling organisations to build, deploy, and scale containerized applications effectively. Its ability to abstract away infrastructure complexities, ensure application reliability, and provide consistent scaling makes it a powerful tool for modern software development and operations.

## Materials:

- A computer with Kubernetes installed (<https://kubernetes.io/docs/setup/>)
- Docker installed (<https://docs.docker.com/get-docker/>)

## Experiment Steps:

### Step 1: Create a Dockerized Web Application

- Create a simple web application (e.g., a static HTML page) or use an existing one.
- Create a Dockerfile to package the web application into a Docker container. Here's an example Dockerfile for a simple web server:

```
# Use an official Nginx base image FROM  
nginx:latest
```

```
# Copy the web application files to the Nginx document root COPY  
./webapp /usr/share/nginx/html
```

- Build the Docker image:

```
docker build -t my-web-app .
```

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker build -t my-web-app .
[+] Building 4.5s (8/8) FINISHED
=> [internal] load build definition from Dockerfile
=> => transferring dockerfile: 220B
=> [internal] load metadata for docker.io/library/httpd:2.4
=> [auth] library/httpd:pull token for registry-1.docker.io
=> [internal] load .dockerignore
=> => transferring context: 2B
=> [internal] load build context
=> => transferring context: 32B
=> [1/2] FROM docker.io/library/httpd:2.4@sha256:09cb4b94edaaa796522c545328b62e9a0db60315c7be9f2b4e02204919926405
=> => resolve docker.io/library/httpd:2.4@sha256:09cb4b94edaaa796522c545328b62e9a0db60315c7be9f2b4e02204919926405
=> CACHED [2/2] COPY index.html /usr/local/apache2/htdocs/
=> exporting to image
=> => exporting layers
=> => exporting manifest sha256:4518ec9b67851941fe7e926b218b7cd1de272fa85f77d39176b9d37f89b7a285
=> => exporting config sha256:e39a14a38dd813b5f45fa3457ada381456be550e26259583fbcc1b2e784e854c
=> => exporting attestation manifest sha256:1158bb7ba679f98f8e49481fb1fac472523ce2b7a1b9c182f22eb7eb2dde2ea9
=> => exporting manifest list sha256:8dfe2e8f48b1d7729af5175e6eaff3b40dafb700c2a0a908728df7f69bbff946
=> => naming to docker.io/library/my-web-app:latest
=> => unpacking to docker.io/library/my-web-app:latest
```

## Step 2: Deploy the Web Application with Kubernetes

Create a Kubernetes Deployment YAML file (web-app-deployment.yaml) to deploy the web application:

```
apiVersion: apps/v1    kind:
Deployment metadata:
name: my-web-app-deployment
spec:
replicas: 3            # Number of pods to
create selector:
matchLabels:
app: my-web-app        # Label to match pods
template:
metadata:
labels:
app: my-web-app        # Label assigned to pods
spec:
containers:
- name: my-web-app-container
image: my-web-app:latest # Docker image to use
ports:
- containerPort: 80     # Port to expose
```

### Explanation of web-app-deployment.yaml:

- apiVersion: Specifies the Kubernetes API version being used (apps/v1 for Deployments).
  - kind: Defines the type of resource we're creating (a Deployment in this case).
  - metadata: Contains metadata for the Deployment, including its name.
  - spec: Defines the desired state of the Deployment.
- replicas: Specifies the desired number of identical pods to run. In this example, we want three replicas of our web application.
- selector: Specifies how to select which pods are part of this Deployment. Pods with the label app: my-web-app will be managed by this Deployment.
  - template: Defines the pod template for the Deployment.
  - metadata: Contains metadata for the pods created by this template.
- labels: Assigns the label app: my-web-app to the pods created by this template.

- spec: Specifies the configuration of the pods.
- containers: Defines the containers to run within the pods. In this case, we have one container named my-web-app-container using the my-web-app:latest Docker image.
- ports: Specifies the ports to expose within the container. Here, we're exposing port 80.

### Step 3: Deploy the Application

- Apply the deployment configuration to your Kubernetes cluster:

```
C:\Users\PALLAVI J S\Desktop\devassignment>kubectl apply -f web-app-deployment.yaml
deployment.apps/my-web-app-deployment configured
```

```
C:\Users\PALLAVI J S\Desktop\devassignment>kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
my-web-app-deployment-5dbc6cbb47-5zbql	0/1	ImagePullBackOff	1 (8m50s ago)	11d
my-web-app-deployment-5dbc6cbb47-kqsf9	0/1	ImagePullBackOff	1 (8m50s ago)	11d
my-web-app-deployment-5dbc6cbb47-nxnp7	0/1	ImagePullBackOff	1 (8m50s ago)	11d
my-web-app-deployment-6bb5cb9b74-ch69f	0/1	ImagePullBackOff	0	104s

***kubectl apply -f web-app-deployment.yaml***

### Step 4: Verify the Deployment

- Check the status of your pods:

***kubectl get pods***

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker container stop registry
registry
```

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker container rm registry
registry
```

```
C:\Users\PALLAVI J S\Desktop\devassignment>docker run -d -p 5000:5000 --name registry registry:2
6073dd93daf55c509bfea37c2fd93ca9ec956e82c5de46ed043d7fa5b4d88038
```

```
C:\Users\PALLAVI J S\Desktop\devassignment>kubectl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
my-web-app-deployment-5dbc6cbb47-5zbql	1/1	Running	2 (13m ago)	11d
my-web-app-deployment-68857b79bd-bct5l	1/1	Running	0	6s
my-web-app-deployment-68857b79bd-blm27	1/1	Running	0	11s
my-web-app-deployment-68857b79bd-gb7q5	0/1	ContainerCreating	0	2s

```
C:\Users\PALLAVI J S\Desktop\devassignment>
```

### Conclusion:

In this experiment, you learned how to create a Kubernetes Deployment for container orchestration. The web-app-deployment.yaml file defines the desired state of the application, including the number of replicas, labels, and the Docker image to use. Kubernetes automates the deployment and scaling of the application, making it a powerful tool for managing containerized workloads.

## CERTIFICATES



### COURSE COMPLETION CERTIFICATE


The certificate is awarded to

**Pallavi J.S**

for successfully completing the course

**Git & GitHub: Working with Git Repositories**

on March 25, 2025



Issued on: Wednesday, March 26, 2025  
To verify, scan the QR code at <https://verify.amwingsan.com>

**Infosys | Springboard**

*Congratulations! You make us proud!*

Thirumala Arohi  
Executive Vice President and Global Head  
Education, Training & Assessment (ETA)  
Infosys Limited



### COURSE COMPLETION CERTIFICATE


The certificate is awarded to

**Pallavi J.S**

for successfully completing the course

**Jenkins for DevOps: The Basics of Jenkins**

on May 18, 2025



Issued on: Monday, May 19, 2025  
To verify, scan the QR code at <https://verify.amwingsan.com>

**Infosys | Springboard**

*Congratulations! You make us proud!*

Thirumala Arohi  
Executive Vice President and Global Head  
Education, Training & Assessment (ETA)  
Infosys Limited



||||| COURSE COMPLETION CERTIFICATE |||||


The certificate is awarded to

**Pallavi J.S**

for successfully completing the course

**Jenkins for DevOps: Practical Uses of Jenkins**

on May 13, 2025



Issued on: Wednesday, May 14, 2025  
To verify, scan the QR code at <https://verify.amiwingyan.com>

Infosys | Springboard

*Congratulations! You make us proud!*

Thirumala Arohi  
Executive Vice President and Global Head  
Education, Training & Assessment (ETA)  
Infosys Limited

||||| COURSE COMPLETION CERTIFICATE |||||


The certificate is awarded to

**Pallavi J.S**

for successfully completing the course

**Git & GitHub: Working with Git Repositories**

on March 25, 2025



Issued on: Wednesday, March 26, 2025  
To verify, scan the QR code at <https://verify.amiwingyan.com>

Infosys | Springboard

*Congratulations! You make us proud!*

Thirumala Arohi  
Executive Vice President and Global Head  
Education, Training & Assessment (ETA)  
Infosys Limited



## COURSE COMPLETION CERTIFICATE


The certificate is awarded to

**Pallavi J.S**

for successfully completing the course

**Learning Git**

on March 24, 2025



Issued on: Tuesday, March 25, 2025  
To verify, scan the QR code at <https://verify.qmwingoan.com>

**Infosys | Springboard**

*Congratulations! You make us proud!*

Thirumala Arohi  
Executive Vice President and Global Head  
Education, Training & Assessment (ETA)  
Infosys Limited



## COURSE COMPLETION CERTIFICATE


The certificate is awarded to

**Pallavi J.S**

for successfully completing the course

**Jenkins for DevOps: Jenkins Configuration for DevOps**

on May 13, 2025



Issued on: Wednesday, May 14, 2025  
To verify, scan the QR code at <https://verify.qmwingoan.com>

**Infosys | Springboard**

*Congratulations! You make us proud!*

Thirumala Arohi  
Executive Vice President and Global Head  
Education, Training & Assessment (ETA)  
Infosys Limited



## ||||| COURSE COMPLETION CERTIFICATE |||||


The certificate is awarded to

**Pallavi J.S**

for successfully completing the course

**DevOps with Docker: Implementing DevOps Using Docker**

on May 13, 2025



Issued on: Wednesday, May 14, 2025  
To verify, scan the QR code at <https://verify.amiwinquan.com>



*Congratulations! You make us proud!*

Thirumala Arohi  
Executive Vice President and Global Head  
Education, Training & Assessment (ETA)  
Infosys Limited