

# Understand the problem

WINNING A KAGGLE COMPETITION IN PYTHON




**Yauhen Babakhin**  
Kaggle Grandmaster

# Solution workflow

Understand the  
Problem

# Solution workflow


EDA



# Solution workflow



# Solution workflow



# Understand the problem

- **Data type:** tabular data, time series, images, text, etc.

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0

# Understand the problem

- **Data type:** tabular data, time series, images, text, etc.


	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0



# Understand the problem

- **Data type:** tabular data, time series, images, text, etc.

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...)	female	38.0	1	0
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0






# Understand the problem

- **Data type:** tabular data, time series, images, text, etc.

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0
1	2	1	1	Cummings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0



- **Problem type:** classification, regression, ranking, etc.
- **Evaluation metric:** ROC AUC, F1-Score, MAE, MSE, etc.

# Metric definition

```
# Some classification and regression metrics
```

```
from sklearn.metrics import roc_auc_score, f1_score, mean_squared_error
```

$$RMSLE = \sqrt{\frac{1}{N} \sum_{i=1}^N (\log(y_i + 1) - \log(\hat{y}_i + 1))^2}$$

```
import numpy as np
```

```
def rmsle(y_true, y_pred):
```

```
    diffs = np.log(y_true + 1) - np.log(y_pred + 1)
```

```
    squares = np.power(diffs, 2)
```

```
    err = np.sqrt(np.mean(squares))
```

```
    return err
```

sklearn

n test set

가

, y

, y hat

RMSE

RMSE : MSE

MSE

RMSE

# Let's practice!

WINNING A KAGGLE COMPETITION IN PYTHON

# Initial EDA

WINNING A KAGGLE COMPETITION IN PYTHON



**Yauhen Babakhin**  
Kaggle Grandmaster

# Goals of EDA

- Size of the data
- Properties of the target variable
- Properties of the features
- Generate ideas for feature engineering

EDA

.

가 ㄹ

# Two sigma connect: rental listing inquiries

## Problem statement

Predict the popularity of an apartment rental listing

target

3

## Target variable

interest\_level

## Problem type

Classification with 3 classes: 'high', 'medium' and 'low'

## Metric

Multi-class logarithmic loss

# EDA. Part I

```
# Size of the data
twosigma_train = pd.read_csv('twosigma_train.csv')
print('Train shape:', twosigma_train.shape)

twosigma_test = pd.read_csv('twosigma_test.csv')
print('Test shape:', twosigma_test.shape)
```

```
Train shape: (49352, 11)
Test shape: (74659, 10)
```

# EDA. Part I

```
print(twosigma_train.columns.tolist())
```

tolist 가 column ,  
value\_counts 가 .

```
['id', 'bathrooms', 'bedrooms', 'building_id', 'latitude', 'longitude',  
'manager_id', 'price', 'interest_level']
```

```
twosigma_train.interest_level.value_counts()
```

low	34284
medium	11229
high	3839



# EDA. Part I

```
# Describe the train data  
twosigma_train.describe()
```

	bathrooms	bedrooms	latitude	longitude	price
count	49352.000000	49352.000000	49352.000000	49352.000000	4.935200e+04
mean	1.21218	1.541640	40.741545	-73.955716	3.830174e+03
std	0.50142	1.115018	0.638535	1.177912	2.206687e+04
min	0.000000	0.000000	0.000000	-118.271000	4.300000e+01
25%	1.000000	1.000000	40.728300	-73.991700	2.500000e+03
50%	1.000000	1.000000	40.751800	-73.977900	3.150000e+03
75%	1.000000	2.000000	40.774300	-73.954800	4.100000e+03
max	10.000000	8.000000	44.883500	0.000000	4.490000e+06

# EDA. Part II

```
import matplotlib.pyplot as plt
plt.style.use('ggplot')
```

```
# Find the median price by the interest level
prices = twosigma_train.groupby('interest_level', as_index=False)['price'].median()
```

(as\_index=False interest\_level 가 groupby .)

# EDA. Part II

```
# Draw a barplot
fig = plt.figure(figsize=(7, 5))
plt.bar(prices.interest_level, prices.price, width=0.5, alpha=0.8)
# Set titles
plt.xlabel('Interest level')
plt.ylabel('Median price')
plt.title('Median listing price across interest level')
# Show the plot
plt.show()
```

bar

.



가

# Let's practice!

WINNING A KAGGLE COMPETITION IN PYTHON


# Local validation

WINNING A KAGGLE COMPETITION IN PYTHON




**Yauhen Babakhin**  
Kaggle Grandmaster

# Motivation




# Holdout set




가  
holdout      train set      holdout set .



# Holdout set




# Holdout set




public

# K-fold cross-validation



# K-fold cross-validation



# K-fold cross-validation

```
# Import KFold
from sklearn.model_selection import KFold
```


```
# Create a KFold object
kf = KFold(n_splits=5, shuffle=True, random_state=123)
```

KFold shuffle  
True .

```
# Loop through each cross-validation split
for train_index, test_index in kf.split(train):
    # Get training and testing data for the corresponding split
    cv_train, cv_test = train.iloc[train_index], train.iloc[test_index]
```

random\_state seed for  
train, test  
set .

# Stratified K-fold



Stratify KFold k fold

class

fold가 가

# Stratified K-fold

```
# Import StratifiedKFold
from sklearn.model_selection import StratifiedKFold

# Create a StratifiedKFold object
str_kf = StratifiedKFold(n_splits=5, shuffle=True, random_state=123)

# Loop through each cross-validation split
for train_index, test_index in str_kf.split(train, train['target']):
    cv_train, cv_test = train.iloc[train_index], train.iloc[test_index]
```

K - fold   sklearn   model\_selection

. K - fold

.

# Let's practice!

WINNING A KAGGLE COMPETITION IN PYTHON



# Validation usage

WINNING A KAGGLE COMPETITION IN PYTHON



**Yauhen Babakhin**  
Kaggle Grandmaster

# Data leakage



ComputerHope.com

- Leak in **features** – using data that will not be available in the real setting
- Leak in **validation strategy** – validation strategy differs from the real-world situation

data leakage


가

,


가

# Time data

가



# Time K-fold cross-validation



# Time K-fold cross-validation

```
# Import TimeSeriesSplit
from sklearn.model_selection import TimeSeriesSplit

# Create a TimeSeriesSplit object
time_kfold = TimeSeriesSplit(n_splits=5)

# Sort train by date
train = train.sort_values('date')

# Loop through each cross-validation split
for train_index, test_index in time_kfold.split(train):
    cv_train, cv_test = train.iloc[train_index], train.iloc[test_index]
```

# Validation pipeline

```
# List for the results
fold_metrics = []
for train_index, test_index in CV_STRATEGY.split(train):
    cv_train, cv_test = train.iloc[train_index], train.iloc[test_index]
    # Train a model
    model.fit(cv_train)
    # Make predictions
    predictions = model.predict(cv_test)
    # Calculate the metric
    metric = evaluate(cv_test, predictions)
    fold_metrics.append(metric)
```

# Model comparison

Fold number	Model A MSE	Model B MSE
Fold 1	2.95	2.97
Fold 2	2.84	2.45
Fold 3	2.62	2.73
Fold 4	2.79	2.83

k      A      B      4      fold가      MSE가      .  
k - fold  
(?)

# Overall validation score

```
import numpy as np

# Simple mean over the folds
mean_score = np.mean(fold_metrics)

# Overall validation score
overall_score_minimizing = np.mean(fold_metrics) + np.std(fold_metrics)
# Or
overall_score_maximizing = np.mean(fold_metrics) - np.std(fold_metrics)
```



# Model comparison

Fold number	Model A MSE	Model B MSE
Fold 1	2.95	2.97
Fold 2	2.84	2.45
Fold 3	2.62	2.73
Fold 4	2.79	2.83
Mean	2.80	2.75
Overall	2.919	2.935

# fold

model B

가

A가



# Let's practice!

WINNING A KAGGLE COMPETITION IN PYTHON