

VPC Peering Communication

VPC Peering is a service that enables communication between two VPCs, either within the same region or across different regions. Here's how to set it up:

1. **Create and Configure VPCs:**
 - First, create the required VPCs. Ensure you configure route tables and internet gateways properly for each VPC.
 - When creating instances, make sure to select the VPC you created earlier.
2. **Test Communication:**
 - Launch instances in each VPC and try to ping the instances using their IP addresses.
 - Initially, there will be no communication because the VPCs are not yet connected.
3. **Set Up VPC Peering:**
 - Go to the VPC Peering section in your AWS console.
 - Create a VPC peering connection by selecting the VPC ID, account, and region of the VPCs you want to connect.
 - Send the peering request to the other VPC.
4. **Accept the Peering Request:**
 - The other party must accept the VPC peering request. Once accepted, the connection will be established.
5. **Update Route Tables:**
 - Even though the peering connection is established, traffic won't flow until you update the route tables.
 - Add routes in the route table section by specifying the destination CIDR block and selecting the peering connection as the target.
6. **Verify Communication:**
 - Once the route tables are updated, test the communication again by pinging the instances. This time, the communication should be successful.

For Cross-Region VPC Peering:

- The process is similar, but you must ensure you configure the route tables correctly for inter-region communication.

Key Interview Question:

- **How do you communicate between two servers using VPC peering?**
 - Explain the above steps, emphasizing the importance of configuring VPC peering, accepting requests, and updating route tables to enable communication between servers in different VPCs.