

1.create a pod for nginx with the pv and pvc:

```
apiVersion: v1
kind: Pod
metadata:
  name: myapp1
  labels:
    name: myapp1
spec:
  containers:
  - name: myapp
    image: nginx
    volumeMounts:
      - mountPath: "/home"
        name: my-storage
  volumes:
  - name: my-storage
    persistentVolumeClaim:
      claimName: mypvc
```

Pvc:

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: mypvc
spec:
  resources:
    requests:
      storage: 500Mi
  accessModes:
    - ReadWriteOnce
```

Pv:

```
root@kubemaster-vm:/home/kubemaster/jithu# cat pv.yaml
apiVersion: v1
kind: PersistentVolume
metadata:
  name: mypv
spec:
  capacity:
    storage: 1Gi
  accessModes:
    - ReadWriteOnce
  hostPath:
    path: "/mnt"
```

2.connection between them:

```
volumes:
  my-storage:
    Type:      PersistentVolumeClaim (a reference to a PersistentVolumeClaim in the same namespace)
    ClaimName: mypvc
    ReadOnly:  false
  kube-api-access-vswkj:
```

Connection blw pv and pvc:

```
root@kubemaster-vm:/home/kubemaster/jithu# kubectl get pv
NAME      CAPACITY  ACCESS MODES  RECLAIM POLICY  STATUS  CLAIM          STORAGECLASS  REASON  AGE
mypv      1Gi       RWO           Retain          Bound   default/mypvc               30m
```

```
root@kubemaster-vm:/home/kubemaster/jithu# kubectl get pvc
NAME      STATUS  VOLUME  CAPACITY  ACCESS MODES  STORAGECLASS  AGE
mypvc     Bound   mypv    1Gi       RWO           default/mypvc  30m
```

```
root@kubemaster-vm:/home/kubemaster/jithu# kubectl get pv,pvc,pod
NAME      CAPACITY  ACCESS MODES  RECLAIM POLICY  STATUS  CLAIM          STORAGECLASS  REASON  AGE
persistentvolume/mypv  1Gi       RWO           Retain          Bound   default/mypvc  17s

NAME      STATUS  VOLUME  CAPACITY  ACCESS MODES  STORAGECLASS  AGE
persistentvolumeclaim/mypvc  Bound   mypv    1Gi       RWO           default/mypvc  14s

NAME      READY  STATUS  RESTARTS  AGE
pod/myapp1  1/1    Running  0         9s
root@kubemaster-vm:/home/kubemaster/jithu#
```

3.And tried to create a file in the path of the persistent volume mounted location and then it appears in the pod container that path stating that those two are connected:

Inside the container:

```
root@myapp1:/home# ls
data  file.txt
```

In pv location path:

```
root@kubemaster-vm:/mnt# ls
file.txt
```

Check the locations in the configuration of pv and pod

As I ran the nginx the index.html is inside the pod

```
root@kubemaster-vm:/home/kubemaster/github# kubectl exec -it myapp1 -- /bin/bash
root@myapp1:/# cd /home
root@myapp1:/home# ls
data file.txt
root@myapp1:/home# cd ..
root@myapp1:/# ls
bin boot dev docker-entrypoint.d docker-entrypoint.sh etc home lib lib64 media mnt opt proc root run sbin srv sys tmp usr var
root@myapp1:/# cd /mnt
root@myapp1:/mnt# ls
root@myapp1:/mnt# cd ..
root@myapp1:/# cd /usr/share/nginx/html/
root@myapp1:/usr/share/nginx/html# ls
50x.html index.html
root@myapp1:/usr/share/nginx/html#
```

```
root@myapp1:/usr/share/nginx/html# cat index.html
<!DOCTYPE html>
<html>
<head>
<title>Welcome to nginx!</title>
<style>
html { color-scheme: light dark; }
body { width: 35em; margin: 0 auto;
font-family: Tahoma, Verdana, Arial, sans-serif; }
</style>
</head>
<body>
<h1>Welcome to nginx!</h1>
<p>If you see this page, the nginx web server is successfully installed and
working. Further configuration is required.</p>

<p>For online documentation and support please refer to
<a href="http://nginx.org/">nginx.org</a>.<br/>
Commercial support is available at
<a href="http://nginx.com/">nginx.com</a>.</p>

<p><em>Thank you for using nginx.</em></p>
</body>
</html>
```