

Data Preprocessing Tools

Importing the libraries

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

Importing the dataset

```
In [2]: dataset = pd.read_csv('Data.csv')
x = dataset.iloc[:, :-1].values
y = dataset.iloc[:, -1].values
print(x)
print(y)

[['France' 44.0 72000.0]
 ['Spain' 27.0 48000.0]
 ['Germany' 30.0 54000.0]
 ['Spain' 38.0 61000.0]
 ['Germany' 40.0 nan]
 ['France' 35.0 58000.0]
 ['Spain' nan 52000.0]
 ['France' 48.0 79000.0]
 ['Germany' 50.0 83000.0]
 ['France' 37.0 67000.0]]
['No' 'Yes' 'No' 'No' 'Yes' 'Yes' 'No' 'Yes' 'No' 'Yes']
```

Taking care of missing data

```
In [3]: from sklearn.impute import SimpleImputer
imputer = SimpleImputer(missing_values=np.nan, strategy='mean')
imputer.fit(x[:,1:])
x[:,1:] = imputer.transform(x[:,1:])
print(x)
```

```
[['France' 44.0 72000.0]
 ['Spain' 27.0 48000.0]
 ['Germany' 30.0 54000.0]
 ['Spain' 38.0 61000.0]
 ['Germany' 40.0 63777.77777777778]
 ['France' 35.0 58000.0]
 ['Spain' 38.77777777777778 52000.0]
 ['France' 48.0 79000.0]
 ['Germany' 50.0 83000.0]
 ['France' 37.0 67000.0]]
```

Encoding categorical data

Encoding the Independent Variable

```
In [4]: from sklearn.compose import ColumnTransformer
from sklearn.preprocessing import OneHotEncoder
ct = ColumnTransformer(transformers=[('encoder', OneHotEncoder(), [0])], remainder='passthrough')
x = np.array(ct.fit_transform(x))
print(x)
```

```
[[1.0 0.0 0.0 44.0 72000.0]
 [0.0 0.0 1.0 27.0 48000.0]
 [0.0 1.0 0.0 30.0 54000.0]
 [0.0 0.0 1.0 38.0 61000.0]
 [0.0 1.0 0.0 40.0 63777.77777777778]
 [1.0 0.0 0.0 35.0 58000.0]
 [0.0 0.0 1.0 38.77777777777778 52000.0]
 [1.0 0.0 0.0 48.0 79000.0]
 [0.0 1.0 0.0 50.0 83000.0]
 [1.0 0.0 0.0 37.0 67000.0]]
```

Encoding the Dependent Variable

```
In [5]: from sklearn.preprocessing import LabelEncoder
le = LabelEncoder()
y = le.fit_transform(y)
print(y)
```

```
[0 1 0 0 1 1 0 1 0 1]
```

Splitting the dataset into the Training set and Test set

```
In [6]: from sklearn.model_selection import train_test_split
x_train,x_test,y_train,y_test = train_test_split(x,y,test_size = 0.2,random_state=1)
```

```
In [7]: print(x_train)

[[0.0 0.0 1.0 38.77777777777778 52000.0]
 [0.0 1.0 0.0 40.0 63777.77777777778]
 [1.0 0.0 0.0 44.0 72000.0]
 [0.0 0.0 1.0 38.0 61000.0]
 [0.0 0.0 1.0 27.0 48000.0]
 [1.0 0.0 0.0 48.0 79000.0]
 [0.0 1.0 0.0 50.0 83000.0]
 [1.0 0.0 0.0 35.0 58000.0]]
```

```
In [8]: print(x_test)

[[0.0 1.0 0.0 30.0 54000.0]
 [1.0 0.0 0.0 37.0 67000.0]]
```

```
In [9]: print(y_train)

[0 1 0 0 1 1 0 1]
```

```
In [10]: print(y_test)

[0 1]
```

Feature Scaling

```
In [11]: from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
x_train[:,3:] = sc.fit_transform(x_train[:,3:])
x_test[:,3:] = sc.transform(x_test[:,3:])
```

```
C:\Users\jithe\Anaconda2\lib\site-packages\sklearn\utils\validation.py:
595: DataConversionWarning: Data with input dtype object was converted
to float64 by StandardScaler.
      warnings.warn(msg, DataConversionWarning)
```

```
In [12]: print(x_train)
```

```
[[0.0 0.0 1.0 -0.19159184384578545 -1.0781259408412425]
 [0.0 1.0 0.0 -0.014117293757057777 -0.07013167641635372]
 [1.0 0.0 0.0 0.566708506533324 0.633562432710455]
 [0.0 0.0 1.0 -0.30453019390224867 -0.30786617274297867]
 [0.0 0.0 1.0 -1.9018011447007988 -1.420463615551582]
 [1.0 0.0 0.0 1.1475343068237058 1.232653363453549]
 [0.0 1.0 0.0 1.4379472069688968 1.5749910381638885]
 [1.0 0.0 0.0 -0.7401495441200351 -0.5646194287757332]]
```

```
In [13]: print(x_test)
```

```
[[0.0 1.0 0.0 -1.4661817944830124 -0.9069571034860727]
 [1.0 0.0 0.0 -0.44973664397484414 0.2056403393225306]]
```

```
In [ ]:
```