html

Why html in playwright
Playwright automates web pages, and web pages are made of HTML. Buttons, text boxes, and links are all HTML elements, so we need HTML to tell Playwright which element to find and perform action.

what is html
HTML (HyperText Markup Language) is the standard language used to create the structure of a web page.

core structure

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8">
    <title>My Page</title>
  </head>
  <body>
    <h1>Welcome</h1>
    <p>Hello, this is my page.</p>
  </body>
</html>
```

<!DOCTYPE html>=Tells the browser this is an HTML5 document
<html>=Root element that wraps the whole page
<head>=Holds page information that is not shown on the page (title, meta tags, CSS links)
<title>=Text shown in the browser tab (this is what page.title() returns)
<body>=Holds everything visible on the page (text, buttons, images, links, forms)

Types of tags in HTML

HTML has two types of tags:
1. Paired tags (container tags)
These have an opening tag and a closing tag, and the content goes in between.
eg:
This is a paragraph.
<h1>Heading</h1>
<button>Login</button>

2. Unpaired tag/Self-closing tags (empty tags)
These have no closing tag
eg:

<img src="logo.png">
<input type="text">
<hr>

3 important to Remember

1)Tag name: anything that comes after < until the first space (or until > if there is no space) is called the tag name.
Example: in <input type="text">, the tag name is input.

2)Attribute: any key-value pair separated by = is called AttributeName=AttributeValue.
LHS (left side) is the AttributeName
RHS (right side) is the AttributeValue
Example: in id="username", id is the AttributeName and "username" is the AttributeValue.

3)Text of an element: anything present between > and < is called the text of an element.
Example: in <button>Login</button>, the text is Login.

important tags

<html>, <head>, <body>	Page structure (page root)
<h1> to <h6>	Headings
<p>	Paragraph
<a>	Link
<img>	Image
<button>	Button
<input>	Text box, checkbox, radio button
<form>	Group of inputs (login/signup forms)
<label>	Label for an input
<select> / <option>	Dropdown list
<textarea>	Multi-line text box
<table>, <tr>, <th>, <td>	Table, row, heading cell, data cell
, ,	Lists (unordered, ordered, list item)
,	Containers (most common wrappers)
<iframe>	Page inside a page

project

```
<!DOCTYPE html>
<html>
<head>
    <title>Registration Form</title>
</head>
<body>
    <h2>Registration Form</h2>
    <form>
        <label>Full Name:</label>
        <input type="text" id="fullname" name="fullname">
        <br><br>

        <label>Last Name:</label>
        <input type="text" id="lastname" name="lastname">
        <br><br>

        <label>Email:</label>
        <input type="email" id="email" name="email">
        <br><br>

        <label>Gender:</label>
        <input type="radio" id="male" name="gender" value="Male">
        <label for="male">Male</label>

        <input type="radio" id="female" name="gender" value="Female">
        <label for="female">Female</label>

        <input type="radio" id="other" name="gender" value="Other">
        <label for="other">Other</label>
        <br><br>

        <label>Select Skills:</label>
        <input type="checkbox" id="java" name="skills" value="Java">
        <label for="java">Java</label>

        <input type="checkbox" id="selenium" name="skills" value="Selenium">
        <label for="selenium">Selenium</label>

        <input type="checkbox" id="playwright" name="skills" value="Playwright">
        <label for="playwright">Playwright</label>
        <br><br>

        <label>Select Course:</label>
        <select id="course" name="course">
            <option value="">--Select Course--</option>
            <option value="java">Java</option>
            <option value="selenium">Selenium</option>
            <option value="playwright">Playwright</option>
            <option value="python">Python</option>
        </select>
        <br><br>
        <button type="button" id="register">Register</button>
    </form>
</body>
</html>
```