Variable-k swap_score per subject — stable_k=2 cohort (n=34, has_swap = 9)
FW max-null: T_obs = max_k swap_score(k); has_swap iff T_obs ≥ 0.5 AND p_fw < 0.05 (1000 perm, seed=0)

endpoint cardinality k

2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26

F_norm
(2/3 = null)

0 0.5 1

epi_139
yuq_zhangjiaqi
yuq_wangyiyang
yuq_gaolan
yuq_zhaochenxi
yuq_chenziyang
epi_958
epi_1073
epi_253
epi_1146
yuq_hanyuxuan
epi_635
epi_583
epi_1125
epi_384
epi_620
yuq_huanghanwen
epi_1077
epi_1096
yuq_liyouran
epi_590
epi_548
yuq_zhangbichen
yuq_sunyuanxin
epi_442
epi_922
yuq_litengsheng
yuq_songzishuo
epi_1084
yuq_zhangkexuan
yuq_xuxinyi
yuq_chengshuai
yuq_pengzihang
epi_1150

0.0 0.2 0.4 0.6 0.8 1.0

swap_score(k) · black ring = decision_k (has_swap=True)