From a Spectrogram CNN to Pseudo-Labelled Ensembles: Closing the Focal-to-Soundscape Gap in BirdCLEF+ 2025

Arshiya Jawahar Ali Sirajudeen, Dhanapalan Swaminathan Sudhishna Janavi, Jamie Gonzales Esguerra, Modi Khushi

College of Computing and Data Science, Nanyang Technological University, Singapore
{c230198, sudhishn001, jamie002, khushi008}@e.ntu.edu.sg

Abstract

BirdCLEF+ 2025 asks for the probability of each of 206 species (birds, amphibians, insects and mammals) in every five-second window of one-minute rainforest soundscapes, scored by macro ROC-AUC, with a 90-minute CPU-only inference limit. The labelled training data are clean focal recordings, so the main difficulty is the shift from focal clips to noisy soundscapes. We built the solution in four controlled stages, each changing one thing at a time. (1) An ImageNet EfficientNet-B0 on log-mel spectrograms (public 0.717) was improved by data-driven changes to a baseline v2 (0.763); random crops, soundscape noise with mixup and secondary labels helped, focal loss did not. (2) A sound-event-detection (SED) head drew level with v2 once trained on 5 s instead of 20 s chunks (0.773). (3) Replacing the backbone with bird- or multi-taxa-pretrained models raised the score to 0.848 (frozen Perch 2.0), but all models kept a validation-to-leaderboard gap of 0.14 to 0.20. (4) Label-free adaptation on unlabelled soundscapes split cleanly: statistics alignment (AdaBN, CORAL) lowered the public score in all seven submissions, while pseudo-label methods (cross-family distillation, noisy student) raised it in all four. Our final rank-average ensemble of a noisy-student CNN and a distilled Perch head with temporal smoothing scores **0.88749** on the public leaderboard in 32.3 CPU minutes, which would place **73rd of 2,032 teams (top 3.6%)** on the public leaderboard.

1 Introduction

Passive acoustic monitoring lets ecologists survey biodiversity by leaving recorders in the field, but the audio they produce is far too much to label by hand. The BirdCLEF+ 2025 Kaggle competition (Cañas et al. 2025) asks for a model that outputs, for every 5 s window of a 1-minute soundscape recorded in the Middle Magdalena region of Colombia, a probability for each of 206 species. The metric is macro ROC-AUC over species with at least one positive window, so a rare species counts as much as a common one. Submissions are Kaggle notebooks that must run on CPU only, offline, in at most 90 minutes for about 700 test soundscapes, which limits the size and number of models.

Challenges. Our data analysis (Section 3) found four difficulties: (i) severe class imbalance (2 to 990 clips per species); (ii) weak labels, one label per recording while predictions are per 5 s window; (iii) a domain shift from clean, close-up focal recordings to noisy soundscapes, with no labelled soundscapes for validation; and (iv) incomplete labels for background species.

What we did. We followed one rule throughout: keep the data split, recipe and inference protocol fixed and change one component at a time, so that every score difference can be attributed. Starting from a spectrogram CNN baseline, we (1) tested one targeted fix per difficulty and combined the helpful ones into baseline v2; (2) re-implemented an SED model and isolated the effect of its chunk length; (3) compared three pretraining paradigms, a supervised bird CNN, frozen multi-taxa Perch 2.0 embeddings and a frozen self-supervised Bird-MAE; (4) studied label-free adaptation on the unlabelled soundscapes; and (5) ensembled complementary models within the CPU budget. The novel parts of our solution are: *cross-family distillation*, in which a Perch head learns from a weaker CNN teacher on pseudo-labelled soundscapes and still improves (an idea related to the cross-lineage teachers of Farazi and Reza (2026), which we arrived at independently for BirdCLEF+ 2025); a *noisy-student* CNN trained on pseudo-labels from a CNN+Perch teacher; a controlled finding that *statistics-level alignment hurts while content-level adaptation helps* on this task; and a rank-average ensemble with temporal smoothing that fits easily in the time limit.

Results. The final ensemble (E4) scores 0.88749 on the public leaderboard, which is the score used for comparison and grading. Our submissions are late (the competition closed in June 2025) and therefore unranked; placing 0.88749 in the public leaderboard gives position 73 of 2,032, a relative ranking of 3.6% (top-10% band). Table 1 lists the role and contributions of each of the four members.

2 Related Work

BirdCLEF 2025 solutions. The first-place solution trains an SED model on 20 s chunks and then runs several rounds of noisy-student self-training on the unlabelled soundscapes (Babych 2025). The second-place team combines in-domain transfer learning, semi-supervised distillation, post-processing and ensembling (Sydorskyi and Gonçalves 2025); we use only their released bird-pretrained backbone.

Copyright © 2027, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

Member	Role and contributions
Jamie Gonzales Esguerra	Repository and Kaggle workflow; exploratory data analysis and figures; baseline training and CPU inference; whole-clip spectrogram pipeline; four baseline improvements and ten ablation submissions; baseline v2; report assembly.
Dhanapalan Swaminathan Sudhishna Janavi	SED model re-implemented from a written description; training and CPU inference notebooks; seven SED submissions incl. chunk-length, overlap, checkpoint and spectrogram-resolution ablations.
Arshiya Jawahar Ali Sirajudeen	Pretrained models A1–A3; CPU speed-up of the inference pipeline; adaptation study (AdaBN, CORAL, mean/std); distillation and noisy student; final ensembles E1–E4 and final submission (19 submissions).
Modi Khushi	Helped prepare the presentation slides.

Table 1: Roles and contributions of each group member.

DS@GT distilled spectrograms into tokens; their best model-zoo model scored 0.810 public (Miyaguchi, Gustineli, and Cheung 2025).

Models. We use EfficientNet (Tan and Le 2019, 2021) from timm (Wightman 2019). SED models predict per time step and pool to clip level, so they can be trained from weak labels (Mesaros et al. 2021; Kong et al. 2020). Perch 2.0 is supervised on multi-taxa recordings and gives a 1536-d embedding per 5 s window (van Merriënboer et al. 2025); Bird-MAE is a masked autoencoder for bird audio (Rauch et al. 2025a); BirdSet benchmarks focal-trained models on soundscapes (Rauch et al. 2025b).

Adaptation and pseudo-labels. AdaBN re-estimates batch-norm statistics on target data (Li et al. 2018); CORAL aligns second-order feature statistics (Sun, Feng, and Saenko 2016); Boudiaf et al. (2023) study source-free adaptation under natural shifts in bioacoustics. Distillation trains a student on a teacher's soft outputs (Hinton, Vinyals, and Dean 2015), and Noisy Student trains a student on noised pseudo-labels (Xie et al. 2020). Cross-lineage teachers were later proposed for BirdCLEF+ 2026 (Farazi and Reza 2026).

3 Data and Exploratory Analysis

The labelled set (train_audio) has 28,564 recordings at 32 kHz, mostly from Xeno-canto and iNaturalist, each with one primary and optionally some secondary species. There are 206 classes: 146 birds, 34 amphibians, 17 insects and 9 mammals. The organisers also give 9,726 unlabelled 1-minute soundscapes (train_soundscapes) from the same recorders as the hidden test set. Our analysis gave four findings, each of which motivated one later change.

Class imbalance. The most common species has 990 clips, while 30 species have five or fewer and 55 have twenty or fewer (Figure 1). Because the metric is a macro average, rare classes weigh as much as common ones. *Weak labels.* The median clip lasts 20.5 s and 8.1% are shorter than 5 s, but a




Figure 1: Training clips per species, sorted. The long tail of rare species matters because every species counts equally in macro ROC-AUC.

label covers the whole clip, so a fixed 5 s crop may contain no call at all. *Domain shift.* Training clips are close-up calls; test soundscapes (Figure 2) contain rain, insects, overlapping calls and distant sources. The unlabelled soundscapes come from the test recorders and are therefore valuable for adaptation and pseudo-labelling. *Label noise.* Only 9.3% of clips list secondary species, so audible background species are often unlabelled, and about 8,000 clips have no quality rating.

4 Methodology

Every model outputs 206 sigmoid probabilities per 5 s window. Figure 3 shows the final system; the components are introduced in the order we built them.

Input features and baseline

Audio is converted to 128-band log-mel spectrograms (FFT 2048, hop 512, i.e. 16 ms per frame, 50–14,000 Hz) with librosa (McFee et al. 2015). We use spectrograms because they turn audio into an image, which lets us reuse ImageNet-pretrained CNNs (Deng et al. 2009), an important help when some species have two clips. The lower limit removes wind and handling rumble; the upper limit keeps high-pitched insects below the Nyquist frequency. Each window is converted to decibels relative to its own maximum, clipped to an 80 dB range and scaled to $[0, 1]$, so quiet, distant calls in the soundscapes and loud focal calls share one scale.

The **baseline** classifies the first 5 s of each clip with EfficientNet-B0 (Tan and Le 2019) (ImageNet weights, one input channel, about 4 M parameters) using binary cross-entropy (BCE), because several species can call at once and the metric scores each separately. We chose the smallest EfficientNet so that several models could later fit into the CPU budget. Training uses AdamW (Loshchilov and Hutter 2019) (learning rate 10^{-3}, weight decay 10^{-2}) with a one-cycle schedule (Smith and Topin 2019), batch 64, 15 epochs, on a stratified 80/20 split (seed 42; 22,851/5,713 clips). Validation AUC is computed on the first 5 s of each hold-out clip against its primary label. At test time each soundscape is cut into twelve windows and scored on CPU.

Baseline improvements (baseline v2)

To sample any part of a recording, we cache whole-clip spectrograms (up to 30 s) once as 8-bit integers over a 120 dB




Figure 2: An unlabelled 60 s training soundscape from a field recorder, split into the twelve 5 s windows that must each be scored. Unlike the close-up focal training clips, calls are faint and short against continuous background noise.




Figure 3: Final system. A 5 s window is scored by a log-mel CNN (bird-pretrained EfficientNetV2-S, trained as a noisy student) and by frozen Perch 2.0 followed by a trained MLP head (distilled from the CNN, "A2d"). Window probabilities are smoothed over neighbouring windows and combined by a per-class rank average with weights 0.4/0.6. The greyed Bird-MAE branch was studied but is not in the final ensemble.

range (35.6 M frames, 4.6 GB) and normalise each cut window exactly as at test time (99th-percentile error 0.005 against spectrograms computed from audio). This pipeline alone reproduces the baseline (validation 0.971 vs. 0.973) and halves training time. We then test one change per difficulty:

- **Random crop** (weak labels): a random 5 s window of the whole clip instead of the first 5 s.
- **Soundscape noise + mixup** (domain shift): with probability 0.5 a random window of an unlabelled soundscape is added at -20 to -3 dB; with probability 0.5 two samples are mixed with Beta(0.4, 0.4) weights and the target is the element-wise maximum (Zhang et al. 2018).
- **Secondary labels** (label noise): secondary species get a soft target of 0.5 instead of 0.
- **Focal loss** (imbalance): BCE is replaced by focal loss with $\gamma = 2$ (Lin et al. 2017).

Baseline **v2** combines the changes that raised the public score (crop, noise/mixup, secondary labels) and is the starting point of every later model.

Sound event detection model

The baseline scores each window as a whole and cannot tell *when* in a weakly labelled clip a species calls. An SED model predicts a score for every short time step and pools them into one clip score for training, so it learns call timing from clip labels alone (Mesaros et al. 2021; Kong et al. 2020). We re-implemented the SED approach described in the first-place write-up (Babych 2025), whose head goes back to a 2021 solution (tattaka 2021), from the written descriptions only.

The input is a 20 s chunk (128×1251). We keep the v2 EfficientNet-B0 but remove its pooling and classifier, so the




Figure 4: SED model. Tensor shapes are for one 20 s chunk (channels × frequency × time). The head turns EfficientNet-B0 features into per-step species scores and attention weights; attention- and max-pooled scores form the training loss.

time axis survives ($1280 \times 4 \times 40$; 0.5 s per step), which means any change in score comes from the head and chunk length, not a larger backbone. Generalised-mean pooling (Radenović, Tolias, and Chum 2019) with $p = 3$ collapses frequency: a call fills few bands, so average pooling would dilute it and max pooling would follow noisy peaks. A shared 1×1 convolution (512 channels, ReLU, dropout 0.25) feeds two 1×1 heads, giving a score and an attention weight (softmax over time) for each species and step (Figure 4). The score bias starts at -4 because nearly every species is absent at nearly every step. The loss is $0.5\,\mathrm{BCE}(\text{attention-pooled}) + 0.5\,\mathrm{BCE}(\text{max over time})$; the max term trains the step scores directly, which are what we use at test time. Training applies the full v2 recipe to random 20 s chunks. At inference, 20 s chunks start every 5 s; each window takes its highest step score and averages over the up to four chunks covering it. A second model is trained identically on 5 s chunks to measure what the long context is worth.

Pretrained models

Keeping v2's recipe, split and inference fixed, we change only the pretrained model. **A1 (supervised bird CNN)** fine-tunes the bird-pretrained `tf_efficientnetv2_s_in21k` backbone released by the second-place team (Sydorskyi and Gonçalves 2025) end to end with v2's recipe (774 of 780 weight tensors loaded; the last convolution and batch-norm start random). **A2 (frozen multi-taxa)** freezes Perch 2.0 (van Merriënboer et al. 2025), run on CPU through a community ONNX conversion (Calotriton 2025), embeds up to 30 s of each clip (106,157 windows) and trains an MLP head (512 hidden units, dropout 0.3) with targets 1.0 (primary) and 0.5 (secondary), each window weighted by one over its clip's window count. **A3 (frozen self-supervised)** does the same with Bird-MAE-Base (Rauch et al. 2025a) (ViT-B/16, 768-d mean-pooled tokens) and its own filterbank front end.

Label-free adaptation

No soundscape labels exist, so all adaptation uses unlabelled `train_soundscapes` audio. We compare two families. *Statistics-level* methods change how features are scaled. AdaBN resets and re-estimates all batch-norm statistics on 12,000 soundscape windows from 1,000 files (Li et al. 2018).

Head (frozen encoder)	Val AUC, mean ± std
A2 Perch head	0.99163 ± 0.00029
A3 Bird-MAE head	0.97451 ± 0.00076
A2d (A1-distilled)	0.99133 ± 0.00047
A3d (A2-distilled)	0.97506 ± 0.00012

Table 2: Seed repeats of the MLP heads (seeds 42–44, split fixed). Seed noise in validation is at most 0.0008, far smaller than the leaderboard effects we report.

For frozen embeddings, mean/std matching maps focal embeddings to the soundscape mean and standard deviation per dimension, and standardised CORAL (Sun, Feng, and Saenko 2016) additionally whitens with the focal and recolours with the soundscape correlation matrix (ridge 1.0); the head is then trained on the mapped focal embeddings. *Content-level* methods change what the model is trained on. In **head distillation**, a teacher labels the 12,000 soundscape windows; probabilities p are sharpened to $p^{1.3}$ and values below 0.01 set to 0, and the student head trains on the real labels plus these windows at loss weight 0.5. We ran two pairs, Perch head → Bird-MAE head (A3d) and, across model families, A1 CNN → Perch head (**A2d**). In the **noisy student** round (Figure 5), a teacher labels all 116,712 windows of the 9,726 soundscapes and a fresh bird-pretrained V2-S student is trained on the focal clips plus 30,000 pseudo-labelled windows per epoch (loss weight 0.5), with mixup and stochastic depth 0.15 (Huang et al. 2016) as noise. The MAIN teacher is the mean of A1 and A2; the ABLATION teacher is A2d alone.

Ensemble and CPU inference

Each model's probabilities are smoothed within a file, $p'_t = 0.25\,p_{t-1} + 0.5\,p_t + 0.25\,p_{t+1}$ (renormalised at the ends), because calls often span window borders. Models are then combined by a per-class weighted rank average, $s_{r,c} = \sum_m w_m \,\mathrm{rank}_c(p^{(m)}_{r,c}) / \sum_m w_m$, with ranks scaled to $[0, 1]$. ROC-AUC depends only on the order within a class, so averaging ranks removes the different probability scales of a CNN and an MLP head. To fit two models into 90 CPU minutes we profiled v2's inference and found mel computation to be the largest cost; the fast pipeline uses four file-level workers, one mel call per file and one batch per file, which cut v2 from 11.1 to 5.5 minutes for 700 files.

5 Experiments

Protocol. All runs use v2's split, seed and recipe; training ran on Kaggle T4 GPUs and inference on Kaggle CPU with internet off. Every variant was submitted once. We quote public-leaderboard scores in the text, as the public leaderboard is used for comparison and grading; the tables also list private scores for completeness. Repeating the small heads over three seeds changed validation AUC by at most 0.0008 (Table 2), so the effects below are not seed noise on the validation side; leaderboard noise could not be measured without repeated submissions. Following our ablations, we treat public differences below 0.01 as noise and select by the




Figure 5: Noisy student, round 1. Teachers (MAIN: mean of A1 and A2; ABLATION: A2d) label all 116,712 soundscape windows; labels are sharpened and a freshly initialised bird-pretrained EfficientNetV2-S student is trained on focal clips plus pseudo-labelled windows. No soundscape label is used anywhere.

Run	Val	Public	Private	Δ pub.
Baseline	0.973	0.717	0.699	–
+ random crop	0.982	0.752	0.754	+0.035
+ noise / mixup	0.975	0.732	0.733	+0.016
+ secondary labels	0.969	0.729	0.733	+0.012
+ focal loss	0.973	0.705	0.710	−0.012
v2 (crop+noise+sec.)	0.977	**0.763**	**0.789**	+0.046
v2 − random crop	0.974	0.753	0.772	−0.010
v2 − noise / mixup	0.981	0.767	0.760	+0.004
v2 − secondary labels	0.979	0.737	0.772	−0.026
v2 + focal loss	0.978	0.743	0.782	−0.020

Table 3: Ablations of the baseline (top, Δ vs. baseline) and of v2 (bottom, Δ vs. v2). Val is best-epoch validation AUC on hold-out focal clips; public/private are leaderboard AUC.




Figure 6: Leaderboard AUC when one change is added to the baseline, and the combined v2. The dashed line is the public top-70% cut-off.

public score, because clean focal validation did not predict the leaderboard (Section 6). Variants and selection rules for the adaptation, distillation and ensemble phases were written down before their scores; the exceptions are stated in the Limitations.

Baseline and ablations

The baseline reaches a validation AUC of 0.973 at epoch 7 and then overfits (0.960 at epoch 15) while training loss falls towards zero. On the leaderboard it scores only 0.71681 public, the first sign of the domain shift. Table 3 and Figure 6 add one change at a time and then remove one from v2.

Random crops give the largest single gain (+0.035 public): many first-5 s windows hold no call, and sampling the whole clip fixes this. They also act as augmentation; the crop and noise runs still improve at epoch 15 instead of overfitting at epoch 5 to 7. Noise/mixup and secondary labels help less on the hold-out clips than on the leaderboard, as expected for changes that target soundscapes. Focal loss does not help (−0.012 public). In the remove-one study, secondary labels matter most once combined (−0.026 when removed, against +0.012 alone); a likely reason is that random crops often contain background species, and secondary labels give those windows correct targets. Removing noise/mixup raises the public score slightly (+0.004, noise) but costs 0.028 private, so we keep it. v2 reaches 0.763 public, +0.046 over the baseline.

SED model

Table 4 lists the SED runs. On 20 s chunks SED stays below v2; the best 20 s run is 0.015 public below v2. Keeping the final instead of the best-validation epoch raised the score by 0.013 to 0.016 public: at the validation peak (epoch 7)

Run (weights; chunk start)	Val	Public	Private
v2 (CNN, 5 s windows)	0.977	0.763	0.789
SED 20 s (best ep.; every 20 s)	0.970	0.726	0.744
+ overlap (every 5 s)	0.970	0.732	0.752
+ final epoch	0.974	0.740	0.749
+ final epoch + overlap	0.974	0.748	0.763
+ 224-band mels	0.972	0.728	0.755
+ 224-band + overlap	0.972	0.740	0.761
SED 5 s (final epoch)	0.980	**0.773**	0.787

Table 4: SED runs; all use the v2 recipe. Val is first-5 s hold-out AUC. "Overlap" starts a 20 s chunk every 5 s and averages the windows' scores.




Figure 7: A hold-out clip of one species (top) and the SED model's score for it every 0.5 s (bottom). Although trained only with clip-level labels, the score rises when the species calls.

Model	Val	Public	Private	Gap	CPU
v2 (B0, ImageNet)	0.977	0.763	0.789	.214	11.1
A1 V2-S, bird	0.983	0.828	0.816	.155	8.0
A2 Perch 2.0	0.992	**0.848**	**0.852**	.144	25.0*
A3 Bird-MAE	0.975	0.776	0.780	.199	61.6*

Table 5: Pretraining paradigms, one submission each. Gap = Val − public. CPU = minutes for 700 files, measured (v2: original pipeline; A1: fast pipeline) or *projected from a 20-file dry run.

Parent	Method	Public	Δpub.	Private	Δpriv.
v2	AdaBN	0.739	−0.024	0.764	−0.025
A1	AdaBN	0.772	−0.056	0.766	−0.051
A2	CORAL	0.688	−0.160	0.709	−0.144
A2	mean/std	0.687	−0.161	0.706	−0.146
A3	CORAL	0.643	−0.134	0.647	−0.133
A3	mean/std	0.670	−0.107	0.680	−0.100
A3	distil.+CORAL	0.693	−0.083	0.689	−0.092
A3	A2-distil. (A3d)	0.812	+0.036	0.802	+0.022
A2	A1-distil. (A2d)	**0.867**	+0.019	**0.857**	+0.005
A1	NS MAIN	0.860	+0.032	0.852	+0.035
A1	NS ABLATION	0.840	+0.012	0.838	+0.022

Table 6: Adaptation with unlabelled soundscapes against the unadapted parent. Top: statistics-level; bottom: content-level (NS = noisy student). The A2d private change is within noise.

the one-cycle learning rate was still 64% of its maximum, so the clean hold-out was again a poor guide. Overlapping chunks helped every time (public +0.006 to +0.012, all six differences with the same sign) for about 7 extra CPU minutes. The first-place spectrogram settings (224 bands, 1.25 s steps) did not help. The largest effect was the **chunk length**: the same model on 5 s chunks scored +0.033 public over 20 s chunks, drawing level with v2 (0.773 vs. 0.763) at an estimated 16 CPU minutes. So the SED head works and the 20 s chunk held it back, the opposite of the first-place finding. Our likely explanation, untested, is padding: 47.9% of our clips are shorter than 20 s, so many 20 s training chunks are mostly silence, unlike the test soundscapes. Trained only with clip labels, the model's step scores still rise exactly when the species calls on hold-out clips (Figure 7).

Pretrained models

Table 5 compares the three paradigms with v2. Perch 2.0 is best (+0.085 public over v2) and the bird CNN second (+0.065). Bird-MAE gains only +0.013 public, close to our noise threshold and not confirmed on the private part, so we do not read it as an improvement. All models have a *transfer gap* (validation minus public AUC) of 0.14 to 0.21: clean validation ranks them in the leaderboard order but compresses the spread (0.017 against 0.071).

Label-free adaptation

Table 6 lists every adaptation submission against its unadapted parent. **Statistics-level alignment lowered the public score in all seven cases**, by 0.024 to 0.161, although focal validation AUC barely moved (Perch 0.9916 to 0.9901). The loss was largest for frozen embeddings. A control run of the unadapted A1 through the same fast notebook reproduced its original score exactly, so the AdaBN drop is not a pipeline error. **Content-level adaptation raised the public score in all four cases**, by 0.012 to 0.036, and narrowed the transfer gap each time (Figure 8). A2d learned from the *weaker* A1 teacher (0.828 vs. A2's 0.848) and still improved, becoming our best single model (0.86651 public). Distillation combined with CORAL recovered only part of the CORAL loss, so the damage from the mapping survives pseudo-labels.

Noisy student. MAIN beats ABLATION by +0.020 public and gains +0.032 public over its initialisation A1 at almost the same CPU cost (9.9 vs. 8.0 minutes). The two arms differ in teacher *and* label density (2.50% vs. 0.74% non-zero labels), so the difference cannot be assigned to the teacher alone. Their validation curves end within 0.002 of each other, so validation could not have chosen between them.

Ensemble and final submission

Table 7 shows the ensembles of the MAIN student and A2d. E1 beats the best single model by +0.017 public, so the CNN and the Perch head are complementary: the per-class Spearman correlation of A1 and A2 probabilities on soundscape windows is only 0.31. Smoothing adds a further +0.003 public. Adding the ABLATION student (E3) moved weight away from Perch and lowered the public score. E4 (0.4 CNN / 0.6




Figure 8: Transfer gap (validation AUC minus leaderboard AUC; dark public, hatched private) of the base models, three statistics-level variants and the four content-level models. Statistics alignment widened the gap; pseudo-labels narrowed it.

	Weights; smoothing	Public	Private	CPU
E1	.5/.5; no	0.88352	0.87203	28.3
E2	.5/.5; yes	0.88662	0.88008	30.4
E3	1/3 each (+ABL.); yes	0.88058	0.87522	39.9
E4	.4/.6; yes	**0.88749**	**0.88029**	32.3

Table 7: Rank-average ensembles of the noisy-student MAIN CNN and A2d (weights in that order). CPU minutes measured on 700 files (limit 90).

Perch) was the pre-registered pick by public score; it and E2 are within noise. Figure 9 summarises the progression.

Leaderboard position. Table 8 places our main milestones in the public leaderboard of 2,032 teams. Because late submissions are unranked, the position is the rank our score would take; Figures 10 and 11 show the score and the corresponding place in the leaderboard. E4 (0.88749) falls between rank 72 (0.88753) and rank 73 (0.88745), a relative ranking of $73/2032 = 3.6\%$, inside the top-10% band (cutoff 0.8808). For reference, the best public score is 0.93376, so E4 is 0.046 below the top of the public leaderboard.

6 Discussion

Clean validation does not predict the leaderboard. This is the common thread of all three parts of the project. In the ablations, v2 without noise has the highest validation AUC of the v2 runs but the lowest private score, and secondary labels lower validation AUC while raising the leaderboard score. In the SED runs, keeping the best-validation epoch cost up to 0.016 public. Among pretrained models, validation spans 0.017 while public scores span 0.071, and AdaBN/CORAL hardly changed validation while losing up to 0.16 on the leaderboard. Figure 12 shows the ablation runs. Hold-out focal clips come from the training distribution and cannot measure robustness to soundscapes, which is why we selected by public score and treated differences below 0.01 as noise.

System	Public	Position	Relative
Baseline	0.71681	1600	78.7%
Baseline v2	0.76299	1481	72.9%
SED 5 s	0.77298	1427	70.2%
A2d (best single)	0.86651	647	31.8%
E4 (final)	**0.88749**	**73**	**3.6%**

Table 8: Position each score would take in the BirdCLEF+ 2025 public leaderboard (2,032 teams) and relative ranking (position / 2,032).

Why statistics alignment failed. A diagnostic notebook found no pipeline bug (CORAL and original inference paths differ by at most 3×10^{-8} with the original head). Our pre-registered explanation, that adapted heads assign much higher probabilities to background windows, is not supported: the mean probability on 12,000 soundscape windows rose for only one variant. What changed instead was the *ranking* within each class (per-class Spearman correlation with the original head 0.29 to 0.37 for Perch), and ROC-AUC is sensitive to exactly this. A plausible but untested cause is that soundscape statistics are dominated by windows with no target species, so aligning to them moves call-bearing clips toward background.

Why pseudo-labels helped. Content-level adaptation changes what the model sees rather than how its features are scaled: pseudo-labelled soundscape windows show the student real background, including that most windows hold no target species, while soft labels carry the teacher's knowledge. A2d improving from a weaker teacher of another family suggests the gain comes from complementary errors rather than teacher strength, in line with the motivation for cross-lineage teachers (Farazi and Reza 2026); two runs are too few to prove it.

Bird-MAE and a misleading probe. A linear probe on Bird-MAE features first reached only 0.750 validation AUC, with a first-epoch loss near $\ln 2$. Initialising the output bias to the class log-prior (Lin et al. 2017), with nothing else changed, gave 0.963, so the default probe measured its initialisation rather than the features. Even after this fix, Bird-MAE transferred worst; mean-pooling 256 patch tokens may dilute short calls, and a self-supervised, bird-only objective may separate 60 non-bird classes less well. We did not test these hypotheses.

Speed. In E4 the Perch encoder is about 73% of the summed CPU time; the whole notebook ran in 32.3 minutes, well under the 90-minute limit, whereas Bird-MAE (61.6 projected minutes) would have left little room for a second model.




Figure 9: Public leaderboard AUC (bars) and private AUC (diamonds) of the main systems in the order they were built, coloured by the member who built them: from the baseline (0.717) to the final ensemble E4 (0.887), one change at a time. Each value is one late submission.



Figure 10: Kaggle submission page for the final ensemble E4: 0.88749 public, 0.88029 private (late submission).




Figure 11: BirdCLEF+ 2025 public leaderboard, ranks 70–76. The highlighted row, added by us, marks where our late E4 score (0.88749) falls: between rank 72 (0.88753) and rank 73 (0.88745) of 2,032.

Limitations. We used one split; CNNs were trained once and only the small heads were repeated over seeds (validation standard deviation at most 0.0008). The 0.01 noise threshold was not measured by repeated submissions, and public and private parts disagree on some close calls. The noisy-student MAIN teacher was chosen after the A2d score was known, and the A1 control was requested after the AdaBN score. Perch 2.0 was released in August 2025, after the competition closed, so A2, A2d and the ensemble are not comparable to official entries, and Perch's training data may overlap with `train_audio`. Without labelled soundscapes we could not test the domain-shift explanations directly.




Figure 12: Validation AUC on clean hold-out clips against public leaderboard AUC for the ten baseline-ablation runs. The two are only weakly related.

7 Future Work

Four directions follow from our results. First, a small labelled soundscape set would give a validation signal that matches the test data, which every part of this project lacked, and would allow per-taxon evaluation of our hypotheses. Second, the first-place solution ran several noisy-student rounds; we ran one, so more rounds, with pseudo-label filtering by confidence or teacher agreement and a density-matched control, would show whether the gain compounds and separate teacher quality from label density. Third, the 5 s SED model scores level with v2 but is a different kind of model, so adding it, or an SED head on the bird-pretrained backbone, to the ensemble is a cheap next step (16 CPU minutes). Fourth, exporting the CNNs to ONNX or OpenVINO would free CPU time for a third model.

8 Conclusion

Working one change at a time from a spectrogram CNN, we raised the public score of BirdCLEF+ 2025 from 0.717 to 0.887, a position of 73 of 2,032 (top 3.6%), within the CPU limit. The most important findings are: data-driven fixes for weak labels and domain shift (random crops, soundscape noise, secondary labels) gave the baseline $+0.046$, while focal loss did not help; an SED head draws level with the CNN only with short chunks; pretraining on bird or multi-taxa audio matters far more than architecture; aligning feature statistics to unlabelled soundscapes hurt in every case, whereas pseudo-labels helped in every case, even from a weaker teacher of another model family; and a rank-average ensemble of a CNN and a Perch head with temporal smoothing combines their complementary errors. Across all stages, clean focal validation was a poor guide to the leaderboard, which is the strongest reason to build a labelled soundscape set next.

Acknowledgements and Use of Existing Code

All code is our own. The SED model was re-implemented from the written descriptions in Babych (2025) and tattaka (2021); no code from them was copied. We used the bird-pretrained EfficientNetV2-S weights released by the second-place team (Sydorskyi and Gonçalves 2025), the community ONNX conversion of Perch 2.0 (Calotriton 2025), Bird-MAE-Base weights (Rauch et al. 2025a) and the timm (Wightman 2019) and librosa (McFee et al. 2015) libraries. We used Claude (Anthropic) as a coding and writing assistant; all experiments, results and design decisions were checked by the authors.

References

Babych, N. 2025. 1st Place Solution: Multi-Iterative Noisy Student Is All You Need. BirdCLEF+ 2025 competition write-up, Kaggle. https://www.kaggle.com/competitions/birdclef-2025/writeups/nikita-babych-1st-place-solution-multi-iterative-n.

Boudiaf, M.; Denton, T.; van Merriënboer, B.; Dumoulin, V.; and Triantafillou, E. 2023. In Search for a Generalizable Method for Source Free Domain Adaptation. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, 2914–2931.

Calotriton. 2025. perch-v2-onnx: ONNX Conversion of Perch 2.0. Hugging Face model repository. https://huggingface.co/Calotriton/perch-v2-onnx.

Cañas, J. S.; Kahl, S.; Denton, T.; Toro-Gómez, M. P.; Rodriguez-Buritica, S.; Benavides-Lopez, J. L.; Ulloa, J. S.; Caycedo-Rosales, P.; Klinck, H.; Goëau, H.; Vellinga, W.-P.; Planqué, R.; and Joly, A. 2025. Overview of BirdCLEF+ 2025: Multi-Taxonomic Sound Identification in the Middle Magdalena, Colombia. In *Working Notes of the Conference and Labs of the Evaluation Forum (CLEF 2025)*, volume 4038 of *CEUR Workshop Proceedings*, 2909–2919.

Deng, J.; Dong, W.; Socher, R.; Li, L.-J.; Li, K.; and Fei-Fei, L. 2009. ImageNet: A Large-Scale Hierarchical Image Database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 248–255.

Farazi, M. T.; and Reza, N. J. 2026. Cross-Mutated Semi-Supervised Learning and Selective State-Space Fusion for BirdCLEF+ 2026 Soundscape Recognition. In *CLEF 2026 Working Notes*, volume 4283 of *CEUR Workshop Proceedings*, 4663–4685.

Hinton, G.; Vinyals, O.; and Dean, J. 2015. Distilling the Knowledge in a Neural Network. NIPS 2014 Deep Learning Workshop, arXiv:1503.02531.

Huang, G.; Sun, Y.; Liu, Z.; Sedra, D.; and Weinberger, K. Q. 2016. Deep Networks with Stochastic Depth. In *Computer Vision – ECCV 2016*, Lecture Notes in Computer Science, 646–661.

Kong, Q.; Cao, Y.; Iqbal, T.; Wang, Y.; Wang, W.; and Plumbley, M. D. 2020. PANNs: Large-Scale Pretrained Audio Neural Networks for Audio Pattern Recognition. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 28: 2880–2894.

Li, Y.; Wang, N.; Shi, J.; Hou, X.; and Liu, J. 2018. Adaptive Batch Normalization for practical domain adaptation. *Pattern Recognition*, 80: 109–117.

Lin, T.-Y.; Goyal, P.; Girshick, R.; He, K.; and Dollár, P. 2017. Focal Loss for Dense Object Detection. In *2017 IEEE International Conference on Computer Vision (ICCV)*, 2999–3007.

Loshchilov, I.; and Hutter, F. 2019. Decoupled Weight Decay Regularization. In *International Conference on Learning Representations (ICLR)*.

McFee, B.; Raffel, C.; Liang, D.; Ellis, D. P. W.; McVicar, M.; Battenberg, E.; and Nieto, O. 2015. librosa: Audio and Music Signal Analysis in Python. In *Proceedings of the 14th Python in Science Conference*, 18–25.

Mesaros, A.; Heittola, T.; Virtanen, T.; and Plumbley, M. D. 2021. Sound Event Detection: A Tutorial. *IEEE Signal Processing Magazine*, 38(5): 67–83.

Miyaguchi, A.; Gustineli, M.; and Cheung, A. 2025. Distilling Spectrograms into Tokens: Fast and Lightweight Bioacoustic Classification for BirdCLEF+ 2025. In *Working Notes of the Conference and Labs of the Evaluation Forum (CLEF 2025)*, volume 4038 of *CEUR Workshop Proceedings*, 3111–3127. ArXiv:2507.08236.

Radenović, F.; Tolias, G.; and Chum, O. 2019. Fine-Tuning CNN Image Retrieval with No Human Annotation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(7): 1655–1668.

Rauch, L.; Heinrich, R.; Moummad, I.; Joly, A.; Sick, B.; and Scholz, C. 2025a. Can Masked Autoencoders Also Listen to Birds? *Transactions on Machine Learning Research*. ArXiv:2504.12880.

Rauch, L.; Schwinger, R.; Wirth, M.; Heinrich, R.; Huseljic, D.; Herde, M.; Lange, J.; Kahl, S.; Sick, B.; Tomforde, S.; and Scholz, C. 2025b. BirdSet: A Large-Scale Dataset for Audio Classification in Avian Bioacoustics. In *International Conference on Learning Representations (ICLR)*. ArXiv:2403.10380.

Smith, L. N.; and Topin, N. 2019. Super-Convergence: Very Fast Training of Neural Networks Using Large Learning Rates. In *Artificial Intelligence and Machine Learning for Multi-Domain Operations Applications*, volume 11006 of *Proc. SPIE*.

Sun, B.; Feng, J.; and Saenko, K. 2016. Return of Frustratingly Easy Domain Adaptation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30.

Sydorskyi, V.; and Gonçalves, F. 2025. Tackling Domain Shift in Bird Audio Classification via Transfer Learning and Semi-Supervised Distillation: A Case Study on BirdCLEF+ 2025. In *Working Notes of the Conference and Labs of the Evaluation Forum (CLEF 2025)*, volume 4038 of *CEUR Workshop Proceedings*, 3208–3228.

Tan, M.; and Le, Q. 2019. EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, 6105–6114.

Tan, M.; and Le, Q. 2021. EfficientNetV2: Smaller Models and Faster Training. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, 10096–10106.

tattaka. 2021. 4th Place Solution. BirdCLEF 2021 competition write-up, Kaggle. https://www.kaggle.com/competitions/birdclef-2021/discussion/243293.

van Merriënboer, B.; Dumoulin, V.; Hamer, J.; Harrell, L.; Burns, A.; and Denton, T. 2025. Perch 2.0: The Bittern Lesson for Bioacoustics. arXiv:2508.04665.

Wightman, R. 2019. PyTorch Image Models. https://github.com/huggingface/pytorch-image-models.

Xie, Q.; Luong, M.-T.; Hovy, E.; and Le, Q. V. 2020. Self-Training With Noisy Student Improves ImageNet Classification. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 10684–10695.

Zhang, H.; Cissé, M.; Dauphin, Y. N.; and Lopez-Paz, D. 2018. mixup: Beyond Empirical Risk Minimization. In *International Conference on Learning Representations (ICLR)*. ArXiv:1710.09412.