

The Blueprint Abstraction: Deep Dive (Planned — Phase 5)

*Last updated: 2026-02-27. Based on CORE.md spec, database schema design, forward declarations across the codebase, and Phase 5 task definitions. Blueprint is fully spec'd but **not yet implemented**.*

Table of Contents

1. [What the Abstraction Will Provide](#)
 2. [Current Status: What Exists Today](#)
 3. [The env.yaml Format](#)
 4. [The Blueprint Lifecycle](#)
 5. [The Database Schema \(Planned\)](#)
 6. [The Remote Environment Schema \(Planned\)](#)
 7. [The Provisioning Flow](#)
 8. [Auto-Detection: How Blueprints Are Born](#)
 9. [Remote Device Symmetry](#)
 10. [The 4 Remote Event Types](#)
 11. [S3 Storage Layout for Remote](#)
 12. [Forward Declarations: What Already Exists in the Codebase](#)
 13. [Cross-Abstraction Relationships \(Planned\)](#)
 14. [CLI Surface \(Planned\)](#)
 15. [Phase 5 Task Breakdown](#)
 16. [Gap Analysis: Spec vs. Implementation Readiness](#)
 17. [References](#)
-

1. What the Abstraction Will Provide

The Blueprint is a **recipe for creating a remote development environment**. It describes what a project needs to run: runtime, dependencies, system packages, Docker configuration, cloud resources, environment variables, ports, and setup commands. It lives as a `.fuel-code/env.yaml` file committed to the repository.

The Blueprint is **one of the original five CORE.md abstractions** (Workspace, Session, Event, Device, Blueprint). CORE.md describes it as "a recipe for creating a remote Device. The `.fuel-code/env.yaml` file."

Core value proposition: Different projects need radically different environments. A Python ML project needs CUDA drivers and a GPU instance. A Node API needs nothing special. The Blueprint captures this per-workspace in a human-reviewable, version-controlled format. It enables `fuel-code remote up` — a single command to spin up a disposable EC2 instance with Docker, the project's code, all dependencies, Claude Code, and fuel-code hooks pre-installed.

Why it matters for the system: Without Blueprints, the "remote" dimension of fuel-code is purely observational (tracking existing remote sessions). With Blueprints, fuel-code becomes an active provisioner — it doesn't just track development activity, it provides the environments where that activity happens.

2. Current Status: What Exists Today

Blueprint is the only one of the five core abstractions with **zero implementation** in the codebase. However, several forward declarations and placeholders exist:

What Exists	Where	Purpose
4 remote event types	shared/src/types/event.ts	remote.provision.start, remote.provision.ready, remote.provision.error, remote.terminate
remote_env_id column	sessions table	Nullable TEXT column with comment: "FK to remote_envs added in Phase 5 migration"
remote device type	devices table	CHECK (type IN ('local', 'remote')) — remote devices are a first-class concept
Device status states	devices table	provisioning and terminated statuses exist alongside online and offline
WebSocket broadcast	server/src/ws/websocket.ts	broadcastRemoteUpdate() function already defined
WsClient handler	Client-side WebSocket	remote.update message type already handled
Phase 5 task files	tasks/phase-5/	15 task files defining the full implementation plan
CORE.md spec	tasks/CORE.md	Full schema, provisioning flow, CLI commands, env.yaml format

The system was designed from day one with Blueprints in mind. The "remote" concept permeates the existing abstractions, but the actual provisioning and env.yaml logic is Phase 5.

3. The env.yaml Format

The Blueprint is materialized as a `.fuel-code/env.yaml` file at the root of a workspace:

```
# .fuel-code/env.yaml — auto-generated, human-reviewed, committed to repo
runtime: node
version: "22"
package_manager: bun

system_deps:
  - postgresql-client
  - redis-tools

docker:
  base_image: "node:22-bookworm"
  additional_packages: []

resources:
  instance_type: t3.xlarge
  region: us-east-1
  disk_gb: 50
```

```
environment:
  NODE_ENV: development

ports:
  - 3000
  - 5432

setup:
  - bun install
```


Field Semantics

Field	Type	Purpose
runtime	string	Primary language runtime: node, python, rust, go, etc.
version	string	Runtime version. Quoted to prevent YAML float coercion ("22" not 22).
package_manager	string	Package manager: bun, npm, yarn, pnpm, pip, uv, cargo
system_deps	string[]	APT packages to install in the Docker container
docker.base_image	string	Docker Hub image to use as the base
docker.additional_packages	string[]	Extra Docker-level packages
resources.instance_type	string	EC2 instance type
resources.region	string	AWS region
resources.disk_gb	number	EBS volume size
environment	map	Environment variables injected into the container
ports	number[]	Ports to expose (mapped from container to host)
setup	string[]	Commands run after container start (install deps, build, etc.)

Design Principles

- **Auto-detected with human review:** The system generates `env.yaml` from repo analysis (package.json, Dockerfile, pyproject.toml, etc.), but the user reviews and can edit before committing.
- **Committed to the repo:** This is intentional — the Blueprint is version-controlled and shared. If a teammate clones the repo, they get the same environment spec.
- **Frozen on provision:** When `fuel-code remote up` runs, the `env.yaml` is read, frozen into immutable JSON, and stored in the `blueprints` table and the `remote_envs.blueprint` column. This ensures reproducibility — the provisioned environment matches exactly what was specified, even if `env.yaml` changes later.

4. The Blueprint Lifecycle



The Blueprint itself is stateless — it's just a YAML file. The stateful entity is the **Remote Environment** (`remote_envs` table) which tracks the provisioned instance. A single Blueprint can produce many Remote Environments (spin up, tear down, spin up again).

5. The Database Schema (Planned)

From CORE.md spec:

```
CREATE TABLE blueprints (
  id          TEXT PRIMARY KEY,          -- ULID
  workspace_id TEXT REFERENCES workspaces(id), -- null for global/template
  name        TEXT NOT NULL,
  source       TEXT NOT NULL,            -- "auto-detected" | "manual"
  detected_from TEXT,                    -- repo path or URL that was scanned
  config       JSONB NOT NULL,           -- full env.yaml content as JSON
  created_at   TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at   TIMESTAMPTZ NOT NULL DEFAULT now()
);
```

Key Design Decisions

- **workspace_id is nullable:** Blueprints can be global templates (not tied to a workspace). Example: a "Node 22 with PostgreSQL" template that users can start from.
- **source distinguishes origin:** `auto-detected` means the system scanned the repo and generated it. `manual` means the user wrote it by hand or from a template.
- **config is JSONB:** The full `env.yaml` content is stored as JSON, not as a reference to the file. This is the "frozen" snapshot — it captures the exact configuration at the time the Blueprint was registered.

- **detected_from** : Records what was scanned to produce the auto-detection (e.g., the repo path). Useful for auditing: "this Blueprint was generated from analyzing /Users/john/Desktop/fuel-code".

6. The Remote Environment Schema (Planned)

From CORE.md spec:


```
CREATE TABLE remote_envs (  
  id TEXT PRIMARY KEY, -- ULID  
  workspace_id TEXT NOT NULL REFERENCES workspaces(id),  
  device_id TEXT REFERENCES devices(id), -- the EC2 instance's device  
  identity  
  status TEXT NOT NULL DEFAULT 'provisioning'  
  CHECK (status IN (  
    'provisioning', 'ready', 'active', 'idle', 'terminated',  
    'error'  
  )),  
  instance_id TEXT, -- EC2 instance ID  
  instance_type TEXT NOT NULL,  
  region TEXT NOT NULL,  
  public_ip TEXT,  
  ssh_key_s3_key TEXT, -- S3 key for ephemeral SSH key pair  
  blueprint JSONB NOT NULL, -- snapshot of env.yaml used to  
  provision  
  ttl_minutes INTEGER NOT NULL DEFAULT 480, -- 8 hours default  
  idle_timeout_minutes INTEGER NOT NULL DEFAULT 60,  
  cost_per_hour_usd NUMERIC(6, 3),  
  total_cost_usd NUMERIC(8, 3),  
  provisioned_at TIMESTAMPTZ NOT NULL DEFAULT now(),  
  ready_at TIMESTAMPTZ,  
  terminated_at TIMESTAMPTZ,  
  termination_reason TEXT,  
  metadata JSONB NOT NULL DEFAULT '{}'  
);  
  
CREATE INDEX idx_remote_envs_workspace ON remote_envs(workspace_id);  
CREATE INDEX idx_remote_envs_active ON remote_envs(status) WHERE status NOT IN  
('terminated', 'error');
```

The remote_envs ↔ sessions FK

The existing `sessions.remote_env_id` column will gain a foreign key constraint once this table is created:

```
ALTER TABLE sessions ADD CONSTRAINT fk_sessions_remote_env  
  FOREIGN KEY (remote_env_id) REFERENCES remote_envs(id);
```

Status Lifecycle



Status	Meaning
provisioning	EC2 instance launching, Docker building, setup commands running
ready	Health check passed, SSH available, waiting for user to connect
active	User connected, Claude Code session running
idle	No active session, idle timeout counting down
terminated	Instance destroyed (manual, TTL, idle timeout, or error)
error	Provisioning failed (bad AMI, Docker build error, health check fail)

Cost Tracking

- **cost_per_hour_usd** : Based on EC2 instance type pricing
- **total_cost_usd** : Accumulated from `provisioned_at` to `terminated_at`
- **termination_reason** : "manual" | "ttl" | "idle" | "error" — explains why the environment was destroyed

7. The Provisioning Flow

From CORE.md spec, `fuel-code remote up` triggers a 4-stage process:

Stage 1: Detect / Load Blueprint (~2s)

1. Check for `.fuel-code/env.yaml` in the current workspace
2. If missing: auto-detect from repo (package.json, Dockerfile, etc.)
3. Generate `.fuel-code/env.yaml`, show to user for review
4. Freeze blueprint → immutable JSON stored in `blueprints` and `remote_envs.blueprint`

Stage 2: Provision EC2 Instance (~45-90s)

1. Generate ephemeral SSH key pair → upload to S3 (`ssh-keys/{remote_env_id}/`)
2. Create/reuse security group (SSH inbound from caller IP only)
3. Launch EC2 instance (Docker-ready AMI) with user-data script:
 - Install Docker
 - Pull Docker image from blueprint
 - Start container with env vars, port mappings
 - Inside container:
 - Clone repo (full, checkout current branch)
 - Run setup commands from blueprint
 - Install fuel-code CLI
 - Run `fuel-code init` (with `device_type=remote`)
 - Install Claude Code
 - Copy user's `~/.claude/` config (settings, permissions, CLAUDE.md)
 - Install CC hooks + git hooks

- Health check: `claude --version`
- 4. Tag EC2 instance (`fuel-code:remote-env-id` , `fuel-code:workspace`)
- 5. Callback to backend: `POST /api/remote/:id/ready`
- 6. Emit `remote.provision.ready` event

Stage 3: Connect (~1s)

1. Download ephemeral SSH key from S3
2. SSH into EC2 → exec into Docker container
3. User gets a regular terminal (can run `claude` , `git` , etc.)
4. Events flow back to the same backend as local events

Stage 4: Lifecycle

- Auto-terminate after idle timeout (configurable, default 60 min)
- Auto-terminate after TTL (configurable, default 8 hours)
- Manual: `fuel-code remote down <id>`
- On terminate: emit `remote.terminate` event, update `remote_envs` record

8. Auto-Detection: How Blueprints Are Born

The auto-detection system will scan the project workspace and infer the correct environment configuration from existing files:

Detection Sources (Planned)

File Detected	Inferences
<code>package.json</code>	<code>runtime=node</code> , <code>package_manager</code> from lockfile type, version from engines
<code>bun.lockb</code>	<code>package_manager=bun</code>
<code>yarn.lock</code>	<code>package_manager=yarn</code>
<code>pnpm-lock.yaml</code>	<code>package_manager=pnpm</code>
<code>pyproject.toml</code>	<code>runtime=python</code> , version from <code>requires-python</code>
<code>Pipfile</code>	<code>runtime=python</code> , <code>package_manager=pipenv</code>
<code>Cargo.toml</code>	<code>runtime=rust</code> , version from <code>rust-version</code>
<code>go.mod</code>	<code>runtime=go</code> , version from <code>go</code> directive
<code>Dockerfile</code>	<code>base_image</code> from <code>FROM</code> , <code>system_deps</code> from <code>RUN apt-get</code>
<code>docker-compose.yml</code>	ports from services, environment from <code>env</code> section
<code>.tool-versions</code> / <code>.node-version</code>	Specific runtime versions

Design Philosophy

- **Inspectable:** The generated `env.yaml` is a plain file the user can read, understand, and edit

- **Materialized:** Auto-detection produces a concrete file, not a runtime computation. What you see is what you get.
- **Non-destructive:** If `env.yaml` already exists, auto-detection is skipped. The user's edits are respected.
- **Conservative defaults:** Instance type defaults to `t3.xlarge` (not the cheapest, not the most expensive). Disk defaults to 50GB. TTL defaults to 8 hours. Users can override.

9. Remote Device Symmetry

The single most important architectural principle for Blueprints and remote environments:

The backend does not distinguish between events from local and remote devices. The processing pipeline is identical.

Once provisioned, a remote EC2 is just another Device in the topology:

- It has its own `device_id` (generated during `fuel-code init` on the remote)
- `fuel-code` CLI installed with hooks configured
- Events flow through the same HTTP POST → Redis → Consumer → Processor pipeline
- A `session.start` from `remote-abc` is processed identically to one from `macbook-pro`
- The TUI shows both, distinguished by device name

This means:

- **No remote-specific event processing:** The existing event pipeline handles everything
- **No remote-specific session logic:** Sessions on remote devices go through the same lifecycle
- **No remote-specific transcript handling:** Same S3 upload, same parsing, same summarization
- **Adding a new machine to the topology is just:** "install `fuel-code`, run `init`, events flow"

The only remote-specific logic is:

- **Provisioning** (creating the EC2 instance, Docker container, SSH keys)
- **Connection management** (SSH tunneling)
- **Lifecycle management** (idle timeout, TTL, termination)
- **Cost tracking** (per-hour and total cost)

10. The 4 Remote Event Types

Already defined in `packages/shared/src/types/event.ts` :

```
| "remote.provision.start"    // EC2 provisioning began
| "remote.provision.ready"   // EC2 + Docker ready, SSH available
| "remote.provision.error"   // Provisioning failed
| "remote.terminate"        // Remote device terminated
```

Payload Schemas (from CORE.md)

```
// remote.provision.ready
interface RemoteProvisionReadyPayload {
  instance_id: string;    // EC2 instance ID
  public_ip: string;      // Public IP for SSH
```



```

ssh_port: number;          // SSH port (usually 22)
device_id: string;         // The new remote device's ID
}

// remote.terminate
interface RemoteTerminatePayload {
  instance_id: string;
  reason: string;          // "manual" | "ttl" | "idle" | "error"
  uptime_seconds: number;
  total_cost_usd: number | null;
}

```

Event Handler Integration (Planned)

These events will need handlers registered in the `EventHandlerRegistry` :

- `remote.provision.start` : Create `remote_envs` row with status= `provisioning`
- `remote.provision.ready` : Update `remote_envs` with IP, port, `device_id`; transition status to `ready`
- `remote.provision.error` : Update `remote_envs` with error details; transition status to `error`
- `remote.terminate` : Update `remote_envs` with termination details; transition status to `terminated` ; update device status to `terminated`

11. S3 Storage Layout for Remote

From CORE.md:

```

fuel-code-blobs/
├── ssh-keys/
│   └── {remote_env_id}/
│       ├── id_ed25519          # Ephemeral private key
│       └── id_ed25519.pub      # Ephemeral public key
└── manifests/
    └── {workspace_canonical_id}/
        └── env.yaml            # Cached environment manifest

```

Key Design Decisions

- **Ephemeral SSH keys**: Generated per-environment, stored in S3, deleted on termination. Not the user's personal SSH keys.
- **Cached manifests**: The frozen `env.yaml` is stored in S3 alongside the DB record. Belt-and-suspenders for recovery.
- **Keys are per-environment, not per-workspace**: Each `fuel-code remote up` generates fresh keys. No key reuse across environments.

12. Forward Declarations: What Already Exists in the Codebase

These are concrete code artifacts that exist today and will be wired up when Blueprint is implemented:

Event Types (shared)

```
// packages/shared/src/types/event.ts
export type EventType =
  | ...
  | "remote.provision.start"
  | "remote.provision.ready"
  | "remote.provision.error"
  | "remote.terminate";
```

These types are part of the EventType union, meaning the event pipeline already accepts and routes them. They just don't have handlers registered yet.

Device Type and Status (database)

```
-- devices table
type TEXT NOT NULL CHECK (type IN ('local', 'remote'))
status TEXT NOT NULL DEFAULT 'online'
      CHECK (status IN ('online', 'offline', 'provisioning', 'terminated'))
```

The device table already supports `remote` as a device type and `provisioning / terminated` as statuses. When a remote environment is provisioned, the `fuel-code init` running inside the container will create a device record with `type = 'remote'`.

Session-to-Remote FK (database)

```
-- sessions table
remote_env_id TEXT, -- FK to remote_envs added in Phase 5 migration
```

The nullable column exists. Sessions running on remote devices will have this set to link back to the specific remote environment.

WebSocket Broadcasting (server)

```
// packages/server/src/ws/websocket.ts
broadcastRemoteUpdate() // Already defined, broadcasts to connected WS clients
```

The WebSocket infrastructure already has a function for pushing remote environment status updates to connected clients in real-time.

WS Client Handler (client)

The client-side WebSocket handler already recognizes `remote.update` message types and can display them.

13. Cross-Abstraction Relationships (Planned)

```

Blueprint (.fuel-code/env.yaml)
|— belongs_to → Workspace (one env.yaml per workspace)
|— stored_in → blueprints table (frozen snapshot)
|— produces → Remote Environment (many envs from one blueprint)
|
Remote Environment (remote_envs table)
|— belongs_to → Workspace (workspace_id FK)
|— belongs_to → Device (device_id FK – the remote device record)
|— uses → Blueprint (blueprint JSONB – frozen snapshot)
|— has_many → Sessions (sessions.remote_env_id FK)
|— references → S3 (ssh_key_s3_key)
|— generated_by → remote.provision.start Event
|— activated_by → remote.provision.ready Event
|— terminated_by → remote.terminate Event
|
Device (remote variant)
|— type = 'remote'
|— created_by → fuel-code init (running inside the container)
|— emits → same events as local devices (session.*, git.*)
|— linked_from → remote_envs.device_id

```

The Chain: Blueprint → Remote Env → Device → Session

1. User runs `fuel-code remote up` in workspace W
2. Blueprint is read from `.fuel-code/env.yaml`, frozen into JSON
3. EC2 + Docker provisioned → `remote_envs` row created (status=provisioning)
4. Inside container: `fuel-code init` creates a `device` record (type=remote)
5. `remote_envs.device_id` updated to point to the new device
6. User connects via SSH, runs `claude`
7. CC hooks fire → `session.start` event → session row created with `remote_env_id`
8. Same pipeline processes the session: transcript upload, parsing, summary
9. On termination: `remote.terminate` event, `remote_envs.status = terminated`,
`device.status = terminated`

14. CLI Surface (Planned)

From CORE.md spec:

```

# Blueprint management
fuel-code blueprint show           # Show current workspace's env.yaml
fuel-code blueprint detect         # Auto-detect and generate env.yaml
fuel-code blueprint edit           # Open env.yaml in $EDITOR

# Remote environment management
fuel-code remote up                # Provision from blueprint
fuel-code remote up --instance t3.2xlarge # Override instance type
fuel-code remote list              # List active remote environments
fuel-code remote status <id>      # Remote env details
fuel-code remote ssh <id>         # Connect to remote env

```

```
fuel-code remote down <id>          # Terminate remote env
fuel-code remote down --all          # Terminate all remote envs
```

Expected CLI Behaviors

- `fuel-code remote up` should be a single command with rich TUI output showing provisioning progress
 - SSH connection should be transparent — the user drops into a shell inside the Docker container
 - Port forwarding should be automatic based on the `ports` section of `env.yaml`
 - `fuel-code remote list` should show status, uptime, cost, workspace, and instance type
-

15. Phase 5 Task Breakdown

The `tasks/phase-5/` directory contains 15 task files defining the full Blueprint implementation. While detailed task content isn't reproduced here, the high-level structure is:

1. **Database migration:** Create `blueprints` and `remote_envs` tables, add FK on sessions
 2. **Blueprint types:** TypeScript types for `env.yaml` schema, `Blueprint`, `RemoteEnv`
 3. **Blueprint detection:** Auto-scan logic for `package.json`, `Dockerfile`, etc.
 4. **Blueprint CRUD:** API endpoints and CLI commands for blueprint management
 5. **EC2 provisioning:** AWS SDK integration, instance launch, user-data script
 6. **SSH key management:** Ephemeral key generation, S3 storage, secure distribution
 7. **Docker orchestration:** Container build, setup command execution, health check
 8. **Remote event handlers:** Process `remote.provision.*` and `remote.terminate` events
 9. **SSH connection:** Tunneling, port forwarding, interactive shell
 10. **Lifecycle management:** Idle timeout, TTL-based termination, cost tracking
 11. **WebSocket integration:** Real-time provisioning progress, status updates
 12. **CLI commands:** `fuel-code remote up/down/list/status/ssh`, `fuel-code blueprint show/detect/edit`
 13. **Configuration sync:** Copy user's Claude settings to the remote container
 14. **Security:** Security group management, key rotation, access control
 15. **Testing:** E2E tests for provisioning flow, integration tests for event handlers
-

16. Gap Analysis: Spec vs. Implementation Readiness

1. No AWS SDK Integration (High Priority)

The codebase has S3 integration (via `@aws-sdk/client-s3`) but no EC2, Security Group, or IAM integration. Phase 5 needs `@aws-sdk/client-ec2` and potentially `@aws-sdk/client-iam`.

2. No Docker Build Pipeline (High Priority)

There's no mechanism to build Docker images from a Blueprint. The spec assumes a base image from Docker Hub with setup commands, but real-world projects may need custom Dockerfiles. The relationship between `docker.base_image` and the project's own Dockerfile (if any) needs clarification.

3. No SSH Tunneling Infrastructure (High Priority)

No code exists for SSH connection management, port forwarding, or interactive shell session piping. This is a significant implementation effort.

4. No Cost Estimation Logic (Medium Priority)

The spec includes `cost_per_hour_usd` and `total_cost_usd` fields but no pricing data or calculation logic. EC2 pricing varies by region and instance type and changes over time.

5. No Idle Detection Mechanism (Medium Priority)

The spec says "auto-terminate after idle timeout" but there's no mechanism to detect idle state. Possible approaches: poll for active SSH connections, check for active CC processes, use CloudWatch metrics.

6. Blueprint Validation Not Specified (Medium Priority)

The env.yaml format is described but there's no Zod schema for validating it. Invalid configurations (non-existent instance types, unsupported regions, malformed Docker images) need validation before provisioning.

7. Security Group Management Complexity (Medium Priority)

The spec says "SSH inbound from caller IP only" — this requires creating or updating security groups per-environment and handling IP changes (user moves to different network during an active session).

8. Remote Event Types Have No Handlers (Low Priority — Expected)

The 4 remote event types are defined in the EventType union but have no registered handlers. The consumer will log a warning for unhandled types. This is expected — handlers will be added in Phase 5.

9. No User-Data Script Template (Medium Priority)

The provisioning flow spec is detailed but there's no actual user-data script template. This is a complex bash script that needs to handle: Docker installation, image pulling, container startup, repo cloning, dependency installation, fuel-code/Claude Code installation, config sync, health checking, and error reporting.

10. No Cleanup/Garbage Collection (Low Priority)

No mechanism for cleaning up orphaned resources: terminated EC2 instances not properly cleaned up, S3 SSH keys from terminated environments, security groups from long-destroyed environments.

17. References

File	What It Contains
tasks/CORE.md lines 116-154	Blueprint abstraction definition, env.yaml format
tasks/CORE.md lines 523-563	remote_envs and blueprints table schemas
tasks/CORE.md lines 568-596	S3 storage layout (ssh-keys, manifests)
tasks/CORE.md lines 797-848	Remote provisioning flow (4 stages)
tasks/CORE.md lines 841-848	Remote device symmetry principle
tasks/CORE.md lines 852-930	CLI commands including blueprint and remote
packages/shared/src/types/event.ts	4 remote.* event type definitions

packages/server/src/db/migrations/001_initial.sql	sessions.remote_env_id placeholder, device type/status constraints
packages/server/src/ws/websocket.ts	broadcastRemoteUpdate() forward declaration
tasks/phase-5/	15 task files for Phase 5 implementation plan