

1. REFER TO BUILDING ELEVATIONS FOR MASONRY VENEER AND METAL PANEL TYPE
2. REFER TO ELEVATION AND WINDOW ELEVATIONS FOR GLAZING TYPE
3. CMU SIZE VARIES REFER TO WALL TYPE

1. REFER TO BUILDING ELEVATIONS FOR MASONRY VENEER AND METAL PANEL TYPE
2. REFER TO ELEVATION AND WINDOW ELEVATIONS FOR GLAZING TYPE
3. CMU SIZE VARIES REFER TO WALL TYPE

04 20 00 A	CLAY MASONRY VENEER [TYPE]
04 20 00 C16	STANDARD CMU [8x8x16]
04 20 00 C26	BOND BEAM CMU [8x8x16]
04 20 00 C28	BOND BEAM CMU [12x8x16]
04 20 00 D1	GROUT FILL
04 20 00 S24	VEEPS [24" O.C.]
04 20 00 H	EMBEDDED FLASHING
04 20 00 J	JOINT REINFORCEMENT
04 20 00 K	CAVITY DRAINAGE MATERIAL
04 20 00 R	TERMINATION BAR
05 05 15 A	POST-INSTALLED CONCRETE ANCHOR
05 12 00	STRUCTURAL STEEL
05 12 00 B	STRUCTURAL STEEL BEAM - REFER TO STRUCTURAL DWGS.
05 12 00 C	STRUCTURAL STEEL ANGLE - REFER TO STRUCTURAL DWGS.
05 12 00 D	STRUCTURAL STEEL BEARING PLATE - REFER TO STRUCTURAL DWGS.
05 12 00 A03	STUDS AND TRACK [5/8" @ 16" O.C.]
05 12 00 A06	STUDS AND TRACK [6" @ 16" O.C.]
05 50 00 C	STEEL PLATE
06 10 00 A24	WOOD BLOCKING [2x4]
06 10 00 A28	WOOD BLOCKING [2x6]
06 10 00 A34	PLYWOOD SHEATHING BOARD [3/4"]
06 10 00 A38	PLYWOOD SHEATHING BOARD [5/8"]
06 10 00 B08	GLASSMATT GYPSUM WALL SHEATHING [5/8"]
07 21 00 A06	BOARD INSULATION [3"]
07 21 00 F	MINERAL WOOL BLANKET
07 25 00 A	WEATHER BARRIERS
07 42 13 13A	FORMED METAL WALL PANEL
07 42 13 13B	FORMED METAL WALL PANEL TRIM
07 42 13 13C	FORMED METAL WALL PANEL CLIP
07 42 85 A	METAL SOFFIT PANELS
07 62 00 C	DRIP EDGE
07 62 00 J	BRAKE METAL TRIM
07 71 00 D	GRAVEL STOP
07 92 00 A	SEALANT
07 95 00 B33	WALL TO WALL EXPANSION JOINT COVER
08 11 13 A	HOLLOW METAL DOOR AND FRAME
08 11 13 F	HOLLOW METAL DOOR FRAME
08 32 26 A	OVERHEAD COILING GRILLES
08 36 13 A	SECTIONAL DOORS
08 41 13 B	ALUMINUM FRAMED STOREFRONT
08 44 13 A	GLAZED ALUMINUM CURTAIN WALLS
08 51 13 A	ALUMINUM WINDOW
08 80 00 C	INSULATING GLASS
09 22 16 A03	STUDS AND TRACK [5/8" @ 16" O.C.]
09 22 16 D	CEILING SUSPENSION SYSTEM
09 29 00 A58	ABUSE RESISTANT GYPSUM BOARD [5/8"]
09 51 13 A	ACoustICAL PANEL CEILINGS
09 51 13 C01	ANION TRIM
23 37 00	HVAC EQUIPMENT - REFER TO MECHANICAL DWGS.

1. PROVIDE 0.72 M2 OF SHEET METAL TOP OVER EXPOSED FACE OF WOOD BLOCKING AND SHEATHING. COLOR: GLOSS TO MATCH METAL SOFFIT PANELS.
2. PREFABRICATED ALUMINUM STOREFRONT EXTRUSION BY WINDOW MANUFACTURER. (WINDOW TYPE: A1K1A)
3. FILL VOID BETWEEN VENEER AND BLOCKING WITH SPRAY FOAM. 70 21.29.
4. LINE INDICATES EXTENT OF VAPOR BARRIER TAPE. TAPE TO WRAP COMPLETELY AROUND BLOCKING AND EXTEND 3" DOWN FACE OF WALL, BEHIND INSULATION SYSTEM.
5. CURTAINED FIRE ALARM CALL STATION TO BE LOCATED FROM ADJACENT FIRE WALL BY 2" AIR SPACE.
6. SNAP TRIM TO MATCH CURTAIN WALL. | STOREFRONTS | ALUMINUM WINDOWS, U.N.O.
7. FIELD VEILY AND COORDINATE CEILING LINES AND OVERHEAD DROPS.
8. CONTINUOUS NON-COMBUSTIBLE VAPOR BARRIER.
9. PROVIDE UNISTRUT SUPPORT FROM STRUCTURE ABOVE TO ALLOW GARAGE DOOR TO FREELY OPEN ABOVE CEILING. UNISTRUT SUPPORT ACoustICAL CEILING GRID, AND LIGHT FIXTURES.
10. COORDINATE CEILING CLEARANCE WITH PANEL PANEL.
11. PROVIDE FINISHING STRIPS TO MATCH EXISTING APPLIES TO STRUCTURAL BEARING PLATE TO PROVIDE THERMAL BREAK BETWEEN EXTERIOR AND INTERIOR CONDITIONS. REFER TO SPECIFICATION 09.96 FOR PRODUCT APPLICATION. THERMAL COATING TO BE APPLIED IN ALL CONDITIONS WHERE BEARING PLATES CONNECT EXTERIOR WALL TO INTERIOR CONSTRUCTION.
12. REFER TO STRUCTURAL DETAIL DRAWINGS.
13. WHERE ROLLER SHADES ARE REQUIRED: SOFFIT DETAILS AND INSTALLATION CONDITIONS MAY VARY. SEE INTERIOR DRAWINGS FOR DETAILS.
14. COORDINATE WITH MECHANICAL DRAWINGS FOR HVAC SYSTEM.

[illegible]

SALEM CSD NEW K-8
2002 WHINNERY ROAD
SALEM OHIO 44460

HEAD DETAILS

ISSUED FOR:	
PERMIT	07/07/2021
BID	08/15/2021
CONSTRUCTION	-/-/-/-/-
RECORD	-/-/-/-/-
PROJECT MANAGER	DESIGNER
CB	LMW

JOB NO.
2024270.01

A-605