

Live DOM Viewer

Markup to test ([permalink](#), [save](#), [upload](#), [download](#), [hide](#)):

```
<table width="100%" border="0" cellspacing="0" cellpadding="0">

<tr>

<td class="h5 white" style="font-family:'Noto Sans', Arial,sans-serif; font-size:16px; line-height:22px; text-align:left; font-weight:bold; color:#ffffff;">FRONT-END DEVELOPMENT</td>
```

DOM view ([hide](#), [refresh](#)):

HTML

HEAD

BODY

TABLE width="100%" border="0" cellspacing="0" cellpadding="0"

#text:

TBODY

TR

#text:

TD style="padding-bottom: 20px;"

#text:

TABLE width="100%" border="0" cellspacing="0" cellpadding="0"

#text:

TBODY

TR

#text:

TD background="images/collage6.png" bgcolor="#114490" valign="top" height="366" class="bg" style="background-size:cover !important; -webkit-background-size:cover !important; background-repeat:none;"

#text:

#comment: [if gte mso 9]> <v:rect xmlns:v="urn:schemas-microsoft-com:vml" fill="true" stroke="false" style="width:650px; height: 366px">
<v:fill type="frame" src="images/t8_bg.jpg" color="#114490" /> <v:textbox inset="0,0,0,0"> <![endif]

#text:

DIV

#text:

TABLE

#text:

#comment: IDEA: boton en overlay

#text:

TBODY

TR

TH

#text:

TR

#text:

TD class="text-button" style="color:#ffffff; font-family:'Lato', Arial, sans-serif; font-size:16px; line-height:20px; text-align:center; text-transform:uppercase; font-weight:bold; min-width:auto !important; padding:12px 22px; background:#0a2641; border-radius:4px;"

#text:

A href="#" target="_blank" class="link-white" style="color:#ffffff; text-decoration:none;"

SPAN class="link-white" style="color:#ffffff; text-decoration:none;"

#text: VIEW OFFERS

#text:

#comment: IDEA: lookforme

#text:

#text:

#text:

#text:

#text:

TABLE width="100%" border="0" cellspacing="0" cellpadding="0"

#text:

TBODY

TR

#text:

TD class="content-spacing" width="30" height="366" style="font-size:0pt; line-height:0pt; text-align:left;"

#text:

TD style="padding: 30px 0px;"

#text:

TABLE width="100%" border="0" cellspacing="0" cellpadding="0"

#text:

TBODY

TR

#text:

TD class="h1 center pb25" style="color:#ffffff; font-family:'Noto Sans', Arial,sans-serif; font-size:40px; line-height:46px; text-align:center; padding-bottom:25px;"

#text: Web Design Services

#text:

#text:

TR

#text:

TD class="text-center" style="color:#ffffff; font-family:'Noto Sans', Arial,sans-serif; font-size:16px; line-height:30px; text-align:center;"

#text: Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

#text:

Rendered view: ([hide](#)):

VIEW OFFERS

innerHTML view: ([show](#), [refresh](#)):

Log: ([hide](#)):

```
rendering mode: BackCompat
document has no title
```

This script puts a function `w(s)` into the global scope of the test page, where *s* is a string or object to output to the log.

► Some files are available for testing purposes, notably "image" is an image.

