windmar ROOFING

PROTECT THE LIFE OF YOUR ROOF!

TAKE ADVANTAGE OF SEALING YOUR ROOF WITH US

- **Sealing with a real warranty**
- ***Sealing guaranteeing the solar system penetrations*** **(o** ***Sealing ensuring the solar system's penetrations*****)**
- **Alliance with Gardner, leaders in Silicone**
- **Manufacturer-Certified Crews (o Manufacturer-Certified Teams)**
- **Best sealing for solar systems**
- **Manufacturer's limited lifetime warranty on materials**

787.395.7766 windmar.com facebook.com/WindMarHome ventas@windmarhome.com

Scope of Work

Pressure washing at 4,000 PSI or more to remove any unadhered material or elastomeric sealant.

Crack repair and application of Gardner "Silicone Roof Patch" on existing anchors and penetrations.

Removal and installation of the solar system, if necessary.

Removal and disposal of compromised asphalt, PVC, or polyurethane membrane, which entails an additional cost if not previously quoted.

Application of Gardner "Elasto Prime" primer, if necessary.

Application of Gardner "100% Silicone Flat Roof Coating" on the entire roof, parapets, and inverted beams.

The "Silver" Sealing Plan includes the manufacturer's limited lifetime warranty on materials and a 1-year labor warranty with Windmar Home.

The "Gold" Plan includes the manufacturer's limited lifetime warranty on materials and a 10-year labor warranty with Windmar Home.

The "Platinum" Plan includes the manufacturer's limited lifetime warranty on materials, a 10-year labor warranty with Windmar Home, and a maintenance visit every 2 years to wash the roof and solar panel system, if applicable, for the duration of the 10-year warranty with Windmar Home.

Our crews are certified by Gardner for the application of their products.

Gardner personnel perform an initial inspection to define the work and a final inspection to validate the manufacturer's warranty.

Additional included work N/A (or *Not Applicable*)

windmar ROOFING

Sealing plans

	Silver	Gold	Platinum
Manufacturer's Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime
Labor Warranty	1 year	10 years	10 years
Cost of Included	$300 per visit	Included for 10 years	Included for 10 years
Preventive Maintenance Visit	No	No	Roof and Panel Cleaning every 2 years for 10 years
Approximate Monthly Payment			

ADVANTAGES OF SILICONE

- ***Guaranteed for Life*** **(o** ***Lifetime Guarantee*****)**
- **Flexible! Adapts to irregular surfaces**
- **Waterproof**
- **Resistant to temperature changes**
- **Compatible with a wide variety of surfaces**
- **Resistant to weather conditions**
- **Simple Maintenance**
- **Energy Efficiency**
- **Fire Resistance**
- ***Pleasing Appearance***
- **Eco-friendly**
- **It's Safe - does not require a gas torch for application**

787.395.7766 windmar.com facebook.com/WindMarHome ventas@windmarhome.com

8015

Sta-Kool® Ultra Turbo-Dri

Elastomeric Premium White Roof Coating

- Turbo-Dri: Rain Safe in 30 Minutes
- Cool-Core pigment helps cool interiors
- High elasticity to resist cracks
- Sta-White finish stays brighter longer
- Commercial-grade durability

STA-KOOL® Ultra is a Premium Elastomeric White Roof Coating offering next generation cool roof technology benefits. STA-KOOL® Turbo-Dri Technology allows for more application opportunities, faster recoat and job completion times, and advanced protection against unexpected rain. Innovative Cool-Core Technology uses specialized pigments to repel heat gain, which helps keep interiors cooler and helps save money on cooling costs. The Sta-White finish stays brighter white longer and blocks UV rays, all while protecting and prolonging roof surfaces. This advanced siliconized acrylic delivers maximum protection against the elements, faster and easier applications, and lasting quality you can depend on.

PREPARATION: Pressure washing entire surface is recommended for best results (use only a wide fan spray tip). All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint, and all other foreign matter. Roofs must have proper ventilation and proper drainage. All ponding water areas need to be corrected prior to coating. Rusty metal must be cleaned with a wire brush and primed with a metal primer/sealer before application of this product. Repair all leaks and cracks with Gardner Waterproofing & Seam Tape or STA-KOOL® White Roof Patch and Universal Patching Fabric in accordance with product instructions. Surfaces previously coated with aluminum, asphalt or tar should be allowed to cure for a minimum of one summer season prior to coating with this product. Surfaces with mildew growth or stains must be cleaned with a bleach solution (two parts water to one part bleach). Be certain that all surfaces are thoroughly rinsed and dry prior to applying coating. Do Not Thin.

APPLICATION: Two coats can be applied in 1 day! Keep lid on container during use, as product will set-up very quickly. Surface and air temperatures must be a minimum of 65°F and rising with good drying conditions. Mix well. Apply on a clear, sunny day in the morning hours with a professional airless paint sprayer or a 3/4" nap exterior paint roller. First, apply one (1) thin coat over all seams and joints. Allow to cure for 1-2 hours or until dry, then apply two (2) uniform coats over entire surface, avoiding excessive rolling. Two full coats are needed for all applications. Apply second coat perpendicular to first coat. Allow 2-4 hours between coats and 24 - 48 hours for full curing. Stop application of product at least 3 hours before sunset.

SPRAY INFO: 2000-3000 PSI, .030 - .041 Tip Size, 1-3 GPM.

COVERAGE RATE: On flat metal 80-100 sq/ft per gal per coat. On traditional surface roofs, 60 - 80 sq/ft. per gal. per coat. All roofs require two coats for proper protection. NOTE: If roof becomes hot (over 100°F) before application, lightly mist roof surface with water spray to prevent coating from drying too fast. Remove any excess or puddling water prior to coating. If roof surfaces become soiled as they age, due to the elements, elastomeric can be cleaned with a mild water and bleach solution. Excess scrubbing should be avoided. If coloring is desired, a typical addition of 3 - 4 ounces per gallon of universal colorant can be added, which will result in light pastel colors. Note: Color tinting will disclaim warranty.

CLEAN-UP: Clean tools with soap and water.

PRECAUTIONS: For exterior use only. Strong ammonia odor, so do not directly inhale vapors. DO NOT allow product to freeze. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. DO NOT allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. For longest life, store in controlled environment, 40°F - 80°F. DO NOT store in direct sunlight. DO NOT store at temperatures above 110°F. Close container after use. DO NOT reuse empty containers. Not intended for use on EPDM, Hypalon, PVC, or TPO. Do not use in drinking water or food systems.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 15 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES

PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
SK-8015	5 gal.	12" x 12" x 14.75"	5 gal. / 18.9 L	55 lbs.	1 ea.	025056880154

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101

SK-8245
100% SILICONE FLAT ROOF COAT-N-SEAL

TECHNICAL DATA SHEET

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Solids Weight	97 ± 3%
Solids Volume	97 ± 3%
Viscosity	7,000 cps
Pounds per Gallon	11.05 ± 0.5 lb.
Hiding Power	98.38%
Gloss	78.60%
Tensile Strength	250 psi
Tear Resistance	37 lb/linear ft
Reflectivity	90 ± 1%
Emissivity	0.90
SRI value	115
Permeability	3 perms
Water Absorbtion	0.1%
Elongation	315%

Approx. Shipping Weights:

(Note: All approx. weights include container)

1 gallon (3.4L)	10.6 lb.
5 gallons (18.9L)	51.1 lb.

VOC: <10 g/L (regulatory)

DESCRIPTION:

Gardner Flat Roof Coat-N-Seal is a 100% silicone, extremely reflective roof coating for flat roofs or areas where ponding water may occur. The high solids, low odor formula sets quick, will not crack and can be applied in a wide temperature range. Can be used on low slope roofs (1:12 pitch or less) and areas with ponding water on the following substrates: metal, aged mod-bit, built-up roofing, concrete, tile, aged TPO and EPDM, and over existing acrylic, asphalt emulsion and aluminum coatings. Gardner Flat Roof Coat-N-Seal exceeds performance requirements of ASTM D6694, ASTM D7281, Title 24 and CRCC rated.

PREPARATION:

All surfaces must be clean, dry, have proper drainage and free of surface rust, dust and any other foreign matter or debris. Surfaces with mildew or stains must be cleaned prior to applying this product. Rinse thoroughly. Pressure washing entire surface is recommended (use only a wide fan tip - do not allow stream to tear into roof surface). Be certain all surfaces are thoroughly rinsed and dry prior to applying coating. Rusty metal must be cleaned with a wire brush and primed with rust inhibiting primer before application of this product. For applications over asphalt roof surfaces, Gardner SK-8705 Elasto-Prime or comparable primer can be used as a base coat for stain blocking protection.

PATCH:

Repair all leaks and cracks before applying any coating. Make repairs with polyester reinforcing fabric and Gardner SK-8601Eterna-Kote Silicone Patch. Allow repair to cure according to product directions before application of roof coating.

APPLICATION:

Mix well before applying. A power drill mixing tool is ideal. Confirm all dew or moisture has completely dried from the roof before applying. Best applied on a clear, dry day with warming temps between 35°F (1°C) and 120°F (48°C) Use a quality, heavy duty 3/4" nap paint roller or professional airless sprayer. Gardner Flat Roof Coat-N-Seal can be applied in 1 coat to surfaces in good condition. Recoat rough or damaged areas as needed ***during application.*** Rain safe in 15 minutes at 70°F (21°C) & 50% relative humidity.

SPRAY INFO:
2000 - 3000 PSI, .030 -.041 Tip Size, 1 - 3 GPM

COVERAGE RATE:

Approximately 71 sq. ft./gal.

CLEAN-UP: Clean with Xylene

STORAGE & HANDLING PRECAUTIONS:

Do not heat or thin. Keep container sealed when not in use. Product must be kept out of sunlight, protected from the elements and in areas where air flows freely and is not restricted. Shelf life is up to 18 months from date of manufacturer for unopened containers. For maximum shelf life store between 50°F (10°C) and 80°F (26°C). Storage at temperatures outside these conditions or at relative humidity over 65% will reduce shelf life. Storage longer than 6 months may require additional mixing. Tightly seal container after opening and when not in use. Opened containers should be used within 3 - 5 days after opening. If a skin forms, remove prior to mixing material.

Gardner-Gibson, Inc.
4161 East 7th Avenue. Tampa, FL 33605
1.800.237.1155 | www.icpgroup.com | D24

SK-8705
Elasto Prime™
Primer/Sealer for use before elastomeric coatings

ELASTOPRIME™

- Seals worn surfaces
- Improves coverage of roof coatings
- Applies quickly and easily
- Fast drying

Gardner® Elasto Prime™ is designed to seal surfaces and act as a primer for worn or older surfaces. This product creates a strong bond between old and new coatings. **Elasto Prime™** is specially formulated to improve the adhesion of white elastomeric roof coatings and enables them to last longer.

PREPARATION: All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Roofs must have proper ventilation. Rusty metal must be cleaned with a wire brush and primed with rust preventative primer. Pressure washing entire surface is recommended for best results. Repair all leaks and cracks with **Gardner White Flash** and **Universal Patching Fabric** in accordance with patching instructions. For best results, use **Elasto Prime™** before applying roof coatings. Surfaces previously coated with aluminum, asphalt or tar coatings, should be allowed to cure for a minimum of one summer season prior to coating with this product. Surfaces with mildew growth or stains must be cleaned with a bleach solution (2 parts water to one part bleach). Be certain all surfaces are thoroughly rinsed and dry prior to applying coating. For longest life, store unused product in a controlled environment, 55 °F-80 °F. Do not store in direct sunlight.

APPLICATION: Surface and air temperatures must be a minimum of 55 °F and rising. DO NOT apply if heavy dew or rain is expected within 24-48 hours. Apply on clear, sunny day in morning hours with a 3/4" nap exterior paint roller. Mix well before using. Do not thin or dilute. Surface must be clean; free of sand, dust, mold, dirt, and loose particles. Using a roller or sprayer, apply a uniform coat of **Elasto Prime™** to the existing surface. Apply additional **Elasto Prime™** on severely worn areas. Allow to cure for 1-2 hours depending on drying conditions. NOT FOR USE ON EPDM OR SOME SINGLE PLY MEMBRANES. ROOFS MUST HAVE PROPER VENTILATION.

COVERAGE RATE: Approximately 50-75 sq. ft. per gal. per coat. Total Coverage for two (2) coat application is 25-35 sq. ft. per gallon.

CLEAN-UP: Clean tools with soap and water.

PRECAUTIONS: For exterior use only. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. DO NOT allow pail to tumble as this will cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. DO NOT store at temperatures above 100°F. This container is recyclable if cleaned immediately. DO NOT reuse empty containers. Close container when not in use. Do not use on EPDM, Hypalon or PVC surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first. Do not use in drinking water or food systems. Protect from freezing. For the longest life, store in controlled environment, 35 °F-80 °F. Do not store in direct sunlight.

WARRANTY AND DISCLAIMER: For limited warranty and disclaimer information, contact the Gardner-Gibson, Inc. corporate office at 1-800-237-1155.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
SK-8705	5 gal.	12" x 12" x 14.75"	5 gal. / 18.9 L	45 lbs.	1 ea.	250568705514

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101

Llevar a cabo tus proyectos nunca ha sido tan sencillo. Ofrecemos opciones de financiamiento diseñadas

Financiamiento Exclusivo de Oriental Bank. Único banco comercial con un prestamo solar

APOC 581 SILICONE ROOF PATCH

TECHNICAL DATA SHEET

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	10.6 lb./gal.
Color	White
Tensile Strength	300 psi
Elongation	500%
Skin Time (50% Relative Humidity, 70 °F)	1-2 hours
Full Cure (50% Relative Humidity, 70 °F)	3-7 days
Application Temperatures	35°F - 100°F
Flash Point	> 200°F

Approx. Shipping Weights:

(Note: All approx. weights include container)

1 gallon (3.4L)	10.6 lb.
2 gallons (7.57L)	21.2 lb.

VOC: <10 g/L (regulatory)

DESCRIPTION:

APOC 581 Silicone Roof Patch is a premium, high solids, highly flexible and durable repair product for use with silicone coatings. APOC 581 can be applied in a wide temperature range. Not recommended for use with acrylic, aluminum or asphalt coatings. APOC 581 exceeds performance requirements of ASTM C920.

PREPARATION:

All surfaces must be clean, dry, have proper drainage and free of surface rust, dust and any other foreign matter or debris. Rusty surfaces must be properly cleaned then primed with APOC 291 Rust Inhibiting Primer or comparable primer. Mold or mildew stains must be cleaned with APOC 801 Heavy Duty Cleaner or comparable cleaner prior to application. Pressure washing entire surface is recommended (use only a wide fan tip - do not allow stream to tear into roof surface).

APPLICATION:

For exterior use only. Damp or wet surfaces will result in adhesion issues or blisters. Metals must be degreased with a suitable solvent. Always apply on a clear, warm sunny day. Apply in morning hours to allow maximum cure time. Application should be completed a minimum of 4 hours prior to sunset. Temperatures must be above 35°F (1°C) for 24 hours and rising, but not above 110°F. Skins over for recoat in 1-2 hours and fully cures in 3-7 days at 70°F (21°C) & 50% relative humidity. Apply with a paint brush or trowel. When using reinforcing fabric, patch entire damaged area and extend 2-3" beyond damaged area. Embed reinforcing fabric into the repair while wet. Apply second layer of patch, brushing over and into embedded fabric. When using Incredible Tape®, adhere tape to damaged area and saturate with 581, extending 2-3" beyond damaged area.

Apply with a paint brush or trowel.

COVERAGE RATE:

Approximately 12.5 sq. ft./gal. @ 1/8 in thickness

CLEAN-UP:

Clean with Xylene

STORAGE & HANDLING PRECAUTIONS:

Do not heat or thin. Keep container sealed when not in use. Product must be kept out of sunlight, protected from the elements and in areas where air flows freely and is not restricted. For maximum shelf life store between 50°F (10°C) and 80°F (26°C). Storage at temperatures outside these conditions or at relative humidity over 65% will reduce shelf life. Storage longer than 6 months may require additional mixing. Tightly seal container after opening and when not in use. When transporting this product, ensure that the lid and openings are tight and unit is secure and upright. Do Not allow products to tumble or shift as this may cause leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure on top of 6 mil plastic sheeting to prevent damage due to accidental spills or loosening of lids.

Gardner-Gibson, Inc.
4161 East 7th Avenue. Tampa, FL 33605
1.800.237.1155 | www.icpgroup.com | C25

¿POR QUÉ WINDMAR?

windmar HOME

TESLA POWERWALL CERTIFIED INSTALLER

PREMIER INSTALLER 2023

SOMOS LA COMPAÑÍA DE ENERGÍA RENOVABLE MÁS GRANDE DEL CARIBE

NUESTRAS OFICINAS

PUERTO RICO

FLORIDA

- Oficinas
- Almacenes
- The Home Depot

¿POR QUÉ WINDMAR?

windmar GROUP

NUESTRAS FACILIDADES

COTO LAUREL
PONCE, PUERTO RICO

SABANA SECA
TOA BAJA, PUERTO RICO