Managing Outliers

```
library(tidynorm)
library(dplyr)
library(tidyr)
library(ggplot2)
library(ggdensity)
library(khroma)
library(tinytable)
```

```
theme_set(
  theme_minimal(
    base_size = 16
  ) +
    theme(
      palette.colour.continuous = as.character(color(palette = "lipari")(50)),
      palette.color.discrete = color(palette = "bright")
    )
)
```

Quick Overview

Stanley (2022) proposes an order of operations for sociophonetic analysis as follows:

1. Identify allophone categories.
2. Identify outliers by allophone category.
3. Carry out speaker normalization.

It's beyond the scope of `{tidynorm}` to define a pipeline for identifying allophone categories, since these will be extremely language, dialect, and label-set specific. I would recommend reviewing the general purpose `dplyr::case_when()` and `dplyr::recode_values()`, or `joeyr::code_allophones()` for this step.

The second and third steps can be achieved in `{tidnorm}` by

2. using `identify_outliers()`, `identify_track_outliers()` or `identify_dct_outliers()` to add an `.outlier` column to your vowel data frame.
3. passing the `.outlier` column to `.exclude` in your normalization function.

Here is how `identify_outliers()` can be incorporated into a workflow normalizing point measures.

```
speaker_data |>
  identify_outliers(
    # Use F1 through F3 to identify outliers
    F1:F3,

    # Identify outliers within speaker and
    # within vowel class
    .by = c(speaker, plt_vclass),

    # The probability level beyond which
    # rows are marked as outliers
    .level = 0.95
  ) |>
  norm_nearey(
    F1:F3,
    .by = speaker,

    # exclude rows marked as outliers
    .exclude = .outlier,
  ) ->
  normed
#> Normalization info
#> • Outliers identified along `F1`, `F2`, and `F3`
#> • grouped by `speaker` and `plt_vclass`
#>
#>
#> Normalization info
#> • normalized with `tidynorm::norm_nearey()`
#> • Normalized `F1`, `F2`, and `F3`
#> • normalized values in `F1_lm`, `F2_lm`, and `F3_lm`
#> • grouped by `speaker`
#> • within formant: FALSE
#> • Exclusion: .outlier
#> • Transformation prior to normalization: log
#> • (.formant - mean(.formant, na.rm = T))/(1)
```

- Both `identify_track_outliers()` and `identify_dct_outliers()` require a `.token_id_col` argument.
- `identify_dct_outliers()` requires a `.param_col` argument.

It's worth noting that passing an expression to `.exclude` only excludes data from the calculation of the normalization parameters. All data points get normalized, so to remove outliers from the rest of your analysis flow, you'll need to do some additional filtering.

```
nrow(speaker_data)
#> [1] 10697
nrow(normed)
#> [1] 10697
```

Details

General Info

The family of outlier identification functions add three new columns to your vowel formant data frames:

`.mahal`

The squared Mahalanobis distance.

`.prob`

The probability of observing a value of `.mahal` this extreme or less.

`.outlier`


A logical vector indicating whether the vowel token exceeded the probability `.level` specified.

The Mahalanobis distance can be thought of as a multi-dimensional z-score. For example, the two speakers in `speaker_data` have very different distributions for their [æ] vowel, and the outlier status for each token is specific to the shape of the distribution for each speaker for each vowel.

```
speaker_data |>
  identify_outliers(
    F1:F2,
    .by = c(speaker, plt_vclass)
  ) |>
  filter(
    plt_vclass == "ae"
  ) ->
  ae_identified
#> Normalization info
#> • Outliers identified along `F1` and `F2`
#> • grouped by `speaker` and `plt_vclass`
```

```
ae_identified |>
  ggplot(
    aes(F2, F1)
  ) +
  geom_point(
    aes(fill = sqrt(.mahal)),
```


```
    shape = 21
  ) +
  scale_y_continuous(
    trans = c("log10", "reverse")
  ) +
  scale_x_continuous(
    trans = c("log10", "reverse")
  ) +
  expand_limits(
    fill = 0
  ) +
  facet_wrap(~speaker)
```



The `.prob` column is based on the chi-squared cumulative probability density function with degrees of freedom equal to the number of data dimensions.

```
ae_identified |>
  ggplot(
    aes(F2, F1)
  ) +
  geom_point(
    aes(fill = .prob),
    shape = 21
  ) +
```

```
  scale_y_continuous(
    trans = c("log10", "reverse")
  ) +
  scale_x_continuous(
    trans = c("log10", "reverse")
  ) +
  scale_fill_continuous(
    limits = c(0, 1)
  ) +
  facet_wrap(~speaker)
```




DCT and Track Outlier Identification

If you have a data frame of DCT coefficients by formant, `identify_dct_outliers()` will treat each DCT parameter for each formant as a data dimension over which the Mahalanobis distance is calculated. For `identify_track_outliers()` each formant track first has the DCT transform applied, and then the Mahalanobis distance is calculated in the same way as `identify_dct_outliers()`.

```
speaker_tracks |>
  identify_track_outliers(
    F1:F2,
    .by = c(speaker, plt_vclass),
    .token_id_col = id,
```

```
    .time_col = t,
    # DCT order
    .order = 5,
    .pre_trans = log,
    .return_dct = TRUE
  ) |>
  filter(plt_vclass == "ey") ->
  ey_identified
#> Normalization info
#> • Outliers identified along `F1` and `F2`
#> • grouped by `speaker` and `plt_vclass`
```

```
ey_identified |>
  reframe_with_idct(
    F1:F2,
    .by = c(speaker, id),
    .param_col = .param
  ) |>
  ggplot(
    aes(F2, F1)
  ) +
  geom_path(
    aes(
      color = .prob,
      group = id
    ),
    arrow = arrow(
      type = "closed",
      length = unit(0.1, "cm")
    )
  ) +
  scale_color_continuous(
    limits = c(0,1)
  ) +
  scale_x_reverse() +
  scale_y_reverse() +
  facet_wrap(~speaker)
```




Extended uses

It's possible to use either the `.mahal` or `.prob` columns to calculate weighted means, or even weighted versions of the normalization methods.

```
ey_identified |>
  mutate(
    .inv_prob = 1 - .prob
  ) |>
  summarise(
    .by = c(speaker, .param),
    across(
      F1:F2,
      list(
        weighted = \(x) weighted.mean(x, .inv_prob),
        unweighted = mean
      )
    )
  ) |>
  pivot_longer(
    starts_with("F")
  ) |>
  separate(
    name,
    into = c("formant", "weight")
```

```
  ) |>
  pivot_wider(
    names_from = formant,
    values_from = value
  ) |>
  reframe_with_idct(
    F1:F2,
    .by = c(speaker, weight),
    .param_col = .param
  ) |>
  ggplot(
    aes(F2, F1, color = weight )
  ) +
  geom_path(
    arrow = arrow(
      type = "closed",
      length = unit(0.1, "cm")
    )
  ) +
  scale_y_reverse() +
  scale_x_reverse() +
  facet_wrap(~speaker)
```




```
speaker_data |>
  identify_outliers(
    F1:F3,
    .by = c(speaker, plt_vclass)
```

```
  ) |>
  mutate(
    .inv_prob = 1-.prob
  ) |>
  # a weighted log-mean normalization
  norm_generic(
    F1:F3,
    .by = c(speaker),
    .pre_trans = log,
    .by_formant = FALSE,
    .exclude = is.na(.inv_prob),
    .L = weighted.mean(.formant, .inv_prob, na.rm = T)
  ) ->
  normed_weighted
#> Normalization info
#> • Outliers identified along `F1`, `F2`, and `F3`
#> • grouped by `speaker` and `plt_vclass`
#>
#>
#> Normalization info
#> • normalized with `tidynorm::norm_generic()`
#> • Normalized `F1`, `F2`, and `F3`
#> • normalized values in `F1_n`, `F2_n`, and `F3_n`
#> • grouped by `speaker`
#> • within formant: FALSE
#> • Exclusion: is.na(.inv_prob)
#> • Transformation prior to normalization: log
#> • (.formant - weighted.mean(.formant, .inv_prob, na.rm = T))/(1)
```

Bibliography

Stanley, J. A. (2022). Order of Operations in Sociophonetic Analysis. *Penn Working Papers in Linguistics*, *28*(2), 151–160.