

Advanced Image Recognition and AI Training

Text extraction with machine learning

Bachelor Thesis

Joakim S. Aarskog, Sondre Lillelien, Sander Riis

B021-G27
Department of Information Technology
Østfold University College
Halden, Norway
22nd April 2021

Contents

Contents	i
List of Figures	iii
1 Introduction	1
1.1 Background and motivation	1
1.1.1 Project Group	1
1.1.2 Employer	1
1.1.3 Problem statement	2
1.1.4 Motivation	2
1.1.5 Objectives	2
1.1.6 Method	2
1.1.7 Deliverables	3
1.2 Report outline	3
2 Analysis	4
2.1 Research topic	4
2.2 Tools	4
2.2.1 OCR engines	4
2.3 Preprocessing	7
2.3.1 Scaling the image	7
2.3.2 Skew correction	7
2.3.3 Remove background noise	7
2.3.4 Binarization	8
3 Design	9
3.1 Overview	9
3.2 API	9
3.3 CNN	9
3.4 OCR	9
3.5 RNN	10
3.6 RNN	10
4 Implementation	11
4.1 REST API	11
4.2 Web solution	11
4.3 Dataset	11
4.4 Pre-processing	12

4.4.1	Data augmentation	12
4.4.2	Image preparation	12
4.5	Convolutional Neural Network	12
5	Evaluation	13
6	Discussion	14
7	Conclusion	15

List of Figures

2.1	Overview of features (list from https://cloud.google.com/vision/pricing) . .	5
2.2	Overview of prices (list from https://cloud.google.com/vision/pricing) . . .	6

Chapter 1

Introduction

A lot of companies have employees that travel in their work. This travel is usually funded by their employer. In order to keep track of all the transactions generated by this travel, the company will store the receipts from the transactions. By saving the receipts in this manner, it greatly reduces the effort needed from employers to refund their employees for their purchases.

Going through these transactions manually is time-consuming and labor intensive. Because of this, creating an automated solution for extracting the data contained in these receipts, will effectively reduce the amount of manpower and manhours required by the company. The goal of this thesis is to explore and discuss these automated solutions, and present a possible solution.

1.1 Background and motivation

1.1.1 Project Group

Joakim Aarskog is a 24-year-old computer science student at Østfold University College. He has an interest in technology and photography.

Sondre Lillelien is a 26-year-old computer engineering student at Østfold University College. Interests include technology, engineering and AI.

Sander Riis is a 23 years old computer science student at Østfold University College. He likes to develop programs and learn about new technology.

1.1.2 Employer

The employer for this thesis is Simployer AS, a tech company that specializes in Human Resource Management (HRM). They deliver HRM software to 15.000 customers and have over 1.2 million users in Norway and Sweden. Simployer is passionate about giving other employers and their employees the tools to be able to effectively organize themselves. Simployer is a sizable company with over 250 employees, and a history going back 35 years. Our main contact in Simployer is Flemming Ottosen, their CTO.

1.1.3 Problem statement

As Simployer delivers HRM software to many Scandinavian companies, they have a large database containing receipts generated by their employees. These documents are stored in an unorganized manner, making manual validation of these documents difficult and time-consuming. The documents are typically in the form of an image of a receipt taken with a mobile camera. The documents lack metadata, which makes searching through them to find a specific document difficult. Simployer would like a way to organize this data automatically and attach relevant metadata to the documents. This metadata includes the price of the transaction, the company the service was purchased from, and the date of the transaction. In addition to attaching metadata to existing documents, Simployer would like to automatically generate and attach metadata to new documents coming in to their database.

1.1.4 Motivation

Artificial intelligence and machine learning is a rapidly growing field in computer science. The biggest obstacles that AI and ML faced in the past, was a lack of computing power and a lack of data. In today's world, both of these obstacles have largely been overcome as computing power keeps growing and data is a more abundant resource than before. The motivation for this thesis is to take advantage of this abundance of computing power and data, to solve real life problems.

1.1.5 Objectives

The objectives for this thesis are:

Objective 1 To create a machine learning model, that can identify desired data in an image of a receipt.

Objective 2 To have the machine learning model be capable of improving its performance when new data is acquired.

Objective 3 To develop an API that can deliver data to the machine learning model and fetch the results.

Objective 4 To research several ways of solving the problem in order to present alternatives to the thesis employer.

1.1.6 Method

The aim of the thesis has pivoted somewhat since the start of the semester. Originally the goal was to create a machine learning model that can correctly identify desired data from a large variety of image types with different quality. The goal is still to create such a model, but more focus will be directed towards the learning module. Therefore, we have de-prioritized being able to work with a large variety of images.

The methods used for this thesis are the following:

- Deep learning literature research
- Text analysis and text extraction articles
- Clearly defining the scope and objectives of the thesis

- .NET Core articles
- Workflow management in Jira

1.1.7 Deliverables

The following items should be delivered by the thesis' end-date:

- A report detailing the entire thesis
- A machine learning model that can extract desired data from the images it is given
- An API that can deliver images to the ML pipeline and request the results of data extraction done on the images

1.2 Report outline

Chapter 2 explains the thesis' topic and scope in detail. In addition; the methods used to complete the work, along with literature the work is based on will be included here.

Chapter 3 provides a detailed walkthrough of how the thesis is designed. The design is made to efficiently and correctly tackle the problem statement.

Chapter 4 describes the implementation of the thesis. This includes how the thesis group chose to implement the design discussed in previous chapters, and the research methods used to arrive at design decisions.

Chapter 5 presents the results the thesis group's work in an objective manner.

Chapter 6 discusses the results discovered in chapter 5. This includes how the results differ from what was expected, how the findings might be relevant to the thesis' field of study, etc.

Chapter 7 concludes and summarizes the thesis in a manner that can be read by someone who did not read the entire report.

Chapter 2

Analysis

2.1 Research topic

Our project is to create a solution that allows a user to take an image of a receipt, and automatically upload the relevant data to a database. This automates the process of handling travel receipts, thus making it less time-consuming and reduces the cost. To achieve this, we will be using Optical Character Recognition software and machine learning. The extracted data from the image consists of date, total amount, and the receipt type.

The app will consist of two main parts: The OCR, and the model that reads the data. We are going to use a free open source OCR, named Tesseract. The OCR is what will allow us to extract text from the images. This OCR will send all the text that is on the receipt in the form of an array to the model. The model will then decide what information is the correct data to extract and keep.

With the app we also need to include an API that will talk with the app and talk with Simployers server. This API gets the data from the model and will prompt the information that is selected for the user for a final validation, before sending it to the Simployer database. This will allow Simployer to easily search in the database based on the metadata that was extracted.

Another objective of this thesis is to analyse and compare solutions that already exists on the market. And then create a prototype of each solution and connect them to the API.

2.2 Tools

This section details the different tools that have been considered for use in the thesis.

2.2.1 OCR engines

There are many OCR engines that could be used for this thesis. Three main ones have been selected for consideration. These are Google Cloud Vision API, Amazon Textract, and Tesseract.

Google Cloud Vision API

Google Cloud Vision API contains a well optimised OCR and good variety of detection. The detection features are listed in figure 2.1.

Feature type	
CROP_HINTS	Determine suggested vertices for a crop region on an image.
DOCUMENT_TEXT_DETECTION	Perform OCR on dense text images, such as documents (PDF/TIFF), and images with handwriting. TEXT_DETECTION can be used for sparse text images. Takes precedence when both DOCUMENT_TEXT_DETECTION and TEXT_DETECTION are present.
FACE_DETECTION	Detect faces within the image.
IMAGE_PROPERTIES	Compute a set of image properties, such as the image's dominant colors.
LABEL_DETECTION	Add labels based on image content.
LANDMARK_DETECTION	Detect geographic landmarks within the image.
LOGO_DETECTION	Detect company logos within the image.
OBJECT_LOCALIZATION	Detect and extract multiple objects in an image.
SAFE_SEARCH_DETECTION	Run SafeSearch to detect potentially unsafe or undesirable content.
TEXT_DETECTION	Perform Optical Character Recognition (OCR) on text within the image. Text detection is optimized for areas of sparse text within a larger image. If the image is a document (PDF/TIFF), has dense text, or contains handwriting, use DOCUMENT_TEXT_DETECTION instead.
WEB_DETECTION	Detect topical entities such as news, events, or celebrities within the image, and find similar images on the web using the power of Google Image Search.

Figure 2.1: Overview of features (list from <https://cloud.google.com/vision/pricing>)

We can see that Google API offers everything from text recognition, to landmark location and crop Hints. The Google API is known to be industry leading in the field, so this comes as no surprise. This API will have almost everything you need to develop an application with text recognition.

The API also has a lot of features in their beta version which is not included in figure 2.1.

Feature	Price per 1000 units		
	First 1000 units/month	Units 1001 - 5,000,000 / month	Units 5,000,001 and higher / month
Label Detection	Free	\$1.50	\$1.00
Text Detection	Free	\$1.50	\$0.60
Document Text Detection	Free	\$1.50	\$0.60
Safe Search (explicit content) Detection	Free	Free with Label Detection, or \$1.50	Free with Label Detection, or \$0.60
Facial Detection	Free	\$1.50	\$0.60
Facial Detection - Celebrity Recognition	Free	\$1.50	\$0.60
Landmark Detection	Free	\$1.50	\$0.60
Logo Detection	Free	\$1.50	\$0.60
Image Properties	Free	\$1.50	\$0.60
Crop Hints	Free	Free with Image Properties, or \$1.50	Free with Image Properties, or \$0.60
Web Detection	Free	\$3.50	Contact Google for more information
Object Localization	Free	\$2.25	\$1.50

Figure 2.2: Overview of prices (list from <https://cloud.google.com/vision/pricing>)

Google is the best in the field, but they are also the most expensive API to use. The prices are calculated for every 1000th request. This means that you are getting the first 1000-requests free and then you will need to pay 1.5\$ for each 1000-request you do on for example text detection. If you have a request size of 50.000-requests this will be $49 \times 1.5\$ = 73,5$ dollars (620 NOK). This will reset every month.

Amazon Textract

Amazon's AWS hosts a service called Textract. This cloud-based service lets you upload an image to their text recognition software.

Detect Document Text API This feature is the classic OCR feature that will extract text from a document. Amazon will charge you 0.0015\$ per page (1.50\$ per 1000) for the first million pages, when you exceed 1 million the price will go down to 0.0006\$ per page (0.6\$ per 1000)

Table Extraction This is an improved version of Detect Document Text API. This will group the text in tables. This is helpful with structured data, such as financial reports. Amazon will charge you 0.015\$ per page (15.0\$ per 1000) for the first million pages, when you exceed 1 million the price will go down to 0.01\$ per page (10\$ per 1000)

Form Extraction This detects key-value pairs in documents, for example if your document has a field named "firstName" it will pair it with "Mike". This way "first name" would be the key and "Mike" would be the value. This makes it easy to either sort it into a database or reuse the values in variables. With normal OCR the relation is lost. Amazon

will charge you 0.05\$ per page (50\$ per 1000) for the first million pages, when you exceed 1 million the price will go down to 0.04\$ per page (40\$ per 1000)

Analyze Document API

This is a combination of the tables and forms extraction Amazon will charge you 0.065\$ per page (65\$ per 1000) for the first million pages, when you exceed 1 million the price will go down to 0.05\$ per page (0.50\$ per 1000)

Note that Amazon changes their pricing on the region you are in (you might want to check the price for your region), they also do not include a free 1000 scans per a month.

Tesseract

Tesseract is an open-source OCR engine that supports over 100 different languages. It has the reputation of being one of the best open-source OCR engines. It was created by HP in the 80's and later made open-source in 2005 and funded by google since 2006. Most other OCR APIs today are build on top of this, like Google Cloud Vision API.

If this engine is used, code that takes advantage of the engine's built-in methods must be written. When dealing with high-quality images and computer generated pdf receipts, writing code to extract the text is relatively simple. When the images are of lower quality, more care must be given to pre-processing to improve the accuracy of the text extraction. This is because OCR software needs good contrast and little to no noise in the images. Another problem is curved text, like in a book. This might be the hardest thing to solve.

2.3 Preprocessing

Having images of ideal quality for use in an OCR is a luxury. Images will often be of low quality or taken from suboptimal angles. In order to mitigate the effects that low quality images will have on the text extraction accuracy, the images should go through a preprocessing stage before getting sent to the OCR software.

2.3.1 Scaling the image

OCR software will have the best performance when given images between 300dpi and 600dpi. Anything less will make it unreadable for the OCR and anything more will consume extra processing power with little to no improvement in accuracy.

2.3.2 Skew correction

OCR engines use line segmentation to separate the text found in an image into different lines of data. Therefore, it is important that the OCR is given images that are as straight as possible. Skew correction is the part of the pre-processing pipeline that addresses this issue.

2.3.3 Remove background noise

Image noise can reduce the accuracy of the OCR engine. Because of this, removing noise in the background is very important to improve readability. Applying a Gaussian blur is one way of reducing the noise in the image.

2.3.4 Binarization

OCR engines are usually designed to handle input images with a black-and-white color scheme. The process of converting a colorized or grayscale image to black-and-white is called binarization. Once an image has gone through binarization, the background should be white and any foreground elements like text should be black.

If your image is in RGB format, it will first need to be converted to grayscale format before thresholding techniques can be used. Adaptive thresholding is one such technique. It involves partitioning the image into smaller regions, and calculating the threshold for what should be black and what should be white, in that region.

Chapter 3

Design

Chapter 3 provides a detailed walkthrough of how the thesis is designed. The design is made to efficiently and correctly tackle the problem statement.

3.1 Overview

This project consists of 2 main parts: the API and the machine learning model.

Something about the api NB!

The machine learning model can be split into three parts. The CNN that, labels the images. OCR that extracts the text from the images, and RNN that takes the text from the OCR and validates key values.

3.2 API

3.3 CNN

The first layer of our model is the Convolutional Neural Network or CNN. This is taking the images and labeling the receipts after what firm the receipts comes from. This is done by having one folder of receipt images per firm and training the model to recognize these receipts. This means that the model is supervised. For our use purpose we need to use a CNN with a single input layer that will take all the images and three output layers. We have three outputs because we only have firms that we for this model.

We need some image here

3.4 OCR

The second layer of our model is the OCR. This is a really simple OCR that does some pre-processing on our images and does a text extraction. The OCR does more or less function as the eyes for our RNN

We need some image here

3.5 RNN

3.6 RNN

Chapter 4

Implementation

Chapter 4 describes the implementation of the thesis. This includes how the thesis group chose to implement the design discussed in previous chapters, and the research methods used to arrive at design decisions.

4.1 REST API

The API exposes several endpoints that allows for saving an image and a receipt to a database. The API is also connected to the ML and OCR module.

4.2 Web solution

The web solution is made with React in JavaScript. The purpose of the web solution is to give the user an interface where they can upload an image of a receipt. And get the corresponding data from the image, and then send in the receipt with the data from the image. This is to make the process of entering the data less time consuming.

When the user uploads an image, the web solution sends a POST request to the API, then the API saves the image to the database. When the image is saved, the image is sent to the OCR for text recognition. If the output makes sense the data is returned and displayed to the user. Then if the returned data is correct the user can then upload the receipt to the database.

4.3 Dataset

The dataset provided by Simployer consists of 1194 unlabeled images and pdfs. However, the variance of the types of receipts in the dataset is very large. Because of this, we end up with a very small amount of images of each type after labeling them. The dataset also includes receipts in several languages, mainly norwegian, english and polish. We filtered the dataset to only include norwegian receipts and removing images of bad quality. At the end of this process, the amount of usable data was very small. The original dataset of 1194 images has been filtered down to 91 images, split into three different types of receipts.

4.4 Pre-processing

4.4.1 Data augmentation

Because of the low amount of images in the filtered dataset, data augmentation has to be done in order to give us enough images to be able to effectively train the CNN. We used an open source data augmentation tool for images for this task [LINK](#). The augmentor takes a directory of images and applies a series of transformations on the images like scaling, skewing and rotating. This creates copies of the images with slight differences, increasing the size of our dataset. After applying enough transformations, the size of the dataset grew from 91 images to 1500.

4.4.2 Image preparation

Many of the images in the dataset are taken in different resolutions. In order to prepare the images to be passed forward to the CNN model, the images resolution is rescaled to 60x60 pixels. This significantly reduces the training time required by the network with minimal to no loss in accuracy. The images are also converted to grayscale instead of RGB. This reduces the amount input nodes required by the network, as each pixel will have one value instead of three.

4.5 Convolutional Neural Network

Our CNN is implemented using Keras. Keras is a library for tensorflow that allows for the creation of neural network models with only a few lines of code. The model consist of an input layer, two hidden layers, and an output layer. The input layer and first hidden layer are convolutional layers with 64 nodes in each layer. The second hidden layer and the output layer are dense layers, where the hidden layer has 64 nodes and the output layer has 3 nodes. The activation function of the first three layers is Rectified Linear Unit (ReLU), while the output layer uses the sigmoid function.

```
opt = tf.keras.optimizers.Adam()
model = Sequential()
model.add(Conv2D(64, (3,3), input_shape = X.shape[1:]))
model.add(Activation("relu"))
model.add(MaxPooling2D(pool_size=(2,2)))
model.add(BatchNormalization())
model.add(Dropout(0.2))

model.add(Conv2D(64, (3,3)))
model.add(Activation("relu"))
model.add(MaxPooling2D(pool_size=(2,2)))
model.add(BatchNormalization())
model.add(Dropout(0.2))

model.add(Flatten())
model.add(Dense(64, activation="relu"))
model.add(Dropout(0.2))

model.add(Dense(3, activation="sigmoid"))
```

The model uses the Adam optimizer and the categorical crossentropy loss function.

Chapter 5

Evaluation

Chapter 5 presents the results the thesis group's work in an objective manner.

Chapter 6

Discussion

Chapter 6 discusses the results discovered in chapter 5. This includes how the results differ from what was expected, how the findings might be relevant to the thesis' field of study, etc.

Chapter 7

Conclusion

Chapter 7 concludes and summarizes the thesis in a manner that can be read by someone who did not read the entire report.

